# Lecture 1 - Introduction

**CPE112 - Programming with Data Structures 19 January 2024** 

Dr. Piyanit Wepulanon

Dr. Taweechai Nuntawisuttiwong

**Department of Computer Engineering KMUTT** 



## What to learn?

#### **Programming with Data Structures**




- Programs manipulate data to solve problems
- Ways to organize & store information
  - Insert/delete/sort numbers: array
  - Student information: structure


Score
67
78
87
90
82
65
68

Name	Midterm	Final
Alice	7.5	67
Bob	8.2	78
Carol	6.0	87
Dave	9.1	90
Eve	8.4	82
Felix	6.5	65
George	6.8	68

## What to learn?

### **Programming with Data Structures**







- 1. Expanded Folder (1st level)
- 2. Expanded Folder (2nd level)
- 3. Unselected File (2nd level)
- 4. Collapsed Folder (1st level) / Hover
- 5. Selected File (1st level)
- 6. Expanded Folder (3rd level)
- 7. Selected File (3rd level)
- 8. Horizontal Scrollbar

## What to learn?

#### **Programming with Data Structures**





- Important data structures strategies for organizing information in a program
- Important algorithms well-known methods for accomplishing particular kinds of tasks
- Efficiency of different data structure algorithms

## Data Structure & Algorithm



Find the first recurring character

"ABCA" -> A
"BCABA" -> B
"ABC" -> NULL

## Data Structure & Algorithm



Find the first recurring character

"ABCA" -> A
"BCABA" -> B
"ABC" -> NULL


Your algorithm will be evaluated.

Correctness (work well)


Efficiency (minimum time & memory)

Style (easy to understand & modify)

# Major Contents



# Review Memory



#### **Pointer**


- A variable type store the address of some value
  - & Get address
  - \* Look into address

```
data-type *pointer-variable-name;

char c='K';
char *cp=&c;
char **cpp=&cp;
```

1001	K	С
1002		
1003		cn
1004		ср
1005		
1006		
1007		cnn
1008		срр
1009		
1010		

#### **Types of Memory - Stack**



#### **Types of Memory - Heap**

```
void function1(int* x)
 int x;
 x[0] = /*...*/;
int main ()
 int *a = malloc(4);
 int *b = malloc(6);
 function1(a);
 free(a);
 free(b);
 return 0;
```

X	100	function1
		main
b	104	
a	100	

# Review Types of Memory

	(How & when they are allocated/deallocated)	(Where they can be accessed)
Stack	Allocate - program enters the function that they are declared <b>Deallocate</b> - program leaves the function	Can be accessed and will have valid value within their own block
Static	Allocate - program starts running  Deallocate - program exits	Can be accessed by <u>any code in C</u> <u>module</u>
Dynamic	Allocate - call calloc  Deallocate - call free	Can be accessed and will have valid values anywhere in the program, by passing around variables that hold the start address

Scope

Life cycle

#### **Dynamic Memory Allocation**

#### **Stack Memory**

1000	Н
1001	i
1002	\0
1003	С
1004	Р
1005	E
1006	1
1007	1
1008	2
1009	\0
1010	

#### Example:

char word1[3] = "Hi"; char word2[10] = "CPE112"

"Hi" -> "Hello"

#### Heap Memory

### calloc free

#### Example:


#define ARRAYSIZE 300 int\* myValues = calloc(ARRAYSIZE,sizeof(int));

Address

# **Review**Dynamic Memory Allocation

calloc but not free

Memory crash!!!



#### Structure

 Create own custom data type that is a composition of multiple other data types

Name	Midterm	Final
Alice	7.5	67
Bob	8.2	78
Carol	6.0	87
Dave	9.1	90
Eve	8.4	82
Felix	6.5	65
George	6.8	68

```
typedef struct {
    char name[100];
    float midterm;
    int final;
} student_info;
```

#### Structure

```
void selectionSort (student info data[], int count)
 int i, j, minPos;
                                                void swap (student info *x,
 for (i = 0, i < count-1; i++)
                                                 student info *y)
   minPos = i;
                                                  student info tmp;
   for (j=i+1; j<count; j++)
                                                  tmp = *x; *x=*y; *y=tmp;
     if (data[j].final < data[minPos].final)</pre>
      minPos = j;
   swap(&data[i], &data[minPos]);
```

## Data Structure


- A data structure a way to organize information stored in computer memory.
- Different kinds of data structures works better for different sorts of problems.
- Appropriate structure -> Good solution

Score
67
78
87
90
82
65
68


Name	Midterm	Final
Alice	7.5	67
Bob	8.2	78
Carol	6.0	87
Dave	9.1	90
Eve	8.4	82
Felix	6.5	65
George	6.8	68

## Data Structure

- Creating a data structure
  - Ability to refer to different memory locations
  - Stitch them together into a custom shape



# Data Structure & Algorithm Example





How to find "Structure"?

	#operations for 1 page	#operations for 100 page	#operations for 1000 page	
Method#1				
Method#2				



### **Big O Notation**





https://towardsdatascience.com

# Algorithm Efficiency Big O Notation

- 1. Understand how the algorithm works
- 2. Identify a basic unit of the algorithm to count
- 3. Map growth of count from step 2 to appropriate Big O class

## Big O - Examples

1	x = 5 + (5 * 5);	O()
2	for (i = 0; i < N; i++) printf("%d", i);	O()
3	for (i = 0; i < N; i++) for (j = 0; i < N; i++) printf("%ld", i*j);	O()
4	x = 5 + (5 * 5); for (i = 0; i < N; i++) printf("%d", i); for (i = 0; i < N; i++) for (j = 0; i < N; i++) printf("%ld", i*j);	?


#### **Big O Definition**

Let f(n) and g(n) be functions from positive integers to positive reals. f(n) = O(g(n)) if there is a constant c > 0 such that  $f(n) \le c*g(n)$  for large n

นิยาม 1: f(n) และ g(n) เป็นฟังก์ชันซึ่งมีโดเมนเป็นเลขจำนวนเต็มบวก และมี ranges เป็นจำนวนจริงบวก <u>สามารถเขียนได้เป็น</u>

f(n) = O(g(n)) ถ้ามีค่าคงที่บวก c ที่ทำให้ f(n) ≤ c\*g(n) เป็นจริงทุกค่าสำหรับ x ที่เป็นจำนวนเต็มบวก

Big O - Examples



Find "Ant", "List", "Zombie", ...

#### Cases

### Find character 'A' in a given string length n

**Best case** 

$$C(n) = 1$$

Worst case

$$C(n) = n$$

Average case

$$C(n) = (1+2+3+...+n)1/n$$
  
=  $[n(n+1)/2] * [1/n]$   
=  $(n+1)/2$ 

#### Complexity Summary of Array Sorting Algorithms

Algorithm	Time Complexity		
	Best	Average	Worst
Quicksort	$\Omega(n \log(n))$	θ(n log(n))	0(n^2)
Mergesort	$\Omega(n \log(n))$	θ(n log(n))	O(n log(n))
<u>Timsort</u>	<u>Ω(n)</u>	θ(n log(n))	O(n log(n))
<u>Heapsort</u>	$\Omega(n \log(n))$	θ(n log(n))	O(n log(n))
<b>Bubble Sort</b>	<u>Ω(n)</u>	Θ(n^2)	0(n^2)
Insertion Sort	<u>Ω(n)</u>	Θ(n^2)	0(n^2)
Selection Sort	Ω(n^2)	Θ(n^2)	0(n^2)
Tree Sort	$\Omega(n \log(n))$	θ(n log(n))	0(n^2)
Shell Sort	$\Omega(n \log(n))$	θ(n(log(n))^2)	0(n(log(n))^2)
<b>Bucket Sort</b>	$\Omega(n+k)$	Θ(n+k)	0(n^2)
Radix Sort	Ω(nk)	Θ(nk)	0(nk)
Counting Sort	$\Omega(n+k)$	$\theta(n+k)$	0(n+k)
Cubesort	<u>Ω(n)</u>	θ(n log(n))	0(n log(n))

## Designing an Algorithm

- Perform operations on the stored data contained in data structures.
- Modularization process a complex algorithm is often divided into smaller units called modules.
  - Top-down approach dividing the complex algorithm into one or more modules
  - Bottom-up approach designing the most basic or concrete modules and then proceed towards designing higher level modules




Figure 2.9 Different approaches of designing an algorithm

## Wrap up

- Course introduction
- What to learn?
- Data structures & algorithms
- Review CPE100
- Big O