

# CS4104 Applied Machine Learning

## Decision Tree Classifier

# Classification Techniques


- Decision Tree based Methods
- Rule-based Methods
- Memory based reasoning
- Neural Networks
- Naïve Bayes and Bayesian Belief Networks
- Support Vector Machines

# Example of a Decision Tree

categorical  
categorical  
continuous  
class

Tid	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes

Training Data




Model: Decision Tree

# Another Example of Decision Tree

categorical  
categorical  
continuous  
class

<i>Tid</i>	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



There could be more than one tree that fits the same data!


# Decision Tree Classification Task

Tid	Attrib1	Attrib2	Attrib3	Class
1	Yes	Large	125K	No
2	No	Medium	100K	No
3	No	Small	70K	No
4	Yes	Medium	120K	No
5	No	Large	95K	Yes
6	No	Medium	60K	No
7	Yes	Large	220K	No
8	No	Small	85K	Yes
9	No	Medium	75K	No
10	No	Small	90K	Yes

Training Set


Tid	Attrib1	Attrib2	Attrib3	Class
11	No	Small	55K	?
12	Yes	Medium	80K	?
13	Yes	Large	110K	?
14	No	Small	95K	?
15	No	Large	67K	?

Test Set



# Apply Model to Test Data

Start from the root of tree.




Test Data

Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?

# Apply Model to Test Data

Test Data


Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?



# Apply Model to Test Data

## Test Data

Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?






# Apply Model to Test Data

## Test Data


Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?



# Apply Model to Test Data

## Test Data


Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?



# Apply Model to Test Data

## Test Data

Refund	Marital Status	Taxable Income	Cheat
No	Married	80K	?



Assign Cheat to "No"

# Exercise

Refund	Marital Status	Taxable Income	Cheat
No	Single	80K	?
Yes	Single	100K	?
Yes	Married	1K	?
Yes	Divorced	50K	?

# Decision Tree Induction

- Many Algorithms:
  - Hunt's Algorithm (one of the earliest)
  - CART
  - ID3, C4.5
  - SLIQ, SPRINT

# Decision Tree Based Classification: Advantages

- Inexpensive to construct
- Extremely fast at classifying unknown records
- Easy to interpret for small-sized trees
- Accuracy is comparable to other classification
- techniques for many simple data sets

# DECISION TREE

An internal node is a test on an attribute

A branch represents an outcome of the test, e.g.,  
Color=red

A leaf node represents a class label or class  
label distribution

At each node, one attribute is chosen to split training  
examples into distinct classes as much as possible

A new case is classified by following a matching path  
to a leaf node


# Weather Data: Play or not Play?

Outlook	Temperature	Humidity	Windy	Play?
sunny	hot	high	false	No
sunny	hot	high	true	No
overcast	hot	high	false	Yes
rain	mild	high	false	Yes
rain	cool	normal	false	Yes
rain	cool	normal	true	No
overcast	cool	normal	true	Yes
sunny	mild	high	false	No
sunny	cool	normal	false	Yes
rain	mild	normal	false	Yes
sunny	mild	normal	true	Yes
overcast	mild	high	true	Yes
overcast	hot	normal	false	Yes
rain	mild	high	true	No

*Note:  
Outlook is the  
Forecast,  
no relation to  
Microsoft  
email program*



# Example Tree for “Play?”







# Building Decision Tree

- Top-down tree construction
  - At start, all training examples are at the root
  - Partition the examples recursively by choosing one attribute each time
- Bottom-up tree pruning
  - Remove subtrees or branches, in a bottom-up manner, to improve the estimated accuracy on new cases

# Choosing the Splitting Attribute

- At each node, available attributes are evaluated on the basis of separating the classes of the training examples. A Goodness function is used for this purpose
- Typical goodness functions:
  - information gain (ID3/C4.5)
  - accuracy
  - gini index
  - others (information gain ratio)

# Which attribute to select?



# A criterion for attribute selection

- Which is the best attribute?
  - The one which will result in the smallest tree
  - Heuristic: choose the attribute that produces the
    - “purest” nodes
- Popular impurity criterion: information gain
  - Information gain increases with the average purity of the subsets that an attribute produces
- Strategy: choose attribute that results in greatest information gain

# Computing information

- Information is measured in *bits*
  - Given a probability distribution, the info required to
    - predict an event is the distribution's *entropy*
  - Entropy gives the information required in bits (this can involve fractions of bits!)
- Formula for computing the entropy:
- $entropy(p_1, p_2, \dots, p_n) = -\sum_{i=1}^n p_i \log p_i$ 
  - $entropy(p_1, p_2, \dots, p_n) = -p_1 \log p_1 - p_2 \log p_2 - \dots - p_n \log p_n$

# Example: attribute “Outlook”

## □ “Outlook” = “Sunny”:

$\text{info}([2,3]) = \text{entropy}(2/5, 3/5) = -2/5 \log(2/5) - 3/5 \log(3/5) = 0.971$   
bits

## • “Outlook” = “Overcast”:

$\text{info}([4,0]) = \text{entropy}(1,0) = -1 \log(1) - 0 \log(0) = 0$   
bits

*Note:  $\log(0)$  is not defined, but we evaluate  $0 \cdot \log(0)$  as zero*

• “Outlook” = “Rainy”:  
 $\text{info}([3,2]) = \text{entropy}(3/5, 2/5) = -3/5 \log(3/5) - 2/5 \log(2/5) = 0.971$   
bits

## • Expected information for attribute:

$\text{info}([2,3],[4,0],[3,2]) = (5/14) \times 0.971 + (4/14) \times 0 + (5/14) \times 0.971$   
 $0.971$

$= 0.693$  bits

# Computing the information gain

- Information gain:

(information before split) – (information after split)

$$\text{gain("Outlook")} = \text{info}([9,5]) - \text{info}([2,3],[4,0],[3,2]) = 0.940 - 0.693 \\ = 0.247 \text{ bits}$$

- Information gain for attributes from weather data:

$$\text{gain("Outlook")} = 0.247 \text{ bits}$$


$$\text{gain("Temperature")} = 0.029$$

$$\text{bits gain("Humidity")} = 0.152$$

$$\text{bits gain("Windy")} = 0.048$$




# Continuing to split



$\text{gain}(\text{"Temperature"}) = 0.571 \text{ bits}$

$\text{gain}(\text{"Humidity"}) = 0.971 \text{ bits}$

# The final decision tree



- Note: not all leaves need to be pure; sometimes identical instances have different classes  
⇒ Splitting stops when data can't be split any further

# CART Splitting Criteria: Gini Index

- index,  $\text{gini}(T)$  is defined as
- $\text{gini}(T) = 1 - \sum_{j=1}^n p_j^2$
- where  $p_j$  is the relative frequency of class  $j$  in  $T$ .  $\text{gini}(T)$  is minimized if the classes in  $T$  are skewed.

# Measure of Impurity: GINI

- Gini Index for a given node  $t$  :
- $gini(T) = 1 - \sum_{j=1}^n (p(j|t))^2$
- (NOTE:  $p(j | t)$  is the relative frequency of class  $j$  at node  $t$ ).
  - Maximum  $(1 - 1/n_c)$  when records are equally distributed among all classes, implying least interesting information
  - Minimum (0.0) when all records belong to one class,
- implying most interesting information

C1	<b>0</b>
C2	<b>6</b>
<b>Gini=0.000</b>	

C1	<b>1</b>
C2	<b>5</b>
<b>Gini=0.278</b>	

C1	<b>2</b>
C2	<b>4</b>
<b>Gini=0.444</b>	

C1	<b>3</b>
C2	<b>3</b>
<b>Gini=0.500</b>	

# Examples for computing GINI

$$GINI(t) = 1 - \sum_j [p(j | t)]^2$$

C1	<b>0</b>
C2	<b>6</b>

$$P(C1) = 0/6 = 0 \quad P(C2) = 6/6 = 1$$

$$Gini = 1 - P(C1)^2 - P(C2)^2 = 1 - 0 - 1 = 0$$

C1	<b>1</b>
C2	<b>5</b>

$$P(C1) = 1/6 \quad P(C2) = 5/6$$

$$Gini = 1 - (1/6)^2 - (5/6)^2 = 0.278$$

C1	<b>2</b>
C2	<b>4</b>

$$P(C1) = 2/6 \quad P(C2) = 4/6$$

$$Gini = 1 - (2/6)^2 - (4/6)^2 = 0.444$$

# Splitting Based on GINI


- Used in CART, SLIQ, SPRINT.
- When a node  $p$  is split into  $k$  partitions (children), the quality of split is computed as,

- $$GINI_{split} = \sum_{i=1}^k \frac{n_i}{n} GINI(i)$$

- where,
- $n_i$  = number of records at child  $i$
- $n$  = number of records at node  $p$

# Binary Attributes: Computing GINI Index

- Splits into two partitions
- Effect of Weighing partitions:
  - Larger and Purer Partitions are sought for.



	Parent
C1	<b>6</b>
C2	<b>6</b>
<b>Gini = 0.500</b>	

$$\begin{aligned}
 \text{Gini}(N1) &= 1 - (5/7)^2 - (2/7)^2 \\
 &= 0.408
 \end{aligned}$$

$$\begin{aligned}
 \text{Gini}(N2) &= 1 - (1/5)^2 - (4/5)^2 \\
 &= 0.32
 \end{aligned}$$

	<b>N1</b>	<b>N2</b>
C1	<b>5</b>	<b>1</b>
C2	<b>2</b>	<b>4</b>

$$\begin{aligned}
 \text{Gini(Children)} &= 7/12 * 0.408 + \\
 &\quad 5/12 * 0.32 \\
 &= 0.371
 \end{aligned}$$

# Categorical Attributes: Computing Gini Index

- For each distinct value, gather counts for each class in the dataset
- Use the count matrix to make decisions

Multi-way split

	CarType		
	Family	Sports	Luxury
C1	1	2	1
C2	4	1	1
Gini	0.393		

Two-way split  
(find best partition of values)

	CarType	
	{Sports, Luxury}	{Family}
C1	3	1
C2	2	4
Gini	0.400	


	CarType	
	{Sports}	{Family, Luxury}
C1	2	2
C2	1	5
Gini	0.419	



# Continuous Attributes: Computing Gini Index

- Use Binary Decisions based on one value
- Several Choices for the splitting value
  - Number of possible splitting values = Number of distinct values
- Each splitting value has a count matrix associated with it
  - Class counts in each of the partitions,  $A$   
 $< v$  and  $A \geq v$
- Simple method to choose best  $v$ 
  - For each  $v$ , scan the database to gather count matrix and compute its Gini index
  - Computationally Inefficient!  
Repetition

Tid	Refund	Marital Status	Taxable Income	Cheat
1	Yes	Single	125K	No
2	No	Married	100K	No
3	No	Single	70K	No
4	Yes	Married	120K	No
5	No	Divorced	95K	Yes
6	No	Married	60K	No
7	Yes	Divorced	220K	No
8	No	Single	85K	Yes
9	No	Married	75K	No
10	No	Single	90K	Yes



# Continuous Attributes: Computing Gini Index...

- For efficient computation: for each attribute,
  - Sort the attribute on values
  - Linearly scan these values, each time updating the count matrix and computing gini index
  - Choose the split position that has the least gini index

Sorted Values  
Split Positions

Cheat	Taxable Income																					
	Taxable Income																					
	60		70		75		85		90		95		100		120		125		220			
	55		65		72		80		87		92		97		110		122		172		230	
	<=		>		<=		>		<=		>		<=		>		<=		>		<=	
Yes	0	3	0	3	0	3	0	3	1	2	2	1	3	0	3	0	3	0	3	0	3	0
No	0	7	1	6	2	5	3	4	3	4	3	4	3	4	4	3	5	2	6	1	7	0
Gini	0.420		0.400		0.375		0.343		0.417		0.400		<u>0.300</u>		0.343		0.375		0.400		0.420	

# Splitting Criteria based on Classification Error

- Classification error at a node  $t$  :

$$Error(t) = 1 - \max_i P(i | t)$$

- Measures misclassification error made by a node.
  - Maximum  $(1 - 1/n_c)$  when records are equally distributed among all classes, implying least interesting information
  - Minimum (0.0) when all records belong to one class, implying most interesting information

# Examples for Computing Error

$$Error(t) = 1 - \max_i P(i |$$

*t*)

C1	<b>0</b>
C2	<b>6</b>

$$P(C1) = 0/6 = 0 \quad P(C2) = 6/6 = 1$$

$$Error = 1 - \max(0, 1) = 1 - 1 = 0$$

C1	<b>1</b>
C2	<b>5</b>

$$P(C1) = 1/6 \quad P(C2) = 5/6$$


$$Error = 1 - \max(1/6, 5/6) = 1 - 5/6 = 1/6$$

C1	<b>2</b>
C2	<b>4</b>

$$P(C1) = 2/6 \quad P(C2) = 4/6$$

$$Error = 1 - \max(2/6, 4/6) = 1 - 4/6 = 1/3$$

# Misclassification Error vs Gini



	Parent
C1	<b>7</b>
C2	<b>3</b>
<b>Gini = 0.42</b>	

$$\begin{aligned}
 &\text{Gini(N1)} \\
 &= 1 - (3/3)^2 - (0/3)^2 \\
 &= 0
 \end{aligned}$$

	N1	N2
C1	<b>3</b>	<b>4</b>
C2	<b>0</b>	<b>3</b>
<b>Gini=0.361</b>		

$$\begin{aligned}
 &\text{Gini(N2)} \\
 &= 1 - (4/7)^2 - (3/7)^2 \\
 &= 0.489
 \end{aligned}$$

$$\begin{aligned}
 &\text{Gini(Children)} \\
 &= 3/10 * 0 \\
 &+ 7/10 * 0.489 \\
 &= 0.342
 \end{aligned}$$

**Gini improves !!**

# Tree Induction

- Greedy strategy.
  - Split the records based on an attribute test that optimizes certain criterion.
- Issues
  - Determine how to split the records
    - How to specify the attribute test condition?
    - How to determine the best split?
  - Determine when to stop splitting

# Stopping Criteria for Tree Induction

- Stop expanding a node when all the records belong to the same class
- Stop expanding a node when all the records have similar attribute values
- Early termination