

Mutual exclusion in distributed system

Last Updated : 30 Apr, 2019

Mutual exclusion is a concurrency control property which is introduced to prevent race conditions. It is the requirement that a process can not enter its critical section while another concurrent process is currently present or executing in its critical section i.e only one process is allowed to execute the critical section at any given instance of time.

Mutual exclusion in single computer system Vs. distributed system:

In single computer system, memory and other resources are shared between different processes. The status of shared resources and the status of users is easily available in the shared memory so with the help of shared variable (For example: [Semaphores](#)) mutual exclusion problem can be easily solved.

In Distributed systems, we neither have shared memory nor a common physical clock and there for we can not solve mutual exclusion problem using shared variables. To eliminate the mutual exclusion problem in distributed system approach based on message passing is used.

A site in distributed system do not have complete information of state of the system due to lack of shared memory and a common physical clock.

Requirements of Mutual exclusion Algorithm:

- **No Deadlock:**

Two or more site should not endlessly wait for any message that will never arrive.

- **No Starvation:**

Every site who wants to execute critical section should get an opportunity to execute it in finite time. Any site should not wait indefinitely to execute critical section while other site are repeatedly executing critical section

- **Fairness:**



Each site should get a fair chance to execute critical section. Any request to execute critical section must be executed in the order they are made i.e Critical section execution requests should be executed in the order of their arrival in the system.

- **Fault Tolerance:**

In case of failure, it should be able to recognize it by itself in order to continue functioning without any disruption.

Solution to distributed mutual exclusion:

As we know shared variables or a local kernel can not be used to implement mutual exclusion in distributed systems. Message passing is a way to implement mutual exclusion. Below are the three approaches based on message passing to implement mutual exclusion in distributed systems:

1. Token Based Algorithm:

- A unique **token** is shared among all the sites.
- If a site possesses the unique token, it is allowed to enter its critical section
- This approach uses sequence number to order requests for the critical section.
- Each requests for critical section contains a sequence number. This sequence number is used to distinguish old and current requests.
- This approach insures Mutual exclusion as the token is unique
- **Example:**
Suzuki-Kasami's Broadcast Algorithm

2. Non-token based approach:

- A site communicates with other sites in order to determine which sites should execute critical section next. This requires exchange of two or more successive round of messages among sites.
- This approach use timestamps instead of sequence number to order requests for the critical section.
- When ever a site make request for critical section, it gets a timestamp.
Timestamp is also used to resolve any conflict between critical section requests.



3. Quorum based approach:

- Instead of requesting permission to execute the critical section from all other sites, Each site requests only a subset of sites which is called a **quorum**.
- Any two subsets of sites or Quorum contains a common site.
- This common site is responsible to ensure mutual exclusion
- **Example:**
Maekawa's Algorithm



Like 0

[I< Previous](#)

[Next >I](#)

RECOMMENDED ARTICLES

Page : [1](#) [2](#) [3](#)

01 **Maekawa's Algorithm for Mutual Exclusion in Distributed System**
26, Apr 19

02 **Ricart-Agrawala Algorithm in Mutual Exclusion in Distributed System**
26, Apr 19

03 **Lamport's Algorithm for Mutual Exclusion in Distributed System**
26, Apr 19

Suzuki-Kasami Algorithm for

05 **Peterson's Algorithm for Mutual Exclusion | Set 2 (CPU Cycles and Memory Fence)**
08, Jul 16

06 **Mutual Exclusion in Synchronization**
20, Mar 20

07 **Peterson's Algorithm for Mutual Exclusion | Set 1 (Basic C implementation)**
06, Jul 16



04

Mutual Exclusion in Distributed System

29, Apr 19

08

Distributed Consensus in Distributed Systems

11, Jan 21

Article Contributed By :

**ihritik**

@ihritik

Vote for difficulty

Easy

Normal

Medium

Hard

Expert

Article Tags : [Distributed System](#), [GATE CS](#), [Operating Systems](#)

Practice Tags : [Operating Systems](#)

Improve Article

Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments



5th Floor, A-118,
Sector 136, Noida, Uttar Pradesh - 201305

Company

[About Us](#)
[Careers](#)
[Privacy Policy](#)
[Contact Us](#)
[Copyright Policy](#)

Practice

[Courses](#)
[Company-wise](#)
[Topic-wise](#)
[How to begin?](#)

Learn

[Algorithms](#)
[Data Structures](#)
[Languages](#)
[CS Subjects](#)
[Video Tutorials](#)

Contribute

[Write an Article](#)
[Write Interview Experience](#)
[Internships](#)
[Videos](#)

