



Kanban

Progress report

Todor Milev, Ph.D.

Senior C++ programmer
FA Enterprise System

May 18



Outline

1 Current architecture plan

Outline

1 Current architecture plan

2 Computational engine

- Cryptography
- C++ driver

Outline

- 1 Current architecture plan
- 2 Computational engine
 - Cryptography
 - C++ driver
- 3 nodejs

Current architecture

- OS: Ubuntu at the moment. Aspirations to support everything.

Current architecture

- OS: Ubuntu at the moment. Aspirations to support everything.
- Computational engine in openCL/C/C++.

Current architecture

- OS: Ubuntu at the moment. Aspirations to support everything.
- Computational engine in openCL/C/C++.
 - Crypto functions in openCL/C++.

Current architecture

- OS: Ubuntu at the moment. Aspirations to support everything.
- Computational engine in openCL/C/C++.
 - Crypto functions in openCL/C++.
 - Data management? Expected solution: stl library (no database).

Current architecture

- OS: Ubuntu at the moment. Aspirations to support everything.
- Computational engine in openCL/C/C++.
 - Crypto functions in openCL/C++.
 - Data management? Expected solution: stl library (no database).
- Networking, management, testing, other non-computational tasks: nodejs.

Computational engine: cryptography

Core crypto functions: code compiled as both openCL/C++.

Computational engine: cryptography

Core crypto functions: code compiled as both openCL/C++.

- Forked Pieter Wuille's secp256k1 library (used in fabcoin & bitcoin).

Computational engine: cryptography

Core crypto functions: code compiled as both openCL/C++.

- Forked Pieter Wuille's secp256k1 library (used in fabcoin & bitcoin).
- Heavy but formal modifications.

Computational engine: cryptography

Core crypto functions: code compiled as both openCL/C++.

- Forked Pieter Wuille's secp256k1 library (used in fabcoin & bitcoin).
- Heavy but formal modifications.
 - openCL major memory types: `__local`, `__global`, `__constant`

Computational engine: cryptography

Core crypto functions: code compiled as both openCL/C++.

- Forked Pieter Wuille's secp256k1 library (used in fabcoin & bitcoin).
- Heavy but formal modifications.
 - openCL major memory types: `__local`, `__global`, `__constant`
 - Mixed arguments: 1 version per combination:

```
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __global const uint32_t * b)
```

```
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __local const uint32_t * b)
```

```
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __constant const uint32_t * b)
```

Computational engine: cryptography

Core crypto functions: code compiled as both openCL/C++.

- Forked Pieter Wuille's secp256k1 library (used in fabcoin & bitcoin).
- Heavy but formal modifications.

- openCL major memory types: `__local`, `__global`, `__constant`
- Mixed arguments: 1 version per combination:

```
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __global const uint32_t * b)  
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __local const uint32_t * b)  
  
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __constant const uint32_t * b)
```

- No C++ templates in openCL: emulate with macros.

Computational engine: cryptography

Core crypto functions: code compiled as both openCL/C++.

- Forked Pieter Wuille's secp256k1 library (used in fabcoin & bitcoin).
- Heavy but formal modifications.

- openCL major memory types: `__local`, `__global`, `__constant`
- Mixed arguments: 1 version per combination:

```
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __global const uint32_t * b)  
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __local const uint32_t * b)
```

```
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __constant const uint32_t * b)
```

- No C++ templates in openCL: emulate with macros.
- No `free`, `malloc`: custom memory pools: 0 runtime memory allocation, minimal openCL-statically allocated RAM memory use

Computational engine: cryptography

Core crypto functions: code compiled as both openCL/C++.

- Forked Pieter Wuille's secp256k1 library (used in fabcoin & bitcoin).
- Heavy but formal modifications.

- openCL major memory types: `__local`, `__global`, `__constant`
- Mixed arguments: 1 version per combination:

```
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __global const uint32_t * b)
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __local const uint32_t * b)

secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __constant const uint32_t * b)
```

- No C++ templates in openCL: emulate with macros.
- No `free`, `malloc`: custom memory pools: 0 runtime memory allocation, minimal openCL-statically allocated RAM memory use
- 4 basic modes of running. TO DO: combine (arbitrarily?).
 - 1 openCL on GPU.
 - 2 openCL on CPU.
 - 3 C/C++ on CPU using openCL entry points.
 - 4 C/C++ direct function call.

Computational engine: cryptography

Core crypto functions: code compiled as both openCL/C++.

- Forked Pieter Wuille's secp256k1 library (used in fabcoin & bitcoin).
- Heavy but formal modifications.

- openCL major memory types: `__local`, `__global`, `__constant`
- Mixed arguments: 1 version per combination:

```
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __global const uint32_t * b)
secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __local const uint32_t * b)

secp256k1_fe_mul_inner(uint32_t *r, const uint32_t *a, __constant const uint32_t * b)
```

- No C++ templates in openCL: emulate with macros.
- No `free`, `malloc`: custom memory pools: 0 runtime memory allocation, minimal openCL-statically allocated RAM memory use
- 4 basic modes of running. TO DO: combine (arbitrarily?).
 - 1 openCL on GPU.
 - 2 openCL on CPU.
 - 3 C/C++ on CPU using openCL entry points.
 - 4 C/C++ direct function call.
- TO DO: computation load balancing.

Core crypto: errors.

- No debugger.
- Error hunting: hardcore: not even `printf` available!
- At least 4 types of errors seen so far:
 - Easy: compiles as C/C++, doesn't as openCL or other way round.
 - Easy: runtime errors show in C/C++.
 - Fix: use `printf`, temporarily breaking openCL, debug as usual.
 - Harder: C/C++ runs correctly, openCL crashes.
 - Manually return from offending function.
 - Print memory pool & compare with C/C++ output.
 - Hard core: 1 machine/setup works correctly, another doesn't.
 - Fix?

Core crypto: testing.

- Compare 4 modes of running against one another.
- Generate signatures & verify.
- Tamper signature and invalidate.
- Compare outputs with same input between runs.

Computational engine: C++ driver

- 3 Binary pipes:
 - Command pipe
 - nodejs \rightarrow C++.
 - nodejs end: non-blocking; C++ end: blocking.
 - Input data pipe
 - nodejs \rightarrow C++.
 - nodejs end: non-blocking; C++ end: blocking.
 - Data pipe nodejs \leftarrow C++.
 - nodejs \leftarrow C++.
 - nodejs end: non-blocking; C++ end: blocking.
- TCP protocol: chosen over named/unnamed pipe, std::cin/std::cout (portability).
- Nodejs \leftrightarrow C++ communication local: no networking, no authentication, no encoding.

Nodejs: networking and management

- TO DO: Networking.
 - p2p discovery (FAB RPC call, Nader's smart engine, ...)
 - Kanban id: which peers are running Kanban? Quick options:
 - 1 Use FAB rpc: `getPeerInfo`, get IP addresses; connect on separate port to ask whether they run Kanban.
 - 2 Alternatively, add Kanban discovery information to `getPeerInfo`.
 - 3 Alternatively, make new RPC function, e.g., `getKanbanPeerInfo`.
 - 4 Alternatively, proposals? Do Kanban p2p in a brand new way or as part of FAB RPC calls?
- Data.

To do list for next week(s)

Immediate to do list.

- 1 Figure out crypto bug(s) causing inconsistent runs across machines (work machines works correctly, laptop doesn't).
- 2 At the moment, tests are parallelized, node runtime is not. Fix.
- 3 Add timing tests for
 - Signature on the CPU.
 - Signature verification on the CPU and GPU.
 - Public key generation on the CPU and GPU.
- 4 Bootstrap a powerful machine for all tests.

To do list for the near future.

- 1 Start signing and verifying actual transactions.
- 2 Implement in-RAM data search.
- 3 p2p network discovery.
- 4 Write heavy test suites.
- 5 Prepare detailed benchmarks.

