DataTypes:

list, dictionary are mutable(you can change)

tuples, String are immutable(you can read, not change it)

List

In [6]:
```
fruits=['mango','banana','apple','pineapple']

students=[25,'ali',3.14]

print(type(fruits))
print(len(fruits))
print(fruits[0])
print(type(fruits[0]))

print(students)
```

```
<class 'list'>
4
mango
<class 'str'>
[25, 'ali', 3.14]
```

1. remove (' ')
2. append (' ')
3. insert (,) | index
4. pop
5. sort ->ascending
6. reverse
7. sort(reverse=True) -> decending

In [15]:
```
fruits=['mango','banana','apple','pineapple']

print('Fruits in List append')
fruits.append('cherry')
print(fruits)

print('\n')
print('Fruits in List remove')
fruits.remove('pineapple')
print(fruits)

print('\n')
```

```
print('Fruits in List insert')
fruits.insert(1,'pear')
print(fruits)

print('\n')
print('Fruits in List reverse')
fruits.reverse()
print(fruits)

print('\n')
print('Fruits in List sort acending')
fruits.sort()
print(fruits)

print('\n')
print('Fruits in List Decending')
fruits.sort(reverse=True)
print(fruits)

print('\n')
print('Fruits in List pop')
fruits.pop(1)
print(fruits)
```

```
Fruits in List append
['mango', 'banana', 'apple', 'pineapple', 'cherry']


Fruits in List remove
['mango', 'banana', 'apple', 'cherry']


Fruits in List insert
['mango', 'pear', 'banana', 'apple', 'cherry']


Fruits in List reverse
['cherry', 'apple', 'banana', 'pear', 'mango']


Fruits in List sort acending
['apple', 'banana', 'cherry', 'mango', 'pear']


Fruits in List Decending
['pear', 'mango', 'cherry', 'banana', 'apple']


Fruits in List pop
['pear', 'cherry', 'banana', 'apple']
```

In [16]:

```
fruits=['mango','banana','apple','pineapple']

vegetables=['carrot','potato','onion']

grocery=fruits+vegetables
```

```
print(grocery)
```

```
['mango', 'banana', 'apple', 'pineapple', 'carrot', 'potato', 'onion']
```