

HX-240 Product Datasheet

Commercial and technical product summary

Document ID	HEL-HX-240-DS-3.1
Version	3.1
Status	Approved
Effective date	15 January 2026
Owner	Product Management
Access	Sales, Service, Engineering

Product overview

HX-240 Standard Process Pump is positioned as General industrial process pump for water and light chemical service.

It is designed for treated water, utility water, light chemicals, CIP return, general process transfer. The standard configuration uses 316L stainless-steel wetted parts.

Key operating data

Parameter	Specification
Flow range	15-85 m³/h
Differential head	up to 62 m
Maximum system pressure	10 bar
Continuous fluid temperature	95°C continuous fluid temperature
Standard seal	EPDM mechanical seal
Standard seal limit	90°C continuous
Optional seals	FKM up to 120°C; PTFE up to 140°C subject to application review
Motor range	5.5-18.5 kW, IE4 options
Solids guidance	Maximum suspended solids size 2 mm

Application guidance

For continuous operation above 90°C, standard EPDM seal is not recommended.

Final product selection must consider fluid chemistry, solids loading, temperature, pressure, duty cycle, NPSH conditions and seal compatibility.

Where customer conditions sit close to a documented operating limit, Helios recommends technical application review before a binding offer.

Typical service and maintenance

Routine inspection every 4,000 operating hours; seal inspection every 2,000 hours in hot chemical service