

HX-300 Product Datasheet

Commercial and technical product summary

Document ID	HEL-HX-300-DS-3.1
Version	3.1
Status	Approved
Effective date	15 January 2026
Owner	Product Management
Access	Sales, Service, Engineering

Product overview

HX-300 High-Pressure Process Pump is positioned as High-pressure process pump for demanding industrial transfer duties.

It is designed for high-pressure utility service, chemical transfer, filtration feed, process circulation. The standard configuration uses 316L stainless-steel wetted parts.

Key operating data

Parameter	Specification
Flow range	20-120 m³/h
Differential head	up to 105 m
Maximum system pressure	16 bar
Continuous fluid temperature	110°C continuous fluid temperature
Standard seal	FKM mechanical seal
Standard seal limit	120°C continuous
Optional seals	PTFE up to 150°C; double mechanical seal available
Motor range	11-37 kW, IE4 options
Solids guidance	Maximum suspended solids size 2 mm

Application guidance

Not intended for hygienic/sterile service without validated cleaning design.

Final product selection must consider fluid chemistry, solids loading, temperature, pressure, duty cycle, NPSH conditions and seal compatibility.

Where customer conditions sit close to a documented operating limit, Helios recommends technical application review before a binding offer.

Typical service and maintenance

Routine inspection every 5,000 operating hours