

HX-400 Product Datasheet

Commercial and technical product summary

Document ID	HEL-HX-400-DS-3.1
Version	3.1
Status	Approved
Effective date	15 January 2026
Owner	Product Management
Access	Sales, Service, Engineering

Product overview

HX-400 High-Temperature Heavy-Duty Pump is positioned as Heavy-duty pump for high-temperature, high-pressure continuous process duties.

It is designed for hot process water, chemical circulation, thermal processes, high-pressure plant utilities. The standard configuration uses 316L stainless steel standard; duplex stainless steel optional.

Key operating data

Parameter	Specification
Flow range	30-180 m³/h
Differential head	up to 128 m
Maximum system pressure	20 bar
Continuous fluid temperature	140°C continuous fluid temperature
Standard seal	FKM mechanical seal
Standard seal limit	130°C continuous
Optional seals	PTFE up to 160°C; double mechanical seal and flush plan options
Motor range	18.5-75 kW, IE4 options
Solids guidance	Maximum suspended solids size 3 mm

Application guidance

Above 130°C, PTFE seal configuration is required.

Final product selection must consider fluid chemistry, solids loading, temperature, pressure, duty cycle, NPSH conditions and seal compatibility.

Where customer conditions sit close to a documented operating limit, Helios recommends technical application review before a binding offer.

Typical service and maintenance

Routine inspection every 6,000 operating hours; every 3,000 hours for severe thermal cycling