

HX-520 Product Datasheet

Commercial and technical product summary

Document ID	HEL-HX-520-DS-3.1
Version	3.1
Status	Approved
Effective date	15 January 2026
Owner	Product Management
Access	Sales, Service, Engineering

Product overview

HX-520 Hygienic CIP Pump is positioned as Hygienic pump for food, beverage and pharmaceutical cleaning and process circuits.

It is designed for CIP return, hygienic water, beverage process transfer, pharmaceutical utilities. The standard configuration uses 316L electropolished wetted parts, Ra ≤ 0.8 µm.

Key operating data

Parameter	Specification
Flow range	10-100 m³/h
Differential head	up to 70 m
Maximum system pressure	12 bar
Continuous fluid temperature	135°C continuous; 145°C for short sterilisation cycles up to 30 minutes
Standard seal	FDA-compliant EPDM hygienic seal
Standard seal limit	125°C continuous
Optional seals	FKM hygienic seal up to 140°C continuous
Motor range	7.5-30 kW, IE4 options
Solids guidance	Not intended for abrasive solids; particles should remain below 1 mm

Application guidance

Standard EPDM hygienic seal is not recommended above 125°C continuous.

Final product selection must consider fluid chemistry, solids loading, temperature, pressure, duty cycle, NPSH conditions and seal compatibility.

Where customer conditions sit close to a documented operating limit, Helios recommends technical application review before a binding offer.

Typical service and maintenance

Hygienic seal inspection every 1,500 operating hours or per validated plant maintenance plan