

Helios Process Pump Family - Selection Guide

Quick reference for commercial and service teams

Document ID	HEL-PUMP-FAMILY-2026
Version	1.0
Status	Approved
Effective date	01 February 2026
Owner	Product Management
Access	Sales, Service, Engineering

Family overview

This guide provides initial product-family orientation only. It does not replace model-specific manuals, seal guidance or application engineering review.

Model comparison

Model	Primary use	Max pressure	Continuous temp	Flow range	Default seal
HX-240	General industrial process pump for water and light chemical service	10 bar	95°C	15-85 m³/h	EPDM mechanical seal
HX-300	High-pressure process pump for demanding industrial transfer	16 bar	110°C	20-120 m³/h	FKM mechanical seal
HX-400	Heavy-duty pump for high-temperature, high-pressure continuous process duties	20 bar	145°C	30-180 m³/h	FKM mechanical seal
HX-520	Hygienic pump for food, beverage and pharmaceutical cleaning	12 bar	135°C	10-100 m³/h	EPDM hygienic

Selection rules

- Use HX-240 for general process duties within 10 bar and 95°C pump-body limits.
- Use HX-300 where pressure requirements exceed HX-240 capability but temperature remains within 110°C.
- Use HX-400 for sustained high-temperature or high-pressure process duty.
- Use HX-520 for hygienic CIP and validated cleanability requirements.
- Seal temperature limits can be lower than pump-body limits; always validate both.