

Proposal PR-2026-026 - MedicaNova SA

Technical-commercial proposal for Pharmaceutical manufacturing application

Proposal ID	PR-2026-026
Customer	MedicaNova SA
Country	France
Date	2026-03-08
Status	Closed / Historical
Owner	Helios Sales Engineering
Access	Sales, Service

1. Customer requirement

Requirement	Customer condition
Fluid	Purified-water / CIP service
Operating temperature	132°C
System pressure	9 bar
Required flow	55 m³/h
Duty	Continuous hot circulation

2. Proposed solution

HX-520 with hygienic FKM seal

132°C is above standard hygienic EPDM continuous guidance, therefore hygienic FKM was specified.

Reference product limits considered during proposal preparation: 12 bar maximum pressure; 135°C continuous; 145°C for short sterilisation cycles up to 30 minutes; 10-100 m³/h flow range.

3. Configuration notes

- Wetted material: 316L electropolished wetted parts, Ra ≤ 0.8 µm.
- Seal arrangement: hygienic FKM seal.
- Final motor sizing to be confirmed against detailed duty point and site electrical standard.
- Installation design, pipe stress and NPSH validation remain customer / EPC responsibilities unless explicitly included.

4. Commercial assumptions

- Proposal is based on the stated process conditions only.
- Material and seal compatibility are subject to complete fluid information.
- Any change in temperature, pressure, fluid composition or duty cycle requires review.
- This historical proposal is provided as enterprise knowledge and is not a current quotation.

5. Sales-engineering note

This proposal may be used as precedent for similar applications, but the current approved product documentation and latest customer conditions must take precedence.