

Scan Report

June 23, 2026

Summary

This document reports on the results of an automatic security scan. All dates are displayed using the timezone “Coordinated Universal Time”, which is abbreviated “UTC”. The task was “meta_2”. The scan started at Tue Jun 23 04:56:44 2026 UTC and ended at Tue Jun 23 05:40:18 2026 UTC. The report first summarises the results found. Then, for each host, the report describes every issue found. Please consider the advice given in each description, in order to rectify the issue.

Contents

1	Result Overview	2
1.1	Host Authentications	2
2	Results per Host	2
2.1	192.168.56.101	2
2.1.1	Critical 8009/tcp	3
2.1.2	Critical 3306/tcp	10
2.1.3	Critical 8787/tcp	11
2.1.4	Critical 80/tcp	12
2.1.5	Critical 25/tcp	14
2.1.6	Critical 5432/tcp	15
2.1.7	Critical 513/tcp	15
2.1.8	Critical general/tcp	16
2.1.9	Critical 512/tcp	17
2.1.10	Critical 21/tcp	18
2.1.11	Critical 5900/tcp	19
2.1.12	Critical 1524/tcp	20
2.1.13	Critical 6200/tcp	21
2.1.14	Critical 3632/tcp	21
2.1.15	High 2121/tcp	22
2.1.16	High 80/tcp	24
2.1.17	High 5432/tcp	28

2.1.18	High 513/tcp	30
2.1.19	High 1099/tcp	31
2.1.20	High 21/tcp	33
2.1.21	High 514/tcp	34
2.1.22	Medium 2121/tcp	35
2.1.23	Medium 80/tcp	36
2.1.24	Medium 25/tcp	50
2.1.25	Medium 5432/tcp	69
2.1.26	Medium 22/tcp	87
2.1.27	Medium 21/tcp	91
2.1.28	Medium 445/tcp	93
2.1.29	Medium 23/tcp	94
2.1.30	Medium 5900/tcp	95
2.1.31	Low general/icmp	96
2.1.32	Low 25/tcp	97
2.1.33	Low 5432/tcp	103
2.1.34	Low 22/tcp	106
2.1.35	Low general/tcp	107

1 Result Overview

Host	Critical	High	Medium	Low	Log	False P.
192.168.56.101	14	9	40	6	0	0
Total: 1	14	9	40	6	0	0

Vendor security updates are not trusted.

Overrides are off. Even when a result has an override, this report uses the actual threat of the result.

Information on overrides is included in the report.

Notes are included in the report.

This report might not show details of all issues that were found.

Issues with the threat level “Log” are not shown.

Issues with the threat level “Debug” are not shown.

Issues with the threat level “False Positive” are not shown.

Only results with a minimum QoD of 70 are shown.

This report contains all 69 results selected by the filtering described above. Before filtering there were 633 results.

1.1 Host Authentications

Host	Protocol	Result	Port/User
192.168.56.101	SMB	Success	Protocol SMB, Port 445, User

2 Results per Host

2.1 192.168.56.101

Host scan start Tue Jun 23 04:57:43 2026 UTC

Host scan end Tue Jun 23 05:40:04 2026 UTC

Service (Port)	Threat Level
8009/tcp	Critical
3306/tcp	Critical
8787/tcp	Critical
80/tcp	Critical
25/tcp	Critical
5432/tcp	Critical
513/tcp	Critical
general/tcp	Critical
512/tcp	Critical

... (continues) ...

... (continued) ...

Service (Port)	Threat Level
21/tcp	Critical
5900/tcp	Critical
1524/tcp	Critical
6200/tcp	Critical
3632/tcp	Critical
2121/tcp	High
80/tcp	High
5432/tcp	High
513/tcp	High
1099/tcp	High
21/tcp	High
514/tcp	High
2121/tcp	Medium
80/tcp	Medium
25/tcp	Medium
5432/tcp	Medium
22/tcp	Medium
21/tcp	Medium
445/tcp	Medium
23/tcp	Medium
5900/tcp	Medium
general/icmp	Low
25/tcp	Low
5432/tcp	Low
22/tcp	Low
general/tcp	Low

2.1.1 Critical 8009/tcp

Critical (CVSS: 9.8)

NVT: Apache Tomcat AJP RCE Vulnerability (Ghostcat) - Active Check

Summary

Apache Tomcat is prone to a remote code execution (RCE) vulnerability in the AJP connector dubbed 'Ghostcat'.

Quality of Detection (QoD): 99%

Vulnerability Detection Result

It was possible to read the file "/WEB-INF/web.xml" through the AJP connector.

Result:

```
AB 8\x0004 Ã\x0088 \x00020K \x0001 \x000CContent-Type \x001Ctext/html; charset=
↳ISO-8859-1 AB\x001FÃ\x0003\x001FÃ_<!--
```

... continues on next page ...

...continued from previous page...

Licensed to the Apache Software Foundation (ASF) under one or more contributor license agreements. See the NOTICE file distributed with this work for additional information regarding copyright ownership. The ASF licenses this file to You under the Apache License, Version 2.0 (the "License"); you may not use this file except in compliance with the License. You may obtain a copy of the License at

<http://www.apache.org/licenses/LICENSE-2.0>

Unless required by applicable law or agreed to in writing, software distributed under the License is distributed on an "AS IS" BASIS, WITHOUT WARRANTIES OR CONDITIONS OF ANY KIND, either express or implied. See the License for the specific language governing permissions and limitations under the License.

-->

```
<?xml version="1.0" encoding="ISO-8859-1"?>
<!DOCTYPE html PUBLIC "-//W3C//DTD XHTML 1.0 Strict//EN"
    "http://www.w3.org/TR/xhtml1/DTD/xhtml1-strict.dtd">
<html xmlns="http://www.w3.org/1999/xhtml" xml:lang="en" lang="en">
  <head>
    <title>Apache Tomcat/5.5</title>
    <style type="text/css">
      /**/
        body {
          color: #000000;
          background-color: #FFFFFF;
          font-family: Arial, "Times New Roman", Times, serif;
          margin: 10px 0px;
        }
        img {
          border: none;
        }

        a:link, a:visited {
          color: blue
        }
        th {
          font-family: Verdana, "Times New Roman", Times, serif;
          font-size: 110%;
          font-weight: normal;
          font-style: italic;
          background: #D2A41C;
          text-align: left;
        }
        td {
          color: #000000;
          font-family: Arial, Helvetica, sans-serif;
        }
      ]]]&gt;</pre>
</div>
<div data-bbox="155 799 377 814" data-label="Text">
<p>...continues on next page ...</p>
</div>
```

...continued from previous page ...

```

td.menu {
    background: #FFDC75;
}
.center {
    text-align: center;
}
.code {
    color: #000000;
    font-family: "Courier New", Courier, monospace;
    font-size: 110%;
    margin-left: 2.5em;
}

#banner {
    margin-bottom: 12px;
}
p#congrats {
    margin-top: 0;
    font-weight: bold;
    text-align: center;
}
p#footer {
    text-align: right;
    font-size: 80%;
}
/*]]>*/
</style>
</head>
<body>
<!-- Header -->
<table id="banner" width="100%">
    <tr>
        <td align="left" style="width:130px">
            <a href="http://tomcat.apache.org/">
                />
            </a>
        </td>
        <td align="left" valign="top"><b>Apache Tomcat/5.5</b></td>
        <td align="right">
            <a href="http://www.apache.org/">
                
            </a>
        </td>
    </tr>
</table>

```

...continues on next page ...

...continued from previous page ...

```

<table>
  <tr>
    <!-- Table of Contents -->
    <td valign="top">
      <table width="100%" border="1" cellspacing="0" cellpadding="3">
        <tr>
          <th>Administration</th>
        </tr>
        <tr>
          <td class="menu">
            <a href="manager/status">Status</a><br/>
            <a href="admin">Tomcat&nbsp;Administration</a><br/>
            <a href="manager/html">Tomcat&nbsp;Manager</a><br/>
            &nbsp;
          </td>
        </tr>
      </table>
    <br />
    <table width="100%" border="1" cellspacing="0" cellpadding="3">
      <tr>
        <th>Documentation</th>
      </tr>
      <tr>
        <td class="menu">
          <a href="RELEASE-NOTES.txt">Release&nbsp;Notes</a><br/>
          <a href="tomcat-docs/changelog.html">Change&nbsp;Log</a><br/>
          <a href="tomcat-docs">Tomcat&nbsp;Documentation</a><br/>
          &nbsp;
          &nbsp;
        </td>
      </tr>
    </table>

    <br/>
    <table width="100%" border="1" cellspacing="0" cellpadding="3">
      <tr>
        <th>Tomcat Online</th>
      </tr>
      <tr>
        <td class="menu">
          <a href="http://tomcat.apache.org/">Home&nbsp;Page</a><br/>
          <a href="http://tomcat.apache.org/faq/">FAQ</a><br/>
          <a href="http://tomcat.apache.org/bugreport.html">Bug&nbsp;D
          <a href="http://issues.apache.org/bugzilla/buglist.cgi?bug_s
          &bug_status=UNCONFIRMED&amp;bug_status=NEW&amp;bug_status=ASSIGNED&amp;bug_status=RE
...continues on next page ...

```

...continued from previous page...	
<pre> ↵OPENED&bug_status=RESOLVED&resolution=LATER&resolution=REMIND& ↵resolution=---&bugidtype=include&product=Tomcat+5&cmdtype=doit& ↵;order=Importance">Open Bugs
 Users&Mailing&List
 Developers&Mailing&List
 IRC
 &nbsp; </td> </tr> </table>
 <table width="100%" border="1" cellspacing="0" cellpadding="3"> <tr> <th>Examples</th> </tr> <tr> <td class="menu"> JSP&Examples
 Servlet&Examples
 WebDAV&capabilities
 &nbsp; </td> </tr> </table>
 <table width="100%" border="1" cellspacing="0" cellpadding="3"> <tr> <th>Miscellaneous</th> </tr> <tr> <td class="menu"> Sun's&Java& ↵bsp;Server&Pages&Site
 Sun's&Se ↵rvlet&Site
 &nbsp; </td> </tr> </table> </td> <td style="width:20px">&nbsp;</td> <!-- Body --> </pre>	
...continues on next page...	

...continued from previous page ... <pre> <td align="left" valign="top"> <p id="congrats">If you're seeing this page via a web browser, it mean ↳s you've setup Tomcat successfully. Congratulations!</p> <p>As you may have guessed by now, this is the default Tomcat home pag ↳e. It can be found on the local filesystem at:</p> <p class="code">\${CATALINA_HOME}/webapps/ROOT/index.jsp</p> <p>where "\${CATALINA_HOME}" is the root of the Tomcat installation direc ↳tory. If you're seeing this page, and you don't think you should be, then eith ↳er you're either a user who has arrived at new installation of Tomcat, or you' ↳re an administrator who hasn't got his/her setup quite right. Providing the la ↳tter is the case, please refer to the Tomcat Documentati ↳on for more detailed setup and administration information than is found in ↳ the INSTALL file.</p> <p>NOTE: This page is precompiled. If you change it, this pag ↳e will not change since it was compiled into a servlet at build time. (See <tt>\${CATALINA_HOME}/webapps/ROOT/WEB-INF/web.xml</tt> as t ↳o how it was mapped.) </p> <p>NOTE: For security reasons, using the administration webapp is restricted to users with role "admin". The manager webapp is restricted to users with role "manager". Users are defined in <code>\${CATALINA_HOME}/conf/tomcat-users.xml</cod ↳e.</p> <p>Included with this release are a host of sample Servlets and JSPs ↳ (with associated source code), extensive documentation (including the Servlet ↳ 2.4 and JSP 2.0 API JavaDoc), and an introductory guide to developing web app ↳lications.</p> <p>Tomcat mailing lists are available at the Tomcat project web site ↳:</p> users@tomc </pre>	Solution: Solution type: VendorFix - Update Apache Tomcat to version 7.0.100, 8.5.51, 9.0.31 or later - For other products using Tomcat please contact the vendor for more information on fixed versions
Affected Software/OS Apache Tomcat versions prior 7.0.100, 8.5.51 or 9.0.31 when the AJP connector is enabled. Other products like JBoss or Wildfly which are using Tomcat might be affected as well.	Vulnerability Insight ... continues on next page ...

...continued from previous page...
Apache Tomcat server has a file containing vulnerability, which can be used by an attacker to read or include any files in all webapp directories on Tomcat, such as webapp configuration files or source code.
Vulnerability Detection Method Sends a crafted AJP request and checks the response. Details: Apache Tomcat AJP RCE Vulnerability (Ghostcat) - Active Check OID:1.3.6.1.4.1.25623.1.0.143545 Version used: 2026-03-18T05:59:10Z
References cve: CVE-2020-1938 url: https://lists.apache.org/thread/bnys5lvgl875dsslkx2vmwxv833l35x url: https://tomcat.apache.org/security-9.html#Fixed_in_Apache_Tomcat_9.0.31 url: https://tomcat.apache.org/security-8.html#Fixed_in_Apache_Tomcat_8.5.51 url: https://tomcat.apache.org/security-7.html#Fixed_in_Apache_Tomcat_7.0.100 url: https://web.archive.org/web/20250114042903/https://www.chaitin.cn/en/ghostcat url: https://www.cnvd.org.cn/flaw/show/CNVD-2020-10487 url: https://github.com/YDHCUI/CNVD-2020-10487-Tomcat-Ajp-lfi url: https://securityboulevard.com/2020/02/patch-your-tomcat-and-jboss-instances-to-protect-from-ghostcat-vulnerability-cve-2020-1938-and/ url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog cisa: Known Exploited Vulnerability (KEV) catalog cert-bund: WID-SEC-2024-0528 cert-bund: WID-SEC-2023-2480 cert-bund: CB-K20/0711 cert-bund: CB-K20/0705 cert-bund: CB-K20/0693 cert-bund: CB-K20/0555 cert-bund: CB-K20/0543 cert-bund: CB-K20/0154 dfn-cert: DFN-CERT-2021-1736 dfn-cert: DFN-CERT-2020-1508 dfn-cert: DFN-CERT-2020-1413 dfn-cert: DFN-CERT-2020-1276 dfn-cert: DFN-CERT-2020-1134 dfn-cert: DFN-CERT-2020-0850 dfn-cert: DFN-CERT-2020-0835 dfn-cert: DFN-CERT-2020-0821 dfn-cert: DFN-CERT-2020-0569 dfn-cert: DFN-CERT-2020-0557 dfn-cert: DFN-CERT-2020-0501 dfn-cert: DFN-CERT-2020-0381

[[return to 192.168.56.101](#)]

2.1.2 Critical 3306/tcp

Critical (CVSS: 9.8)
NVT: MySQL / MariaDB Default Credentials (MySQL Protocol)
Product detection result cpe:/a:mysql:mysql:5.0.51a Detected by MariaDB / Oracle MySQL Detection (MySQL Protocol) (OID: 1.3.6.1.4.1. ↪25623.1.0.100152)
Summary It was possible to login into the remote MySQL using default credentials.
Quality of Detection (QoD): 95%
Vulnerability Detection Result It was possible to login as user "root" with an empty password.
Solution: Solution type: Mitigation - Change the password as soon as possible - Contact the vendor for other possible fixes / updates
Affected Software/OS The following products are known to use such weak credentials: - CVE-2001-0645: Symantec/AXENT NetProwler 3.5.x - CVE-2002-1809: Windows binary release of MySQL 3.23.2 through 3.23.52 - CVE-2004-1532: AppServ 2.5.x and earlier - CVE-2004-2357: Proofpoint Protection Server - CVE-2006-1451: MySQL Manager in Apple Mac OS X 10.3.9 and 10.4.6 - CVE-2007-2554: Associated Press (AP) Newspaper 4.0.1 and earlier - CVE-2007-6081: AdventNet EventLog Analyzer build 4030 - CVE-2009-0919: XAMPP - CVE-2014-3419: Infoblox NetMRI before 6.8.5 - CVE-2015-4669: Xsuite 2.x - CVE-2016-6531, CVE-2018-15719: Open Dental before version 18.4 - CVE-2024-22901: Vinchin Backup & Recovery 7.2 and prior - No CVE / GHSA-g38h-mr9p-fjmf: Vvweb CMS 1.0.8 and prior Other products might be affected as well.
Vulnerability Detection Method Details: MySQL / MariaDB Default Credentials (MySQL Protocol) OID:1.3.6.1.4.1.25623.1.0.103551 Version used: 2026-05-27T08:10:51Z
... continues on next page ...

...continued from previous page ...
Product Detection Result Product: cpe:/a:mysql:mysql:5.0.51a Method: MariaDB / Oracle MySQL Detection (MySQL Protocol) OID: 1.3.6.1.4.1.25623.1.0.100152)
References cve: CVE-2001-0645 cve: CVE-2002-1809 cve: CVE-2004-1532 cve: CVE-2004-2357 cve: CVE-2006-1451 cve: CVE-2007-2554 cve: CVE-2007-6081 cve: CVE-2009-0919 cve: CVE-2014-3419 cve: CVE-2015-4669 cve: CVE-2016-6531 cve: CVE-2018-15719 cve: CVE-2024-22901

[\[return to 192.168.56.101 \]](#)

2.1.3 Critical 8787/tcp

Critical (CVSS: 10.0)
NVT: Distributed Ruby (dRuby/DRb) Multiple RCE Vulnerabilities
Summary Systems using Distributed Ruby (dRuby/DRb), which is available in Ruby versions 1.6 and later, may permit unauthorized systems to execute distributed commands.
Quality of Detection (QoD): 99%
Vulnerability Detection Result The service is running in \$SAFE >= 1 mode. However it is still possible to run a ↵rbbitrary syscall commands on the remote host. Sending an invalid syscall the s ↵ervice returned the following response: Flo:Errno::ENOSYS:bt["3/usr/lib/ruby/1.8/drb/drb.rb:1555:in 'syscall'"0/usr/lib/ ↵ruby/1.8/drb/drb.rb:1555:in 'send'"4/usr/lib/ruby/1.8/drb/drb.rb:1555:in '__se ↵nd__'"A/usr/lib/ruby/1.8/drb/drb.rb:1555:in 'perform_without_block'"3/usr/lib/ ↵ruby/1.8/drb/drb.rb:1515:in 'perform'"5/usr/lib/ruby/1.8/drb/drb.rb:1589:in 'm ↵ain_loop'"0/usr/lib/ruby/1.8/drb/drb.rb:1585:in 'loop'"5/usr/lib/ruby/1.8/drb/ ↵...continues on next page ...

...continued from previous page...
<pre>↪drb.rb:1585:in 'main_loop'"1/usr/lib/ruby/1.8/drb/drb.rb:1581:in 'start'"5/usr ↪/lib/ruby/1.8/drb/drb.rb:1581:in 'main_loop'"/usr/lib/ruby/1.8/drb/drb.rb:143 ↪0:in 'run'"1/usr/lib/ruby/1.8/drb/drb.rb:1427:in 'start'"/usr/lib/ruby/1.8/dr ↪b/drb.rb:1427:in 'run'"6/usr/lib/ruby/1.8/drb/drb.rb:1347:in 'initialize'"/us ↪r/lib/ruby/1.8/drb/drb.rb:1627:in 'new'"9/usr/lib/ruby/1.8/drb/drb.rb:1627:in ↪'start_service'"/usr/sbin/druby_timeserver.rb:12:errnoi+:mesg"Function not im ↪plemented</pre>
Impact By default, Distributed Ruby does not impose restrictions on allowed hosts or set the \$SAFE environment variable to prevent privileged activities. If other controls are not in place, especially if the Distributed Ruby process runs with elevated privileges, an attacker could execute arbitrary system commands or Ruby scripts on the Distributed Ruby server. An attacker may need to know only the URI of the listening Distributed Ruby server to submit Ruby commands.
Solution: Solution type: Mitigation Administrators of environments that rely on Distributed Ruby should ensure that appropriate controls are in place. Code-level controls may include: - Implementing taint on untrusted input - Setting \$SAFE levels appropriately (>=2 is recommended if untrusted hosts are allowed to submit Ruby commands, and >=3 may be appropriate) - Including drb/acl.rb to set ACLEntry to restrict access to trusted hosts
Vulnerability Detection Method Send a crafted command to the service and check for a remote command execution via the instance_eval or syscall requests. Details: Distributed Ruby (dRuby/DRb) Multiple RCE Vulnerabilities OID:1.3.6.1.4.1.25623.1.0.108010 Version used: 2024-06-28T05:05:33Z
References url: https://tools.cisco.com/security/center/viewAlert.x?alertId=22750 url: http://www.securityfocus.com/bid/47071 url: http://blog.recurity-labs.com/archives/2011/05/12/druby_for_penetration_testing/ url: http://www.ruby-doc.org/stdlib-1.9.3/libdoc/drb/rdoc/DRb.html

[\[return to 192.168.56.101 \]](#)

2.1.4 Critical 80/tcp

Critical (CVSS: 10.0)
NVT: TWiki < 4.2.4 Multiple XSS / Command Execution Vulnerabilities
Summary TWiki is prone to multiple cross-site scripting (XSS) and command execution vulnerabilities.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 01.Feb.2003 Fixed version: 4.2.4
Impact Successful exploitation could allow execution of arbitrary script code or commands. This could let attackers steal cookie-based authentication credentials or compromise the affected application.
Solution: Solution type: VendorFix Update to version 4.2.4 or later.
Affected Software/OS TWiki versions prior to 4.2.4.
Vulnerability Insight The flaws are due to: - %URLPARAM}% variable is not properly sanitized which lets attackers conduct cross-site scripting attack. - %SEARCH}% variable is not properly sanitised before being used in an eval() call which lets the attackers execute perl code through eval injection attack.
Vulnerability Detection Method Details: TWiki < 4.2.4 Multiple XSS / Command Execution Vulnerabilities OID:1.3.6.1.4.1.25623.1.0.800320 Version used: 2025-12-11T05:46:19Z
References cve: CVE-2008-5304 cve: CVE-2008-5305 url: http://twiki.org/cgi-bin/view/Codev.SecurityAlert-CVE-2008-5304 url: http://www.securityfocus.com/bid/32668 url: http://www.securityfocus.com/bid/32669 url: http://twiki.org/cgi-bin/view/Codev/SecurityAlert-CVE-2008-5305

[[return to 192.168.56.101](#)]

2.1.5 Critical 25/tcp

Critical (CVSS: 9.3) NVT: SpamAssassin Milter Plugin 'mlfi_envrcpt()' Remote Arbitrary Command Injection Vulnerability - Active Check	
Summary SpamAssassin Milter Plugin is prone to a remote command injection vulnerability because it fails to adequately sanitize user-supplied input data.	
Quality of Detection (QoD): 70%	
Vulnerability Detection Result By sending the following SMTP command sequences using a 'sleep 16' it was determined that the system is answering with a delay of 16 seconds to the final request in comparison to the previous used commands: <pre>HELO kali MAIL FROM: openvasvt@kali RCPT TO: root+:"; sleep 16 ;"</pre>	
Impact Remote attackers can exploit this issue to execute arbitrary shell commands with root privileges.	
Solution: Solution type: WillNotFix No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.	
Affected Software/OS SpamAssassin Milter Plugin 0.3.1 is known to be affected. Other versions or products may also be vulnerable.	
Vulnerability Detection Method Sends multiple crafted SMTP commands including a 'sleep 16' and tries to determine if the answer of the service is delayed for these 16 seconds. Details: SpamAssassin Milter Plugin 'mlfi_envrcpt()' Remote Arbitrary Command Injection . <pre>↪.. OID:1.3.6.1.4.1.25623.1.0.100528 Version used: 2023-10-31T05:06:37Z</pre>	
References cve: CVE-2010-1132 url: http://www.securityfocus.com/bid/38578 url: http://seclists.org/fulldisclosure/2010/Mar/140	
... continues on next page ...	

...continued from previous page ...
dfn-cert: DFN-CERT-2010-0594
dfn-cert: DFN-CERT-2010-0494

[\[return to 192.168.56.101 \]](#)

2.1.6 Critical 5432/tcp

Critical (CVSS: 9.0)
NVT: PostgreSQL Default Credentials (PostgreSQL Protocol)
Product detection result cpe:/a:postgresql:postgresql:8.3.1 Detected by PostgreSQL Detection Consolidation (OID: 1.3.6.1.4.1.25623.1.0.12802 ↪5)
Summary It was possible to login into the remote PostgreSQL as user postgres using weak credentials.
Quality of Detection (QoD): 99%
Vulnerability Detection Result It was possible to login as user postgres with password "postgres".
Solution: Solution type: Mitigation Change the password as soon as possible.
Vulnerability Detection Method Details: PostgreSQL Default Credentials (PostgreSQL Protocol) OID:1.3.6.1.4.1.25623.1.0.103552 Version used: 2024-07-19T15:39:06Z
Product Detection Result Product: cpe:/a:postgresql:postgresql:8.3.1 Method: PostgreSQL Detection Consolidation OID: 1.3.6.1.4.1.25623.1.0.128025)

[\[return to 192.168.56.101 \]](#)

2.1.7 Critical 513/tcp

Critical (CVSS: 10.0) NVT: rlogin Passwordless Login
Summary The rlogin service allows root access without a password.
Quality of Detection (QoD): 80%
Vulnerability Detection Result It was possible to gain root access without a password.
Impact This vulnerability allows an attacker to gain complete control over the target system.
Solution: Solution type: Mitigation Disable the rlogin service and use alternatives like SSH instead.
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: rlogin Passwordless Login OID:1.3.6.1.4.1.25623.1.0.113766 Version used: 2020-09-30T09:30:12Z

[\[return to 192.168.56.101 \]](#)

2.1.8 Critical general/tcp

Critical (CVSS: 10.0) NVT: Operating System (OS) End of Life (EOL) Detection
Product detection result cpe:/o:canonical:ubuntu_linux:8.04 Detected by OS Detection Consolidation and Reporting (OID: 1.3.6.1.4.1.25623.1.0 ↪.105937)
Summary The Operating System (OS) on the remote host has reached the end of life (EOL) and should not be used anymore.
Quality of Detection (QoD): 80% ... continues on next page ...

...continued from previous page ...
Vulnerability Detection Result The "Ubuntu" Operating System on the remote host has reached the end of life. CPE: cpe:/o:canonical:ubuntu_linux:8.04 Installed version, build or SP: 8.04 EOL date: 2013-05-09 EOL info: https://documentation.ubuntu.com/project/release-team/list-of ↪-releases/
Impact An EOL version of an OS is not receiving any security updates from the vendor. Unfixed security vulnerabilities might be leveraged by an attacker to compromise the security of this host.
Solution: Solution type: Mitigation Update the OS on the remote host to a version which is still supported and receiving security updates by the vendor. Note / Important: Please create an override for this result if the target host is a: - Windows system with Extended Security Updates (ESU) - System with additional 3rd-party / non-vendor security updates like e.g. from 'TuxCare', 'Freexian Extended LTS' or similar
Vulnerability Detection Method Checks if an EOL version of an OS is present on the target host. Details: Operating System (OS) End of Life (EOL) Detection OID:1.3.6.1.4.1.25623.1.0.103674 Version used: 2025-05-21T05:40:19Z
Product Detection Result Product: cpe:/o:canonical:ubuntu_linux:8.04 Method: OS Detection Consolidation and Reporting OID: 1.3.6.1.4.1.25623.1.0.105937)

[[return to 192.168.56.101](#)]

2.1.9 Critical 512/tcp

Critical (CVSS: 10.0) NVT: The rexec service is running
Summary This remote host is running a rexec service.
... continues on next page ...

...continued from previous page ...
Quality of Detection (QoD): 80%
Vulnerability Detection Result The rexec service was detected on the target system.
Solution: Solution type: Mitigation Disable the rexec service and use alternatives like SSH instead.
Vulnerability Insight rexec (remote execution client for an exec server) has the same kind of functionality that rsh has: you can execute shell commands on a remote computer. The main difference is that rexec authenticate by reading the username and password *unencrypted* from the socket.
Vulnerability Detection Method Checks whether an rexec service is exposed on the target host. Details: The rexec service is running OID:1.3.6.1.4.1.25623.1.0.100111 Version used: 2023-09-12T05:05:19Z
References cve: CVE-1999-0618

[[return to 192.168.56.101](#)]

2.1.10 Critical 21/tcp

Critical (CVSS: 9.8)
NVT: vsftpd Compromised Source Packages Backdoor Vulnerability - Active Check
Summary vsftpd is prone to a backdoor vulnerability.
Quality of Detection (QoD): 99%
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact Attackers can exploit this issue to execute arbitrary commands in the context of the application. Successful attacks will compromise the affected application.
... continues on next page ...

...continued from previous page ...
Solution: Solution type: VendorFix The repaired package can be downloaded from the referenced vendor homepage. Please validate the package with its signature.
Affected Software/OS vsftpd 2.3.4 source packages downloaded between 20110630 and 20110703 are affected.
Vulnerability Insight The tainted source package contains a backdoor which opens a shell on port 6200/tcp.
Vulnerability Detection Method Details: vsftpd Compromised Source Packages Backdoor Vulnerability - Active Check OID:1.3.6.1.4.1.25623.1.0.103185 Version used: 2026-02-18T05:57:21Z
References cve: CVE-2011-2523 url: https://scarybeastsecurity.blogspot.com/2011/07/alert-vsftpd-download-backdoor.html url: https://web.archive.org/web/20210127090551/https://www.securityfocus.com/bid/48539/

[\[return to 192.168.56.101 \]](#)

2.1.11 Critical 5900/tcp

Critical (CVSS: 9.0) NVT: VNC Brute Force Login
Summary Try to log in with given passwords via VNC protocol.
Quality of Detection (QoD): 95%
Vulnerability Detection Result It was possible to connect to the VNC server with the password: password
Solution: Solution type: Mitigation Change the password to something hard to guess or enable password protection at all.
... continues on next page ...

...continued from previous page...

Vulnerability Insight

This script tries to authenticate to a VNC server with the passwords set in the password preference. It will also test and report if no authentication / password is required at all.

Note: Some VNC servers have a blacklisting scheme that blocks IP addresses after five unsuccessful connection attempts for a period of time. The script will abort the brute force attack if it encounters that it gets blocked.

Note as well that passwords can be max. 8 characters long.

Vulnerability Detection Method

Details: VNC Brute Force Login

OID:1.3.6.1.4.1.25623.1.0.106056

Version used: 2021-07-23T07:56:26Z

[\[return to 192.168.56.101 \]](#)

2.1.12 Critical 1524/tcp

Critical (CVSS: 10.0)

NVT: Possible Backdoor: Ingreslock

Summary

A backdoor is installed on the remote host.

Quality of Detection (QoD): 99%

Vulnerability Detection Result

The service is answering to an 'id;' command with the following response: uid=0(↔root) gid=0(root)

Impact

Attackers can exploit this issue to execute arbitrary commands in the context of the application. Successful attacks will compromise the affected isystem.

Solution:

Solution type: Workaround

A whole cleanup of the infected system is recommended.

Vulnerability Detection Method

Details: Possible Backdoor: Ingreslock

OID:1.3.6.1.4.1.25623.1.0.103549

Version used: 2023-07-25T05:05:58Z

[\[return to 192.168.56.101 \]](#)

2.1.13 Critical 6200/tcp

Critical (CVSS: 9.8)	
NVT: vsftpd Compromised Source Packages Backdoor Vulnerability - Active Check	
Summary	vsftpd is prone to a backdoor vulnerability.
Quality of Detection (QoD):	99%
Vulnerability Detection Result	Vulnerability was detected according to the Vulnerability Detection Method.
Impact	Attackers can exploit this issue to execute arbitrary commands in the context of the application. Successful attacks will compromise the affected application.
Solution:	
Solution type:	VendorFix
The repaired package can be downloaded from the referenced vendor homepage. Please validate the package with its signature.	
Affected Software/OS	vsftpd 2.3.4 source packages downloaded between 20110630 and 20110703 are affected.
Vulnerability Insight	The tainted source package contains a backdoor which opens a shell on port 6200/tcp.
Vulnerability Detection Method	Details: vsftpd Compromised Source Packages Backdoor Vulnerability - Active Check OID:1.3.6.1.4.1.25623.1.0.103185 Version used: 2026-02-18T05:57:21Z
References	cve: CVE-2011-2523 url: https://scarybeastsecurity.blogspot.com/2011/07/alert-vsftpd-download-backdoor.html url: https://web.archive.org/web/20210127090551/https://www.securityfocus.com/bid/48539/

[\[return to 192.168.56.101 \]](#)

2.1.14 Critical 3632/tcp

Critical (CVSS: 9.3)	
NVT: DistCC RCE Vulnerability (CVE-2004-2687)	
Summary	DistCC is prone to a remote code execution (RCE) vulnerability.
Quality of Detection (QoD):	99%
Vulnerability Detection Result	It was possible to execute the "id" command. Result: uid=1(daemon) gid=1(daemon)
Impact	DistCC by default trusts its clients completely that in turn could allow a malicious client to execute arbitrary commands on the server.
Solution:	
Solution type:	VendorFix
	Vendor updates are available. Please see the references for more information. For more information about DistCC's security see the references.
Vulnerability Insight	DistCC 2.x, as used in XCode 1.5 and others, when not configured to restrict access to the server port, allows remote attackers to execute arbitrary commands via compilation jobs, which are executed by the server without authorization checks.
Vulnerability Detection Method	Details: DistCC RCE Vulnerability (CVE-2004-2687) OID:1.3.6.1.4.1.25623.1.0.103553 Version used: 2022-07-07T10:16:06Z
References	cve: CVE-2004-2687 url: https://distcc.github.io/security.html url: https://web.archive.org/web/20150511045306/http://archives.neohapsis.com:80 ↪/archives/bugtraq/2005-03/0183.html dfn-cert: DFN-CERT-2019-0381

[[return to 192.168.56.101](#)]

2.1.15 High 2121/tcp

High (CVSS: 7.5)
NVT: FTP Brute Force Logins With Default Credentials Reporting
Summary It was possible to login into the remote FTP server using weak/known credentials.
Quality of Detection (QoD): 95%
Vulnerability Detection Result It was possible to login with the following credentials <User>:<Password> msfadmin:msfadmin postgres:postgres service:service user:user
Impact This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.
Solution: Solution type: Mitigation Change the password as soon as possible.
Vulnerability Insight The following devices are / software is known to be affected: - CVE-2001-1594: Codonics printer FTP service as used in GE Healthcare eNTEGRA P&R - CVE-2013-7404: GE Healthcare Discovery NM 750b - CVE-2014-9198: Schneider Electric ETG3000 FactoryCast HMI gateways - CVE-2015-7261: QNAP iArtist Lite distributed with QNAP Signage Station - CVE-2016-8731: Foscam C1 devices - CVE-2017-8218: vsftpd on TP-Link C2 and C20i devices - CVE-2018-9068: IMM2 for IBM and Lenovo System x - CVE-2018-17771: Ingenico Telium 2 PoS terminals - CVE-2018-19063, CVE-2018-19064: Foscam C2 and Opticam i5 devices - CVE-2018-25147: Microhard Systems IPn4G - CVE-2020-36915: Adtec Digital SignEdge Digital Signage Player Note: As the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.
Vulnerability Detection Method Reports weak/known credentials detected by the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717). Details: FTP Brute Force Logins With Default Credentials Reporting OID:1.3.6.1.4.1.25623.1.0.108718
... continues on next page ...

...continued from previous page ...
Version used: 2026-01-16T15:42:49Z
References cve: CVE-1999-0501 cve: CVE-1999-0502 cve: CVE-1999-0507 cve: CVE-1999-0508 cve: CVE-2001-1594 cve: CVE-2013-7404 cve: CVE-2014-9198 cve: CVE-2015-7261 cve: CVE-2016-8731 cve: CVE-2017-8218 cve: CVE-2018-9068 cve: CVE-2018-17771 cve: CVE-2018-19063 cve: CVE-2018-19064 cve: CVE-2018-25147 cve: CVE-2020-36915

[\[return to 192.168.56.101 \]](#)

2.1.16 High 80/tcp

High (CVSS: 7.5) NVT: Test HTTP dangerous methods
Summary Misconfigured web servers allows remote clients to perform dangerous HTTP methods such as PUT and DELETE.
Quality of Detection (QoD): 99%
Vulnerability Detection Result We could upload the following files via the PUT method at this web server: http://192.168.56.101/dav/puttest1280713373.html We could delete the following files via the DELETE method at this web server: http://192.168.56.101/dav/puttest1280713373.html
Impact - Enabled PUT method: This might allow an attacker to upload and run arbitrary code on this web server. - Enabled DELETE method: This might allow an attacker to delete additional files on this web server.
... continues on next page ...

...continued from previous page ...
Solution: Solution type: Mitigation Use access restrictions to these dangerous HTTP methods or disable them completely.
Affected Software/OS Web servers with enabled PUT and/or DELETE methods.
Vulnerability Detection Method Checks if dangerous HTTP methods such as PUT and DELETE are enabled and can be misused to upload or delete files. Details: Test HTTP dangerous methods OID:1.3.6.1.4.1.25623.1.0.10498 Version used: 2023-08-01T13:29:10Z
References url: http://www.securityfocus.com/bid/12141 owasp: OWASP-CM-001

High (CVSS: 7.5)
NVT: EasyPHP Webserver <= 12.1 Multiple Vulnerabilities - Active Check
Summary EasyPHP Webserver is prone to multiple vulnerabilities.
Quality of Detection (QoD): 99%
Vulnerability Detection Result Vulnerable URL: http://192.168.56.101/phpinfo.php Concluded from: <pre><title>phpinfo()</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIV ↵E" /></head> <tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/ph ↵p5/cgi </td></tr> <h2>PHP Core</h2> <h2>PHP Variables</h2></pre>
Impact Successful exploitation will allow attackers to gain administrative access, disclose the information, inject PHP code/shell and execute a remote PHP Code.
Solution: Solution type: WillNotFix
... continues on next page ...

...continued from previous page ...
No known solution was made available for at least one year since the disclosure of this vulnerability. Likely none will be provided anymore. General solution options are to upgrade to a newer release, disable respective features, remove the product or replace the product by another one.
Affected Software/OS EasyPHP version 12.1 and prior.
Vulnerability Insight The bug in EasyPHP WebServer Manager, its skipping authentication for certain requests. Which allows to bypass the authentication, disclose the information or execute a remote PHP code.
Vulnerability Detection Method Sends a crafted HTTP GET request and checks the response. Note: It is currently expected that a result of this VT is reported if the system is generally exposing a phpinfo() output on the relevant URL / endpoint (independent from the running product). Exposing such sensitive information is generally seen as a security misconfiguration and should be avoided. Details: EasyPHP Webserver <= 12.1 Multiple Vulnerabilities - Active Check OID:1.3.6.1.4.1.25623.1.0.803189 Version used: 2025-11-11T05:40:18Z
References url: https://cxsecurity.com/issue/WLB-2013040069

High (CVSS: 7.5)

NVT: PHP < 5.3.13, 5.4.x < 5.4.3 Multiple Vulnerabilities - Active Check

Summary

PHP is prone to multiple vulnerabilities.

Quality of Detection (QoD): 95%

Vulnerability Detection Result

By doing the following HTTP POST request:

"HTTP POST" body : <?php phpinfo();?>

URL : http://192.168.56.101/cgi-bin/php?%2D%64+%61%6C%6C%6F%77%5F%7
↳5%72%6C%5F%69%6E%63%6C%75%64%65%3D%6F%6E+%2D%64+%73%61%66%65%5F%6D%6F%64%65%3D
↳%6F%66%66+%2D%64+%73%75%68%6F%73%69%6E%2E%73%69%6D%75%6C%61%74%69%6F%6E%3D%6F%
↳6E+%2D%64+%64%69%73%61%62%6C%65%5F%66%75%6E%63%74%69%6F%6E%73%3D%22%22+%2D%64+
↳%6F%70%65%6E%5F%62%61%73%65%64%69%72%3D%6E%6F%6E%65+%2D%64+%61%75%74%6F%5F%70%
↳72%65%70%65%6E%64%5F%66%69%6C%65%3D%70%68%70%3A%2F%2F%69%6E%70%75%74+%2D%64+%6
↳3%67%69%2E%66%6F%72%63%65%5F%72%65%64%69%72%65%63%74%3D%30+%2D%64+%63%67%69%2E
↳%72%65%64%69%72%65%63%74%5F%73%74%61%74%75%73%5F%65%6E%76%3D%30+%2D%6E

... continues on next page ...

...continued from previous page ...
it was possible to execute the "<?php phpinfo();?>" command. Result: <pre> <title>phpinfo()</title><meta name="ROBOTS" content="NOINDEX,NOFOLLOW,NOARCHIV ↵E" /></head> <tr><td class="e">Configuration File (php.ini) Path </td><td class="v">/etc/ph ↵p5/cgi </td></tr> <h2>PHP Core</h2> <h2>PHP Variables</h2> </pre>
Impact Exploiting this issue allows remote attackers to view the source code of files in the context of the server process. This may allow the attacker to obtain sensitive information and to run arbitrary PHP code on the affected computer. Other attacks are also possible.
Solution: Solution type: VendorFix PHP: Update to version 5.3.13, 5.4.3 or later - Other products / applications: Please contact the vendor for a solution
Affected Software/OS PHP versions prior to 5.3.13 and 5.4.x prior to 5.4.3. Other products / applications might be affected by the tested CVE-2012-1823 as well.
Vulnerability Insight When PHP is used in a CGI-based setup (such as Apache's mod_cgid), the php-cgi receives a processed query string parameter as command line arguments which allows command-line switches, such as -s, -d or -c to be passed to the php-cgi binary, which can be exploited to disclose source code and obtain arbitrary code execution. An example of the -s command, allowing an attacker to view the source code of index.php is below: http://example.com/index.php?-s
Vulnerability Detection Method Send multiple a crafted HTTP POST requests and checks the responses. Notes: - This script checks for the presence of CVE-2012-1823 which indicates that the system is also affected by the other included CVEs. - It is currently expected that a result of this VT is reported if the system is generally exposing a phpinfo() output on the relevant URL / endpoint (independent from the running product). Exposing such sensitive information is generally seen as a security misconfiguration and should be avoided. Details: PHP < 5.3.13, 5.4.x < 5.4.3 Multiple Vulnerabilities - Active Check OID:1.3.6.1.4.1.25623.1.0.103482 Version used: 2026-04-23T06:21:05Z
References
... continues on next page ...

...continued from previous page ...

```

cve: CVE-2012-1823
cve: CVE-2012-2311
cve: CVE-2012-2336
cve: CVE-2012-2335
url: https://web.archive.org/web/20190212080415/http://eindbazen.net/2012/05/php
    ↪-cgi-advisory-cve-2012-1823/
url: https://www.kb.cert.org/vuls/id/520827
url: https://bugs.php.net/bug.php?id=61910
url: https://www.php.net/manual/en/security.cgi-bin.php
url: https://web.archive.org/web/20210121223743/http://www.securityfocus.com/bid
    ↪/53388
url: https://web.archive.org/web/20120709064615/http://www.h-online.com/open/new
    ↪s/item/Critical-open-hole-in-PHP-creates-risks-Update-2-1567532.html
url: https://www.cisa.gov/known-exploited-vulnerabilities-catalog
cisa: Known Exploited Vulnerability (KEV) catalog
dfn-cert: DFN-CERT-2013-1494
dfn-cert: DFN-CERT-2012-1316
dfn-cert: DFN-CERT-2012-1276
dfn-cert: DFN-CERT-2012-1268
dfn-cert: DFN-CERT-2012-1267
dfn-cert: DFN-CERT-2012-1266
dfn-cert: DFN-CERT-2012-1173
dfn-cert: DFN-CERT-2012-1101
dfn-cert: DFN-CERT-2012-0994
dfn-cert: DFN-CERT-2012-0993
dfn-cert: DFN-CERT-2012-0992
dfn-cert: DFN-CERT-2012-0920
dfn-cert: DFN-CERT-2012-0915
dfn-cert: DFN-CERT-2012-0914
dfn-cert: DFN-CERT-2012-0913
dfn-cert: DFN-CERT-2012-0907
dfn-cert: DFN-CERT-2012-0906
dfn-cert: DFN-CERT-2012-0900
dfn-cert: DFN-CERT-2012-0880
dfn-cert: DFN-CERT-2012-0878

```

[\[return to 192.168.56.101 \]](#)**2.1.17 High 5432/tcp**

High (CVSS: 7.4)

NVT: SSL/TLS: OpenSSL CCS Man in the Middle Security Bypass Vulnerability

Summary

... continues on next page ...

...continued from previous page ...
OpenSSL is prone to a security bypass vulnerability.
Quality of Detection (QoD): 70%
Vulnerability Detection Result Vulnerability was detected according to the Vulnerability Detection Method.
Impact Successfully exploiting this issue may allow attackers to obtain sensitive information by conducting a man-in-the-middle attack. This may lead to other attacks.
Solution: Solution type: VendorFix Updates are available. Please see the references for more information.
Affected Software/OS OpenSSL before 0.9.8za, 1.0.0 before 1.0.0m and 1.0.1 before 1.0.1h.
Vulnerability Insight OpenSSL does not properly restrict processing of ChangeCipherSpec messages, which allows man-in-the-middle attackers to trigger use of a zero-length master key in certain OpenSSL-to-OpenSSL communications, and consequently hijack sessions or obtain sensitive information, via a crafted TLS handshake, aka the 'CCS Injection' vulnerability.
Vulnerability Detection Method Send two SSL ChangeCipherSpec request and check the response. Details: SSL/TLS: OpenSSL CCS Man in the Middle Security Bypass Vulnerability OID:1.3.6.1.4.1.25623.1.0.105042 Version used: 2025-01-17T15:39:18Z
References cve: CVE-2014-0224 url: https://www.openssl.org/news/secadv/20140605.txt url: http://www.securityfocus.com/bid/67899 cert-bund: WID-SEC-2026-0180 cert-bund: WID-SEC-2023-0500 cert-bund: CB-K15/0567 cert-bund: CB-K15/0415 cert-bund: CB-K15/0384 cert-bund: CB-K15/0080 cert-bund: CB-K15/0079 cert-bund: CB-K15/0074 cert-bund: CB-K14/1617 cert-bund: CB-K14/1537 cert-bund: CB-K14/1299 cert-bund: CB-K14/1297
... continues on next page ...

...continued from previous page ...

```

cert-bund: CB-K14/1294
cert-bund: CB-K14/1202
cert-bund: CB-K14/1174
cert-bund: CB-K14/1153
cert-bund: CB-K14/0876
cert-bund: CB-K14/0756
cert-bund: CB-K14/0746
cert-bund: CB-K14/0736
cert-bund: CB-K14/0722
cert-bund: CB-K14/0716
cert-bund: CB-K14/0708
cert-bund: CB-K14/0684
cert-bund: CB-K14/0683
cert-bund: CB-K14/0680
dfn-cert: DFN-CERT-2016-0388
dfn-cert: DFN-CERT-2015-0593
dfn-cert: DFN-CERT-2015-0427
dfn-cert: DFN-CERT-2015-0396
dfn-cert: DFN-CERT-2015-0082
dfn-cert: DFN-CERT-2015-0079
dfn-cert: DFN-CERT-2015-0078
dfn-cert: DFN-CERT-2014-1717
dfn-cert: DFN-CERT-2014-1632
dfn-cert: DFN-CERT-2014-1364
dfn-cert: DFN-CERT-2014-1357
dfn-cert: DFN-CERT-2014-1350
dfn-cert: DFN-CERT-2014-1265
dfn-cert: DFN-CERT-2014-1209
dfn-cert: DFN-CERT-2014-0917
dfn-cert: DFN-CERT-2014-0789
dfn-cert: DFN-CERT-2014-0778
dfn-cert: DFN-CERT-2014-0768
dfn-cert: DFN-CERT-2014-0752
dfn-cert: DFN-CERT-2014-0747
dfn-cert: DFN-CERT-2014-0738
dfn-cert: DFN-CERT-2014-0715
dfn-cert: DFN-CERT-2014-0714
dfn-cert: DFN-CERT-2014-0709

```

[\[return to 192.168.56.101 \]](#)

2.1.18 High 513/tcp

High (CVSS: 7.5)
NVT: The rlogin service is running
Summary This remote host is running a rlogin service.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The rlogin service is running on the target system.
Solution: Solution type: Mitigation Disable the rlogin service and use alternatives like SSH instead.
Vulnerability Insight rlogin has several serious security problems, - all information, including passwords, is transmitted unencrypted. - .rlogin (or .rhosts) file is easy to misuse (potentially allowing anyone to login without a password)
Vulnerability Detection Method Details: The rlogin service is running OID:1.3.6.1.4.1.25623.1.0.901202 Version used: 2025-03-05T05:38:53Z
References cve: CVE-1999-0651

[\[return to 192.168.56.101 \]](#)

2.1.19 High 1099/tcp

High (CVSS: 7.5)
NVT: Java RMI Server Insecure Default Configuration RCE Vulnerability - Active Check
Summary Multiple Java products that implement the RMI Server contain a vulnerability that could allow an unauthenticated, remote attacker to execute arbitrary code (remote code execution/RCE) on a targeted system with elevated privileges.
Quality of Detection (QoD): 95%
... continues on next page ...

...continued from previous page...	
Vulnerability Detection Result	
By doing an RMI request it was possible to trigger the vulnerability and make the remote host send a request back to the scanner host (Details on the received packet follows).	
Destination IP: 192.168.56.102 (receiving IP on scanner host side)	
Destination port: 28361/tcp (receiving port on scanner host side)	
Originating IP: 192.168.56.101 (originating IP from target host side)	
Impact	
An unauthenticated, remote attacker could exploit the vulnerability by transmitting crafted packets to the affected software. When the packets are processed, the attacker could execute arbitrary code on the system with elevated privileges.	
Solution:	
Solution type: Workaround	
Disable class-loading. Please contact the vendor of the affected system for additional guidance.	
Vulnerability Insight	
The vulnerability exists because of an incorrect default configuration of the Remote Method Invocation (RMI) Server in the affected software.	
Vulnerability Detection Method	
Sends a crafted JRMI request and checks if the target is connecting back to the scanner host.	
Note: For a successful detection of this flaw the target host needs to be able to reach the scanner host on a TCP port randomly generated during the runtime of the VT (currently in the range of 10000-32000).	
Details: Java RMI Server Insecure Default Configuration RCE Vulnerability - Active Check	
OID:1.3.6.1.4.1.25623.1.0.140051	
Version used: 2026-04-17T15:51:27Z	
References	
cve: CVE-2011-3556	
url: https://web.archive.org/web/20211208040855/http://www.securitytracker.com/id?1026215	
url: https://web.archive.org/web/20110824060234/http://download.oracle.com/javase/1.3/docs/guide/rmi/spec/rmi-protocol.html	
url: https://tools.cisco.com/security/center/viewAlert.x?alertId=23665	
dfn-cert: DFN-CERT-2012-1829	
dfn-cert: DFN-CERT-2012-1380	
dfn-cert: DFN-CERT-2012-1377	
dfn-cert: DFN-CERT-2012-1156	
dfn-cert: DFN-CERT-2012-1155	
dfn-cert: DFN-CERT-2012-0956	
dfn-cert: DFN-CERT-2012-0828	
dfn-cert: DFN-CERT-2012-0815	
dfn-cert: DFN-CERT-2012-0638	
... continues on next page ...	

...continued from previous page ...

```
dfn-cert: DFN-CERT-2012-0451
dfn-cert: DFN-CERT-2012-0418
dfn-cert: DFN-CERT-2012-0354
dfn-cert: DFN-CERT-2012-0146
dfn-cert: DFN-CERT-2012-0142
dfn-cert: DFN-CERT-2012-0126
dfn-cert: DFN-CERT-2012-0095
dfn-cert: DFN-CERT-2012-0047
dfn-cert: DFN-CERT-2011-1844
dfn-cert: DFN-CERT-2011-1826
dfn-cert: DFN-CERT-2011-1804
dfn-cert: DFN-CERT-2011-1743
dfn-cert: DFN-CERT-2011-1738
dfn-cert: DFN-CERT-2011-1706
dfn-cert: DFN-CERT-2011-1628
dfn-cert: DFN-CERT-2011-1627
dfn-cert: DFN-CERT-2011-1619
```

[\[return to 192.168.56.101 \]](#)

2.1.20 High 21/tcp

High (CVSS: 7.5)

NVT: FTP Brute Force Logins With Default Credentials Reporting

Summary

It was possible to login into the remote FTP server using weak/known credentials.

Quality of Detection (QoD): 95%

Vulnerability Detection Result

It was possible to login with the following credentials <User>:<Password>

```
msfadmin:msfadmin
postgres:postgres
service:service
user:user
```

Impact

This issue may be exploited by a remote attacker to e.g. gain access to sensitive information or modify system configuration.

Solution:

Solution type: Mitigation

Change the password as soon as possible.

... continues on next page ...

...continued from previous page...

Vulnerability Insight

The following devices are / software is known to be affected:

- CVE-2001-1594: Codonics printer FTP service as used in GE Healthcare eNTEGRA P&R
- CVE-2013-7404: GE Healthcare Discovery NM 750b
- CVE-2014-9198: Schneider Electric ETG3000 FactoryCast HMI gateways
- CVE-2015-7261: QNAP iArtist Lite distributed with QNAP Signage Station
- CVE-2016-8731: Foscam C1 devices
- CVE-2017-8218: vsftpd on TP-Link C2 and C20i devices
- CVE-2018-9068: IMM2 for IBM and Lenovo System x
- CVE-2018-17771: Ingenico Telium 2 PoS terminals
- CVE-2018-19063, CVE-2018-19064: Foscam C2 and Opticam i5 devices
- CVE-2018-25147: Microhard Systems IPn4G
- CVE-2020-36915: Adtec Digital SignEdge Digital Signage Player

Note: As the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717) might run into a timeout the actual reporting of this vulnerability takes place in this VT instead.

Vulnerability Detection Method

Reports weak/known credentials detected by the VT 'FTP Brute Force Logins With Default Credentials' (OID: 1.3.6.1.4.1.25623.1.0.108717).

Details: FTP Brute Force Logins With Default Credentials Reporting

OID:1.3.6.1.4.1.25623.1.0.108718

Version used: 2026-01-16T15:42:49Z

References

- cve: CVE-1999-0501
- cve: CVE-1999-0502
- cve: CVE-1999-0507
- cve: CVE-1999-0508
- cve: CVE-2001-1594
- cve: CVE-2013-7404
- cve: CVE-2014-9198
- cve: CVE-2015-7261
- cve: CVE-2016-8731
- cve: CVE-2017-8218
- cve: CVE-2018-9068
- cve: CVE-2018-17771
- cve: CVE-2018-19063
- cve: CVE-2018-19064
- cve: CVE-2018-25147
- cve: CVE-2020-36915

[\[return to 192.168.56.101 \]](#)

2.1.21 High 514/tcp

High (CVSS: 7.5) NVT: rsh Unencrypted Cleartext Login
Summary This remote host is running a rsh service.
Quality of Detection (QoD): 80%
Vulnerability Detection Result The rsh service currently has issues with name resolution and is not allowing connections from this host.
Solution: Solution type: Mitigation Disable the rsh service and use alternatives like SSH instead.
Vulnerability Insight rsh (remote shell) is a command line computer program which can execute shell commands as another user, and on another computer across a computer network. Remark: NIST don't see 'configuration issues' as software flaws so the referenced CVE has a severity of 0.0. The severity of this VT has been raised by Greenbone to still report a configuration issue on the target.
Vulnerability Detection Method Details: rsh Unencrypted Cleartext Login OID:1.3.6.1.4.1.25623.1.0.100080 Version used: 2021-10-20T09:03:29Z
References cve: CVE-1999-0651

[\[return to 192.168.56.101 \]](#)

2.1.22 Medium 2121/tcp

Medium (CVSS: 4.8) NVT: FTP Unencrypted Cleartext Login
Summary The remote host is running a FTP service that allows cleartext logins over unencrypted connections.
... continues on next page ...

...continued from previous page ...
Quality of Detection (QoD): 70%
Vulnerability Detection Result The remote FTP service accepts logins without a previous sent 'AUTH TLS' command ↔. Response(s): Non-anonymous sessions: 331 Password required for openvasvt Anonymous sessions: 331 Password required for anonymous
Impact An attacker can uncover login names and passwords by sniffing traffic to the FTP service.
Solution: Solution type: Mitigation Enable FTPS or enforce the connection via the 'AUTH TLS' command. Please see the manual of the FTP service for more information.
Vulnerability Detection Method Tries to login to a non FTPS enabled FTP service without sending a 'AUTH TLS' command first and checks if the service is accepting the login without enforcing the use of the 'AUTH TLS' command. Details: FTP Unencrypted Cleartext Login OID:1.3.6.1.4.1.25623.1.0.108528 Version used: 2023-12-20T05:05:58Z

[\[return to 192.168.56.101 \]](#)

2.1.23 Medium 80/tcp

Medium (CVSS: 6.8)
NVT: TWiki Cross-Site Request Forgery Vulnerability (Sep 2010)
Summary TWiki is prone to a cross-site request forgery (CSRF) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 01.Feb.2003 Fixed version: 4.3.2
Impact Successful exploitation will allow attacker to gain administrative privileges on the target application and can cause CSRF attack.
... continues on next page ...

...continued from previous page ...
Solution: Solution type: VendorFix Upgrade to TWiki version 4.3.2 or later.
Affected Software/OS TWiki version prior to 4.3.2
Vulnerability Insight Attack can be done by tricking an authenticated TWiki user into visiting a static HTML page on another side, where a Javascript enabled browser will send an HTTP POST request to TWiki, which in turn will process the request as the TWiki user.
Vulnerability Detection Method Details: TWiki Cross-Site Request Forgery Vulnerability (Sep 2010) OID:1.3.6.1.4.1.25623.1.0.801281 Version used: 2024-03-01T14:37:10Z
References cve: CVE-2009-4898 url: http://www.openwall.com/lists/oss-security/2010/08/03/8 url: http://www.openwall.com/lists/oss-security/2010/08/02/17 url: http://twiki.org/cgi-bin/view/Codev/SecurityAuditTokenBasedCsrfFix url: http://twiki.org/cgi-bin/view/Codev/DownloadTWiki

Medium (CVSS: 6.1) NVT: TWiki < 6.1.0 XSS Vulnerability
Summary bin/statistics in TWiki 6.0.2 allows XSS via the webs parameter.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 01.Feb.2003 Fixed version: 6.1.0
Solution: Solution type: VendorFix Update to version 6.1.0 or later.
Affected Software/OS
... continues on next page ...

...continued from previous page ...
TWiki version 6.0.2 and probably prior. Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: TWiki < 6.1.0 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141830 Version used: 2023-07-14T16:09:27Z References cve: CVE-2018-20212 url: https://seclists.org/fulldisclosure/2019/Jan/7 url: http://twiki.org/cgi-bin/view/Codev/DownloadTWiki

Medium (CVSS: 6.1) NVT: jQuery < 1.9.0 XSS Vulnerability
Summary jQuery is prone to a cross-site scripting (XSS) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 1.3.2 Fixed version: 1.9.0 Installation path / port: /mutillidae/javascript/ddsmoothmenu/jquery.min.js Detection info (see OID: 1.3.6.1.4.1.25623.1.0.150658 for more info): - Identified file: http://192.168.56.101/mutillidae/javascript/ddsmoothmenu/jquery.min.js - Referenced at: http://192.168.56.101/mutillidae/
Solution: Solution type: VendorFix Update to version 1.9.0 or later.
Affected Software/OS jQuery prior to version 1.9.0.
Vulnerability Insight ... continues on next page ...

...continued from previous page ...
The jQuery(strInput) function does not differentiate selectors from HTML in a reliable fashion. In vulnerable versions, jQuery determined whether the input was HTML by looking for the '<' character anywhere in the string, giving attackers more flexibility when attempting to construct a malicious payload. In fixed versions, jQuery only deems the input to be HTML if it explicitly starts with the '<' character, limiting exploitability only to attackers who can control the beginning of a string, which is far less common.
Vulnerability Detection Method Checks if a vulnerable version is present on the target host. Details: jQuery < 1.9.0 XSS Vulnerability OID:1.3.6.1.4.1.25623.1.0.141636 Version used: 2023-07-14T05:06:08Z
References cve: CVE-2012-6708 url: https://bugs.jquery.com/ticket/11290 cert-bund: WID-SEC-2026-1752 cert-bund: WID-SEC-2022-0673 cert-bund: CB-K22/0045 cert-bund: CB-K18/1131 dfn-cert: DFN-CERT-2025-1803 dfn-cert: DFN-CERT-2023-1197 dfn-cert: DFN-CERT-2020-0590

Medium (CVSS: 6.0)
NVT: TWiki CSRF Vulnerability
Summary TWiki is prone to a cross-site request forgery (CSRF) vulnerability.
Quality of Detection (QoD): 80%
Vulnerability Detection Result Installed version: 01.Feb.2003 Fixed version: 4.3.1
Impact Successful exploitation will allow attacker to gain administrative privileges on the target application and can cause CSRF attack.
Solution: Solution type: VendorFix Upgrade to version 4.3.1 or later.
... continues on next page ...