
CNNs

CV Jawahar

IIIT-H


11 April 2025

Convolution




Filter 1





6 x 6 image




-2


-1

-2

Revisit: Convolution layer

- Window size
- Stride
- Padding
- Pool





Window size: 3x3


Stride: 1

Padding: 0

Window size: 3x3


Stride: 1


Padding: 1



CNNs

Strides reduces dimension







$$O = \frac{(W - K + 2P)}{S} + 1$$

Revisit: Convolution layer

- Window size
- Stride
- Padding
- Pool





Window size: 3x3

Stride: 1

Padding: 0


Window size: 3x3


Stride: 1

Padding: 1


Max Pool and Stride

- Window Size = 3
- Stride =1






Max pooling in 2-D



Softmax

- Normalizes the output.
- K is total number of classes




Terminologies


- # Input Channels
- # Output channels

- Feature Maps/Channels
- Filters/Weights
- Filter Size/Window Size

- Stride
- Pooling (Max/Average)
- Fully Connected Layer
- Soft-Max
- Normalization
- Flattening
- Convolution Layer

Layer wise abstraction






11


1-D Convolution 2-D Convolution

Deep Learnt Features


• It's deep if it has more than one stage of non-linear feature transformation.




AlexNet Architecture




Learned Representations: Pre-Train and Fine Tune




Design Guidelines: Smaller Convolutions and Deeper nw






- 1. Less Parameters; Faster
- 2. Same Receptive Field
- 3. More nonlinearities (2 ReLU)




Performance over ImagenetBenchmark




Accuracy vs Model complexity Vs comput. complexity


- Size of point denotes the Model complexity
- The band around 95% accuracy has varying complexity of 4-25 G-FLOPs
- The band between 10-15 G-FLOPs have high variance in both Model Complexity (size of the point) and accuracy
- Recognition accuracy is not only dependent on the model or computational complexity



What goes on inside a convnet?




Visualizing CNNs



A. How do I interpret the learned filters?





Source: Zeiler e.t. al. ECCV'14

Early Layers Converge Faster






Figure: Evolution of randomly chosen subset of model features generated using deconvnet through training at epoch 1, 2, 5, 10, 20, 30, 40, 64.

CNN




RNNs

RNN basic architecture




23

RNN basic architecture



Forward Pass, Loss



$$h_t = f(Ux_t + Wh_{t-1})$$

$$\hat{o}_t = \operatorname{softmax}(Vh_t)$$

$$E(o,\hat{o}) = \sum_{t} E_{t}(o_{t},\hat{o}_{t})$$

Questions?