Unsaid: Frontend Build Spec

A clickable UI shell for every screen, with nothing wired up yet.

HackTX 2026 · Meta track: "Bringing People Closer Together with AI" Companion to `Unsaid_Product_Spec.md` (v4), `Demo_Script.md`, and **`Claude_Code_Frontend_Prompt.md`** (the phased, ready-to-paste Claude Code prompt that builds this spec).

Purpose: tell Claude (Claude Code) exactly how to build the Unsaid frontend as a clickable, mock-data-only UI shell, and give Mudit (backend owner) one table of every button he will wire up later.

Spec version: v2 · Oct 24, 2026

> ***"The last thing my kid ever texted me was 'k.'"***
>
> *The cold open of the animated demo (Scene 1). Every screen below exists so that text never has to be the last one.*

Table of Contents

1. The One Rule: Frontend Only
2. Mock Data
3. Design System
4. Tech Stack
5. Folder Structure
6. Component List
7. Navigation Map
8. Screens
9. The Frontend-Backend Contract
10. Ready-to-Paste Prompt for Claude
11. Changelog

---

1. The One Rule: Frontend Only

This build is a **UI shell**. It looks and moves like the real app, but **no feature works**.

- **Every action button is a non-functional placeholder, marked NOT YET CONNECTED.** That means three things on every one of them:
    1. **A visible marker:** a small pill badge reading `NOT YET CONNECTED` in the button's top-right corner (amber outline, 9px uppercase), plus a tooltip on hover: "not connected yet · `<feature-id>`".
    2. **A data attribute:** `data-backend="<feature-id>"`, using the exact kebab-case ID from the contract table.
    3. **A toast-only click handler:** `onClick` does one thing: it shows a soft toast, **"Not connected yet"**, with the feature ID in small text underneath. No fetch, no state change, no navigation, no `tel:` or `sms:` links.
- **All data is hard-coded mock data** in `frontend/lib/mock/`. No API calls, no environment keys, no auth, no camera, microphone, or photo access.
- **Navigation is the only thing that works.** The tab bar, back chevrons, the screen switcher, and swipe/tap gestures that only move between mock screens or mock story cards are plain frontend routing. They are listed separately in Section 9.2 and carry no badge.
- **Two attributes.** From v2, every placeholder carries both `data-backend` and an identical alias, `data-feature-id`. Tests and the later animation may use either one.
- **Badges can be hidden for recording.** A single flag (`?badges=off` in the URL, or `NEXT_PUBLIC_SHOW_BADGES=false`) hides the pills so the same screens can be recorded or rendered in Remotion. The `data-backend` attribute and the toast stay either way.
- **Honesty about Meta surfaces (v2).** Screens 11 and 15 and the fake Meta apps (Section 4.1) are **concept screens**. A real version would need a partnership with Meta and access beyond its public APIs. Every Apple and Meta app icon and screen is a **look-alike recreated in SVG/CSS** (brand-colored gradient plus a simple drawn glyph), and real app names (Instagram, WhatsApp, Facebook, Messenger, Threads, Meta AI, Edits) may appear **as plain text**. **Never** download or embed official logo files, app icons, wordmarks, glyph files, screenshots, or proprietary fonts (SF Pro, Optimistic). Each such page carries a small "concept · look-alike" label, plus "concept mock · not affiliated with Apple or Meta" outside the device. *Risk note:* recognizable look-alikes of trademarked icons are still a trademark gray area. Fine for a labeled hackathon concept; never ship them.
- **Navigation is real, the scripted animation is not part of this build.** App-to-app navigation runs through an interactive **iOS navigation shell** (Section 4.1). The scripted demo animation is out of scope here and will come in a separate prompt later (timings are saved in `Demo_Script.md`).

- **Features follow the backend.** Read (never edit) `backend/` as Mudit builds it. Backend features missing from the frontend are added to the app and to Section 9 with a new ID; anything not built on the backend stays a placeholder. The build ends with a report of every button that still has no backend (feature ID, screen, label).

Placeholder button reference (copy this pattern):

```
<PlaceholderButton featureId="rant-record" variant="primary">
  hold to talk
</PlaceholderButton>
// renders: <button data-backend="rant-record" ...>hold to talk<NotConnectedBadge/>
</button>
// onClick: toast("Not connected yet", { description: "rant-record" })
```

---

2. Mock Data

All of it lives in `frontend/lib/mock/` as typed TypeScript objects. Avatars and photos are soft illustrated placeholders (generate them; never use real people's photos).

Kind	Mock entries
People	**Mom** (calls a lot, "no emergency. just miss you."), **Dad** (called on tuesday, no call back yet), **Priya** (best friend, drifting: "4 months"), **Jordan** (partner, the argument)
Group chats	**Fam** (Mom, Dad, you), **Roommates** (Priya, you, two faded nodes), **Marfa Trip** (Priya, Jordan, you)
Memories	lake trip, june · mom's birthday dinner · moving-day selfie · marfa sunset · graduation photo · 2 AM laughing fit
Brain-graph gaps	"last talked: 2019" · "4 months" · "never replied"
Unsends	Mom: "no emergency. I just wanted to hear your voice." · Mom: "I'm so proud of you. I always was." · Jordan: "I'm sorry. Dinner Friday?" · Priya: "found these and miss you all. reunion soon?"
Rant	"I'm so tired of always being the one who reaches out…" (about Jordan, tone: frustrated)
Plan	Your old favorite taco spot · Friday, Nov 6 · 7:00 PM
Posthumous	June 12, 2034 · Graduation Day · proxies: Dad, Priya, Jordan
Call log	Mom: 10 missed calls · Dad: missed call, tuesday

The user is "you" (the kid); where another person's phone needs a sender name, use the mock display name **Riley**. Mom's side of the story appears on the left screen of the Duo layouts where it helps.

3. Design System

Warm and minimal: a lamp, not a screen. It matches the Animated Demo Plan visual style in the product spec.

3.1 Color tokens

Token	Value	Use
`accent`	`#E8A15A` (amber)	The one accent: key buttons, the moments that matter, the ripple ring
`accent-soft`	`#F6D3AE`	Accent backgrounds, selected chips
`ink`	`#4A1F35` (deep plum)	All primary text, icons, the logo gradient end
`ink-muted`	`#7A5A6A`	Secondary text, timestamps
`ink-faint`	`#B9A3AE`	Faded graph links, disabled text
`cream`	`#FBF5EC`	App background
`cream-deep`	`#F3E7D7`	Cards on cream, the brain-graph canvas ("dark cream")
`card`	`#FFFDF9`	Raised cards
`dusk-rose`	`#E9B7B4`	Gradient start
`peach`	`#F6C9A4`	Gradient middle
`line`	`#EADBCB`	Hairlines and card borders
`safety`	`#3E5C76` (calm slate)	Safety screens only; never red, never alarming
`badge`	`#E8A15A` outline on `#FFF4E8`	The NOT YET CONNECTED pill

Gradients - `bg-dusk`: `linear-gradient(180deg, #E9B7B4 0%, #F6C9A4 45%, #FBF5EC 100%)` (dusk rose → peach → warm cream). Sits behind the phone frames. - `logo-gradient`: `linear-gradient(135deg, #E8A15A 0%, #4A1F35 100%)` (amber → deep plum).

3.2 Type

Inter for all interface text. **Caveat** (handwritten) for anything the user or a loved one actually wrote or said: unsend text, letters, rant quotes on cards. Load both from Google Fonts via `next/font`.

Token	Font	Size / line height (px)	Weight	Use
`display`	Inter	32 / 38	600	Screen titles (rare)
`title`	Inter	22 / 28	600	Card headers
`body`	Inter	16 / 24	400	Default
`small`	Inter	13 / 18	400	Timestamps, captions
`micro`	Inter	9 / 12	600, uppercase, 0.06em tracking	NOT YET CONNECTED badge, "concept" labels
`hand-lg`	Caveat	34 / 40	500	Letters, featured unsends
`hand`	Caveat	24 / 30	500	Unsend text in cards

3.3 Radii, spacing, shadow

Token	Value
`radius-sm` / `md` / `lg` / `xl` / `pill`	10 / 16 / 24 / 32 / 999 px
Spacing scale (4px base)	4, 8, 12, 16, 24, 32, 48, 64
Screen padding	24px sides, 32px top below the status bar
Gaps	16px between cards; 32px between sections (generous whitespace, never cramped)
`shadow-card`	`0 8px 24px rgba(74,31,53,0.08)`
`shadow-float`	`0 20px 48px rgba(74,31,53,0.14)` (phone frames)
Frosted overlay circle	`rgba(255,255,255,0.35)` + `backdrop-filter: blur(10px)`

3.4 Motion tokens

Nothing snaps; everything settles.

Token	Value	Use
`ease-soft`	`cubic-bezier(0.22, 1, 0.36, 1)`	Default for everything
`ease-breath`	`cubic-bezier(0.45, 0, 0.55, 1)`	Loops: pulse, tide, waveform
`dur-fast`	240ms	Hover, press, chip select
`dur-base`	480ms	Card enter, sheet slide
`dur-slow`	900ms	Screen fades, photo reveals
`dur-hold`	1200ms	Big moments (the date card, the call connecting)
`fade-in`	opacity 0 → 1 over `dur-slow`	Default enter
`scale-in`	scale 0.96 → 1 plus fade, `dur-base`	Cards, photos
`spring-soft`	Framer Motion `{ type: "spring", stiffness: 120, damping: 20 }`	Sheets, notifications
`stagger`	120ms between siblings	Photo grids, list items
`pulse-once`	scale 1 → 1.08 → 1 over 1200ms, `ease-breath`	The logo heartbeat
`ripple-ring`	ring scales 0.6 → 1.8, opacity 0.5 → 0, 900ms, amber	**The haptic**, shown visually
Reduced motion	Swap all motion for 200ms fades	`prefers-reduced-motion`

Sound and haptic (shown, not played): a **soft chime** when an unsend lands and a **haptic pulse** when the phone-activity trigger delivers. In the shell both are drawn as the `RippleRing` component (one amber ring expanding from the notification or button), with an optional small chime icon. No audio plays in the UI shell; the Remotion render adds the chime.

3.5 Microcopy rules

- Short, human, lowercase, slightly imperfect. Run every line past "would a person say this?"
- Yes: "Mom left you something." · "you haven't talked in a while." · "no emergency. just miss you." · "that sounds exhausting." · "whenever you're ready."
- Never: "Strengthen your relationships today!" or anything that sounds like an ad.
- Names keep their capital (Mom, Priya). Safety resource names keep normal capitalization.

3.6 The Unsaid mark

A single-line speech-bubble outline **left slightly open** (the gap where the words never got said), inside a small rounded square as the app badge. Overlay version: a 24–28px white mark on a frosted, semi-transparent circle with a faint shadow. Wordmark: "unsaid" in lowercase, rounded sans; the dot of the "i" is the open bubble. Build it as an inline SVG component (`UnsaidMark`).

4. Tech Stack

Layer	Choice	Notes
Framework	**React + Next.js (App Router) + TypeScript**	One route per screen
Styling	**Tailwind CSS**	Tokens from Section 3 go in `tailwind.config.ts` and CSS variables
UI motion	**Framer Motion** (with the **Motion AI Kit**, `npx motion-ai`, docs) and/or **GSAP** (gsap-skills)	Framer Motion for enters, sheets, and story transitions; GSAP only if a timeline gets complex
Brain graph	**react-force-graph** (2D)	Soft physics; custom canvas painting for photo leaves and gap labels
Toasts	`sonner` (or a small custom toast)	Only for "Not connected yet"
Demo video	**Remotion** (later, separate prompt)	Will render the demo MP4 from the **same screen components**; not installed in this build
Device	**Custom `IPhoneDuo`** component (white, fictional)	See the note below; snapcn Phone Frame is optional now
Fonts	Inter + Caveat via `next/font/google`	

The device: a white "iPhone Duo" (v2). - The **iPhone Duo is fictional**: a book-style, dual-screen iPhone with two iPhone-proportioned panels on a 360° hinge. **White is the default finish everywhere.** Folded, it reads as one white iPhone; unfolded, it shows two displays side by side with a white hinge between them. It is a custom React component drawn in CSS (`components/device/IPhoneDuo.tsx`) with full hardware detail: frame, bezel, Dynamic Island, hinge, buttons, Camera Control, a camera bump on the back, and specular gloss. The geometry is in `Claude_Code_Frontend_Prompt.md` Phase 1. No Apple bezel images are used. - **`PhoneFrame` and `DuoFrame` now wrap `IPhoneDuo`.** `PhoneFrame` = one **folded** white Duo; `DuoFrame` = one **unfolded** white Duo, with its left/right display slots (plus a spanning slot across the hinge) replacing v1's "two frames side by side". - **New layout `TwoPhones`:** two **folded** white Duos side by side (scale 0.86, 96px apart, captions underneath). Use it when a screen shows **two different people's phones** (Screens 4, 7, 11, 12, 14). Screen 15 uses three folded Duos. - snapcn Phone Frame (v1) is no longer needed.

4.1 Opening, home screen, and the iOS navigation shell (v2)

- **Messages scene** (`/scene/messages?state=`): the kid's iOS Messages thread with "Mom": her messages "hi sweetheart 💛 tried calling you a few times today" / "no emergency. just miss you." / "I made your favorite this weekend and saved you some. call me when you can? love you", and his reply "k". States age the timestamp from today to last year.
- **Home screen** (`/scene/home?state=`), spread across both panels of the unfolded white Duo:
- Left panel: Apple apps and widgets (Weather, Calendar, Photos).

- Right panel: the **Meta apps, most prominent**: Instagram, WhatsApp, Facebook and Messenger, then Meta AI (the Ray-Ban Meta glasses companion app), Threads, Edits and **Unsaid**. Below them, a Batteries widget with the Ray-Ban Meta glasses.
- Dock: Phone, Messages, Safari, Calendar.
- No "Muse" app.
- **iOS navigation shell (interactive, real in the built app):** this is how the Duo moves between apps.
- **Open:** tapping an icon zooms the app open from the icon's exact rect. The corner radius morphs from the icon to the screen, the icon crossfades into the app, and the home screen dims and recedes.
- **Close:** swipe up on the home indicator. The app follows the finger, rubber-bands, and springs back into its icon.
- **App switcher:** swipe up and hold. Swipe a card up to kill it; tap a card to resume it.
- **Switch apps:** swipe sideways along the home indicator to move between recent apps.
- **Keyboard and dev bar:** shortcuts and a dev control bar do the same, for recording.
- **Panels:** an app opens on one panel or spans both.
- **Springs:** about 300–400 stiffness and 30–35 damping. Reduced motion is supported.
- **One registry:** every app (Messages, Unsaid, Instagram, Meta AI, Facebook, WhatsApp, Messenger, Threads, Edits, and Apple-app stubs) registers with the shell, so every transition is identical.
- **Fake Meta apps** (`/apps/instagram`, `/apps/meta-ai`, `/apps/facebook`, `/apps/whatsapp`, plus Messenger and Threads stubs): SVG/CSS look-alikes with Unsaid touchpoints. Their buttons are rows 95–110 in Section 9.4.
- **The scripted opening** (black cold-open card → the black is the folded Duo's screen → Messages "k" → unfold → wallpaper and "Some things go unsaid." → app-close to home → tap Unsaid) is **not built here**. It comes in a later, separate animation prompt, which will drive the navigation shell programmatically. Its beat table lives in `Demo_Script.md` under "Animation Production Notes".
- **Every screen takes `?state=`** for an exact static frame. `?badges=off`, `?labels=off`, and `?frame=bare` give clean recording.

---

5. Folder Structure

```
frontend/
├── app/
│   ├── layout.tsx                # fonts, Toaster, gradient backdrop,
ScreenSwitcher
│   ├── page.tsx                  # 1  Home
```

```
│   ├── rant/page.tsx               # 2  Rant journal
│   ├── memories/page.tsx           # 3  Camera-roll memory surfacing
│   ├── send/page.tsx               # 4  Send to partner
│   ├── graph/page.tsx              # 5  Brain graph
│   ├── posthumous/page.tsx         # 6  Posthumous setup
│   ├── proxy/page.tsx              # 7  Proxy confirmation
│   ├── breakup/page.tsx            # 8  Ex / breakup toggle + safety
│   ├── inbox/page.tsx              # 9  Unsends inbox
│   ├── reminisce/[person]/page.tsx # 10 Reminisce mode (default: mom)
│   ├── story-notification/page.tsx # 11 Contextual story notification (concept)
│   ├── plans/page.tsx              # 12 Plans picker
│   ├── group/page.tsx              # 13 Group-chat unsend
│   ├── settings/delivery/page.tsx  # 14 Phone-activity settings
│   └── overlays/page.tsx           # 15 Logo overlay on look-alike posts (concept)
├── components/
│   ├── ui/          # PlaceholderButton, NotConnectedBadge, PlaceholderToggle,
PlaceholderSegmented,
│   │                # PlaceholderSlider, Card, Chip, Sheet, Avatar, TabBar,
ConceptLabel, ScreenSwitcher
│   ├── frames/      # PhoneFrame (CSS), DuoFrame, StatusBar
│   ├── motion/      # FadeIn, ScaleIn, Stagger, RippleRing, PulseOnce, TideLine,
Waveform
│   ├── brand/       # UnsaidMark, Wordmark
│   ├── lookalike/   # PhotoFeedPost, ChatAppBubble, SocialFeedPost, StoryViewer
(generic, no Meta assets)
│   └── screens/     # HomeScreen, RantScreen, ... one per screen; pure and prop-
driven, reused by Remotion
├── lib/
│   ├── mock/        # people.ts, groups.ts, memories.ts, unsends.ts, plans.ts,
calls.ts, graph.ts
│   ├── contract.ts  # FEATURE_IDS: every data-backend ID as a typed union, with
screen + backend feature
│   ├── tokens.ts    # colors, type, radii, spacing, motion
│   └── toast.ts     # notConnected(featureId)
├── remotion/
│   ├── Root.tsx     # compositions reuse components/screens/*
│   └── scenes/      # Scene1K ... Scene7Close (timings in one config, per
Demo_Script.md)
├── public/mock/     # illustrated avatars, photos, envelope, library story frame
├── tailwind.config.ts
└── README.md        # how to run; points to this spec

backend/             # Mudit's: implements every feature ID in Section 9 (not part
of this build)
```

Rule for screen components: every screen in `components/screens/` takes its mock data as props and has no side effects, so the Next.js page and the Remotion scene render exactly the same thing.

---

6. Component List

Component	What it is
`PlaceholderButton`	The only button used for actions. Props: `featureId`, `variant` (`primary` amber, `secondary` outline, `ghost`, `chip`, `icon`), children. Adds `data-backend`, the badge, the tooltip, and the toast.
`NotConnectedBadge`	9px uppercase amber pill, "NOT YET CONNECTED"; hidden when badges are off.
`PlaceholderToggle` / `PlaceholderSegmented` / `PlaceholderSlider`	Same rule for toggles, segmented controls, and sliders: they may animate locally for feel, but show the badge, carry `data-backend`, and toast on change.
`PhoneFrame`	CSS iPhone-style frame: 320 × 656, 53px radius, dynamic island, `shadow-float`.
`DuoFrame`	Two `PhoneFrame`s side by side, with optional captions under each ("mom's phone" / "your phone").
`StatusBar`	Mock time ("9:41" by default; "3:02 AM" on the rant screen), battery, signal.
`TabBar`	home · graph · inbox · you. Navigation only.
`ScreenSwitcher`	Small floating pill outside the phone that opens a list of all 15 screens. Dev navigation only.
`Card`, `MemoryCard`, `UnsendCard`	Rounded cards; `UnsendCard` sets the message in Caveat.
`EmotionChip`	Pill with tone and person ("frustrated · about Jordan").
`Waveform`	Animated mock voice waveform (decorative).
`TranscriptPane`	Live-transcript placeholder: mock text fades in word by word.
`RecipientPicker`	Avatar row of Mom, Dad, Priya, Jordan.
`DateCard`	Large card that "turns forward" (flip-up fade) to a date.
`ProxySlot`	Avatar, name, and status ("invited", "confirmed").
`StoryViewer`	Full-screen story layout: progress bars, name and avatar header, tap-left/right zones, source label.
`NotificationSheet`	Soft notification that slides down from the top, with a ripple ring.
`ForceGraph`	Wrapper around react-force-graph-2d with Unsaid styling, labeled gap links, and photo leaves.
`TimeSlider`	Year slider under the graph (2019 → 2026).
`SafetyResources`	The calm resource card with the entries from the product spec.
`ConceptLabel`	Small "concept · look-alike" tag for screens 11 and 15.
`UnsaidMark`, `Wordmark`	Inline SVG logo.
`RippleRing`, `PulseOnce`, `TideLine`, `FadeIn`, `ScaleIn`, `Stagger`	Motion primitives using the Section 3.4 tokens. `TideLine` is the "this too shall pass" motif (a slow tide line) on screens 6, 7, and 9.

Component	What it is
`Toaster`	Global toast host for "Not connected yet".

---

7. Navigation Map

Every arrow is frontend routing (tab bar, back, screen switcher, or a "next" dev link). No arrow depends on a backend call.

```
flowchart TD
  OV[15 Logo overlay on look-alike posts] --> HOME
  HOME[1 Home] --> RANT[2 Rant journal]
  RANT --> MEM[3 Memory surfacing]
  RANT -. mock safety signal .-> EX[8 Ex / breakup + safety resources]
  MEM --> SEND[4 Send to partner]
  SEND --> PLANS[12 Plans picker]
  SEND --> DELIV[14 Phone-activity settings]
  HOME --> GROUP[13 Group-chat unsend]
  GROUP --> PLANS
  HOME --> GRAPH[5 Brain graph]
  GRAPH --> SEND
  GRAPH --> GROUP
  HOME --> INBOX[9 Unsends inbox]
  INBOX --> REM[10 Reminisce mode]
  INBOX --> PLANS
  STORY[11 Story notification concept] --> REM
  STORY --> INBOX
  HOME --> POST[6 Posthumous setup]
  POST --> PROXY[7 Proxy confirmation]
  HOME --> EX
  HOME --> DELIV
```

Tab bar: **home** (1) · **graph** (5) · **inbox** (9) · **you** (a simple list linking to 6, 8, 12, 14). Screens 11 and 15 are reached from the screen switcher, since they live "inside" other apps.

---

8. Screens

Every screen sits in a `PhoneFrame` (or a `DuoFrame`) centered on the `bg-dusk` gradient. Every button named under "Placeholder buttons" is a `PlaceholderButton` (or placeholder toggle/segmented/slider)

and is **NOT YET CONNECTED**; its feature ID is in brackets and matches the contract table in Section 9.

8.1 Screen 1 — Home

- **Purpose:** a calm landing that shows who might need you today, without nagging.
- **Frame:** single phone.
- **Layout (top to bottom):**
    1. Status bar; `Wordmark` on the left; a "get help" text link on the right (navigation to the resources on screen 8).
    2. Greeting in `title`: "hey. who's on your mind?"
    3. Big amber circle with a mic: "start a rant" (navigation to screen 2).
    4. Ask bar: "try 'I miss Mom'" with an arrow button.
    5. Missed-call card: Dad's avatar, "your dad called on tuesday." with a small photo from his birthday and "want to send him something?"
    6. Drift card: Priya, "you haven't talked in a while. 4 months." with a faded memory thumbnail (marfa sunset).
    7. Pending strip: "1 unsend waiting for Jordan to be awake", with a tiny ripple ring.
    8. Tab bar.
- **Components:** `StatusBar`, `Wordmark`, `Card`, `Avatar`, `MemoryCard`, `RippleRing`, `TabBar`.
- **Placeholder buttons (NOT YET CONNECTED):** ask-bar arrow [`muse-ask`] · "send him something" [`missed-call-nudge`] · "not now" [`nudge-dismiss`] · "say something to Priya" [`drift-reach-out`] · "review" on the pending strip [`pending-unsend-review`].
- **Motion:** cards fade and scale in with a 120ms stagger; the pending ripple ring breathes every 4s.

8.2 Screen 2 — Rant journal

- **Purpose:** be heard, not sent. Record a raw rant, watch it transcribe live, and see the AI's read of the emotion.
- **Frame:** Duo. **Left screen:** the recorder. **Right screen:** the live transcript and emotion chip.
- **Layout, left (top to bottom):** status bar showing "3:02 AM"; header "say it here. nobody else hears this."; a large `Waveform`; a big round record button, "hold to talk"; under it "stop" and "start over"; small text "your rant stays private. always."
- **Layout, right (top to bottom):** header "heard."; `TranscriptPane` with the mock rant ("I'm so tired of always being the one who reaches out…") fading in word by word; a "transcribing…" shimmer line; `EmotionChip` "frustrated · about Jordan" with a "not quite" link; the empathy line: "that sounds exhausting."; two buttons, "keep it private" and "show me the good stuff"; a quiet "type instead" link.
- **Components:** `StatusBar`, `Waveform`, `TranscriptPane`, `EmotionChip`, `DuoFrame`.

- **Placeholder buttons (NOT YET CONNECTED):** "hold to talk" [`rant-record`] · "stop" [`rant-stop`] · "start over" [`rant-discard`] · "type instead" [`rant-type`] · "not quite" on the chip [`emotion-chip-edit`] · "keep it private" [`rant-save-private`] · "show me the good stuff" [`memory-surface-request`].
- **Motion:** the waveform loops with `ease-breath` (decorative only). Transcript words fade in at about six per second. The emotion chip scales in 600ms after the transcript ends.

8.3 Screen 3 — Camera-roll memory surfacing

- **Purpose:** "this too shall pass," shown with proof. Good-time photos with Jordan appear with the "everything will be okay" message.
- **Frame:** single phone.
- **Layout (top to bottom):**
    1. Back chevron; small text "from your camera roll and memories".
    2. Message in `hand-lg`: "Everything will be okay. Here's what you two have been through together."
    3. Photo grid (three cards, staggered): lake trip, june · birthday dinner · moving-day selfie. Each has a small heart "keep" button and a date caption.
    4. A face chip on one photo: "who's this?"
    5. "Remember this?" card: a past unsend from Jordan in Caveat ("I'm sorry. Dinner Friday?") with "open".
    6. Source row: "add from instagram or facebook" and "use camera roll" (plain text buttons, no logos).
    7. Primary amber button "I'm ready" and a ghost button "save for later".
- **Components:** `MemoryCard`, `UnsendCard`, `Chip`, `Stagger`, `ScaleIn`.
- **Placeholder buttons (NOT YET CONNECTED):** "keep" heart [`memory-select`] · "who's this?" [`face-cluster-name`] · "open" on Remember this [`past-unsend-resurface`] · "add from instagram or facebook" [`graph-api-photo-import`] · "use camera roll" [`camera-roll-scan`] · "I'm ready" [`unsend-draft-generate`] · "save for later" [`memory-save-later`].
- **Motion:** the message fades in first and holds alone for 1.2s; then photos scale in one by one (900ms each, 300ms stagger). Let it sit.
- **Note:** in the real app this screen only appears after the safety check passes (product spec Section 7). The shell just shows it.

8.4 Screen 4 — Send to partner

- **Purpose:** turn the feeling into an unsend the user wrote, then let the phone-activity trigger pick the moment.
- **Frame:** Duo. **Left screen (your phone):** the composer. **Right screen (Jordan's phone, later):** the delivered notification, captioned "delivered on jordan's 2nd unlock, 6:40 PM".

- **Layout, left (top to bottom):**
    1. "to" row with `RecipientPicker` (Mom, Dad, Priya, Jordan; Jordan selected).
    2. Draft in Caveat inside an editable-looking card: "Hey. I was upset earlier and I didn't say it well. I looked back at these and remembered how much you mean to me. Can we talk tonight?"
    3. Small chips: "rewrite gently" and "say it with my voice".
    4. Attached photo strip (two photos) with "+ photos"; a "make a cover" chip.
    5. "+ add a plan" row.
    6. "send through" segmented control: messages / whatsapp / messenger (text labels only, no logos).
    7. Delivery card: "we'll hold this until Jordan is actually awake. 2nd or 3rd unlock, later in the day." with a "change" link.
    8. Primary button "send when they're ready".
- **Layout, right:** a look-alike lock screen; a notification slides down: "Riley is missing you. they sent you an unsaid, take a look." (the spec's "XYZ is missing you" line); a ripple ring for the haptic.
- **Components:** `RecipientPicker`, `UnsendCard`, `Chip`, `PlaceholderSegmented`, `Card`, `NotificationSheet`, `RippleRing`.
- **Placeholder buttons (NOT YET CONNECTED):** recipient avatar [`recipient-pick`] · "rewrite gently" [`unsend-draft-rewrite`] · "say it with my voice" [`unsend-voice-record`] · "+ photos" [`unsend-attach-photos`] · "make a cover" [`muse-image-cover`] · "+ add a plan" [`plan-attach`] · "send through" segmented [`delivery-channel-pick`] · "change" on the delivery card [`delivery-rule-open`] · "send when they're ready" [`unsend-queue-send`].
- **Motion:** in the Remotion version the right screen stays dark, then softly lights up 1.5s after the send tap. In the app, it is simply shown in its delivered state.
- **Copy note:** there is no time or date picker for everyday unsends. Delivery timing comes only from the phone-activity trigger.

8.5 Screen 5 — Brain graph

- **Purpose:** show loss before the fix. A sparse map of your people, with labeled gaps, that fills in.
- **Frame:** single phone (the Remotion scene can render it wide, outside a frame).
- **Layout (top to bottom):**
    1. Header "your people"; a small "ask your graph" field: "when did I last see Priya?"
    2. `ForceGraph` on `cream-deep`: three hubs, **Fam**, **Roommates**, and **Marfa Trip**; people nodes Mom, Dad, Priya, and Jordan orbiting their hubs; memory leaves as tiny rounded photo thumbnails; two faint unnamed nodes in Roommates.
    3. Faded, dashed links with small labels: a faint Roommates node "last talked: 2019", Priya "4 months", the other faint node "never replied". Faded links pulse slowly, as if waiting.

4. Tapping a node opens a bottom sheet (navigation/local state): name, relationship ("best friend") with "edit", last memory with "show memory", and "reach out".
5. `TimeSlider` 2019 → 2026 with year ticks.
6. Footer link: "add your message history (meta data export)".

- **Components:** `ForceGraph`, `Sheet`, `TimeSlider`, `PlaceholderSlider`.
- **Placeholder buttons (NOT YET CONNECTED):** ask-field submit [`graph-ask`] · "reach out" in the sheet [`graph-reach-out`] · "edit" relationship [`relationship-edit`] · "show memory" [`graph-memory-open`] · time slider [`graph-time-slider`] (slides locally, toasts on release) · "add your message history" [`dyi-export-upload`].
- **Motion:** start nearly empty and hold for 1.5s; hubs light up one at a time (Fam, Roommates, Marfa Trip, 600ms apart); people drift in with soft physics (velocity decay around 0.4); leaves bloom with `scale-in`. Gap labels fade in last.

8.6 Screen 6 — Posthumous setup

- **Purpose:** leave words for later: a timed message with a milestone date, released after you're gone only when your proxies confirm.
- **Frame:** Duo. **Left:** the message and the date. **Right:** the three proxies.
- **Layout, left (top to bottom):** header "some words are meant for later."; a letter card in Caveat: "I'm so proud of you. I always was." with a `Waveform` and "record"; a "when" segmented control: 1 year / 5 years / 10 years / a milestone; `DateCard` showing **June 12, 2034 · Graduation Day** with "change date"; toggle "only after I'm gone"; the `TideLine` motif along the bottom.
- **Layout, right (top to bottom):** header "who confirms?"; copy "pick 3 people you trust. all of them confirm before anything is released."; three `ProxySlot`s (Dad, Priya, Jordan), each "invited", each with "choose"; "+ add a backup proxy"; small rule text: "if a proxy doesn't answer for 30 days, your backup or the others can confirm."; primary button "seal it".
- **Components:** `UnsendCard`, `Waveform`, `PlaceholderSegmented`, `DateCard`, `PlaceholderToggle`, `ProxySlot`, `TideLine`.
- **Placeholder buttons (NOT YET CONNECTED):** "record" [`timed-message-record`] · "when" segmented [`timed-delivery-pick`] · "change date" [`milestone-date-set`] · "only after I'm gone" toggle [`posthumous-toggle`] · "choose" on each of the three proxy slots [`proxy-invite`] · "+ add a backup proxy" [`backup-proxy-invite`] · "seal it" [`timed-message-seal`].
- **Copy note:** the product spec allows 2 to 3 proxies; this screen shows the 3-proxy case used in the demo.
- **Motion:** the date card turns forward slowly (`dur-hold`). The tide line drifts over 8s.

8.7 Screen 7 — Proxy confirmation

- **Purpose:** the quietest moment. The proxies have confirmed, the date arrives, and the letter opens.

- **Frame:** Duo. **Left:** proxy status. **Right:** the recipient's view on the date.
- **Layout, left:** a calm card, "**Proxy confirmation 3 of 3 received**"; three proxy rows with check marks (Dad, Priya, Jordan); "view details".
- **Layout, right (top to bottom):** `DateCard` "**June 12, 2034 · Graduation Day**"; a sealed illustrated envelope with "open the letter"; the handwritten letter in `hand-lg`, "I'm so proud of you. I always was.", with a `Waveform` and "play"; two buttons, "keep it forever" and "not now"; small text "you can always choose. some days aren't the day."; `TideLine` in the background.
- **Components:** `Card`, `ProxySlot`, `DateCard`, `Waveform`, `TideLine`, `RippleRing`.
- **Placeholder buttons (NOT YET CONNECTED):** "view details" [`proxy-status`] · "open the letter" [`posthumous-letter-open`] · "play" [`letter-voice-play`] · "keep it forever" [`message-accept`] · "not now" [`message-reject`].
- **Motion:** "3 of 3" counts up from "1 of 3" over 1.5s; the date card turns forward and **holds a full second**; the envelope opens with a slow scale-in and the letter unfolds over 900ms; a ripple ring (the chime) when the letter opens. This sequence plays on page load as decoration; "open the letter" itself still only toasts.

8.8 Screen 8 — Ex / breakup toggle (with safety)

- **Purpose:** closure on your terms, never a back door. Also the safety screen that replaces reconciliation content when it would cause harm.
- **Frame:** Duo. **Left:** the breakup toggle. **Right:** recipient protections and safety resources.
- **Layout, left (top to bottom):** header "closure, on your terms."; a profile row for the ex (use a generic "your ex" mock profile, not one of the four main people); toggle "breakup"; when on (local state), two choice cards: **block** ("no unsends, plans, or messages. starts now.") and **allow up to 3 future messages** ("video, text, or voice. 3 total, then it's done."), with a counter "0 of 3 used"; primary button "save".
- **Layout, right (top to bottom):** a "your protections" card: "you can block after any one of them." · "block and report work from day one, for everyone." · "no memories or reconciliation prompts after a block or report."; buttons "block" and "report"; a divider; then the `SafetyResources` card in the calm `safety` color, headed "you deserve to feel safe. here's real help.", with these rows exactly as in the product spec:
  - **National Domestic Violence Hotline:** Call **1-800-799-7233** · Text **START** to **88788**
  - **988 Suicide & Crisis Lifeline:** Call or text **988**
  - **Immediate danger:** Call **911**
  - Footer: "unsaid isn't a crisis service. these people are."
- **Safety-mode variant:** the same right-screen resources card is what the rant flow shows instead of screen 3 when the mock safety signal is on, headed "we're not going to show memories right now."
- **Components:** `PlaceholderToggle`, `Card`, `SafetyResources`, `DuoFrame`.

- **Placeholder buttons (NOT YET CONNECTED):** "breakup" toggle [`breakup-toggle`] · "block" choice card [`ex-block`] · "allow up to 3 future messages" choice card [`ex-allow-three`] · "save" [`ex-settings-save`] · "block" [`recipient-block`] · "report" [`recipient-report`] · "call 1-800-799-7233" [`hotline-ndvh-call`] · "text START to 88788" [`hotline-ndvh-text`] · "call or text 988" [`hotline-988`] · "call 911" [`emergency-911`].
- **Important:** in the shell the resource buttons **must not** use real `tel:` or `sms:` links, so nobody dials by accident during a demo. They toast like every other placeholder, and the numbers stay visible as plain text so anyone can read them.
- **Motion:** minimal. Plain fades only; no pulses, ripples, or playful motion on this screen.

8.9 Screen 9 — Unsends inbox (swipeable story layout)

- **Purpose:** the unsends people left you, one at a time, like a stack of letters.
- **Frame:** single phone.
- **Layout (top to bottom):**
  1. Header "for you".
  2. A horizontal row of story rings: Mom (amber ring, new), Jordan, Priya, Dad (greyed, seen).
  3. A full-height swipeable card stack. Each card: sender avatar and name, time ("this morning"), the unsend in Caveat, one or two photos, and actions. Cards: Mom, "no emergency. I just wanted to hear your voice." (voice, with "listen") · Jordan, "I'm sorry. Dinner Friday?" with a Plan chip (your old favorite taco spot · Friday, Nov 6 · 7:00 PM) and accept/reject · Priya, "found these and miss you all. reunion soon?" (from Marfa Trip).
  4. Page dots under the stack; a faint `TideLine` in the background.
- **Components:** `StoryViewer` rings, `UnsendCard`, `Chip`, `Sheet`, `TideLine`, `RippleRing`.
- **Placeholder buttons (NOT YET CONNECTED):** "listen" [`unsend-play`] · "reply with an unsend" [`unsend-reply`] · "keep it" [`vault-save`] · "accept" on the plan [`plan-accept`] · "reject" on the plan [`plan-reject`] · "block" in the card's "…" menu [`recipient-block`] · "report" in the same menu [`recipient-report`].
- **Navigation only:** swiping between cards (local index) and tapping a story ring (routes to screen 10).
- **Motion:** cards move with `spring-soft`; the next card peeks 12px behind the current one; a new card arrives with a soft ripple ring (the chime).

8.10 Screen 10 — Reminisce mode

- **Purpose:** swipe through someone's love for you, one moment at a time. Everyone already knows how stories work.
- **Frame:** single phone, full-bleed story.

- **Layout (top to bottom):**
    1. **Progress bars:** five segments across the top.
    2. **Header:** Mom's profile picture, "Mom", and a small source label for the current item ("unsend", "from instagram", "from your camera roll", "from whatsapp"); a close X (navigation back to 9).
    3. **Content (five items, mixed):** (1) Mom's unsend in Caveat, "no emergency. just miss you.", with a waveform · (2) a photo from Instagram: her birthday dinner · (3) a photo from the camera roll: graduation · (4) a photo from WhatsApp: a blurry family selfie from the Fam chat · (5) Mom's unsend, "I'm so proud of you. I always was."
    4. **Footer:** a "reply" field, a "call Mom" button, and a small heart "keep".
- **Interaction (navigation only, no backend):** tap the **right** third to go forward, tap the **left** third to go back, press and hold to pause; each progress bar fills over 5s.
- **Components:** `StoryViewer`, `UnsendCard`, `Waveform`.
- **Placeholder buttons (NOT YET CONNECTED):** "reply" [`reminisce-reply`] · "call Mom" [`call-start`] · "keep" heart [`memory-favorite`].
- **Source labels are plain text**, never app logos.
- **Motion:** items cross-fade over 480ms; progress bars fill linearly; nothing snaps between items.

8.11 Screen 11 — Contextual story notification (concept)

- **Purpose:** the full circle from "k" to a phone call. Mom's waiting unsend shows up at a natural break, while her kid is on a story.
- **Frame:** Duo. **Left (Mom's phone, earlier):** "10 missed calls" to her kid, then a voice-unsend recorder with a waveform, a "record" button, and the line "No emergency. I just wanted to hear your voice." **Right (the kid's phone):** a **generic look-alike story viewer** showing an illustrated cozy library study scene (lamp, books, laptop, coffee), a story progress bar, and a generic avatar with "you · 2h". A `ConceptLabel` above it: "concept · look-alike. a real version needs a Meta partnership."
- **Layout, right (top to bottom):** the `NotificationSheet` slides down from the top over the story: `UnsaidMark`, "**Mom left you something.**", a one-line preview "no emergency. just miss you.", and two buttons, **"Reply with an unsend"** and **"Call Mom"**; a small drag handle to dismiss. A second state (shown in the Remotion version after "Call Mom") is a warm call screen: "Mom", "0:01… 0:02…", and "end".
- **Components:** `DuoFrame`, `StoryViewer` (look-alike), `NotificationSheet`, `UnsaidMark`, `Waveform`, `RippleRing`, `ConceptLabel`.
- **Placeholder buttons (NOT YET CONNECTED):** left "record" [`mom-voice-unsend-record`] · "Reply with an unsend" [`contextual-reply-unsend`] · "Call Mom" [`contextual-call`] · swipe-up dismiss handle [`contextual-dismiss`] · "end" on the call screen [`call-end`].
- **Look-alike only (v2):** Meta-style story chrome is drawn in SVG/CSS with the app name as plain text; no official logos, icons, glyph files, or screenshots.

- **Motion:** the story plays for 2s; the notification slides in with `spring-soft` and a ripple ring; hold. The call screen warms from cream to peach over 1.2s.

8.12 Screen 12 — Plans picker

- **Purpose:** from "we should hang out" to "see you Friday at 7." Attach a Plan to an unsend.
- **What "Plans" means here:** the product spec's Plans section (Section 9) defines a Plan as **a restaurant, a date, and a time** attached to an unsend, which the recipient can **accept** or **reject**. **That section has no pricing tiers or prices**, so this screen has none, and none are invented. It uses only the fields and example values written in the spec.
- **Frame:** Duo. **Left (your phone):** the picker. **Right (Jordan's phone):** what the recipient sees.
- **Layout, left (top to bottom):** header "make it real."; three rows matching the spec's Plans table exactly:

Field	Mock value (from the spec)
Restaurant	Your old favorite taco spot
Date	Friday, Nov 6
Time	7:00 PM

  then a primary button "attach plan". - **Layout, right:** the unsend card ("I'm sorry. Dinner Friday?") with the Plan chip and two buttons, **Accept** and **Reject**; small text "no pressure. no follow-ups." - **Components:** `Card`, `Chip`, `UnsendCard`, `DuoFrame`. - **Placeholder buttons (NOT YET CONNECTED):** "restaurant" row [`plan-restaurant-pick`] · "date" row [`plan-date-pick`] · "time" row [`plan-time-pick`] · "attach plan" [`plan-attach-confirm`] · "Accept" [`plan-accept`] · "Reject" [`plan-reject`]. - **Motion:** rows fade in with a stagger; the Plan chip scales in on the right screen.

8.13 Screen 13 — Group-chat unsend

- **Purpose:** for the friend group that went quiet.
- **Frame:** single phone.
- **Layout (top to bottom):** header "for the group that went quiet."; group chips **Fam**, **Roommates**, **Marfa Trip** (Marfa Trip selected); member avatars (Priya, Jordan, you); a "photos with all of you" strip (marfa sunset, road trip, 2 AM laughing fit) with "find more"; the draft in Caveat, "found these and miss you all. reunion soon?", with "sound more like us"; "+ add a plan"; a "send through" row (whatsapp group / messages group, as text labels); primary button "send to the group".
- **Components:** `Chip`, `Avatar`, `MemoryCard`, `UnsendCard`, `PlaceholderSegmented`.

- **Placeholder buttons (NOT YET CONNECTED):** group chip [`group-pick`] · "find more" [`group-photo-match`] · "sound more like us" [`group-draft-tone`] · "+ add a plan" [`plan-attach`] · "send through" row [`delivery-channel-pick`] · "send to the group" [`group-send`].
- **Motion:** member avatars fade in for the selected group; photos stagger in.

8.14 Screen 14 — Phone-activity settings

- **Purpose:** "**record at 3 AM, deliver when they're actually awake.**" Explain and tune the only delivery rule for everyday unsends.
- **Frame:** Duo. **Left (your phone, 3:02 AM):** the settings, with a recorded unsend marked "waiting". **Right (Jordan's phone, later):** a mock day timeline with unlock dots: 7:10 AM (skipped, "groggy"), 12:30 PM, and 6:40 PM ("delivered here"), with a ripple ring on the delivery dot.
- **Layout, left (top to bottom):** header in `hand-lg`: "record at 3 AM, deliver when they're actually awake."; explainer: "we skip their first, groggy unlock. we wait for the 2nd or 3rd, and lean later in the day."; segmented "deliver on" **2nd unlock / 3rd unlock**; toggle "lean later in the day" (on); toggles "soft chime" and "haptic pulse"; a pending list, "to Jordan · waiting", with "review" and "cancel"; a permission row, "allow phone activity" (the recipient side); a demo-only button, "simulate an unlock".
- **No scheduling:** there is deliberately **no time picker, date picker, or "send at" control** here or anywhere for everyday unsends. Only the timed and posthumous messages on screen 6 have dates.
- **Components:** `PlaceholderSegmented`, `PlaceholderToggle`, `Card`, `RippleRing`, `DuoFrame`.
- **Placeholder buttons (NOT YET CONNECTED):** "deliver on" segmented [`delivery-unlock-pick`] · "lean later in the day" toggle [`delivery-later-weight`] · "soft chime" toggle [`chime-toggle`] · "haptic pulse" toggle [`haptic-toggle`] · "review" [`pending-unsend-review`] · "cancel" [`pending-unsend-cancel`] · "allow phone activity" [`phone-activity-permission`] · "simulate an unlock" [`unlock-simulate`].
- **Motion:** unlock dots appear left to right along the timeline; the delivered dot gets the ripple ring (the haptic).

8.15 Screen 15 — Logo overlay on look-alike posts (concept)

- **Purpose:** show that Unsaid meets people where they already are, inside the app each generation already uses.
- **Frame:** three phone frames side by side (on narrow screens, one phone with three swipeable panels), each captioned underneath. A `ConceptLabel` above the row: "concept · look-alike screens. a real overlay needs a Meta partnership."
- **Layout:**

    - **Frame 1, caption "Gen Z":** a generic photo-feed look-alike: a square photo post from Mom (her birthday dinner) with generic heart/comment/share outlines in plum, not any real app's icons.
    - **Frame 2, caption "your parents":** a generic chat-app look-alike: the Fam group with a shared photo bubble from Dad.
    - **Frame 3, caption "the grandparents":** a generic social-feed look-alike: a "memories"-style card, "6 years ago today", with a family photo.
    - On **each image, top-right corner:** the Unsaid open-speech-bubble mark, 26px, white on a frosted circle with a faint shadow.
    - A line under the row: "unsaid meets you where you already are."
- **Components:** `PhoneFrame` ×3, `PhotoFeedPost`, `ChatAppBubble`, `SocialFeedPost`, `UnsaidMark`, `PulseOnce`, `RippleRing`, `ConceptLabel`.
- **Placeholder buttons (NOT YET CONNECTED):** the mark on the photo-feed post [`overlay-open-memory`] · the mark on the chat-app photo [`overlay-open-unsend-draft`] · the mark on the social-feed card [`overlay-open-graph-node`]. In the real concept a tap opens Unsaid to that person; in the shell each one only toasts.
- **Look-alike only (v2):** from Phase 5 of the prompt, the three frames reuse the Instagram / WhatsApp / Facebook look-alike components (drawn SVG/CSS, real names as text); no official logos, wordmarks, glyph files, or screenshots.
- **Motion:** each mark does `pulse-once` (the heartbeat), 600ms apart from frame 1 to 3; a tap shows a ripple ring before the toast.

---

9. The Frontend-Backend Contract

9.1 Every button, and what it will connect to

This is the full list of action buttons across all 15 screens: **94 buttons, using 87 unique feature IDs.** *(v2: with the fake Meta apps in Section 9.4, the total is **110 buttons, 94 unique feature IDs, 16 shared IDs**.)* Every one renders with `data-backend="<Feature ID>"`, shows the NOT YET CONNECTED badge, and only toasts "Not connected yet". A feature ID appears on more than one screen only when it is the same backend action; 7 IDs are shared this way (`pending-unsend-review`, `plan-attach`, `delivery-channel-pick`, `recipient-block`, `recipient-report`, `plan-accept`, `plan-reject`). The three proxy slots on screen 6 are one row because they share one button type and ID.

Mudit fills in the "Expected request/response" column. Each cell starts as "TBD by Mudit" with a one-line hint. The `backend/` folder implements each feature ID; when one is done, its status here changes to CONNECTED and the button's placeholder handler is swapped for the real one.

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
1	ask-bar arrow ("try 'I miss Mom'")	1 Home	`muse-ask`	Muse connector + Muse Spark: surface the right hidden, categorized unsends for "I miss Mom"	TBD by Mudit. Hint: query text in, ranked unsends + memories out	NOT YET CONNECTED
2	send him something	1 Home	`missed-call-nudge`	Missed-call reminders (mock call-log data) → parent unsend draft	TBD by Mudit. Hint: person ID in, draft + suggested photo out	NOT YET CONNECTED
3	not now	1 Home	`nudge-dismiss`	Nudge cooldown, so reminders never nag	TBD by Mudit. Hint: nudge ID in, ok out	NOT YET CONNECTED
4	say something to Priya	1 Home	`drift-reach-out`	Drift detection (Appendix A) → unsend draft	TBD by Mudit. Hint: person ID in, draft + memory out	NOT YET CONNECTED
5	review (pending strip)	1 Home	`pending-unsend-review`	Phone-activity delivery queue: read a pending unsend	TBD by Mudit. Hint: unsend ID in, unsend + status out	NOT YET CONNECTED
6	hold to talk	2 Rant journal	`rant-record`	Muse Voice Transcribe (streaming transcription + voice tone cues)	TBD by Mudit. Hint: audio stream in, transcript chunks out	NOT YET CONNECTED
7	stop	2 Rant journal	`rant-stop`	Muse Voice Transcribe end of stream → Muse Spark emotion analysis → safety gate	TBD by Mudit. Hint: session ID in, final transcript + tone + person + safety flag out	NOT YET CONNECTED
8	start over	2 Rant journal	`rant-discard`	Rant journal storage: discard the draft rant	TBD by Mudit. Hint: session ID in, ok out	NOT YET CONNECTED
9	type instead	2 Rant journal	`rant-type`	Muse Spark emotion analysis on typed text → safety gate	TBD by Mudit. Hint: text in, tone + person + safety flag out	NOT YET CONNECTED
10	not quite (emotion chip)	2 Rant journal	`emotion-chip-edit`	Muse Spark emotion/person result correction	TBD by Mudit. Hint: rant ID + corrected tone/person in, ok out	NOT YET CONNECTED

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
11	keep it private	2 Rant journal	`rant-save-private`	Private rant journal storage (raw rants never leave the app)	TBD by Mudit. Hint: rant in, rant ID out	NOT YET CONNECTED
12	show me the good stuff	2 Rant journal	`memory-surface-request`	Safety gate first, then Muse Spark memory picking (camera roll + Graph API photos) and the "everything will be okay" caption	TBD by Mudit. Hint: rant ID in, photos + caption out, or a safety-mode flag	NOT YET CONNECTED
13	keep (heart)	3 Memory surfacing	`memory-select`	Memory selection for the unsend	TBD by Mudit. Hint: memory ID in, ok out	NOT YET CONNECTED
14	who's this?	3 Memory surfacing	`face-cluster-name`	On-device face clustering: name a cluster once, tag every photo of that person	TBD by Mudit. Hint: cluster ID + name in, tagged count out (runs on device)	NOT YET CONNECTED
15	open (Remember this?)	3 Memory surfacing	`past-unsend-resurface`	Past unsends resurface (spec Section 10)	TBD by Mudit. Hint: person ID in, past unsends out (none if blocked or reported)	NOT YET CONNECTED
16	add from instagram or facebook	3 Memory surfacing	`graph-api-photo-import`	Facebook Graph API / Instagram Graph API photo import	TBD by Mudit. Hint: auth token in, photos + tags + dates out	NOT YET CONNECTED
17	use camera roll	3 Memory surfacing	`camera-roll-scan`	Camera roll access + on-device face clustering + photo metadata	TBD by Mudit. Hint: permission in, face clusters + photo refs out	NOT YET CONNECTED
18	I'm ready	3 Memory surfacing	`unsend-draft-generate`	Muse Spark unsend drafting (the user edits every word)	TBD by Mudit. Hint: rant ID + chosen memories in, draft text out	NOT YET CONNECTED
19	save for later	3 Memory surfacing	`memory-save-later`	Saved memories store	TBD by Mudit. Hint: memory IDs in, ok out	NOT YET CONNECTED
20	recipient avatar	4 Send to partner	`recipient-pick`	People list (Unsaid users; Graph API friends who	TBD by Mudit. Hint: nothing in, people list out	NOT YET CONNECTED

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
				also use Unsaid)		
21	rewrite gently	4 Send to partner	`unsend-draft-rewrite`	Muse Spark rewrite (suggestion only; the user stays the author)	TBD by Mudit. Hint: draft text in, gentler draft out	NOT YET CONNECTED
22	say it with my voice	4 Send to partner	`unsend-voice-record`	Muse Voice Transcribe for a voice unsend	TBD by Mudit. Hint: audio in, audio URL + transcript out	NOT YET CONNECTED
23	+ photos	4 Send to partner	`unsend-attach-photos`	Memory picker / photo store	TBD by Mudit. Hint: photo IDs in, attachment refs out	NOT YET CONNECTED
24	make a cover	4 Send to partner	`muse-image-cover`	Muse Image unsend cover art (from real shared moments, never invented)	TBD by Mudit. Hint: memory IDs in, image URL out	NOT YET CONNECTED
25	+ add a plan	4 Send to partner	`plan-attach`	Plans: attach a restaurant, date, and time to an unsend	TBD by Mudit. Hint: unsend ID in, plan draft ID out	NOT YET CONNECTED
26	send through (segmented)	4 Send to partner	`delivery-channel-pick`	Share-flow delivery channel (Messages / `wa.me` / `m.me`, Appendix D)	TBD by Mudit. Hint: channel in, deep-link template out	NOT YET CONNECTED
27	change (delivery card)	4 Send to partner	`delivery-rule-open`	Phone-activity delivery settings for this unsend	TBD by Mudit. Hint: unsend ID in, current rule out	NOT YET CONNECTED
28	send when they're ready	4 Send to partner	`unsend-queue-send`	Phone-activity delivery queue + safety check at delivery time	TBD by Mudit. Hint: unsend payload in, queued ID + status out	NOT YET CONNECTED
29	ask your graph (submit)	5 Brain graph	`graph-ask`	Muse Spark "ask your graph" (e.g., "when did I last see Priya?")	TBD by Mudit. Hint: question in, answer + node IDs out	NOT YET CONNECTED
30	reach out (node sheet)	5 Brain graph	`graph-reach-out`	Unsend draft for a person in the graph	TBD by Mudit. Hint: person ID in, draft + memory out	NOT YET CONNECTED
31	edit (relationship)	5 Brain graph	`relationship-edit`	Relationship guessing override (Appendix A)	TBD by Mudit. Hint: person ID + relationship in, ok out	NOT YET CONNECTED

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
32	show memory (node sheet)	5 Brain graph	`graph-memory-open`	Memory detail from Graph API / data-export memories	TBD by Mudit. Hint: memory ID in, photo + caption + date out	NOT YET CONNECTED
33	time slider	5 Brain graph	`graph-time-slider`	Brain graph history: the graph at a point in time	TBD by Mudit. Hint: year in, nodes + links out	NOT YET CONNECTED
34	add your message history	5 Brain graph	`dyi-export-upload`	Meta "Download Your Information" export ingestion → Muse Spark memory extraction and relationship guessing	TBD by Mudit. Hint: export file in, job ID + graph build status out	NOT YET CONNECTED
35	record	6 Posthumous setup	`timed-message-record`	Timed message capture (text, voice, or video)	TBD by Mudit. Hint: media in, message draft ID out	NOT YET CONNECTED
36	when (1 / 5 / 10 years / a milestone)	6 Posthumous setup	`timed-delivery-pick`	Timed message delivery: 1, 5, or 10 years, or a milestone date	TBD by Mudit. Hint: message ID + option in, ok out	NOT YET CONNECTED
37	change date	6 Posthumous setup	`milestone-date-set`	Milestone date for a timed message (June 12, 2034, Graduation Day)	TBD by Mudit. Hint: message ID + date + label in, ok out	NOT YET CONNECTED
38	only after I'm gone (toggle)	6 Posthumous setup	`posthumous-toggle`	Posthumous release flag (proxy-gated)	TBD by Mudit. Hint: message ID + on/off in, ok out	NOT YET CONNECTED
39	choose (each of the 3 proxy slots)	6 Posthumous setup	`proxy-invite`	Proxy confirmation service: invite a proxy (min 2, max 3)	TBD by Mudit. Hint: person ID in, invite status out	NOT YET CONNECTED
40	+ add a backup proxy	6 Posthumous setup	`backup-proxy-invite`	Proxy confirmation service: named backup proxy (30-day fallback)	TBD by Mudit. Hint: person ID in, invite status out	NOT YET CONNECTED

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
41	seal it	6 Posthumous setup	`timed-message-seal`	Durable long-term message storage + release rules	TBD by Mudit. Hint: message ID in, sealed confirmation out	NOT YET CONNECTED
42	view details	7 Proxy confirmation	`proxy-status`	Proxy confirmation service: status ("Proxy confirmation 3 of 3 received")	TBD by Mudit. Hint: user ID in, proxy statuses out	NOT YET CONNECTED
43	open the letter	7 Proxy confirmation	`posthumous-letter-open`	Released posthumous message fetch	TBD by Mudit. Hint: message ID in, content + media out	NOT YET CONNECTED
44	play	7 Proxy confirmation	`letter-voice-play`	Voice message playback	TBD by Mudit. Hint: message ID in, audio URL out	NOT YET CONNECTED
45	keep it forever	7 Proxy confirmation	`message-accept`	Recipient accepts → saved forever in their vault	TBD by Mudit. Hint: message ID in, ok out	NOT YET CONNECTED
46	not now	7 Proxy confirmation	`message-reject`	Recipient rejects (a respected choice; not shown)	TBD by Mudit. Hint: message ID in, ok out	NOT YET CONNECTED
47	breakup (toggle)	8 Ex / breakup	`breakup-toggle`	Ex feature: the breakup toggle on the profile	TBD by Mudit. Hint: person ID + on/off in, ok out	NOT YET CONNECTED
48	block (choice card)	8 Ex / breakup	`ex-block`	Ex feature: block, effective immediately	TBD by Mudit. Hint: person ID in, ok out	NOT YET CONNECTED
49	allow up to 3 future messages (choice card)	8 Ex / breakup	`ex-allow-three`	Ex feature: 3-message hard cap (video, text, or voice)	TBD by Mudit. Hint: person ID in, cap + used count out	NOT YET CONNECTED
50	save	8 Ex / breakup	`ex-settings-save`	Ex feature settings	TBD by Mudit. Hint: settings in, ok out	NOT YET CONNECTED
51	block	8 Ex / breakup	`recipient-block`	Recipient protections: block (from day one, for everyone) + stop memories and reconciliation prompts	TBD by Mudit. Hint: person ID in, ok out	NOT YET CONNECTED

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
52	report	8 Ex / breakup	`recipient-report`	Recipient protections: report → safety trigger	TBD by Mudit. Hint: person ID + reason in, report ID out	NOT YET CONNECTED
53	call 1-800-799-7233	8 Ex / breakup	`hotline-ndvh-call`	No server call: native dialer link to the National Domestic Violence Hotline	TBD by Mudit. Hint: client-only `tel:` link to 1-800-799-7233	NOT YET CONNECTED
54	text START to 88788	8 Ex / breakup	`hotline-ndvh-text`	No server call: native SMS link to the National Domestic Violence Hotline	TBD by Mudit. Hint: client-only `sms:` link to 88788 with body START	NOT YET CONNECTED
55	call or text 988	8 Ex / breakup	`hotline-988`	No server call: native call/SMS link to the 988 Suicide & Crisis Lifeline	TBD by Mudit. Hint: client-only `tel:` / `sms:` link to 988	NOT YET CONNECTED
56	call 911	8 Ex / breakup	`emergency-911`	No server call: native dialer link for immediate danger	TBD by Mudit. Hint: client-only `tel:` link to 911	NOT YET CONNECTED
57	listen	9 Unsends inbox	`unsend-play`	Voice unsend playback	TBD by Mudit. Hint: unsend ID in, audio URL out	NOT YET CONNECTED
58	reply with an unsend	9 Unsends inbox	`unsend-reply`	Unsend composer reply → phone-activity delivery queue	TBD by Mudit. Hint: parent unsend ID in, draft ID out	NOT YET CONNECTED
59	keep it	9 Unsends inbox	`vault-save`	Recipient vault: save forever	TBD by Mudit. Hint: unsend ID in, ok out	NOT YET CONNECTED
60	accept (plan)	9 Unsends inbox	`plan-accept`	Plans: recipient accepts (confirms for both people)	TBD by Mudit. Hint: plan ID in, confirmed plan out	NOT YET CONNECTED
61	reject (plan)	9 Unsends inbox	`plan-reject`	Plans: recipient rejects (no follow-up nagging)	TBD by Mudit. Hint: plan ID in, ok out	NOT YET CONNECTED
62	block (… menu)	9 Unsends inbox	`recipient-block`	Recipient protections: block	TBD by Mudit. Hint: same endpoint as the block on screen 8	NOT YET CONNECTED

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
63	report (… menu)	9 Unsends inbox	`recipient-report`	Recipient protections: report	TBD by Mudit. Hint: same endpoint as the report on screen 8	NOT YET CONNECTED
64	reply	10 Reminisce mode	`reminisce-reply`	Unsend composer reply from a story item	TBD by Mudit. Hint: person ID + item ID in, draft ID out	NOT YET CONNECTED
65	call Mom	10 Reminisce mode	`call-start`	Call handoff to the native dialer or a call link	TBD by Mudit. Hint: person ID in, call link out (likely client-side)	NOT YET CONNECTED
66	keep (heart)	10 Reminisce mode	`memory-favorite`	Favorite a memory or unsend in the vault	TBD by Mudit. Hint: item ID in, ok out	NOT YET CONNECTED
67	record (Mom's phone)	11 Story notification (concept)	`mom-voice-unsend-record`	Muse Voice Transcribe for a missed-call voice unsend → delivery queue	TBD by Mudit. Hint: audio in, unsend ID out	NOT YET CONNECTED
68	Reply with an unsend	11 Story notification (concept)	`contextual-reply-unsend`	Contextual trigger reply (concept; real version needs a Meta partnership)	TBD by Mudit. Hint: unsend ID in, reply draft ID out (demo stays mock)	NOT YET CONNECTED
69	Call Mom	11 Story notification (concept)	`contextual-call`	Contextual trigger call (concept; real version needs a Meta partnership)	TBD by Mudit. Hint: person ID in, call link out	NOT YET CONNECTED
70	swipe-up dismiss handle	11 Story notification (concept)	`contextual-dismiss`	Contextual trigger cooldown, so it never nags	TBD by Mudit. Hint: notification ID in, ok out	NOT YET CONNECTED
71	end (call screen)	11 Story notification (concept)	`call-end`	Call handoff end	TBD by Mudit. Hint: probably client-only; confirm	NOT YET CONNECTED
72	restaurant (row)	12 Plans picker	`plan-restaurant-pick`	Plans: restaurant field	TBD by Mudit. Hint: query in, restaurant options out (data source TBD)	NOT YET CONNECTED
73	date (row)	12 Plans picker	`plan-date-pick`	Plans: date field	TBD by Mudit. Hint: date in, ok out	NOT YET CONNECTED
74	time (row)	12 Plans picker	`plan-time-pick`	Plans: time field	TBD by Mudit. Hint: time in, ok out	NOT YET CONNECTED

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
75	attach plan	12 Plans picker	`plan-attach-confirm`	Plans: save the restaurant, date, and time on the unsend	TBD by Mudit. Hint: unsend ID + restaurant/date/time in, plan ID out	NOT YET CONNECTED
76	Accept	12 Plans picker	`plan-accept`	Plans: recipient accepts	TBD by Mudit. Hint: same endpoint as accept on screen 9	NOT YET CONNECTED
77	Reject	12 Plans picker	`plan-reject`	Plans: recipient rejects	TBD by Mudit. Hint: same endpoint as reject on screen 9	NOT YET CONNECTED
78	group chip (Fam / Roommates / Marfa Trip)	13 Group-chat unsend	`group-pick`	Group membership from Messenger and Facebook group data (data export)	TBD by Mudit. Hint: nothing in, groups + members out	NOT YET CONNECTED
79	find more	13 Group-chat unsend	`group-photo-match`	Photo matching: photos where several group members appear together	TBD by Mudit. Hint: group ID in, photo list out	NOT YET CONNECTED
80	sound more like us	13 Group-chat unsend	`group-draft-tone`	Muse Spark draft in the group's natural tone	TBD by Mudit. Hint: group ID + draft in, rewritten draft out	NOT YET CONNECTED
81	+ add a plan	13 Group-chat unsend	`plan-attach`	Plans attached to a group unsend	TBD by Mudit. Hint: same endpoint as "+ add a plan" on screen 4	NOT YET CONNECTED
82	send through (row)	13 Group-chat unsend	`delivery-channel-pick`	Share-flow delivery channel for a group	TBD by Mudit. Hint: same endpoint as "send through" on screen 4	NOT YET CONNECTED
83	send to the group	13 Group-chat unsend	`group-send`	Group unsend via a deep link into the group's existing app (Appendix D)	TBD by Mudit. Hint: group unsend payload in, deep link out	NOT YET CONNECTED
84	deliver on (2nd / 3rd unlock)	14 Phone-activity settings	`delivery-unlock-pick`	Phone-activity delivery queue: which unlock to deliver on	TBD by Mudit. Hint: 2 or 3 in, ok out	NOT YET CONNECTED
85	lean later in the day (toggle)	14 Phone-activity settings	`delivery-later-weight`	Phone-activity delivery queue: weighting toward later in the day	TBD by Mudit. Hint: on/off in, ok out	NOT YET CONNECTED

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
86	soft chime (toggle)	14 Phone-activity settings	`chime-toggle`	Notification preferences (chime on delivery)	TBD by Mudit. Hint: on/off in, ok out	NOT YET CONNECTED
87	haptic pulse (toggle)	14 Phone-activity settings	`haptic-toggle`	Notification preferences (haptic on delivery)	TBD by Mudit. Hint: on/off in, ok out	NOT YET CONNECTED
88	review	14 Phone-activity settings	`pending-unsend-review`	Phone-activity delivery queue: read a pending unsend	TBD by Mudit. Hint: same endpoint as "review" on screen 1	NOT YET CONNECTED
89	cancel	14 Phone-activity settings	`pending-unsend-cancel`	Phone-activity delivery queue: cancel before delivery	TBD by Mudit. Hint: unsend ID in, ok out	NOT YET CONNECTED
90	allow phone activity	14 Phone-activity settings	`phone-activity-permission`	Recipient phone-activity (unlock events) permission	TBD by Mudit. Hint: permission grant in, device registration out	NOT YET CONNECTED
91	simulate an unlock (demo only)	14 Phone-activity settings	`unlock-simulate`	Demo unlock-event simulator for the delivery queue (MVP scope)	TBD by Mudit. Hint: recipient ID in, delivered unsend or "skipped: 1st unlock" out	NOT YET CONNECTED
92	Unsaid mark on the photo-feed post ("Gen Z")	15 Logo overlay (concept)	`overlay-open-memory`	Logo overlay tap → that friend's memory page (concept; needs a Meta partnership)	TBD by Mudit. Hint: post/person ref in, memory page out	NOT YET CONNECTED
93	Unsaid mark on the chat-app photo ("your parents")	15 Logo overlay (concept)	`overlay-open-unsend-draft`	Logo overlay tap → unsend draft to that person or group (concept)	TBD by Mudit. Hint: chat/person ref in, draft ID out	NOT YET CONNECTED
94	Unsaid mark on the social-feed card ("the grandparents")	15 Logo overlay (concept)	`overlay-open-graph-node`	Logo overlay tap → brain-graph node + shared group chats (concept)	TBD by Mudit. Hint: person ref in, node + groups out	NOT YET CONNECTED

9.2 Navigation-only controls (not backend)

These are the only controls that actually do something in the shell. They change the visible mock screen or story card and never call anything, so they get no badge and no `data-backend`.

Control	Where	What it does
Tab bar (home, graph, inbox, you)	Most screens	Routes to 1, 5, 9, or the "you" list
Back chevron / close X	All sub-screens	Goes back
ScreenSwitcher pill	Outside the phone, every page	Jumps to any of the 15 screens
"next →" dev link	Under each phone, outside the frame	Follows the navigation map in Section 7
"start a rant"	1 Home	Routes to 2
"get help"	1 Home (persistent)	Routes to the resources on 8
Node tap	5 Brain graph	Opens the node bottom sheet (local state)
Story rings	9 Unsends inbox	Routes to 10 for that person
Swipe between cards	9 Unsends inbox	Changes the local card index
Tap right / tap left / press and hold	10 Reminisce mode	Next item / previous item / pause

9.3 Notes for Mudit

- `frontend/lib/contract.ts` mirrors table 9.1. Wiring a feature means: build it in `backend/`, fill in its request/response cell here, set its status to CONNECTED, then replace the placeholder handler for that `featureId` with the real call. Keep the `data-backend` attribute so tests can still find every button.
- `grep -r 'data-backend' frontend/` lists every placeholder still in the UI.
- Left **TBD** for you: every request/response shape, the API style (REST routes vs. server actions), auth, where media is stored, the restaurant data source for `plan-restaurant-pick`, and how the unlock signal for the phone-activity trigger is collected on a real device.
- Rows 53–56 (the safety hotlines) need no server call. They become plain `tel:`/`sms:` links in the real app; they are placeholders in the shell only so nothing dials by accident during a demo.
- Rows 67–71, 92–94, and 95–110 are concept features. A real version needs a Meta partnership; for the hackathon they stay mock.
- **Backend sync (v2):** the frontend reads `backend/` (read-only) every build phase and keeps `docs/backend-sync.md`. A backend feature with no frontend control gets a new ID and row here (after row 110). The build ends with `docs/unconnected-buttons.md`: every button with no backend behind it (feature ID, screen, label), so Gurneal can delete it or keep it as a blank button the animation won't use.

9.4 v2 additions: fake Meta apps (rows 95–110)

These buttons live in the look-alike Meta apps (`Claude_Code_Frontend_Prompt.md` Phase 5). That adds **7 new unique IDs**; 9 rows reuse existing IDs. **Totals: 110 buttons, 94 unique feature IDs, 16 shared IDs:** the 7 shared in v1, plus `overlay-open-memory`, `contextual-reply-unsend`, `contextual-call`, `contextual-dismiss`, `overlay-open-graph-node`, `unsend-reply`, `call-start`, `call-end`, and `unsend-play`.

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
95	Unsaid mark on Mom's birthday-dinner post	Instagram look-alike · feed	`overlay-open-memory`	Same as row 92 (shared)	Same as row 92	NOT YET CONNECTED
96	send an unsaid (DM composer chip)	Instagram look-alike · DM with Mom	`ig-dm-unsend-compose`	Compose an unsend from inside a DM thread (concept; needs a Meta partnership)	TBD by Mudit. Hint: thread/person ref in, draft ID out	NOT YET CONNECTED
97	Reply with an unsend	Instagram look-alike · story notification	`contextual-reply-unsend`	Same as row 68 (shared)	Same as row 68	NOT YET CONNECTED
98	Call Mom	Instagram look-alike · story notification	`contextual-call`	Same as row 69 (shared)	Same as row 69	NOT YET CONNECTED
99	dismiss grabber	Instagram look-alike · story notification	`contextual-dismiss`	Same as row 70 (shared)	Same as row 70	NOT YET CONNECTED
100	send ("help me say sorry to Jordan")	Meta AI look-alike · chat	`meta-ai-chat-ask`	Meta AI / Muse Spark chat request that can return an unsend suggestion	TBD by Mudit. Hint: prompt in, reply + optional draft out	NOT YET CONNECTED
101	open in Unsaid	Meta AI look-alike · chat	`meta-ai-unsaid-handoff`	Hand off a Meta AI suggestion into an Unsaid draft	TBD by Mudit. Hint: suggestion ref in, draft ID out	NOT YET CONNECTED
102	import to Unsaid (glasses captures)	Meta AI look-alike · glasses tab	`glasses-media-import`	Import Ray-Ban Meta captures as memories (concept)	TBD by Mudit. Hint: media refs in, memory IDs out	NOT YET CONNECTED
103	record an unsend hands-free	Meta AI look-alike · glasses tab	`glasses-voice-unsend`	Voice unsend recorded through the glasses ("Hey Meta, tell Mom I miss her"; concept)	TBD by Mudit. Hint: audio in, draft ID out	NOT YET CONNECTED
104	Unsaid mark on Nana Ruth's memories photo	Facebook look-alike · feed	`overlay-open-graph-node`	Same as row 94 (shared)	Same as row 94	NOT YET CONNECTED

#	Button label	Screen	Feature ID	Backend feature it will connect to	Expected request/response	Status
105	send to Messenger	Facebook look-alike · post	`messenger-handoff`	Deliver an unsend through Messenger (concept)	TBD by Mudit. Hint: unsend ID + recipient in, ok out	NOT YET CONNECTED
106	open in Unsaid (group unsend card)	WhatsApp look-alike · Marfa Trip	`wa-group-unsend-open`	Open a group unsend from a WhatsApp group (concept)	TBD by Mudit. Hint: group/unsend ref in, unsend out	NOT YET CONNECTED
107	reply with an unsend	WhatsApp look-alike · Marfa Trip	`unsend-reply`	Same as row 58 (shared)	Same as row 58	NOT YET CONNECTED
108	header call icon	WhatsApp look-alike · Marfa Trip	`call-start`	Same as row 65 (shared)	Same as row 65	NOT YET CONNECTED
109	end (call screen)	WhatsApp look-alike · call	`call-end`	Same as row 71 (shared)	Same as row 71	NOT YET CONNECTED
110	listen (Mom's voice-unsend bubble)	Messenger look-alike stub	`unsend-play`	Same as row 57 (shared)	Same as row 57	NOT YET CONNECTED

10. Ready-to-Paste Prompt for Claude

```
(v2 note: for the full build, use the phased prompt in
Claude_Code_Frontend_Prompt.md; it supersedes this one-shot prompt. This version is
kept as a short summary and is consistent with v2.)
You are a senior front-end engineer and motion designer. Build the FRONTEND-ONLY UI
shell for "Unsaid", an AI app (powered by Meta AI; HackTX 2026, Meta track) that
helps people say the words they never said to the people they love. Follow
Unsaid_Frontend_Build_Spec.md exactly; it is the source of truth for every screen,
string, button, and feature ID. Build everything in the frontend/ folder of this
repo. Do not touch backend/.

HARD RULES
- Frontend only. No feature works. No API calls, no env keys, no auth, no
camera/mic/photo access, no tel: or sms: links.
- Every action button is a PlaceholderButton: it shows a small "NOT YET CONNECTED"
pill badge and a hover tooltip, carries data-backend="<feature-id>" and data-
feature-id="<feature-id>" using the exact IDs in Sections 9.1 and 9.4 of the spec,
```

```
and its onClick ONLY shows a toast "Not connected yet" with the feature ID
underneath. Toggles, segmented controls, and sliders follow the same rule (they may
animate locally).
- Only navigation works: the tab bar, back, a floating ScreenSwitcher listing all
15 screens, "next" dev links, story tap-left/right, and inbox swipes (Section 9.2).
- All data is hard-coded mock data in frontend/lib/mock/: people Mom, Dad, Priya,
Jordan; group chats Fam, Roommates, Marfa Trip; plus the memories, unsends, plan,
and posthumous date in Section 2.
- Badges can be hidden with ?badges=off or NEXT_PUBLIC_SHOW_BADGES=false (for
recording); data-backend and the toasts stay.
- Meta app screens and icons are LOOK-ALIKES recreated in SVG/CSS, labeled "concept
· look-alike"; real app names may appear as plain text. Never download or embed
official logo files, icons, wordmarks, screenshots, or fonts.
- App-to-app navigation runs through the interactive iOS navigation shell (Section
4.1). The scripted demo animation is out of scope; it comes in a later prompt.
- Read backend/ (never edit it). Add backend features the frontend lacks (new IDs
in Section 9); leave unbuilt ones as placeholders; end with a report of every
button that has no backend.
- Screen 12 (Plans) is a restaurant + date + time picker with Accept/Reject,
exactly as in the spec. Do not add pricing tiers or prices.
- Screen 14 has no time/date scheduling controls. Everyday delivery is only the
phone-activity trigger (2nd or 3rd unlock, weighted later in the day).

STACK
- Next.js (App Router) + React + TypeScript + Tailwind. Framer Motion (use the
Motion AI Kit: npx motion-ai) for motion; GSAP only if a timeline needs it. react-
force-graph-2d for the brain graph. sonner for toasts. Inter + Caveat via
next/font/google.
- Device: the fictional WHITE iPhone Duo (IPhoneDuo, Section 4; geometry in
Claude_Code_Frontend_Prompt.md Phase 1). PhoneFrame = one folded Duo, DuoFrame =
one unfolded Duo, TwoPhones = two folded Duos for two people's phones.
- Every screen takes ?state= for exact static frames. No Remotion in this build
(the later animation prompt adds it).

DESIGN
- Tokens from Section 3: amber #E8A15A accent, deep plum #4A1F35 text, warm cream
#FBF5EC background, a dusk rose -> peach -> cream gradient behind the phones,
rounded cards, generous whitespace.
- Caveat for anything a person wrote or said (unsends, letters, rant quotes); Inter
for UI.
- Gentle motion only: slow fades, soft scale-ins, ease cubic-bezier(0.22,1,0.36,1);
nothing snaps. Show the chime and the haptic as an amber RippleRing. Respect
prefers-reduced-motion.
- Microcopy short, human, lowercase ("Mom left you something.", "no emergency. just
miss you.").
```

```
STEPS
1. Scaffold frontend/ with the folder structure in Section 5; put the tokens in
tailwind.config.ts and lib/tokens.ts.
2. Build the shared components in Section 6 first (PlaceholderButton,
NotConnectedBadge, PhoneFrame, DuoFrame, motion primitives, UnsaidMark).
3. Create lib/contract.ts from table 9.1: a typed union of every feature ID with
its screen and backend feature.
4. Build all 15 screens in Section 8 as pure, prop-driven components in
components/screens/, each with its own route. Match the layout, copy, buttons,
feature IDs, and Duo left/right split exactly.
5. Verify: write a small script that collects every data-backend value from the
rendered pages and checks it against lib/contract.ts (all 110 buttons, 94 unique
IDs), confirm every click toasts, and confirm the app makes no network requests.
6. Tell me the exact commands to install, run the dev server, and render the
Remotion video.
```

---

11. Changelog

Version	Date (CT)	Change
v2	Oct 24, 2026	The device is now the fictional **white iPhone Duo**: `PhoneFrame`/`DuoFrame` wrap `IPhoneDuo`, and a new `TwoPhones` layout replaces "two frames side by side". New Section 4.1 covers the Messages "k" scene, the home screen with Meta apps prominent, the interactive **iOS navigation shell** (open from icon, swipe-up close, app switcher, swipe between apps), and the fake Meta apps. The honesty rule now allows SVG/CSS look-alike icons and real app names as text, but never official files, plus a trademark risk note. Added the `data-feature-id` alias. New **Section 9.4** (rows 95–110: 7 new IDs; totals 110 buttons / 94 unique / 16 shared). Backend-sync rule and final unconnected-button report. The scripted animation is out of scope (later prompt; timings in `Demo_Script.md`). The Section 10 prompt was updated and points to the new `Claude_Code_Frontend_Prompt.md`; heavy Meta styling is required there (M1–M10). Companion to product spec v4.
v1	Oct 24, 2026	Created: the frontend-only rule (NOT YET CONNECTED badge, `data-backend`, toast-only buttons), mock data, design tokens, tech stack, folder structure, component list, navigation map, 15 screen specs, the 94-button frontend-backend contract for Mudit, and the ready-to-paste Claude prompt. Companion to product spec v3.

Unsaid · HackTX 2026 · For the words we never got to say.