

Project No. : 24167

Borehole Number : OW-03

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR02 (Bang Khun Non Station)

Co-ordinate (N) : 1,522,122

Ground Elevation (m) : +102.075 m.MSL

Co-ordinate (E) : 659,037

G.W.L. (m) : 3.0 (below ground level)

Date Started : 09 Sep 2024

Total Depth (m) : 60.45

Date Finished : 13 Sep 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □					
								20	40	60	80		
0				Ground Surface									
1				Fill Material / Top Soil	0.00								
2	■	ST	1										
3	■	ST	2	Medium stiff CLAY, trace of sand, grey, high plasticity (CH)	2.50		●			40.2	Δ		
4					4.00					17.6			
5	■	ST	3	Very soft to soft CLAY, except medium stiff clay for ST-5, trace to few sand, grey, high plasticity (CH)			●			10.6	Δ		
6	■	ST	4				●			28			
7	■	ST	5				●			11.3	Δ		
8	■	ST	6				●			18.7			
9	■	ST	7				●			14.6	Δ		
10	■	ST	8				●			48.2			
11	■	ST	9	Medium stiff CLAY, trace of sand, grey, high plasticity (CH)	14.50		●			27	□		
12	■	SS	10	Very stiff CLAY, trace of sand, brown, high plasticity (CH)	15.50		●			30	□		
13	■	SS	11				●			32	□		
14	■	SS	12	Hard CLAY, trace of sand, brown, high plasticity (CH)	17.50		●			17	□		
15	■	SS	13	Very stiff CLAY, trace of sand, brown, high plasticity (CH)	19.00		●			20	□		
16	■	SS	14				●			5	□		
17	■	SS	15	Medium stiff CLAY, trace of sand, grey, low plasticity (CL)	22.00		●			7	□		
18	■	SS	16				●						
19	■	SS	17	Very dense silty SAND / SAND with silt, few gravel at SS-12 and SS-13, brown and grey, fine to medium grained (SM, SW-SM, SP-SM)	25.00		●			50/125	□		
20	■	SS	18				●			56	□		
21	■	SS	19				●			50/125	□		
22	■	SS	20				●			56/100	□		
23	■	SS	21				●			63	□		
24	■	SS	22				●			54	□		
25	■	SS	23				●			60	□		
26	■	SS	24				●			67	□		
27	■	SS	25				●			30	□		
28	■	SS	26	Very stiff sandy CLAY, grey, low plasticity (CL)	37.00		●			33	□		
29	■	SS	27				●						
30	■	SS	28	Hard sandy CLAY, grey, low plasticity (CL)	38.50		●						
31	■	SS	29				●						
32	■	SS	30				●						
33	■	SS	31				●						
34	■	SS	32				●						
35	■	SS	33				●						
36	■	SS	34				●						
37	■	SS	35				●						
38	■	SS	36				●						
39	■	SS	37				●						

Project : MRT Orange Line (West Section)

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%)	Unit Weight (kN/m ³)	Suc (kN/m ²)			
	Symbol	Type	Number	Description	Symbol			SPT-N (Blows/300mm)			
								20	40	60	80
								20	40	60	80
40				Hard sandy CLAY, grey, low plasticity (CL)				35			
41	SS	18									
42	SS	19		Very dense silty SAND / SAND with silt, brown and grey, fine to medium grained (SM, SW-SM, SP-SM)	41.50					74	
43	SS	20								65/225	
44	SS	20									
45	SS	21								72/225	
46	SS	21									
47	SS	22								53/75	
48	SS	22									
49	SS	23								50/75	
50	SS	23									
51	SS	24								50/75	
52	SS	24									
53	SS	25								50/125	
54	SS	25									
55	SS	26		Hard sandy CLAY, greyish brown, low plasticity (CL)	53.50					50/50	
56	SS	26									
57	SS	27		Very dense silty SAND, grey and greyish brown, fine to medium grained (SM)	55.00					50/150	
58	SS	27									
59	SS	28								50/100	
60	SS	28									
61	SS	29								50/50	
62	SS	29									
63	SS	30								50/50	
64	SS	30									
65	SS	31								50/100	
66	SS	31									
67				End of Borehole	60.45						
68											
69											
70											
71											
72											
73											
74											
75											
76											
77											
78											
79											
80											
81											
82											
83											

Thin wall tube

Split spoon

Rock core

Wash

Auger

Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)