

Project No. : 24167

Borehole Number : OW-06

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR02 (Bang Khun Non Station)

Co-ordinate (N) : 1,521,872

Ground Elevation (m) : +102.520 m.MSL

Co-ordinate (E) : 659,373

G.W.L. (m) : 1.0 (below ground level)

Date Started : 30 Oct 2024

Total Depth (m) : 60.45

Date Finished : 05 Nov 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □					
								20	40	60	80		
0				Ground Surface									
0				Fill Material / Top Soil	0.00								
3	■	ST	1	Medium stiff CLAY, trace of sand, grey, high plasticity (CH)	2.50		●					36.7 Δ	
5	■	ST	2	Soft CLAY with sand, grey, high plasticity (CH)	4.00		●					17.9 Δ	
6	■	ST	3	Soft sandy CLAY, grey, low plasticity (CL)	5.50		●					13.4 Δ	
9	■	ST	4										
10	■	SS	5				●					4 □	
11	■	SS	2	Medium stiff silty CLAY, few sand, grey, low plasticity (CL)	10.00		●					5 □	
12	■	ST	6	Soft CLAY, trace of sand, grey, high plasticity (CH)	11.50								
15	■	ST	7				●					20.1 Δ	
16	■	SS	8	Very stiff silty CLAY, trace to few sand, grey and brown, high to low plasticity (CH, CL)	14.50		●					24 □	147.2 Δ
17	■	SS	4				●					21 □	
18	■	SS	5				●					27 □	
19	■	SS	6				●					29 □	
21	■	SS	7				●					20 □	
22	■	SS	8				●					22 □	
23	■	SS	9				●					25 □	
24	■	SS	10				●					23 □	
25	■	SS	11				●					25 □	
26	■	SS	12				●					24 □	
27	■	SS	13	Very stiff silty CLAY with sand / sandy CLAY, brown, low plasticity (CL)	29.50		●					26 □	
28	■	SS	14				●					27 □	
33	■	SS	15	Very dense silty SAND / SAND with silt, brown, fine to medium grained (SM, SP-SM)	32.50		●						50/100 □
34	■	SS	16				●						50/50 □
35	■	SS	17				●						50/100 □
36	■	SS	18				●						50/125 □
37	■	SS	19	Very stiff silty CLAY, trace of sand, grey, low plasticity (CL)	38.50		●					21 □	

Project : MRT Orange Line (West Section)

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ 20 40 60 80 Δ			
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □ 20 40 60 80			
40											
41	SS	20	Very stiff silty CLAY, trace of sand, grey, low plasticity (CL)								
42	SS	21									
43	SS	22	Hard silty CLAY, trace to few sand, grey, low plasticity (CL)								
44	SS	23									
45	SS	23									
46	SS	24									
47	SS	24									
48	SS	25	Hard silty CLAY with sand, grey, low plasticity (CL)								
49	SS	26									
50	SS	26									
51	SS	27	Hard sandy CLAY, brown, low plasticity (CL)								
52	SS	28									
53	SS	28									
54	SS	29	Very dense silty SAND, brown, fine to medium grained (SM)								
55	SS	30									
56	SS	30									
57	SS	31									
58	SS	31									
59	SS	32									
60	SS	33									
61			End of Borehole								
62											
63											
64											
65											
66											
67											
68											
69											
70											
71											
72											
73											
74											
75											
76											
77											
78											
79											
80											
81											
82											
83											

Thin wall tube

Split spoon

Rock core


Wash

Auger

Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)



Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test
SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)