

Project No. : 24167

Borehole Number : OW-11

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR03 (Siriraj Station)

Co-ordinate (N) : 1,521,781

Ground Elevation (m) : +102.160 m.MSL

Co-ordinate (E) : 660,275

G.W.L. (m) : 2.0 (below ground level)

Date Started : 01 Oct 2024


Total Depth (m) : 60.45

Date Finished : 05 Oct 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%)	Unit Weight (kN/m ³)	Suc (kN/m ²)					
	Symbol	Type	Number	Description	Symbol			20	40	60	80		
0				Ground Surface									
1				Fill Material / Top Soil									
2	■	ST	1										
3	■	ST	2	Medium stiff CLAY, trace of sand, grey, high plasticity (CH)						39.8	Δ		
4										13.5	Δ		
5	■	ST	3	Very soft to soft CLAY, trace of sand, grey, high plasticity (CH)									
6	■	ST	4										
7	■	ST	5							7.5	Δ		
8	■	ST	6							10.3	Δ		
9	■	ST	7							6.8	Δ		
10	■	ST	8							17.9	Δ		
11	■	ST	9	Medium stiff CLAY, trace of sand, grey, high plasticity (CH)						25.6	Δ		
12	■	ST	10										
13	■	ST	11	Stiff to very stiff silty CLAY, trace of sand, grey and greyish brown, low plasticity (CL)						55.5	Δ		
14	■	ST	12							10	□		
15	■	ST	13							13	□		
16	■	ST	14							18	□		
17	■	ST	15							22	□		
18	■	ST	16							34	□		
19	■	ST	17	Hard silty CLAY, trace of sand, greyish brown, low plasticity (CL)						28	□		
20	■	ST	18							26	□		
21	■	ST	19	Very stiff silty CLAY, trace of sand, greyish brown, low plasticity (CL)						28	□		
22	■	ST	20							20	□		
23	■	ST	21							18	□		
24	■	ST	22							34	□		
25	■	ST	23	Hard silty CLAY, greyish brown, low plasticity (CL)						38	□		
26	■	ST	24							53	□		
27	■	ST	25	Medium dense to very dense silty SAND / SAND with silt, grey, fine to medium grained (SM, SP-SM)						46	□		
28	■	ST	26							30	□		
29	■	ST	27							22	□		
30	■	ST	28	Very stiff silty CLAY, trace of sand, grey, low plasticity (CL)						30	□		
31	■	ST	29										
32	■	ST	30										
33	■	ST	31										
34	■	ST	32										
35	■	ST	33										
36	■	ST	34										
37	■	ST	35										
38	■	ST	36										
39	■	ST	37										

Project : MRT Orange Line (West Section)

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%)	Unit Weight (kN/m ³)	Suc (kN/m ²)			
	Symbol	Type	Number	Description	Symbol			Δ	Δ		
								20 40 60 80	20 40 60 80		
SPT-N (Blows/300mm)											
40											
41	SS		18	Hard silty CLAY, trace to few sand, greyish brown, low plasticity (CL)				32			
42	SS		19						70		
43	SS		20	Dense to very dense silty SAND, greyish brown, fine to medium grained (SM)				38			
44	SS		21						82/225		
45	SS		22						50/50		
46	SS		23	Hard silty CLAY, trace to few sand, grey, low plasticity (CL)					59		
47	SS		24						65		
48	SS		25	Dense to very dense silty SAND / SAND with silt, grey, fine to medium grained (SM, SP-SM)				62			
49	SS		26					52			
50	SS		27					61			
51	SS		28					50			
52	SS		29					37			
53	SS		30					43			
54	SS		31					52			
55				End of Borehole							
56											
57											
58											
59											
60											
61											
62											
63											
64											
65											
66											
67											
68											
69											
70											
71											
72											
73											
74											
75											
76											
77											
78											
79											
80											
81											
82											
83											



Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)