

Project No. : 24167

Borehole Number : OW-16

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR04 (Sanam Luang Station)

Co-ordinate (N) : 1,521,674

Ground Elevation (m) : +101.396 m.MSL

Co-ordinate (E) : 661,342

G.W.L. (m) : 1.5 (below ground level)

Date Started : 28 Sep 2024

Total Depth (m) : 80.00

Date Finished : 07 Oct 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ						
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □						
								20	40	60	80			
0				Ground Surface										
1				Fill Material / Top Soil	0.00									
2	■	ST	1	Very soft to soft CLAY, trace of sand, little sand for ST-8, grey, high plasticity (CH)	2.50		●	9.5						
3	■	ST	2				●	12.5						
4	■	ST	3				●	12.6						
5	■	ST	4				●	22.4						
6	■	ST	5				●	16.6						
7	■	ST	6				●	18.8						
8	■	ST	7				●	14.9						
9	■	ST	8				●							
10	■	ST	9	Medium stiff CLAY, few sand, grey, high plasticity (CH)	13.00		●	43.6						
11	■	ST	10				●							
12	■	ST	11	Very stiff silty CLAY, trace of sand, little sand for SS-5, light greyish brown to light brown, high to low plasticity (CH, CL)	14.50		●	18						
13	■	SS	1				●	19						
14	■	SS	2				●	26						
15	■	SS	3				●	25						
16	■	SS	4				●	26						
17	■	SS	5				●	20						
18	■	SS	6				●	19						
19	■	SS	7				●	23						
20	■	SS	8	Hard silty CLAY with sand, brown, low plasticity (CL)	26.50		●	36						
21	■	SS	9				●	39						
22	■	SS	10	Medium dense to dense silty SAND / SAND with silt, brown and light grey, fine to medium grained (SM, SW-SM, SP-SM)	28.00		●	39						
23	■	SS	11				●	49						
24	■	SS	12				●	52						
25	■	SS	13				●	21						
26	■	SS	14				●	31						
27	■	SS	15				●	47						
28	■	SS	16		Hard sandy CLAY, light brown, low plasticity (CL)	37.00		●	47					
29	■	SS	17					●						

Project : MRT Orange Line (West Section)

