

Project No. : 24167

Borehole Number : OW-17

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR04 (Sanam Luang Station)

Co-ordinate (N) : 1,521,549

Ground Elevation (m) : +101.600 m.MSL

Co-ordinate (E) : 661,405

G.W.L. (m) : 1.0 (below ground level)

Date Started : 12 Nov 2024

Total Depth (m) : 80.00

Date Finished : 19 Nov 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m ³) 5 15	Suc (kN/m ²) Δ 20 40 60 80 Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □ 20 40 60 80					
0				Ground Surface									
1				Fill Material / Top Soil	0.00								
2	■	ST	1										
3	■	ST	2	Medium stiff CLAY, grey, high plasticity (CH)	2.50							34.7 Δ	
4													
5	■	ST	3	Very soft to soft CLAY, except medium stiff clay for ST-4, trace of sand, grey, high plasticity (CH)	4.00							19.4 Δ	
6	■	ST	4									32.2 Δ	
7													
8	■	ST	5									11.9 Δ	
9	■	ST	6	Medium stiff CLAY with sand, grey, high plasticity (CH)	8.50							25.1 Δ	
10	■	ST	7	Soft CLAY, trace of sand, grey, high plasticity (CH)	10.00							16.7 Δ	
11	■	ST	8	Medium stiff CLAY, few sand, grey, high plasticity (CH)	11.50							42.4 Δ	
12	■	ST	9		13.00								
13	■	ST	10	Stiff to very stiff CLAY, trace to few sand, greyish brown, high plasticity (CH)									94.3 Δ
14	■	SS	1									14 □	
15	■	SS	2									18 □	
16	■	SS	3									27 □	
17	■	SS	4									30 □	
18	■	SS	5									27 □	
19	■	SS	6									29 □	
20	■	SS	7	Hard CLAY, trace of sand, greyish brown, high plasticity (CH)	22.00							31 □	
21	■	SS	8	Very stiff silty CLAY / CLAY with sand, few to little sand, greyish brown, low plasticity (CL)	23.50							21 □	
22	■	SS	9									22 □	
23	■	SS	10	Dense to very dense silty SAND / SAND with silt, greyish brown and grey, fine to medium grained (SM, SP-SM)	26.50							41 □	
24	■	SS	11									38 □	
25	■	SS	12									42 □	
26	■	SS	13									49 □	
27	■	SS	14									52 □	
28	■	SS	15										66 □
29	■	SS	16										80/250 □
30	■	SS	17	Hard silty CLAY / CLAY with sand, greyish brown and grey, low plasticity (CL)	37.00							46 □	
31	■	SS	18									60 □	

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ 20 40 60 80 Δ															
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □ 20 40 60 80															
40																							
41	⊠	SS	19	Hard silty CLAY / CLAY with sand, greyish brown and grey, low plasticity (CL)			•					67	□										
42	⊠	SS	20												•						74/225	□	
43	⊠	SS	21												•						69	□	
44	⊠	SS	22																				
45	⊠	SS	22	Very dense silty SAND / SAND with silt, brown and grey, fine to medium grained (SM, SP-SM)			•					50/150	□										
46	⊠	SS	23											□	•						50/150	□	
47	⊠	SS	23											□	•						50/125	□	
48	⊠	SS	24											□	•						50/125	□	
49	⊠	SS	25											□	•						50/125	□	
50	⊠	SS	26											□	•						61/225	□	
51	⊠	SS	26											□	•						50/150	□	
52	⊠	SS	27											□	•						50/125	□	
53	⊠	SS	27											□	•						50/125	□	
54	⊠	SS	28											□	•						50/75	□	
55	⊠	SS	29											□	•							50/125	□
56	⊠	SS	29																				
57	⊠	SS	30																				
58	⊠	SS	30																				
59	⊠	SS	31																				
60	⊠	SS	32																				
61	⊠	SS	32																				
62	⊠	SS	33																				
63	⊠	SS	34																				
64	⊠	SS	35																				
65	⊠	SS	35																				
66	⊠	SS	36	□	•						50/125	□											
67	⊠	SS	37	□	•						50/150	□											
68	⊠	SS	37	□	•						50/125	□											
69	⊠	SS	38	□	•						50/125	□											
70	⊠	SS	39	□	•							50/125	□										
71	⊠	SS	39																				
72	⊠	SS	40																				
73	⊠	SS	40																				
74	⊠	SS	41																				
75	⊠	SS	42																				
76	⊠	SS	42																				
77	⊠	SS	43																				
78	⊠	SS	44																				
79	⊠	SS	44																				
80	⊠	SS	45	□	•						50/125	□											
81				End of Borehole	80.00																		
82																							
83																							

Thin wall tube

Split spoon

Rock core


Wash

Auger

Atterberg Limits : PL — Wn — LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)



Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test
SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)