

Project No. : 24167

Borehole Number : OW-18

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR04 (Sanam Luang Station)

Co-ordinate (N) : 1,521,507

Ground Elevation (m) : +101.469 m.MSL

Co-ordinate (E) : 661,483

G.W.L. (m) : 1.0 (below ground level)

Date Started : 08 Oct 2024

Total Depth (m) : 80.00

Date Finished : 18 Oct 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □					
								20	40	60	80		
0				Ground Surface									
0				Fill Material / Top Soil	0.00								
1	■	ST	1										
2	■	ST	2	Very soft to soft CLAY, trace of sand, little sand for ST-7, grey, high plasticity (CH)	2.50					●		22.4	Δ
3	■	ST	3										
4	■	ST	4							●		8.2	Δ
5	■	ST	5							●		19.9	Δ
6	■	ST	6							●		6.8	Δ
7	■	ST	7							●		20	Δ
8	■	ST	8	Medium stiff CLAY, trace of sand, grey, high plasticity (CH)	11.50					●		38.6	Δ
9	■	ST	9										
10	■	ST	10	Stiff to very stiff silty CLAY, trace of sand, little sand for SS-1, light grey and light brown, high to low plasticity (CH, CL)	13.00					●		15	Δ
11	■	SS	1							●		19	□
12	■	SS	2							●		22	□
13	■	SS	3							●		24	□
14	■	SS	4							●		9	□
15	■	SS	5	Stiff silty CLAY with sand, light brown, low plasticity (CL)	19.00					●		31	□
16	■	SS	6							●		26	□
17	■	SS	7	Hard silty CLAY, trace of sand, light brown, low plasticity (CL)	20.50					●		27	□
18	■	SS	8							●		23	□
19	■	SS	9	Very stiff silty CLAY, trace to few sand, brown, high to low plasticity (CH, CL)	22.00					●		27	□
20	■	SS	10							●		49	□
21	■	SS	11	Medium dense to dense silty SAND, brown, fine to medium grained (SM)	26.50					●		48	□
22	■	SS	12							●		26	□
23	■	SS	13							●		38	□
24	■	SS	14	Hard sandy CLAY, light brown, low plasticity (CL)	32.50					●		40	□
25	■	SS	15							●		39	□
26	■	SS	16	Dense silty SAND / SAND with silt, brown and light grey, fine to medium grained (SM, SP-SM)	34.00					●		29	□
27	■	SS	17							●		30	□
28	■	SS	18	Very stiff silty CLAY with sand, light brown, low plasticity (CL)	37.00					●			
29	■	SS	18							●			

Project : MRT Orange Line (West Section)

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m ³) 5 15	Suc (kN/m ²) Δ 20 40 60 80 Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □ 20 40 60 80					
40					40.00				34				
41	SS		19	Hard silty CLAY / CLAY with sand, few to little sand, light brown, low plasticity (CL)									
42	SS		20										
43	SS		21										
44	SS		22										
45	SS		22										
46	SS		23										
47	SS		23										
48	SS		24	Very dense silty SAND, light brown to brown, fine grained (SM)									
49	SS		25										
50	SS		26										
51	SS		26										
52	SS		27	Very dense silty SAND / SAND with silt, light brown to brown and light grey, fine to medium grained (SM, SP-SM)									
53	SS		27										
54	SS		28										
55	SS		28										
56	SS		29										
57	SS		30										
58	SS		31										
59	SS		31										
60	SS		32										
61	SS		32										
62	SS		33										
63	SS		34										
64	SS		35										
65	SS		35										
66	SS		36										
67	SS		37										
68	SS		37										
69	SS		38										
70	SS		38										
71	SS		39										
72	SS		40										
73	SS		41										
74	SS		41										
75	SS		42										
76	SS		43										
77	SS		43										
78	SS		44										
79	SS		45										
80	SS		45										
81				End of Borehole	80.00								
82													
83													

Thin wall tube

Split spoon

Rock core


Wash

Auger

Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)



Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test
SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)