

Project No. : 24167

Borehole Number : OW-20/1

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : Tunnel (Sta. 13+350 WB)

Co-ordinate (N) : 1,521,404

Ground Elevation (m) : +101.180 m.MSL

Co-ordinate (E) : 661,852

G.W.L. (m) : 1.5 (below ground level)

Date Started : 05 Feb 2025

Total Depth (m) : 60.45

Date Finished : 07 Feb 2025

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □					
								20	40	60	80		
0				Ground Surface									
1				Fill Material / Top Soil	0.00								
2	■	ST	1	Very soft to soft CLAY, trace of sand, grey, high plasticity (CH)	2.50		●	9.8					
3	■	ST	2				●	15.5					
4	■	ST	3				●	18.3					
5	■	ST	4				●	9.8					
6	■	ST	5										
7	■	ST	6										
8	■	ST	7										
9	■	ST	8	Medium stiff CLAY, trace of sand, grey, high plasticity (CH)	11.50		●	23.9					
10	■	ST	9				●	30.5					
11	■	ST	10	Very stiff CLAY, trace of sand, grey, high plasticity (CH)	14.50		●	40.8					
12	■	ST	11				●	18					
13	■	ST	12				●	28					
14	■	SS	1	Hard CLAY, trace to few sand, grey and greyish brown, high plasticity (CH)	17.50		●	33					
15	■	SS	2				●	34					
16	■	SS	3				●	37					
17	■	SS	4				●	29					
18	■	SS	5	Very stiff silty CLAY, trace of sand, greyish brown, low plasticity (CL)	22.00		●	25					
19	■	SS	6				●	47					
20	■	SS	7	Dense to very dense silty SAND / SAND with silt, greyish brown and grey, fine to medium grained (SM, SP-SM)	25.00		●	61					
21	■	SS	8				●	49					
22	■	SS	9				●	53					
23	■	SS	10				●	50					
24	■	SS	11				●	52					
25	■	SS	12				●	53					
26	■	SS	13				●	56					
27	■	SS	14				●	54					
28	■	SS	15	Hard silty CLAY, trace of sand, greyish brown to brown, high to low plasticity (CH, CL)	37.00		●	58					
29	■	SS	16				●						
30	■	SS	17				●						

Project : MRT Orange Line (West Section)

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m ³) 5 15	Suc (kN/m ²) Δ 20 40 60 80 Δ						
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □ 20 40 60 80						
40														
41	SS		18	Hard silty CLAY, trace of sand, greyish brown to brown, high to low plasticity (CH, CL)									59	
42	SS		19											63
43				Very dense silty SAND / SAND with silt, greyish brown and grey, fine to medium grained (SM, SW-SM)										
44	SS		20		43.00									73/225
45	SS		21											50/150
46														
47	SS		22											50/125
48	SS		23											50/150
49														
50	SS		24											50/150
51	SS		25											65/200
52														
53	SS		26											50/150
54	SS		27											50/150
55														
56	SS		28											76/250
57														
58	SS		29										73/200	
59	SS		30										50/75	
60	SS		31	End of Borehole	60.00								70/225	
61														
62														
63														
64														
65														
66														
67														
68														
69														
70														
71														
72														
73														
74														
75														
76														
77														
78														
79														
80														
81														
82														
83														

Thin wall tube

Split spoon

Rock core


Wash

Auger

Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)



Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)