

Project No. : 24167

Borehole Number : OW-21

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : Tunnel (Sta. 13+600 EB)

Co-ordinate (N) : 1,521,404

Ground Elevation (m) : +101.395 m.MSL

Co-ordinate (E) : 662,124

G.W.L. (m) : 1.0 (below ground level)

Date Started : 27 Oct 2024

Total Depth (m) : 50.45

Date Finished : 30 Oct 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ							
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □							
								20	40	60	80				
0				Ground Surface											
0				Fill Material / Top Soil	0.00										
1	■	ST	1	Soft CLAY, trace of sand, grey, high plasticity (CH)	1.00			●			20.9	Δ			
2	■	ST	2												
3	■	ST	3												
4	■	ST	4												
5	■	ST	5	Medium stiff CLAY, trace of sand, grey, high plasticity (CH)	7.00			●			23	Δ			
6	■	ST	6									15.4	Δ		
7	■	ST	7	Soft CLAY, trace of sand, grey, high plasticity (CH)	8.50			●			30.6	Δ			
8	■	ST	8												
9	■	ST	9	Medium stiff CLAY, grey, high plasticity (CH)	10.00			●			23.1	Δ			
10	■	ST	10												
11	■	ST	11	Stiff to very stiff silty CLAY, trace of sand, except very stiff silty clay with sand for SS-5, light grey to grey and light brown, high to low plasticity (CH, CL)	11.50			●			31.7	Δ			
12	■	ST	12									42.1	Δ		
13	■	ST	13					●							
14	■	ST	14									66.1	Δ		
15	■	ST	15												
16	■	ST	16												
17	■	ST	17												
18	■	ST	18												
19	■	ST	19												
20	■	ST	20												
21	■	ST	21	Hard silty CLAY with sand, light brown, low plasticity (CL)	26.50			●			30	□			
22	■	ST	22									20	□		
23	■	ST	23												
24	■	ST	24									18	□		
25	■	ST	25												
26	■	ST	26									24	□		
27	■	ST	27												
28	■	ST	28									20	□		
29	■	ST	29	Dense to very dense silty SAND, light brown and light grey, fine to medium grained (SM)	29.50			●			20	□			
30	■	ST	30												
31	■	ST	31												
32	■	ST	32												
33	■	ST	33												
34	■	ST	34												
35	■	ST	35												
36	■	ST	36												
37	■	ST	37	Hard silty CLAY with sand, light grey and light brown, low plasticity (CL)	37.00			●			28	□			
38	■	ST	38									29	□		
39	■	ST	39												
											42	□			
											43	□			
											</				

Project : MRT Orange Line (West Section)

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ			
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □			
								20	40	60	80
40	■	SS	18	Hard CLAY, light brown to brown and light grey, high plasticity (CH)	40.00	■	•				54
41	■	SS	19		■	•				57	
42	■	SS	20		■	•			37		
43	■	SS	21		■	•			39		
44	■	SS	22		■	•				56	
45	■	SS	23	Very desne silty SAND, light greyish light brown, fine grained (SM)	47.50	■	•				50/100
46	■	SS	24		■	•				50/125	
47				End of Borehole	50.00						
48											
49											
50											
51											
52											
53											
54											
55											
56											
57											
58											
59											
60											
61											
62											
63											
64											
65											
66											
67											
68											
69											
70											
71											
72											
73											
74											
75											
76											
77											
78											
79											
80											
81											
82											
83											

Thin wall tube

Split spoon

Rock core

Wash

Auger

Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)