

Project No. : 24167

Borehole Number : OW-22

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR05 (Democracy Monument)

Co-ordinate (N) : 1,521,366

Ground Elevation (m) : +101.373 m.MSL

Co-ordinate (E) : 662,310

G.W.L. (m) : 1.5 (below ground level)

Date Started : 22 Dec 2024

Total Depth (m) : 80.00

Date Finished : 26 Dec 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ				
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □				
								20	40	60	80	
								20	40	60	80	
0				Ground Surface								
1				Fill Material / Top Soil	0.00							
2	■	ST	1	Very soft to soft CLAY, except medium stiff clay for ST-2, trace of sand, grey, high plasticity (CH)	2.50					●	24.2 Δ	
3	■	ST	2						●	25.2 Δ		
4	■	ST	3						●	16.2 Δ		
5	■	ST	4						●	14.5 Δ		
6	■	ST	5						●	10.7 Δ		
7	■	ST	6						●	14.5 Δ		
8	■	ST	7						●			
9	■	ST	8						●			
10				Medium stiff CLAY, grey, high plasticity (CH)	11.50					●	39.1 Δ	
11	■	ST	9	Stiff to very stiff CLAY, few sand, grey and greyish brown, high plasticity (CH)	13.00					●		78.6 Δ
12	■	SS	1						●	18 □		
13	■	SS	2						●	23 □		
14	■	SS	3						●	24 □		
15	■	SS	4						●	24 □		
16	■	SS	5	Hard CLAY, trace of sand, grey, high plasticity (CH)	19.00					●		55 □
17	■	SS	6						●	24 □		
18	■	SS	7	Very stiff sandy CLAY, greyish brown, low plasticity (CL)	20.50					●		
19	■	SS	8						●	24 □		
20	■	SS	9	Very stiff silty CLAY, trace of sand, brown, low plasticity (CL)	22.00					●	21 □	
21	■	SS	10						●	21 □		
22	■	SS	11						●	24 □		
23	■	SS	12	Dense to very dense silty SAND / SAND with silt, brown and grey, fine to medium grained (SM, SP-SM)	28.00					●		74/300 □
24	■	SS	13						●			68/225 □
25	■	SS	14						●			50/150 □
26	■	SS	15						●			70 □
27	■	SS	16						●	56 □		
28	■	SS	17						●	65 □		
29	■	SS	18						●	55 □		
30	■	SS	19	Hard CLAY, trace of sand, greyish brown, high plasticity (CH)	38.50					●		50 □
31	■	SS	20						●			

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m ³) 5 15	Suc (kN/m ²) Δ 20 40 60 80 Δ			
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □ 20 40 60 80			
40	⊠	SS	19	Hard sandy CLAY, greyish brown, low plasticity (CL) Very dense silty SAND / SAND with silty, greyish brown and grey, fine to medium grained (SM, SP-SM)	40.00	⊠					50/100
41	⊠	SS	20		41.50	⊠					61
42	⊠	SS	21			⊠					64/225
43	⊠	SS	22			⊠					74/225
44	⊠	SS	23			⊠					70/250
45	⊠	SS	24			⊠					50/125
46	⊠	SS	25			⊠					50/125
47	⊠	SS	26			⊠					62
48	⊠	SS	27			⊠					64
49	⊠	SS	28			⊠					50/100
50	⊠	SS	29			⊠					50/100
51	⊠	SS	30			⊠					50/150
52	⊠	SS	31			⊠					50/150
53	⊠	SS	32			⊠					50/150
54	⊠	SS	33			⊠					50/125
55	⊠	SS	34			⊠					50/125
56	⊠	SS	35		⊠					50/125	
57	⊠	SS	36	Hard silty CLAY, little sand, grey, low plasticity (CL)	65.50	⊠					70/275
58	⊠	SS	37	Very dense silty SAND, grey, fine to medium grained (SM)	67.00	⊠					50/75
59	⊠	SS	38			⊠					50/125
60	⊠	SS	39			⊠					50/100
61	⊠	SS	40			⊠					50/125
62	⊠	SS	41	Very dense silty SAND, grey, fine grained (SM)	73.00	⊠					50/125
63	⊠	SS	42			⊠					50/150
64	⊠	SS	43			⊠					50/100
65	⊠	SS	44	Very dense silty SAND, grey, fine to medium grained (SM)	77.50						50/125
66	⊠	SS	45			⊠					50/100
67				End of Borehole	80.00						
68											
69											
70											
71											
72											
73											
74											
75											
76											
77											
78											
79											
80											
81											
82											
83											

Thin wall tube

Split spoon

Rock core


Wash

Auger

Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)



Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test
SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)