

Project No. : 24167B

Borehole Number : OW-23/2

Project : MRT Orange Line (West Section)

Borehole Location : OR05 (Democracy Monument)

Co-ordinate (N) : 1,521,332

Ground Elevation (m) : +101.257 m.MSL

Co-ordinate (E) : 662,490

G.W.L. (m) : 1.5 (below ground level)

Date Started : 26 Jan 2025

Total Depth (m) : 70.95

Date Finished : 29 Jan 2025

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80		Unit Weight (kN/m^3) 5 15		Suc (kN/m^2) Δ 20 40 60 80 Δ			
	Symbol	Type	Number	Description	Symbol					SPT-N □ (Blows/300mm) □ 20 40 60 80			
0				Ground Surface									
30	SS		1	Wash out	0.00	⊗						66 □	
31				Hard CLAY, greyish brown, medium	30.00	▨							
32	SS		2	Dense to very dense SAND, greyish brown	31.00	▧						50 □	
33				and grey, fine to medium grained									
34	SS		3			▧						57 □	
35													
36	SS		4			▧						53 □	
37													
38	SS		5			▧						58 □	
39													
40	SS		6			▧						82/250 □	
41													
42	SS		7			▧						50/125 □	
43													
44	SS		8			▧						50/125 □	
45													
46	SS		9			▧						50/125 □	
47													
48	SS		10	Hard sandy CLAY, greyish green, medium plasticity	43.00	▨						67 □	
49													
50	SS		11			▨						50/125 □	
51													
52	SS		12	Very dense SAND, grey and greyish brown, fine to medium grained, except	46.00	▧						50/100 □	
53				medium to coarse grained for SS-15 and SS-25									
54	SS		13			▧						50/150 □	
55													
56	SS		14			▧						58 □	
57													
58	SS		15			▧						60 □	
59													
60	SS		16			▧						50 □	
61													
62	SS		17			▧						50/150 □	
63													
64	SS		18			▧						57 □	
65													
66	SS		19			▧						50/125 □	
67													
68	SS		20			▧						50/150 □	
69													
70	SS		21			▧						50/125 □	
71													
72	SS		22			▧						50/100 □	
73													
74	SS		23			▧						50/125 □	
75													
76	SS		24			▧						50/125 □	
77													
78	SS		25			▧						50/150 □	
79													
80	SS		26			▧						50/125 □	
81													
82	SS		27			▧						50/125 □	
83													
84	SS		28			▧						50/150 □	
85													
86	SS			End of Borehole	70.95								
Thin wall tube Split spoon				Rock core Wash Auger		Atterberg Limits : PL Wn LL Suc : Undrained shear strength from UC test SPT-N : Field SPT-N (donut hammer with pulley)		Source : Geo-Technology Consultants Co., Ltd.					