

Project No. : 24167

Borehole Number : OW-25

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR05 (Democracy Monument)

Co-ordinate (N) : 1,521,305

Ground Elevation (m) : +101.363 m.MSL

Co-ordinate (E) : 662,637

G.W.L. (m) : 1.5 (below ground level)

Date Started : 04 Oct 2024

Total Depth (m) : 80.00

Date Finished : 19 Oct 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □					
								20	40	60	80		
0				Ground Surface									
0				Fill Material / Top Soil	0.00								
3	■	ST	1	Very soft CLAY, trace of sand, grey, high plasticity (CH)	2.50		●	12.8	Δ				
5	■	ST	2				●	12.9	Δ				
6	■	ST	3	Medium stiff CLAY, trace of sand, grey, high plasticity (CH)	5.50		●			31	Δ		
7	■	ST	4	Very soft to soft CLAY, trace to fow sand, grey, high plasticity (CH)	7.00		●	8.3	Δ				
8	■	ST	5				●			23	Δ		
12	■	ST	7	Medium stiff CLAY, grey, high plasticity (CH)	11.50		●			32.8	Δ		
14	■	ST	8	Very stiff CLAY, trace to few sand, grey and brown, high plasticity (CH)	13.00		●					112.5	Δ
15	■	SS	2				●	17	□	19	□		
16	■	SS	3	Hard CLAY, trace of sand, brown, high plasticity (CH)	16.00		●			31	□		
18	■	SS	4				●			33	□		
20	■	SS	5				●					52	□
21	■	SS	6				●					50/100	□
22	■	SS	7	Very stiff CLAY, trace of sand, grey, low plasticity (CL)	22.00		●			27	□		
23	■	SS	8				●			24	□		
24	■	SS	9				●			24	□		
25	■	SS	10				●			23	□		
28	■	SS	11	Very dense clayey SAND, grey, fine to medium grained (SC)	28.00		●					50/150	□
29	■	SS	12	Hard sandy CLAY, grey, low plasticity (CL)	29.50		●					50/125	□
30	■	SS	13	Very dense silty SAND, grey, fine to medium grained (SM)	30.00		●					50/100	□
33	■	SS	14				●			55	□		
34	■	SS	15				●			59	□		
35	■	SS	16	Hard silty CLAY with sand, grey, low plasticity (CL)	35.50		●					66	□
36	■	SS	17				●					50/100	□
38	■	SS	18	Dense to very dense silty SAND / SAND with silt, brown and grey, fine to medium grained (SM, SW-SM, SP-SM)	38.50		●						
39	■	SS					●			50	□		

Project : MRT Orange Line (West Section)

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m^3) 5 15	Suc (kN/m^2) Δ 20 40 60 80 Δ				
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □ 20 40 60 80				
40	■	SS	19	Dense to very dense silty SAND / SAND with silt, brown and grey, fine to medium grained (SM, SW-SM, SP-SM)		□		●			50/75	□
41	■	SS	20			□		●			70	□
42	■	SS	21			□		●			60/200	□
43	■	SS	22			□		●			50/75	□
44	■	SS	23			□		●			50/100	□
45	■	SS	24			□		●			50/100	□
46	■	SS	25			□		●			50/100	□
47	■	SS	26			□		●			50/100	□
48	■	SS	27			□		●			50/75	□
49	■	SS	28			□		●			50/50	□
50	■	SS	29			□		●			50/50	□
51	■	SS	30			□		●			50/100	□
52	■	SS	31			□		●			50/50	□
53	■	SS	32			Hard silty CLAY / CLAY with sand, trace of sand, little sand for SS-37 and SS-45, grey and brown, high to low plasticity (CH, CL)		■	■	●		
60	■	SS	33	■	■			●			60	□
61	■	SS	34	■	■			●			63	□
62	■	SS	35	■	■			●			65/225	□
63	■	SS	36	□				●			50/75	□
64	■	SS	37	■	■			●			50/125	□
65	■	SS	38	□				●			50/125	□
66	■	SS	39	■	■			●			50/150	□
67	■	SS	40	□				●			50/125	□
68	■	SS	41	■	■			●			50/100	□
69	■	SS	42	□				●			54	□
70	■	SS	43	■	■			●			57	□
71	■	SS	44	□				●			55	□
72	■	SS	45	■	■	●			58	□		
73				End of Borehole	80.00							
81												
82												
83												

Thin wall tube

Split spoon

Rock core

Wash

Auger

PL


Wn

LL

Atterberg Limits :

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)



Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)