

Page 1 of 2

Date Finished : 05 Nov 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N (Blows/300mm) □					
								20	40	60	80		
0				Ground Surface									
0				Fill Material / Top Soil	0.00								
1	■	ST	1										
2	■	ST	2	Very soft to soft CLAY, trace to few sand, grey, high plasticity (CH)	2.50		●				13.9	Δ	
3	■	ST	3				●				11.7	Δ	
4	■	ST	4				●				7.7	Δ	
5	■	ST	5				●				21.6	Δ	
6	■	ST	6	Medium stiff CLAY, few sand, grey, high plasticity (CH)	8.50		●				27.6	Δ	
7	■	ST	7	Soft CLAY, trace of sand, grey, high plasticity (CH)	10.00		●				22.7	Δ	
8	■	ST	8	Medium stiff silty CLAY, trace of sand for ST-8, little sand for ST-9, light grey to grey, high to low plasticity (CH, CL)	11.50		●				27.2	Δ	
9	■	ST	9				●				43.6	Δ	
10	■	ST	10	Stiff to very stiff silty CLAY, trace to few sand, light brown and light grey, high to low plasticity (CH, CL)	14.50		●				63.7	Δ	
11	■	SS	1				●				19	□	
12	■	SS	2				●				25	□	
13	■	SS	3				●				25	□	
14	■	SS	4				●				15	□	
15	■	SS	5				●				19	□	
16	■	SS	6				●				23	□	
17	■	SS	7	Very stiff sandy CLAY, brown, low plasticity (CL)	23.50		●				27	□	
18	■	SS	8	Medium dense to very dense silty SAND, light grey and light brown to brown, fine to medium grained (SM)	25.00		●				38	□	
19	■	SS	9				●				29	□	
20	■	SS	10				●				41	□	
21	■	SS	11				●				55	□	
22	■	SS	12				●				49	□	
23	■	SS	13				●				53	□	
24	■	SS	14				●				49	□	
25	■	SS	15				●				55	□	
26	■	SS	16	Hard silty CLAY, few sand, light brown, low plasticity (CL)	37.00		●				49	□	
27	■	SS	17				●				47	□	

Project : MRT Orange Line (West Section)

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m ³) 5 15	Suc (kN/m ²) Δ 20 40 60 80 Δ				
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □ 20 40 60 80				
40					40.00							83/300
41	SS		18	Hard sandy CLAY, light brown, low plasticity (CL)	41.50	□	→	•				□
42	SS		19	Very dense silty SAND / SAND with silt, light brown to brown, fine to medium grained (SM, SP-SM)		□		•				50/150
43							□		•			57
44	SS		20				□		•			□
45	SS		21				□		•			50/125
46									•			□
47	SS		22					•			50/100	
48	SS		23			□		•			53	
49								•			44	
50	SS		24	Hard CLAY, trace of sand, light brownish light grey, high plasticity (CH)	49.00	□	→	•			□	
51	SS		25			□		•			48	
52								•			□	
53	SS		26	Dense clayey SAND, light brownish light grey, medium grained (SC)	52.00	□	→	•			41	
54								•			□	
55	SS		27	Very dense silty SAND, light grey, fine to medium grained (SM)	53.50	□		•			57	
56								•			□	
57	SS		28	Hard sandy CLAY, light brown, high to low plasticity (CH, CL)	55.00	□	→	•			68/300	
58								•			□	
59	SS		30	Very dense silty SAND, light grey, fine to medium grained (SM)	58.00			•			56	
60								•			□	
61	SS		31			□		•			50/100	
62											76	
63											□	
64												
65												
66												
67												
68												
69												
70												
71												
72												
73												
74												
75												
76												
77												
78												
79												
80												
81												
82												
83												
Thin wall tube Split spoon Rock core Wash Auger				Atterberg Limits : PL Wn LL Suc : Undrained shear strength from UC test SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)								