

Project No. : 24167

Borehole Number : OW-28

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR06 (Lan Luang Station)

Co-ordinate (N) : 1,521,293

Ground Elevation (m) : +101.110 m.MSL

Co-ordinate (E) : 663,288

G.W.L. (m) : 1.0 (below ground level)

Date Started : 21 Nov 2024

Total Depth (m) : 80.00

Date Finished : 26 Nov 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □					
								20	40	60	80		
0				Ground Surface									
1				Fill Material / Top Soil	0.00								
2	■	ST	1	Very soft to soft CLAY, trace to few sand, grey, high plasticity (CH)	2.50								
3	■	ST	2								21.2 Δ		
4	■	ST	3								20.9 Δ		
5	■	ST	4								14.8 Δ		
6	■	ST	5										
7	■	ST	6								19.9 Δ		
8	■	ST	7	Medium stiff CLAY, grey, high plasticity (CH)	10.00								
9	■	ST	8								35.1 Δ		
10	■	ST	9								33.2 Δ		
11	■	ST	10										
12	■	ST	11										
13	■	ST	12										
14	■	ST	13	Stiff to very stiff silty CLAY, trace to few sand, except clay with sand for SS-5, greyish brown and light grey, high to low plasticity (CH, CL)	13.00								
15	■	SS	1								24 □	66 Δ	
16	■	SS	2								24 □		
17	■	SS	3								26 □		
18	■	SS	4								26 □		
19	■	SS	5								18 □		
20	■	SS	6								27 □		
21	■	SS	7										
22	■	SS	8								48 □		
23	■	SS	9								50 □		
24	■	SS	10	Dense to very dense silty SAND / SAND with silt, greyish brown to brown and grey, fine to medium grained (SM, SP-SM)	22.00								
25	■	SS	11								52 □		
26	■	SS	12								61 □		
27	■	SS	13								52 □		
28	■	SS	14								51 □		
29	■	SS	15								61/275 □		
30	■	SS	16										
31	■	SS	17								41 □		
32	■	SS	18								65/275 □		
33	■	SS	19								64/275 □		
34	■	SS	20	Hard silty CLAY, few sand, light brown, low plasticity (CL)	38.50								
35	■	SS	21								53 □		
36	■	SS	22								50 □		
37	■	SS	23										
38	■	SS	24										

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m ³) 5 15	Suc (kN/m ²) Δ 20 40 60 80 Δ			
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □ 20 40 60 80			
40	■	SS	19	Hard sandy CLAY, light brown, low plasticity (CL) Dense to very dense silty SAND / SAND with silt, light brown to greyish brown and grey, fine to medium grained (SM, SP-SM)	40.00	■	●				79/275
41	■	SS	20		41.50	□	●				82/250
42	■	SS	21			□	●				65/275
43	■	SS	22			□	●				67/300
44	■	SS	23				●				50/150
45	■	SS	24			□	●				61
46	■	SS	25				●		43		
47	■	SS	26			□	●				75/275
48	■	SS	27			□	●			47	
49	■	SS	28				●			52	
50	■	SS	29			□	●				76
51	■	SS	30				●				50/150
52	■	SS	31			□	●				50/125
53	■	SS	32				●				50/150
54	■	SS	33			□	●				50/125
55	■	SS	34				●				50/125
56	■	SS	35			□	●				50/125
57	■	SS	36				●				70/250
58	■	SS	37			□	●				50/125
59	■	SS	38			●				50/125	
60	■	SS	39	Hard silty CLAY, trace of sand, light grey and light brown to brown, high to low plasticity (CH, CL)	70.00	■	●				74
61	■	SS	40		□	●					67/250
62	■	SS	41		■	●					50/125
63	■	SS	42		□	●					50/150
64	■	SS	43		□	●					50/125
65	■	SS	44		■	●					50/125
66	■	SS	45		□	●					50/125
67				End of Borehole	80.00	■	●				
68											
69											
70											
71											
72											
73											
74											
75											
76											
77											
78											
79											
80											
81											
82											
83											

Thin wall tube

Split spoon


Rock core

Wash

Auger

Atterberg Limits : PL — Wn — LL

Suc : Undrained shear strength from UC test
SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)



Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test
SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)