

Project No. : 24167

Borehole Number : OW-29

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR06 (Lan Luang Station)

Co-ordinate (N) : 1,521,316

Ground Elevation (m) : +101.310 m.MSL

Co-ordinate (E) : 663,321

G.W.L. (m) : 1.0 (below ground level)

Date Started : 31 Oct 2024

Total Depth (m) : 80.00

Date Finished : 12 Nov 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □					
								20	40	60	80		
0				Ground Surface									
0				Fill Material / Top Soil	0.00								
1	■	ST	1	Soft CLAY, trace to few sand, grey, high plasticity (CH)	2.50		●	17.2					
2	■	ST	2				●	22.5					
3	■	ST	3				●	22.2					
4	■	ST	4				●	22					
5	■	ST	5				●						
6	■	ST	6				●						
7	■	ST	7	Medium stiff CLAY, trace of sand, grey, high plasticity (CH)	10.00		●	35.5					
8	■	ST	8				●	39.1					
9	■	ST	9	Very stiff silty CLAY, trace to few sand, greyish brown, high to low plasticity (CH, CL)	13.00		●				105.3		
10	■	SS	1				●	16					
11	■	SS	2				●	26					
12	■	SS	3				●	20					
13	■	SS	4	Hard sandy CLAY, greyish brown, low plasticity (CL)	19.00		●	26					
14	■	SS	5				●	40					
15	■	SS	6	Very stiff sandy CLAY, greyish brown, low plasticity (CL)	20.50		●	27					
16	■	SS	7				●				73/300		
17	■	SS	8	Hard sandy CLAY, greyish brown, low plasticity (CL)	22.00		●				57		
18	■	SS	9				●	63					
19	■	SS	10	Very dense silty SAND / SAND with silt, greyish brown and grey, fine to medium grained (SM, SP-SM)	23.50		●	47					
20	■	SS	11				●				50/125		
21	■	SS	12				●				50/125		
22	■	SS	13				●				50/125		
23	■	SS	14				●				50/150		
24	■	SS	15				●	55					
25	■	SS	16				●				71/275		
26	■	SS	17				●				50/125		
27	■	SS	18	Hard sandy CLAY, grey, low plasticity (CL)	38.50		●				78/250		

Project : MRT Orange Line (West Section)

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m ³) 5 15	Suc (kN/m ²) Δ 20 40 60 80 Δ			
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □ 20 40 60 80			
40				Very dense silty SAND, grey, fine grained (SM)	40.00						50/100
41	SS		19	Very dense silty SAND / SAND with silt, greyish brown and grey, fine to medium grained (SM, SP-SM)	44.50	□		•			50/125
42	SS	20	□				•		50/150		
43	SS	21	□				•		50/125		
44	SS	22	□				•		50/100		
45	SS	23	□				•		50/100		
46	SS	24	□				•		50/150		
47	SS	25	□				•		50/125		
48	SS	26	□				•		50/125		
49	SS	27	□				•		70		
50	SS	28	□				•		50/125		
51	SS	29	□				•		50/150		
52	SS	30	□				•		50/125		
53	SS	31	□				•		50/100		
54	SS	32	□				•		50/100		
55	SS	33	□				•		50/125		
56	SS	34	□				•		50/125		
57	SS	35	□				•		50/100		
58	SS	36	□				•		50/125		
59	SS	37	□				•		50/100		
60	SS	38	□				•		50/150		
61	SS	39	□				•		50/100		
62	SS	40	□				•		50/150		
63	SS	41	□				•		69/250		
64	SS	42				Hard silty CLAY / CLAY with sand, few to little sand, greyish brown, low plasticity (CL)	74.50	▬		•	
65	SS	43		▬				•	50/125		
66	SS	44		▬				•	50/150		
67	SS	45		▬				•			
68				End of Borehole	80.00						
69											
70											
71											
72											
73											
74											
75											
76											
77											
78											
79											
80											
81											
82											
83											

Thin wall tube

Split spoon

Rock core

Wash

Auger

Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)

Thin wall tube



Split spoon



Rock core



Wash



Auger



Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)