

Project No. : 24167

Borehole Number : OW-33

Page 1 of 2

Project : MRT Orange Line (West Section)

Borehole Location : OR07 (Yommarat Station)

Co-ordinate (N) : 1,521,326

Ground Elevation (m) : +101.282 m.MSL

Co-ordinate (E) : 664,053

G.W.L. (m) : 2.0 (below ground level)

Date Started : 17 Sep 2024

Total Depth (m) : 80.00

Date Finished : 23 Sep 2024

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ					
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □					
								20	40	60	80		
0				Ground Surface									
0				Fill Material	0.00								
1	■	ST	1	Very soft to soft CLAY, trace of sand, greenish grey to grey, high plasticity (CH)	2.00								
2	■	ST	2										
3	■	ST	3										
4	■	ST	4										
5	■	ST	5										
6	■	ST	6										
7	■	ST	7										
8	■	ST	8										
9	■	ST	9										
10	■	ST	10	Medium stiff CLAY, grey, high plasticity (CH)	13.00								
11	■	ST	11										
12	■	ST	12	Stiff to very stiff silty CLAY, trace to few sand, greenish grey to grey, high to low plasticity (CH, CL)	14.50								
13	■	SS	1										
14	■	SS	2										
15	■	SS	3	Hard silty CLAY, trace of sand, grey, low plasticity (CL)	19.00								
16	■	SS	4										
17	■	SS	5										
18	■	SS	6	Very stiff sandy CLAY, greyish brown, low plasticity (CL)	20.50								
19	■	SS	7										
20	■	SS	8	Very stiff silty CLAY, except hard silty clay for SS-7, greyish brown, low plasticity (CL)	22.00								
21	■	SS	9										
22	■	SS	10	Hard silty CLAY, trace of sand, greyish brown, low plasticity (CL)	26.50								
23	■	SS	11										
24	■	SS	12										
25	■	SS	13	Dense to very dense silty SAND / SAND with silt, little gravel at SS-17, greyish brown and grey, fine to medium grained (SM, SP-SM)	28.00								
26	■	SS	14										
27	■	SS	15										
28	■	SS	16										
29	■	SS	17										
30	■	SS	18										
31	■	SS	19										
32	■	SS	20										
33	■	SS	21										
34	■	SS	22										
35	■	SS	23										
36	■	SS	24										
37	■	SS	25										
38	■	SS	26										
39	■	SS	27										

Project : MRT Orange Line (West Section)

Depth (m)	SAMPLE			SUBSURFACE PROFILE		Atterberg Limits (%) 20 40 60 80	Unit Weight (kN/m³) 5 15	Suc (kN/m²) Δ				
	Symbol	Type	Number	Description	Symbol			SPT-N □ (Blows/300mm) □				
								20	40	60	80	
40	■	SS	18	Hard silty CLAY, trace of sand, grey, low plasticity (CL) Very dense silty SAND, grey, fine to medium grained (SM)	40.00	□					75	
41	■	SS	19		41.50	□					50/150	
42	■	SS	20			□					75/250	
43	■	SS	21			□					71/225	
44	■	SS	22		Hard silty CLAY, few sand, grey, low plasticity (CL) Very dense silty SAND / SAND with silt, greyish brown and grey, fine to medium grained (SM, SW-SM, SP-SM)	46.00	■				50/125	
45	■	SS	23			47.50	□					68/225
46	■	SS	24				□					66
47	■	SS	25				□					71/250
48	■	SS	26				□					50/50
49	■	SS	27				□					50/50
50	■	SS	28			□					50/125	
51	■	SS	29			□					50/75	
52	■	SS	30			□					50/100	
53	■	SS	31			□					50/125	
54	■	SS	32		□					50/150		
55	■	SS	33		□					70/275		
56	■	SS	34		□					50/150		
57	■	SS	35		□					50/125		
58	■	SS	36		□					50/150		
59	■	SS	37		□					50/150		
60	■	SS	38		□					61		
61	■	SS	39		□					50/125		
62	■	SS	40		□					50/75		
63	■	SS	41	Hard silty CLAY, greyish brown and grey, high to low plasticity (CH, CL)	74.50	■				67/275		
64	■	SS	42		■					50/150		
65	■	SS	43		■					50/150		
66	■	SS	44		■					50/150		
67	End of Borehole				80.00							
81												
82												
83												

Thin wall tube

Split spoon

Rock core


Wash

Auger

Atterberg Limits : PL — Wn — LL

Suc : Undrained shear strength from UC test

SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)



Atterberg Limits : PL Wn LL

Suc : Undrained shear strength from UC test
SPT-N : Field SPT-N (donut hammer with pulley and use split spoon sampling with liner)