

0.1.78 OAS 3.0.3

# Blockfrost.io ~ API Documentation

[Download OpenAPI Document](#)

Blockfrost is an API as a service that allows users to interact with the Cardano blockchain and parts of its ecosystem.

## Tokens

After signing up on <https://blockfrost.io>, a `project_id` token is automatically generated for each project. HTTP header of your request MUST include this `project_id` in order to authenticate against Blockfrost servers.

## Available networks

At the moment, you can use the following networks. Please, note that each network has its own `project_id`.

Network	Endpoint
Cardano mainnet	<code>https://cardano-mainnet.blockfrost.io/api/v0</code>
Cardano preprod	<code>https://cardano-preprod.blockfrost.io/api/v0</code>
Cardano preview	<code>https://cardano-preview.blockfrost.io/api/v0</code>
InterPlanetary File System	<code>https://ipfs.blockfrost.io/api/v0</code>
Milkomeda mainnet	<code>https://milkomeda-mainnet.blockfrost.io/api/v0</code>
Milkomeda testnet	<code>https://milkomeda-testnet.blockfrost.io/api/v0</code>

## Milkomeda

For more information about how to use Milkomeda as well as the list of available endpoints, see the [Milkomeda section](#).

## Concepts

- All endpoints return either a JSON object or an array.
- Data is returned in *ascending* (oldest first, newest last) order, if not stated otherwise.
  - You might use the `?order=desc` query parameter to reverse this order.
- By default, we return 100 results at a time. You have to use `?page=2` to list through the results.

- All time and timestamp related fields (except `server_time`) are in seconds of UNIX time.
- All amounts are returned in Lovelaces, where 1 ADA = 1 000 000 Lovelaces.
- Addresses, accounts and pool IDs are in Bech32 format.
- All values are case sensitive.
- All hex encoded values are lower case.
- Examples are not based on real data. Any resemblance to actual events is purely coincidental.
- We allow to upload files up to 100MB of size to IPFS. This might increase in the future.
- Only pinned IPFS files are counted towards the IPFS quota.
- Non-pinned IPFS files are subject to regular garbage collection and will be removed unless pinned.
- We allow maximum of 100 queued pins per IPFS user.

## Errors

### HTTP Status codes

The following are HTTP status code your application might receive when reaching Blockfrost endpoints and it should handle all of these cases.

- HTTP `400` return code is used when the request is not valid.
- HTTP `402` return code is used when the projects exceed their daily request limit.
- HTTP `403` return code is used when the request is not authenticated.
- HTTP `404` return code is used when the resource doesn't exist.
- HTTP `418` return code is used when the user has been auto-banned for flooding too much after previously receiving error code `402` or `429`.
- HTTP `425` return code is used in Cardano networks, when the user has submitted a transaction when the mempool is already full, not accepting new txs straight away.
- HTTP `425` return code is used in IPFS network, when the user has submitted a pin when the pin queue is already full, not accepting new pins straight away.
- HTTP `429` return code is used when the user has sent too many requests in a given amount of time and therefore has been rate-limited.
- HTTP `500` return code is used when our endpoints are having a problem.

### Error codes

An internal error code number is used for better indication of the error in question. It is passed using the following payload.

```
{
  "status_code": 403,
  "error": "Forbidden",
  "message": "Invalid project token."
}
```

## Limits

There are two types of limits we are enforcing:

The first depends on your plan and is the number of request we allow per day. We defined the day from midnight to midnight of UTC time.

The second is rate limiting. We limit an end user, distinguished by IP address, to 10 requests per second. On top of that, we allow each user to send burst of 500 requests, which cools off at rate of 10 requests per second. In essence, a user is allowed to make another whole burst after (currently)  $500/10 = 50$  seconds. E.g. if a user attempts to make a call 3 seconds after whole burst, 30 requests will be processed. We believe this should be sufficient for most of the use cases. If it is not and you have a specific use case, please get in touch with us, and we will make sure to take it into account as much as we can.

## SDKs

We support a number of SDKs that will help you in developing your application on top of Blockfrost.

Programming language	SDK
JavaScript	<a href="#">blockfrost-js</a>
Haskell	<a href="#">blockfrost-haskell</a>
Python	<a href="#">blockfrost-python</a>
Rust	<a href="#">blockfrost-rust</a>
Golang	<a href="#">blockfrost-go</a>
Ruby	<a href="#">blockfrost-ruby</a>
Java	<a href="#">blockfrost-java</a>
Scala	<a href="#">blockfrost-scala</a>
Swift	<a href="#">blockfrost-swift</a>
Kotlin	<a href="#">blockfrost-kotlin</a>
Elixir	<a href="#">blockfrost-elixir</a>
.NET	<a href="#">blockfrost-dotnet</a>

Arduino	<a href="#">blockfrost-arduino</a>
PHP	<a href="#">blockfrost-php</a>
Crystal	<a href="#">blockfrost-crystal</a>

---

## Health

### ENDPOINTS

[GET](#) /  
[GET](#) /health  
[GET](#) /health/clock

---

## Root endpoint

Root endpoint has no other function than to point end users to documentation.

### Responses

---

➤ 200 Information pointing to the documentation.

---

- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /

Shell Curl ▾

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/ \  
2 --header 'Project_id: YOUR_SECRET_TOKEN'
```

 Test Request

200 400 403 418 429 500

Show Schema ☐

```
{  
  "url": "https://blockfrost.io/",  
  "version": "0.1.0"  
}
```

Information pointing to the documentation.

## Backend health status

Return backend status as a boolean. Your application should handle situations when backend for the given chain is unavailable.

### Responses

- > 200 Return the boolean indicating the health of the backend.
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached

> 500 Internal Server Error

GET /health

Shell Curl ▾

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/health \  
2 --header 'Project_id: YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 403 418 429 500

Show Schema ☐

```
{  
  "is_healthy": true  
}
```

Return the boolean indicating the health of the backend.

## Current backend time

This endpoint provides the current UNIX time. Your application might use this to verify if the client clock is not out of sync.

### Responses

> 200 Return the current UNIX time in milliseconds.

> 400 Bad request

> 403 Authentication secret is missing or invalid

> 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached

> 429 Usage limit reached

> 500 Internal Server Error

GET /health/clockShell Curl ▾

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/health/clock \  
2 --header 'Project_id: YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 403 418 429 500Show Schema ☐

```
{  
  "server_time": 1603600958967
```

# Metrics

ENDPOINTS

GET /metrics

GET /metrics/endpoints

Show More ▾

# Cardano » Accounts

ENDPOINTS

GET /accounts/{stake\_address}

GET /accounts/{stake\_address}/rewards

GET /accounts/{stake\_address}/history

GET /accounts/{stake\_address}/delegations

GET /accounts/{stake\_address}/registrations

GET /accounts/{stake\_address}/withdrawals

GET /accounts/{stake\_address}/mirs

GET /accounts/{stake\_address}/addresses

GET /accounts/{stake\_address}/addresses/assets

GET /accounts/{stake\_address}/addresses/total

GET /accounts/{stake\_address}/utxos

Show More ▾

# Cardano » Addresses

## ENDPOINTS

```
GET /addresses/{address}
GET /addresses/{address}/extended
GET /addresses/{address}/total
GET /addresses/{address}/utxos
GET /addresses/{address}/utxos/{asset}
GET /addresses/{address}/txs
GET /addresses/{address}/transactions
```

## Specific address

Obtain information about a specific address.

### Path Parameters

address string **required**

Bech32 address.

### Responses

- > 200 Return the address content.
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error



GET /addresses/{address} Shell Curl ▾

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/addresses/addr1qxqs59lphg8
2 --header 'Project_id: YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 403 404 418 429 500 Show Schema ☐

```
{
  "address": "addr1qxqs59lphg8g6qndelq8xwqn60ag3aeyfcp33c2kdp46a09re5df3pzwwmy",
  "amount": [
    {
      "unit": "lovelace",
      "quantity": "42000000"
    },
    {
      "unit": "b0d07d45fe9514f80213f4020e5a61241458be626841cde717cb38a76e75746",
      "quantity": "12"
    }
  ],
  "stake_address": "stake1ux3g2c9dx2nhhehyrezypkstartcqu9hk63qgfkccw5rqttygt",
  "type": "shelley",
  "script": false
}
```

Return the address content.

AUTHENTICATION ▾

Name	project_id
Value	QUxMIFIPVVlqQkFTRSBBUkUgQkVMT05HFRPIFVT

# Extended information of a specific address

CLIENT LIBRARIES

Obtain extended information about a specific address.

Shell

Ruby

Node.js

PHP

Python

More

Path Parameters

curl -s https://cardano-mainnet.blockfrost.io/api/v0/addresses/addr1qxqs59lphg8g6qndelq8xwqn60ag3aeyfcp33c2kdp46a09re5df3pzwwmy

address string required  
Bech32 address.

Responses

- > 200 Return the address content.
- > 400 Bad request

- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /addresses/{address}/extended

Shell Curl ▾

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/addresses/addr1qxqs59lphg8
2 --header 'Project_id: YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐

```
{
  "address": "addr1qxqs59lphg8g6qndelq8xwqn60ag3aeyfcp33c2kdp46a09re5df3pzwwmy",
  "amount": [
    {
      "unit": "lovelace",
      "quantity": "42000000",
      "decimals": 6,
      "has_nft_onchain_metadata": false
    },
    {
      "unit": "b0d07d45fe9514f80213f4020e5a61241458be626841cde717cb38a76e75746",
      "quantity": "12",
      "decimals": null,
      "has_nft_onchain_metadata": true
    }
  ],
  "stake_address": "stake1ux3g2c9dx2nhhehyrezypkstartcqm9hk63qgfkccw5rqttygt",
  "type": "shelley",
  "script": false
}
```

Return the address content.

## Address details

Obtain details about an address.

## Path Parameters

`address` string **required**  
Bech32 address.

## Responses

- > 200 Return the Address details.
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /addresses/{address}/total

Shell Curl ▾

1 curl https://cardano-mainnet.blockfrost.io/api/v0/addresses/addr1qxqs59lphg8

2 --header 'Project\_id: YOUR\_SECRET\_TOKEN'

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐

```
{
  "address": "addr1qxqs59lphg8g6qndelq8xwqn60ag3aeyfcp33c2kdp46a09re5df3pzwwmy",
  "received_sum": [
    r
```

## Address UTXOs

UTXOs of the address.

### Path Parameters

**address** string **required**

Bech32 address.

### Query Parameters

**count** integer · min: 1 · max: 100 · default: 100

The number of results displayed on one page.

**page** integer · min: 1 · max: 21474836 · default: 1

The page number for listing the results.

**order** string · enum · default: asc

The ordering of items from the point of view of the blockchain, not the page listing itself. By default, we return oldest first, newest last.

└ asc

└ desc

### Responses

> **200** Return the address content

> **400** Bad request

> **403** Authentication secret is missing or invalid

> **404** Component not found

> **418** IP has been auto-banned for extensive sending of requests after usage limit has been reached

> **429** Usage limit reached

> 500 Internal Server Error

GET /addresses/{address}/utxos

Shell Curl ▾

1 curl https://cardano-mainnet.blockfrost.io/api/v0/addresses/addr1qxqs59Lphg8

2 --header 'Project\_id: YOUR\_SECRET\_TOKEN'

▶ Test Request

Address UTXOs of a given asset

Show Schema ☐

UTXOs of the address.

{

Path Parameters

"address": "addr1qxqs59Lphg8g6qndelq8xwqn60ag3aeyfcp33c2kdp46a09re5df3pzww

"tx\_hash": "39a7a284c2a0948189dc45dec670211cd4d72f7b66c5726c08d9b3df11e44d!

address string required

"output\_index": 0,

amount

Bech32 address.

"unit": "lovelace",

asset string required

"quantity": "42000000"

Concatenation of the policy\_id and hex-encoded asset\_name

Query Parameters	<pre> "block": "7eb8e27d18686c7db9a18f8bbcf34e3fed6e047afaa2d969904d15e934847e6 "data_hash": "9e478573ab81ea7a8e31891ce0648b81229f408d596a3483e6f4f9b92d3c "inline_datum": null, count integer · min: 1 · max: 100 · default: 100 "reference_script_hash": null The number of results displayed on one page. { page integer · min: 1 · max: 2147483647 · default: 1 "tx_hash": "4c4e67bafa15e742c13c592b65c8f74c769cd7d9af04c848099672d1ba391b "output_index": 0 Return the address content order string · enum · default: asc </pre>
------------------	---

The ordering of items from the point of view of the blockchain, not the page listing itself. By default, we return oldest first, newest last.

- └ asc
- └ desc

## Responses

- > 200 Return the address content
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /addresses/{address}/utxos/{asset}

DEPRECATED

Shell Curl ▾

### Address txs

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/addresses/addr1qxqs59lphg8
2 --header 'Project_id: YOUR_SECRET_TOKEN'
```

Transactions on the address.

▶ Test Request

### Path Parameters

200 400 403 404 418 429 500

Show Schema ☐

~~address~~ string **required**

Bech32 address.

### Query Parameters

~~count~~ integer · min: 1 · max: 100 · default: 100

The number of transactions per page.

```
"address": "addr1qxqs59lphg8g6qndelq8xwqn60ag3aeyfcp33c2kdp46a09re5df3pzww
"tx_hash": "32e7e284c2a0948189dc45dec670211cd4d72f7b66c5726c08d9b3df11e44d
"output_index": 0
"amount": [
{
"unit": "Lovelace",
"quantity": 42990000
},
{
"block": "7eb8e27d18686c7db9a18f8bbcf34e3fed6e047afaa2d969904d15e934847e6
"data_hash": "9e478573ab81ea7a8e31891ce0648b81229f408d596a3483e6f4f9b92d3c
"inline datum": null.
```

The page number for listing the results.

~~order~~ string · enum · default: asc

The ordering of items from the point of view of the blockchain, not the page listing itself. By default, we return oldest first, newest last.

```
asc ],
"block": "7eb8e27d18686c7db9a18f8bbcf34e3fed6e047afaa2d969904d15e934847e6
desc" data_hash": "9e478573ab81ea7a8e31891ce0648b81229f408d596a3483e6f4f9b92d3c
"inline datum": null.
```

Return the address content

### Responses

- > **200** Return the address content

---

- > **400** Bad request

---

- > **403** Authentication secret is missing or invalid

---

- > **404** Component not found

---

- > **418** IP has been auto-banned for extensive sending of requests after usage limit has been reached

---

- > **429** Usage limit reached

---

- > **500** Internal Server Error

---

## Address transactions

Transactions on the address.

### Path Parameters

---

**address** string **required**

Bech32 address.

### Query Parameters

---

**count** integer · min: 1 · max: 100 · default: 100



The number of addresses per page.

**page** integer · min: 1 · max: 21474836 · default: 1

The page number for listing the results.

**order** string · enum · default: asc

The ordering of items from the point of view of the blockchain, not the page listing itself. By default, we return oldest first, newest last.

└ asc

└ desc

**from** string

The block number and optionally also index from which (inclusive) to start search for results, concatenated using colon. Has to be lower than or equal to **to** parameter.

**GET** /addresses/{address}/txs

Shell Curl ▾

The block number and optionally also index where (inclusive) to end the search for results, concatenated using colon. Has to be higher than or equal to **from** parameter.

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/addresses/addr1qxqs59lphg8
2 --header 'Project-Id: YOUR_SECRET_TOKEN'
```

## Responses

▶ Test Request

> **200** Return the address content

Show Schema ☐

> **400** Bad request  
"2dd15e0ef6e6a17841cb9541c27724072ce4d4b79b91e58432fbaa32d9572531",  
"1a0570af966fb355a7160e4f82d5a80b8681b7955f5d44bec0dde628516157f0"

> **403** Authentication secret is missing or invalid

> **404** Component not found  
Return the address content

> **418** IP has been auto-banned for extensive sending of requests after usage limit has been reached

> **429** Usage limit reached

> **500** Internal Server Error

## Cardano » Assets

ENDPOINTS

[GET](#) /assets

[GET](#) /assets/{asset}

[GET](#) /assets/{asset}/history

[GET](#) ~~/assets/{asset}/txs~~

[GET](#) /assets/{asset}/transactions

[GET](#) /assets/{asset}/addresses

[GET](#) /assets/policy/{policy\_id}

Show More ▾

## Cardano » Blocks

ENDPOINTS

[GET](#) /blocks/latest

```
GET /blocks/latest/txs
GET /blocks/latest/txs/cbor
GET /blocks/{hash_or_number}
GET /blocks/{hash_or_number}/next
GET /blocks/{hash_or_number}/previous
GET /blocks/slot/{slot_number}
GET /blocks/epoch/{epoch_number}/slot/{slot_number}
GET /blocks/{hash_or_number}/txs
GET /blocks/{hash_or_number}/txs/cbor
GET /blocks/{hash_or_number}/addresses
```

[Show More ▾](#)

## Cardano » Epochs

### ENDPOINTS

```
GET /epochs/latest
GET /epochs/latest/parameters
GET /epochs/{number}
GET /epochs/{number}/next
GET /epochs/{number}/previous
GET /epochs/{number}/stakes
GET /epochs/{number}/stakes/{pool_id}
GET /epochs/{number}/blocks
GET /epochs/{number}/blocks/{pool_id}
GET /epochs/{number}/parameters
```

[Show More ▾](#)

## Cardano » Governance

### ENDPOINTS

```
GET /governance/dreps
GET /governance/dreps/{drep_id}
GET /governance/dreps/{drep_id}/delegators
GET /governance/dreps/{drep_id}/metadata
```

GET /governance/dreps/{drep\_id}/updates

GET /governance/dreps/{drep\_id}/votes

GET /governance/proposals

GET /governance/proposals/{tx\_hash}/{cert\_index}

GET /governance/proposals/{tx\_hash}/{cert\_index}/parameters

GET /governance/proposals/{tx\_hash}/{cert\_index}/withdrawals

GET /governance/proposals/{tx\_hash}/{cert\_index}/votes

GET /governance/proposals/{tx\_hash}/{cert\_index}/metadata

Show More ▾

## Cardano » Ledger

ENDPOINTS

GET /genesis

## Blockchain genesis

Return the information about blockchain genesis.

### Responses

- > 200 Return the genesis parameters.
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /genesis

Shell Curl ▾

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/genesis \
2   --header 'Project_id: YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 403 418 429 500 Show Schema ☐

```
{
  "active_slots_coefficient": 0.05,
  "update_quorum": 5,
  "max_lovelace_supply": "450000000000000000",
  "network_magic": 764824073,
  "epoch_length": 432000,
  "system_start": 1506203091,
  "slots_per_kes_period": 129600,
  "slot_length": 1,
  "max_kes_evolution": 62,
  "security_param": 2160
}
```

Return the genesis parameters.

# Cardano » Mempool

ENDPOINTS

GET /mempool

GET /mempool/{hash}

GET /mempool/addresses/{address}

Show More ▾

# Cardano » Metadata

ENDPOINTS

GET /metadata/txs/labels

GET /metadata/txs/labels/{label}

[GET](#) /metadata/txs/labels/{label}/cbor

Show More ▾

## Cardano » Network

### ENDPOINTS

[GET](#) /network  
[GET](#) /network/eras

Show More ▾

## Cardano » Pools

### ENDPOINTS

[GET](#) /pools  
[GET](#) /pools/extended  
[GET](#) /pools/retired  
[GET](#) /pools/retiring  
[GET](#) /pools/{pool\_id}  
[GET](#) /pools/{pool\_id}/history  
[GET](#) /pools/{pool\_id}/metadata  
[GET](#) /pools/{pool\_id}/relays  
[GET](#) /pools/{pool\_id}/delegators  
[GET](#) /pools/{pool\_id}/blocks  
[GET](#) /pools/{pool\_id}/updates  
[GET](#) /pools/{pool\_id}/votes

Show More ▾

## Cardano » Scripts

## ENDPOINTS

[GET](#) /scripts  
[GET](#) /scripts/{script\_hash}  
[GET](#) /scripts/{script\_hash}/json  
[GET](#) /scripts/{script\_hash}/cbor  
[GET](#) /scripts/{script\_hash}/redeemers  
[GET](#) /scripts/datum/{datum\_hash}  
[GET](#) /scripts/datum/{datum\_hash}/cbor

[Show More](#) ▾

## Cardano » Transactions

## ENDPOINTS

[GET](#) /txs/{hash}  
[GET](#) /txs/{hash}/utxos  
[GET](#) /txs/{hash}/stakes  
[GET](#) /txs/{hash}/delegations  
[GET](#) /txs/{hash}/withdrawals  
[GET](#) /txs/{hash}/mirs  
[GET](#) /txs/{hash}/pool\_updates  
[GET](#) /txs/{hash}/pool\_retires  
[GET](#) /txs/{hash}/metadata  
[GET](#) /txs/{hash}/metadata/cbor  
[GET](#) /txs/{hash}/redeemers  
[GET](#) /txs/{hash}/required\_signers  
[GET](#) /txs/{hash}/cbor  
[POST](#) /tx/submit

## Specific transaction

Return content of the requested transaction.

### Path Parameters

**hash** string · 64-character case-sensitive hexadecimal string. **required**

Hash of the requested transaction

Responses

✓ 200 Return the contents of the transaction.

object

× Hide Child Attributes	
hash string required	Transaction hash
block string required	Block hash
block_height integer required	Block number
block_time integer required	Block creation time in UNIX time
slot integer required	Slot number
index integer required	Transaction index within the block
output_amount array object[] required	The sum of all the UTXO per asset
+ Show Child Attributes	
fees string required	Fees of the transaction in Lovelaces
deposit string required	Deposit within the transaction in Lovelaces
size integer required	Size of the transaction in Bytes
invalid_before string   nullable required	Left (included) endpoint of the timelock validity intervals
invalid_hereafter string   nullable required	Right (excluded) endpoint of the timelock validity intervals
utxo_count integer required	



Count of UTXOs within the transaction

`withdrawal_count` integer **required**

Count of the withdrawals within the transaction

`mir_cert_count` integer **required**

Count of the MIR certificates within the transaction

`delegation_count` integer **required**

Count of the delegations within the transaction

`stake_cert_count` integer **required**

Count of the stake keys (de)registration within the transaction

`pool_update_count` integer **required**

Count of the stake pool registration and update certificates within the transaction

`pool_retire_count` integer **required**

Count of the stake pool retirement certificates within the transaction

`asset_mint_or_burn_count` integer **required**

Count of asset mints and burns within the transaction

`redeemer_count` integer **required**

Count of redeemers within the transaction

`valid_contract` boolean **required**

True if contract script passed validation

> 400 Bad request

> 403 Authentication secret is missing or invalid

> 404 Component not found

> 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached

> 429 Usage limit reached

> 500 Internal Server Error

---

## Transaction UTXOs

Return the inputs and UTXOs of the specific transaction.

### Path Parameters

**hash** string · 64-character case-sensitive hexadecimal string **required**

Hash of the requested transaction

### Responses

- **200** Return the contents of the transaction.
- **400** Bad request
- **403** Authentication secret is missing or invalid
- **404** Component not found
- **418** IP has been auto-banned for extensive sending of requests after usage limit has been reached

> 429 Usage limit reached

> 500 Internal Server Error

GET /txs/{hash}/utxos

Shell Curl ▾

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a
2 --header 'Project_id: YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐

```
{
  "hash": "1e043f100dce12d107f679685acd2fc0610e10f72a92d412794c9773d11d8477",
  "inputs": [
    {
      "address": "addr1q9ld26v2lv8wvrxxmvg90pn8n8n5k6tdst06q2s856rwmvnue1dzuuq",
      "amount": [
        {
          "unit": "lovelace",
          "quantity": "42000000"
        },
        {
          "unit": "b0d07d45fe9514f80213f4020e5a61241458be626841cde717cb38a76e7",
          "quantity": "12"
        }
      ],
      "tx_hash": "1a0570af966fb355a7160e4f82d5a80b8681b7955f5d44bec0dce6285161",
      "output_index": 0,
      "data_hash": "9e478573ab81ea7a8e31891ce0648b81229f408d596a3483e6f4f9b92d",
      "inline_datum": "19a6aa",
      "reference_script_hash": "13a3a5d825703a352a8f71f6a2758d08a28a566a8df000"
```

Return the contents of the transaction.

## Transaction stake addresses certificates

Obtain information about (de)registration of stake addresses within a transaction.

### Path Parameters

**hash** string · 64-character case-sensitive hexadecimal string. **required**

Hash of the requested transaction.

## Responses

- > 200 Obtain information about (de)registration of stake addresses within a transaction.
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /txs/{hash}/stakes

Shell Curl ▾

1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a

2 --header 'Project\_id: YOUR\_SECRET\_TOKEN'

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐

[

{

cert\_index: 0,

"address": "stake1u9t3a0tcwune5xrnfjg4q7cpvjlgx9lcv0cuqf5mhfjwrvcwru1da",

Obtain information about delegation certificates of a specific transaction.

registration: true

}

]

Path Parameters

Obtain information about (de)registration of stake addresses within a transaction.

hash string · 64-character case-sensitive hexadecimal string required

unit: Lovelace ,

"quantity": "42000000"

Hash of the requested transaction.

```
{
  "unit": "b0d07d45fe9514f80213f4020e5a61241458be626841cde717cb38a76e75746",
  "quantity": "12"
}
```

Responses

> 200 Obtain information about delegation certificates of a specific transaction

> 400 "fees": "182485",

> 400 "deposit": "0",

> 400 "size": 433,

> 403 "invalid\_before": null,

> 403 Authentication secret is missing or invalid

> 404 Component not found

> 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached

> 429 Usage limit reached

> 500 Internal Server Error

GET /txs/{hash}/delegations

Shell Curl ▾

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a
2 --header 'Project_id: YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐

```
[
  {
    "index": 0,
    "cert_index": 0,
    "address": "stake1u9r76ypf5fskppa0cmttas05cgcswrtn6jrq4yd7jpdnvc7gt0yc",
    "pool_id": "pool1pu5jlj4q9w9jlx370a3c9myx47md5j5m2str0naunn2q3lkdy",
    "active_epoch": 210
  }
]
```

Transaction withdrawal

Obtain information about withdrawals of a specific transaction.

## Path Parameters

**hash** string · 64-character case-sensitive hexadecimal string **required**  
Hash of the requested transaction.

## Responses

- > 200 Obtain information about withdrawals of a specific transaction.
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /txs/{hash}/withdrawals

Shell Curl ▾

1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a

2 --header 'Project\_id: YOUR\_SECRET\_TOKEN'

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐

## Transaction MIRs

Obtain information about Move Instantaneous Rewards (MIRs) of a specific transaction.

```
"address": "stake1u9r76ypf5fskppa0cmttas05cgcswrtn6jrqr4yd7jpdnvc7gt0yc",
```

### Hash of the requested transaction

## Responses

- > **200** Obtain information about Move Instantaneous Rewards (MIRs) of a specific transaction.
- > **400** Bad request
- > **403** Authentication secret is missing or invalid
- > **404** Component not found
- > **418** IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > **429** Usage limit reached
- > **500** Internal Server Error

Shell Curl ▾

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a
2 --header 'Project_id: YOUR_SECRET_TOKEN'
```

▶ Test Request

Show Schema ☐

```
[
  {
    "pot": "reserve",
    "cert_index": 0,
    "address": "etake1xQz74m5F5dmsQmtho2F9mzwtt44d9r4d7index7etQw"
```

# Transaction stake pool registration and update certificate

}  
s]

Obtain information about stake pool registration and update certificates of a specific transaction.

## Path Parameters

hash string · 64-character case-sensitive hexadecimal string **required**  
Hash of the requested transaction

## Responses

- > 200 Obtain information about stake pool certificates of a specific transaction
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /txs/{hash}/pool\_updates

Shell Curl ▾

1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a

2 --header 'Project\_id: YOUR\_SECRET\_TOKEN'

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐



```
[
  {
    "cert_index": 0,
    "pool_id": "pool1pu5jlj4q9w9jlx370a3c9myx47md5j5m2str0naunn2q3lkdy",
    "vrf_key": "0b5245f9934ec2151116fb8ec00f35fd00e0aa3b075c4ed12cce440f999d82",
    "pledge": "5000000000",
    "margin_cost": 0.05,
    "fixed_cost": "3400000000",
    "reward_account": "stake1uxkptsa4lkr55jleztw43t37vgdn88l6ghclfwuxld2eykgpg",
    "owners": [
      "stake1u98nnlkvkk23vtvf9273uq7cph5ww6u2yq2389psuqet90sv4xv9v"
    ]
  }
]
```

## Transaction stake pool retirement certificates

Obtain information about stake pool retirements within a specific transaction.

### Path Parameters

**hash** string · 64-character case-sensitive hexadecimal string. **required**

Hash of the requested transaction

### Responses

- > **200** Obtain information about stake pool retirements within a specific transaction.
- > **400** Bad request
- > **403** Authentication secret is missing or invalid
- > **404** Component not found
- > **418** IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > **429** Usage limit reached
- > **500** Internal Server Error

GET /txs/{hash}/pool\_retires

Shell Curl ▾

1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a

2 --header 'Project\_id: YOUR\_SECRET\_TOKEN'

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐

[

{

"cert\_index": 0,

"pool\_id": "pool1pu5jlj4q9w9jlxev370a3c9myx47md5j5m2str0naunn2q3lkdy",

"retiring\_epoch": 216

}

]

### Transaction metadata

Obtain the transaction metadata.

### Path Parameters

Obtain information about stake pool retirements within a specific transaction.

hash string · 64-character case-sensitive hexadecimal string. **required**

Hash of the requested transaction

## Responses

- > 200 Obtain metadata information associated with a specific transaction.
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /txs/{hash}/metadata

Shell Curl ▾

1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a

2 --header 'Project\_id: YOUR\_SECRET\_TOKEN'

[▶ Test Request](#)

200 400 403 404 418 429 500

Show Schema ☐

```
[
  {
    "label": "1967",
    "json_metadata": {
      "metadata": "https://nut.link/metadata.json",
      "hash": "6bf124f217d0e5a0a8adb1dbd8540e1334280d49ab861127868339f43b3948a"
    }
  },
  {
    "label": "1968",
    "json_metadata": {
      "ADAUSD": [
        {
          "value": "0.10409800535729975",
          "source": "ergoOracles"
        }
      ]
    }
  }
]
```

Obtain metadata information associated with a specific transaction.

## Transaction metadata in CBOR

Obtain the transaction metadata in CBOR.

### Path Parameters

**hash** string · 64-character case-sensitive hexadecimal string. **required**

Hash of the requested transaction

### Responses

- > 200 Obtain metadata information associated with a specific transaction.
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found

- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /txs/{hash}/metadata/cbor

Shell Curl ▾

1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a

2 --header 'Project\_id: YOUR\_SECRET\_TOKEN'

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐

[

{

table:

1968

"cbor\_metadata": "\\xa100a16b436f6d62696e617469666e86010101010c",

Obtain the transaction redeemers

Metadata:

4100a16b436f6d62696e617469666e86010101010c"

}

]

Transaction redeemers

Path Parameters

Obtain metadata information associated with a specific transaction.  
hash string · 64-character case-sensitive hexadecimal string. 

required

Hash of the requested transaction

Responses

- > 200 Obtain information about redeemers within a specific transaction.
- > 400 Bad request
- > 403 Authentication secret is missing or invalid

- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /txs/{hash}/redeemers

Shell Curl ▾

```
1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a
2 --header 'Project_id: YOUR_SECRET_TOKEN'
```

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐

```
[
  {
    "tx_index": 0,
    "purpose": "spend",
    "script_hash": "ec26b89af41bef0f7585353831cb5da42b5b37185e0c8a526143b824",
    "redeemer_data_hash": "923918e403bf43c34b4ef6b48eb2ee04babed17320d8d1b9ff9",
    "datum_hash": "923918e403bf43c34b4ef6b48eb2ee04babed17320d8d1b9ff9ad086e86",
    "unit_mem": "1700",
    "unit_steps": "476468",
    "fee": "172033"
  }
]
```

Obtain information about redeemers within a specific transaction.

## Transaction required signers

Obtain the extra transaction witnesses.

### Path Parameters

**hash** string · 64-character case-sensitive hexadecimal string. **required**

Hash of the transaction

### Responses

- > 200 Query required signers (extra transaction witnesses)
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /txs/{hash}/required\_signers

Shell Curl ▾

1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a

2 --header 'Project\_id: YOUR\_SECRET\_TOKEN'

Transaction CBOR

▶ Test Request

Obtain the CBOR serialized transaction

Show Schema ☐

Path Parameters

{

hash { "witness\_hash": "d52e11f3e48436dd42dbec6d88c239732e503b8b7a32af58e5f87625"

} string · 64-character case-sensitive hexadecimal string. required

Hash of the transaction

Query required signers (extra transaction witnesses)

Responses

>	200	Query transaction CBOR
>	400	Bad request
>	403	Authentication secret is missing or invalid
>	404	Component not found
>	418	IP has been auto-banned for extensive sending of requests after usage limit has been reached
>	429	Usage limit reached
>	500	Internal Server Error

## Submit a transaction

GET /txs/{hash}/cbor

Shell Curl ▾

Submit an already serialized transaction to the network.

1 curl https://cardano-mainnet.blockfrost.io/api/v0/txs/6e5f825c82c1c6d6b77f2a

2 --header 'Project id: YOUR\_SECRET\_TOKEN'

Hosted Endpoint only available for hosted variant.

Body

▶ Test Request application/cbor

The transaction to submit, serialized in CBOR.

200 400 403 404 418 429 500

Show Schema ☐

The transaction to submit, serialized in CBOR.

"cbor": "84a40081825820203e5b61e0949ffc8fe594727cf7ed73c7396cc2bd212af9a680c"

string

The transaction to submit, serialized in CBOR.

Query transaction CBOR

https://docs.blockfrost.io/#tag/ipfs--gateway/GET/ipfs/gateway/{IPFS\_path}

39/44

## Responses

- > 200 Return the ID of the submitted transaction.
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 425 Mempool is already full, not accepting new txs straight away
- > 429 Usage limit reached
- > 500 Internal Server Error

## Cardano » Utilities

### ENDPOINTS

GET /utils/addresses/xpub/{xpub}/{role}/{index}

POST /utils/txs/evaluate



**POST** /utils/txs/evaluate/utxos

Show More ▾

▶ Test Request

# IPFS » Add

200 400 403 404 418 425 429 500

Show Schema ☐

## ENDPOINTS

**POST** /ipfs/add

## Add a file to IPFS

You need to `/ipfs/pin/add` an object to avoid it being garbage collected. This usage is being counted in your user account quota.

Hosted Endpoint only available for hosted variant.

### Body

multipart/form-data

**file** string · binary  
binary data, used to describe files

### Responses

- > **200** Returns information about added IPFS object
- > **400** Bad request
- > **403** Authentication secret is missing or invalid
- > **404** Component not found
- > **418** IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > **429** Usage limit reached
- > **500** Internal Server Error

POST /ipfs/add

cURL ▾

```
1 curl "https://ipfs.blockfrost.io/api/v0/ipfs/add" \  
2   -X POST \  
3   -H "project_id: $PROJECT_ID" \  
4   -F "file=@./README.md" \  
5
```

IPFS » Gateway

▶ Test Request

200 400 403 404 418 429 500

Show Schema ☐

ENDPOINTS

GET /ipfs/gateway/{IPFS\_path}

```
"size": "125297" \  
{
```

Returns information about added IPFS object

## Relay to an IPFS gateway

Retrieve an object from the IPFS gateway (useful if you do not want to rely on a public gateway, such as `ipfs.blockfrost.dev`).

Hosted Endpoint only available for hosted variant.

### Path Parameters

IPFS\_path string required  
Path to the IPFS object

## Responses

- > 200 Returns the object content
- > 400 Bad request
- > 403 Authentication secret is missing or invalid
- > 404 Component not found
- > 418 IP has been auto-banned for extensive sending of requests after usage limit has been reached
- > 429 Usage limit reached
- > 500 Internal Server Error

GET /ipfs/gateway/{IPFS\_path} cURL ▾

1 curl "https://ipfs.blockfrost.io/api/v0/ipfs/gateway/{IPFS\_path}" \  
2 -H "project\_id: \$PROJECT\_ID" \  
3

▶ Test Request

200 400 403 404 418 429 500
No Body
Returns the object content

## IPFS » Pins

ENDPOINTS

```
POST /ipfs/pin/add/{IPFS_path}
GET /ipfs/pin/list
GET /ipfs/pin/list/{IPFS_path}
POST /ipfs/pin/remove/{IPFS_path}
```

[Show More ▾](#)

## Nut.link

### ENDPOINTS

```
GET /nutlink/{address}
GET /nutlink/{address}/tickers
GET /nutlink/{address}/tickers/{ticker}
GET /nutlink/tickers/{ticker}
```

[Show More ▾](#)