

SQL

by

APNA
COLLEGE

Database



Database is a collection of data organized in a way that allows for easy access, retrieval, and management. It is a structured set of data that is stored and organized in a way that allows for easy access, retrieval, and management.

Database is a collection of data organized in a way that allows for easy access, retrieval, and management. It is a structured set of data that is stored and organized in a way that allows for easy access, retrieval, and management.

APNA
COLLEGE

Types of Databases



What is SQL?




Structured Query Language

SQL is a standard language for managing data in a database.

It is used to create, modify, and delete data in a database.

APNA
COLLEGE

Database Structure



What is a table?

Student table

RollNo	Name	Class	DOB	Gender	City	Marks
1	Nanda	X	1995-06-06	M	Agra	551
2	Saurabh	XII	1993-05-07	M	Mumbai	462
3	Sonal	XI	1994-05-06	F	Delhi	400
4	Trisla	XII	1995-08-08	F	Mumbai	450
5	Store	XII	1995-10-08	M	Delhi	369
6	Marisla	XI	1994-12-12	F	Dubai	250
7	Neha	X	1995-12-08	F	Moscow	377
8	Nishant	X	1995-06-12	M	Moscow	489

Creating our First Database

Our first SQL Query

```
CREATE DATABASE db_name;
```

```
DROP DATABASE db_name;
```

APNA
COLLEGE

Creating our First Table

USE *db_name*;

CREATE TABLE *table_name* (
 column_name1 datatype constraint,
 column_name2 datatype constraint,
 column_name2 datatype constraint
);

```
CREATE TABLE student (  
  id INT PRIMARY KEY,  
  name VARCHAR(50),  
  age INT NOT NULL
```



SQL Datatypes

They define the **type of values** that can be stored in a column

DATATYPE	DESCRIPTION	USAGE	
CHAR	string(0-255), can store characters of fixed length	CHAR(50)	
VARCHAR	string(0-255), can store characters up to given length	VARCHAR(50)	
BLOB(1000)	BLOB	string(0-65535), can store binary large object	
INT	INT	Integer(-2,147,483,648 to 2,147,483,647)	
TINYINT	TINYINT	Integer(-128 to 127)	
BIGINT	BIGINT	Integer(-9,223,372,036,854,775,808 to 9,223,372,036,854,775,807)	
to 64	BIT(2)	BIT	can store x-bit values. x can range from 1
to 53 digits	DOUBLE	DOUBLE	Decimal number - with 24
YYYY-MM-DD ranging from 0000-01-01 to 9999-12-31	DATE	DATE	date in format of YYYY-MM-DD
year in 4 digits format ranging from 1901 to 2155	YEAR	YEAR	year in 4 digits format

SQL Datatypes

Signed & Unsigned

TINYINT UNSIGNED (0 to 255)

TINYINT (-128 to 127)

APNA
COLLEGE

Types of SQL Commands

DDL (Data Definition Language) : create, alter, rename, truncate & drop

DQL (Data Query Language) : select

DML (Data Manipulation Language) : select, insert, update & delete

DCL (Data Control Language) : grant & revoke permission to users

TCL (Transaction Control Language) : start transaction, commit, rollback etc.



Database related Queries

CREATE DATABASE *db_name*;

CREATE DATABASE **IF NOT EXISTS** *db_name*;

~~CREATE DATABASE IF NOT EXISTS college;~~

DROP DATABASE *db_name*;

DROP DATABASE **IF EXISTS** *db_name*;

SHOW DATABASES;

SHOW TABLES;

APNA
COLLEGE

Table related Queries

Create

```
CREATE TABLE table_name (  
    column_name1 datatype constraint,  
    column_name2 datatype constraint,  
);
```

```
CREATE TABLE student (  
    rollno INT PRIMARY KEY,  
    name VARCHAR(50)  
);
```

Table related Queries

Select & View ALL columns

```
SELECT * FROM table_name;
```

```
SELECT * FROM student;
```

Table related Queries

Insert

```
INSERT INTO table_name  
(colname1, colname2);  
VALUES  
(col1_v1, col2_v1),  
(col1_v2, col2_v2);
```

```
INSERT INTO student  
(rollno, name)  
VALUES  
(101, "karan"),  
(102, "arjun");
```

Keys

Primary Key

It is a column (or set of columns) in a table that uniquely identifies each row. (a unique id)

There is only 1 PK & it should be NOT null.

Foreign Key

A foreign key is a column (or set of columns) in a table that refers to the primary key in another table.

There can be multiple FKs.

FKs can have duplicate & null values.

Keys

table1 - Student

id	name	cityId	city
101	karan	1	Pune
102	arjun	2	Mumbai
103	ram	1	Pune
104	shyam	3	Delhi

table2 - City

id	city_name
1	Pune
2	Mumbai
3	Delhi

Constraints

SQL constraints are used to specify rules for data in a table.

NOT NULL columns cannot have a null value

```
col1 int NOT NULL
```

UNIQUE all values in column are different

```
col2 int UNIQUE
```

PRIMARY KEY makes a column unique & not null but used only for one

```
id int PRIMARY KEY
```

```
CREATE TABLE temp (  
  id int not null,  
  PRIMARY KEY (id)  
);
```

Constraints

```
CREATE TABLE temp (  
  cust_id int,  
  FOREIGN KEY (cust_id) references customer(id)  
);
```

Constraints

CHECK it can limit the values allowed in a column

```
CREATE TABLE city (  
  id INT PRIMARY KEY,  
  city VARCHAR(50),  
  age INT,  
  CONSTRAINT age_check CHECK (age >= 18 AND city="Delhi")  
);
```

```
CREATE TABLE newTab (  
  age INT CHECK (age >= 18)  
);
```

Create this sample table

```
CREATE DATABASE college;
USE college;

CREATE TABLE student (
  rollno INT PRIMARY KEY,
  name VARCHAR(50),
  marks INT NOT NULL,
  grade VARCHAR(1),
  city VARCHAR(20)
);
```

Insert this data

```
INSERT INTO student
(rollno, name, marks, grade, city)
VALUES
(101, "anil", 78, "C", "Pune"),
(102, "bhumika", 93, "A", "Mumbai"),
(103, "chetan", 85, "B", "Mumbai"),
(104, "dhruv", 96, "A", "Delhi"),
(105, "emanuel", 12, "F", "Delhi"),
(106, "farah", 82, "B", "Delhi");
```

Select in Detail

used to select any data from the database

Basic Syntax

```
SELECT col1, col2 FROM table_name;
```

To Select ALL

```
SELECT * FROM table_name;
```



Where Clause

To define some conditions

```
SELECT col1, col2 FROM table_name  
WHERE conditions;
```

```
SELECT * FROM student WHERE marks > 80;  
SELECT * FROM student WHERE city = "Mumbai";
```


Where Clause

Using Operators in WHERE

Arithmetic Operators : +(addition) , -(subtraction), *(multiplication), /(division), %(modulus)

Comparison Operators : = (equal to), != (not equal to), > , >=, <, <=

Logical Operators : AND, OR , NOT, IN, BETWEEN, ALL, LIKE, ANY

Bitwise Operators : & (Bitwise AND), | (Bitwise OR)



Operators

AND (to check for both conditions to be true)

```
SELECT * FROM student WHERE marks > 80 AND city = "Mumbai";
```

OR (to check for one of the conditions to be true)

```
SELECT * FROM student WHERE marks > 90 OR city = "Mumbai";
```

Operators

Between (selects for a given range)

```
SELECT * FROM student WHERE marks BETWEEN 80 AND 90;
```

In (matches any value in the list)

```
SELECT * FROM student WHERE city IN ("Delhi", "Mumbai");
```

NOT (to negate the given condition)

```
SELECT * FROM student WHERE city NOT IN ("Delhi", "Mumbai");
```

Limit Clause

Sets an upper limit on number of (tuples)rows to be returned

```
SELECT * FROM student LIMIT 3;
```

```
SELECT col1, col2 FROM table_name  
LIMIT number;
```

Order By Clause

To sort in ascending (ASC) or descending order (DESC)

```
SELECT * FROM student  
ORDER BY city ASC;
```

```
SELECT col1, col2 FROM table_name  
ORDER BY col_name(s) ASC;
```

Aggregate Functions

Aggregate functions perform a calculation on a set of values, and return a single value.

- COUNT()
- MAX()
- MIN()
- SUM()
- AVG()

Get Maximum Marks

```
marks) SELECT max(marks)  
FROM student;
```

Get Average marks

```
SELECT avg(marks)  
FROM student;
```

Group By Clause

Groups rows that have the same values into summary rows.

It collects data from multiple records and groups the result by one or more column.

*Generally we use group by with some *aggregation function*.

Count number of students in each city

```
SELECT city, count(name)
FROM student
GROUP BY city;
```

Having Clause

Similar to Where i.e. applies some condition on rows.

Used when we want to apply any **condition after grouping**.

Count number of students in each city where max marks cross 90.

```
SELECT count(name), city  
FROM student  
GROUP BY city  
HAVING max(marks) > 90;
```

General Order

```
SELECT column(s)  
FROM table_name  
WHERE condition  
GROUP BY column(s)  
HAVING condition  
ORDER BY column(s) ASC;
```


Having Clause

Similar to Where i.e. applies some condition on rows.

Used when we want to apply any **condition after grouping**.

Count number of students in each city where max marks cross 90.

```
SELECT count(name), city
FROM student
GROUP BY city
HAVING max(marks) > 90;
```

Table related Queries

Update (to update existing rows)

```
UPDATE table_name  
SET col1 = val1, col2 = val2  
WHERE condition;
```

```
UPDATE student  
SET grade = "0"  
WHERE grade = "A";
```

Table related Queries

Delete (to delete existing rows)

```
DELETE FROM table_name  
WHERE condition;
```

```
DELETE FROM student  
WHERE marks < 33;
```

Cascading for FK

On Delete Cascade

On Update Cascade



APNA
COLLEGE

Table related Queries

Alter (to change the schema)

ADD Column

ALTER TABLE *table_name*

ADD COLUMN *column_name datatype constraint;*

DROP Column

ALTER TABLE *table_name*

DROP COLUMN *column_name;*

RENAME Table

ALTER TABLE *table_name*

RENAME TO *new_table_name;*



Table related Queries

CHANGE Column (rename)

ALTER TABLE *table_name*

CHANGE COLUMN *old_name new_name new_datatype new_constraint;*

MODIFY Column (modify datatype/ constraint)

ALTER TABLE *table_name*

MODIFY *col_name new_datatype new_constraint;*



ADD Column

```
ALTER TABLE student  
ADD COLUMN age INT NOT NULL DEFAULT 19;
```

DROP Column

```
ALTER TABLE student  
DROP COLUMN stu_age;
```

MODIFY Column

```
ALTER TABLE student  
MODIFY age VARCHAR(2);
```

RENAME Table

```
ALTER TABLE student  
RENAME TO stu;
```

CHANGE Column (rename)

```
ALTER TABLE student  
CHANGE age stu_age INT;
```

APNA
COLLEGE

Table related Queries

Truncate (to delete table's data)


TRUNCATE TABLE *table_name* ;

```
UPDATE student  
SET grade = "0"  
WHERE grade = "A";
```



Joins in SQL

Join is used to combine rows from two or more tables, based on a related column between them.


Types of Joins




Inner Join



Left Join



Right Join



Full Join



Outer Joins

APNA
COLLEGE

Inner Join

Returns records that have matching values in both tables


Syntax

SELECT *column(s)*

FROM *tableA*

INNER JOIN *tableB*

ON *tableA.col_name = tableB.col_name;*



Inner Join

Example

student

student_id	name
101	adam
102	bob
103	casey

course

student_id	course
102	english
105	math
103	science
107	computer science

Result

student_id	name	course
102	bob	english
103	casey	science

```
SELECT *  
FROM student  
INNER JOIN course  
ON student.student_id = course.student_id;
```



Left Join

Returns all records from the left table, and the matched records from the right table


Syntax

SELECT *column(s)*

FROM *tableA*

LEFT JOIN *tableB*

ON *tableA.col_name = tableB.col_name;*



APNA
COLLEGE

Left Join

Example

student

student_id	name
101	adam
102	bob
103	casey

course

student_id	course
102	english
105	math
103	science
107	computer science

Result

student_id	name	course
101	adam	<i>null</i>
102	bob	english
103	casey	science

```
SELECT *  
FROM student as s  
LEFT JOIN course as c  
ON s.student_id = c.student_id;
```

Right Join

Returns all records from the right table, and the matched records from the left table


Syntax

SELECT *column(s)*

FROM *tableA*

RIGHT JOIN *tableB*

ON *tableA.col_name = tableB.col_name;*



Right Join

Example

student

student_id	name
101	adam
102	bob
103	casey

course

student_id	course
102	english
105	math
103	science
107	computer science

```
SELECT *  
FROM student as s  
RIGHT JOIN course as c  
ON s.student_id = c.student_id;
```

Result

student_id	course	name
102	english	bob
105	math	<i>null</i>
103	science	casey
107	computer science	<i>null</i>

Full Join

Returns all records when there is a match in either left or right table


Syntax in MySQL

```
SELECT * FROM student as a
LEFT JOIN course as b
ON a.id = b.id
UNION
SELECT * FROM student as a
RIGHT JOIN course as b
ON a.id = b.id;
```

LEFT JOIN

UNION

RIGHT JOIN



APNA
COLLEGE

Full Join

Example

student

student_id	name
101	adam
102	bob
103	casey

course

student_id	course
102	english
105	math
103	science
107	computer science

Result

student_id	name	course
101	adam	<i>null</i>
102	bob	english
103	casey	science
105	<i>null</i>	math
107	<i>null</i>	computer science



Self Join

It is a regular join but the table is joined with itself.

Syntax

SELECT *column(s)*

FROM *table as a*

JOIN *table as b*

ON *a.col_name = b.col_name;*

Self Join

Example

Employee

id	name	manager_id
101	adam	103
102	bob	104
103	casey	<i>null</i>
104	donald	103

Result

```
SELECT a.name as manager_name, b.name
FROM employee as a
JOIN employee as b
ON a.id = b.manager_id;
```

Union

It is used to combine the result-set of two or more SELECT statements.
Gives UNIQUE records.

To use it :

- every SELECT should have same no. of columns
- columns must have similar data types
- columns in every SELECT should be in same order

Syntax

SELECT *column(s)* **FROM** *tableA*

UNION

SELECT *column(s)* **FROM** *tableB*




SQL Sub Queries

A Subquery or Inner query or a Nested query is a query within another SQL query.

It involves 2 select statements.

Syntax

```
SELECT column(s)  
FROM table_name  
WHERE col_name operator  
( subquery );
```



SQL Sub Queries

Example

Get names of all students who scored more than class average.

Step 1. Find the avg of class

Step 2. Find the names of students with marks > avg

rollno	name	marks
101	anil	78
102	bhumika	93
103	chetan	85
104	dhruv	96
105	emanuel	92
106	farah	82

SQL Sub Queries

Example

Find the names of all students with even roll numbers.

Step 1. Find the even roll numbers

Step 2. Find the names of students with even roll no

rollno	name	marks
101	anil	78
102	bhumika	93
103	chetan	85
104	dhruv	96
105	emanuel	92
106	farah	82

SQL Sub Queries

Example with *FROM*

Find the max marks from the students of Delhi

Step 1. Find the students of Mumbai

Step 2. Find their max marks using the sublist in step 1

rollno	name	marks	city
101	anil	78	Pune
102	bhumika	93	Mumbai
103	chetan	85	Mumbai
104	dhruv	96	Delhi
105	emanuel	92	Delhi
106	farah	82	Delhi

MySQL Views

A view is a virtual table based on the result-set of an SQL statement.

```
CREATE VIEW view1 AS  
SELECT rollno, name FROM student;  
  
SELECT * FROM view1;
```

*A view always shows up-to-date data. The database engine recreates the view, every time a user queries it.