Webhooks

telegram ↳ request → n8n.

pooling.
↳ request. ← bacha

Python → interpretor → Machine code.

Variable :- → It is a storage box
→ Changeable.

vary able
change.

var name = data.
assignment.



a = 25

a = 60.

datatype :-

→ int 2 5 9 0 -5 -6.
→ float 2.0 2.5 -11.25 0.25
→ str "abdul" or 'abdul' "ASBXR005"
→ bool True False.

2 → quotient
7) 14. → dividend.
14
divisor
0 → Remain.

7 % 14

15 % 7

7) 15 (2
14
1
Remainder.

x = 15

x >= 15
greater than or equal.

15 >= 15 (True)

age = 20
has_id = True

not (age >= 18)
20 >= 18 ⇒ True
False.

age >= 18 and has_id == True.

20 >= 18 and True == True.
True and True ⇒ True.
True

True and True ⇒ True.
True and False ⇒ False
False and True ⇒ False
False and False ⇒ False.

a = 90
b = 60
c = 40.

a == b or b > c

90 == 60

90 == 60 or 60 > 40.
False or True. ⇒ True.

T or T ⇒ T
T or F ⇒ T
F or T ⇒ T
F or F ⇒ False

age 16

not

5

```
age= int(input ("Enter the age!"))

if age>=18 :
    print ("You are adult")

elif age>=50:
    print (" You are old")

else:
    print(" You are a child")
```

```
print(" Put milk in")
print( "Put sugar in")
print ( "Put tealeaves in")
```

↳ loops
↳ for , while.

→ things that remain same → hardcode

→ things that change. → variable.

ingredient tealeaves

for loop

```
① ③ ⑤ for ingredient in "milk", "sugar", "tealeaves":
  ⑥ ② ④ print ("Put ", ingredient, "in")
```

Put milk in.

Put sugar in

Put tealeaves in