



NOTE (S):

1-REFER P&ID 3563-R-DB-0000-002 FOR LEGENDAND GENERAL NOTES

2-ALL CONNECTIONS FROM THE TOP OF HEADER

3-MANHOLE EXTENDED OUTSIDE THE EARTH MOUND

4-VESSELS WITH 1.0M MIN. EARTH MOUNDING

5-VORTEX BREAKER SHOULD BE INSTALLED.

6-NOZZLE N2 WILL BE EXTENDED OUTSIDE THE EARTH MOUND HORIZONTALLY AND THEN VALVES WILL BE INSTALLED FOR ISOLATION AND DRAIN.

7-NOZZLE N8 WILL BE EXTENDED INSIDE THE VESSEL.

8-SPRING LOADED BALL VALVE WITH 90° ROTATION.

12

22.12.16

GLG ADDED

MHS

SMM

IS

14

17.12.03

SECOND AS BUILT

MAA

IU

SNR

11

3.7.2K

FIRST AS BUILT

MIM

IU

SNR

10

06-12-99

AS BUILT

YM

ZM

IA

9

09-02-99

AS MARKED

YM

ZM

MH

8

06-02-99

AS MARKED

YM

ZM

MH

REV

DATE

DESCRIPTION

INIT. SIGN BY

INIT. SIGN CHK'D

INIT. SIGN APP'VD

REVISIONS

UNAUTHORIZED REPRODUCTION OF ANY KIND IS PROHIBITED; ALL RIGHTS ARE RESERVED BY DESCON ENGINEERING LIMITED, LAHORE, PAKISTAN

DESCON

DESCON ENGINEERING LTD.

P.O. BOX 1201, LAHORE 54000, PAKISTAN

CLIENT

ENGRO

ENGRO PAKTANK

TERMINAL LTD.