


hassan.mohyuddin@lums.edu.pk
Syed Babar Ali School of Science and Engineering, LUMS, Pakistan
©This is a proprietary document and may not be copied, shared, or distributed without the author's consent.

About the Cover Image

The cover image presents artificial intelligence as a journey from foundational knowledge to purposeful innovation. The luminous human profile, interwoven with neural networks, mathematical symbols, logical structures, and computational pathways, represents the union of human reasoning and machine intelligence. The open book symbolizes scholarship and the enduring intellectual foundations of the field, while the ascending staircase suggests progressive learning – from data representation, probability, optimization, and algorithms to machine learning, evaluation, deployment, and responsible decision-making. The networked tree signifies the growth of knowledge, the interconnectedness of AI disciplines, and the emergence of increasingly sophisticated systems from fundamental principles. Together, these elements reflect the central philosophy of this course is not merely a collection of algorithms, but a complete, evolving discipline grounded in mathematics, data, computation, judgment, ethics, and real-world application.


Disclaimer

In the compilation of this document, I have utilized GPT-based tools, including ChatGPT 5.6 Sol, to assist with the generation of cover and module images, schematics, flowcharts, infographics, tables, workflows, and synthetic examples, as well as with the identification and synthesis of published references, historical information, and other relevant background material. These tools were also used to support the organization, refinement, and presentation of the material. All generated content and references were reviewed, edited, and, where appropriate/possible, independently verified by the author. Nevertheless, errors, omissions, or inaccuracies may remain, and I would be grateful to readers for identifying and bringing any such issues to my attention so that they may be corrected in future revisions.

I do not harbor unbridled enthusiasm or fascination of AI. I firmly believe that technology should remain *semi-autonomous* i.e., operating under informed judgment, ethical oversight, and deliberate control of a wise human mind. In this spirit, AI is treated here as a supportive tool rather than a substitute for human reasoning, creativity, or responsibility.

About the Instructor

Dr. Hassan Mohy-ud-Din is the Director of Algorithms in Theory and Practice Lab and an Assistant Professor of Electrical Engineering, Syed Babar Ali School of Science and Engineering, LUMS. He completed his PhD and MSE in Electrical and Computer Engineering and MA in Applied Mathematics and Statistics from Johns Hopkins University (2009 – 2015). He was recipient of PhD Fellowship from Johns Hopkins University. From 2015 – 2017 he was a postdoctoral associate in the Department of Radiology and Biomedical Imaging at the Yale School of Medicine. From 2017 – 2018 he was a Clinical Research Scientist at Shaukat Khanum Memorial Cancer Hospital and Research Centre, Lahore, Pakistan. His research is at the intersection of applied mathematics and clinical imaging – exploiting tools in machine learning, optimization, statistics, and information theory to develop novel algorithms for clinical and translational imaging. He has done extensive research in multimodality imaging including PET/CT, SPECT/CT, PET/MR, Low-dose CT, and multiparametric MRI and developed computational pipelines for brain imaging, cardiac imaging, and abdominal imaging. His work on dynamic cardiac PET imaging won the 2014 SNMMI Bradley-Alavi fellowship and the 2014 SIAM student award. He is also a recipient of the 2019 Charles Wallace Fellowship from the British Council, Pakistan. He also serves as a reviewer on major scientific journals and a member of IEEE and SIAM societies. He carries a university teaching experience of over fifteen years (including five years at Johns Hopkins University) and is deeply interested in the development, implementation, and evaluation of (pragmatic and effective) pedagogical approaches in schools, colleges, and universities.



hassan.mohyuddin@lums.edu.pk
Syed Babar Ali School of Science and Engineering, LUMS, Pakistan
©This is a proprietary document and may not be copied, shared, or distributed without the author's consent.

Historical and Philosophical Roots

Although today's discussions of artificial intelligence (AI) are dominated by deep learning (DL), large language models (LLMs), and generative AI (GenAI), these technologies **represent only the latest chapter in a much longer intellectual history**. To understand AI as a field, it is important to distinguish between its current methods and its enduring questions.

Long before neural networks were trained on billions of examples, mathematicians, philosophers, engineers, psychologists, linguists, economists, and computer scientists were asking **whether intelligence itself could be understood in formal terms**. If thinking follows **discoverable principles**, could those principles be **expressed as rules**, **symbols**, **probabilities**, **algorithms**, or **mathematical models**? If so, might a machine be able to perform some of the same intellectual tasks as a human?

The history of AI is therefore not simply a history of increasingly powerful computers. It is the history of successive attempts to formalize intelligence – each contributing concepts that continue to shape modern AI, even when the underlying technologies have changed.

Modern AI is often associated with neural networks, massive datasets, specialized hardware such as Graphics Processing Units (GPUs), and generative models. Its intellectual roots, however, are much older and emerge from several intersecting traditions including:

- formal logic and the mechanization of reasoning;
- probability and statistical inference;
- computation and algorithms;
- information theory;
- control and feedback;
- cognitive science and theories of intelligence;
- operations research and optimization;
- philosophy of mind, language, knowledge, and agency.

AI is therefore not a single invention. It is the convergence of multiple attempts to answer a deeper question:

Can perception, reasoning, learning, decision-making, and intelligent action be represented sufficiently precisely to be carried out by a machine?

1.1.1 From formal reasoning to machine intelligence

Logic and the possibility of mechanized reasoning

One historical root of AI is the idea that **valid reasoning can be represented through formal symbols and rules**. Once an argument is formalized, it becomes possible to ask whether its steps can be executed mechanically.

This tradition ultimately influenced symbolic AI, theorem proving, planning, expert systems, knowledge representation, and logic programming. The **underlying philosophical position** is that at least **some forms of intelligence** can be understood as **operations over structured representations**. This idea remains visible in contemporary systems:

- a search algorithm explores a formal state space;
- a planner applies operators to move from an initial state to a goal;
- a knowledge graph represents entities and relations;
- a rule engine applies explicit conditions;
- a probabilistic graphical model expresses conditional dependencies;
- a language model manipulates learned representations rather than hand-written logical symbols.

The important lesson is that **intelligence requires representation**. A machine **cannot reason directly about an unrepresented world**[1]. It reasons over variables, symbols, vectors, tokens, states, graphs, probabilities, or other

[1] A **world model** is an internal representation of **how an environment works** that enables an **intelligent agent** to **understand**, **predict**, and **reason** about the consequences of its actions. Instead of relying solely on direct trial and error, a world model learns the **structure and dynamics of the surrounding world**, allowing it to **simulate future states**, **anticipate outcomes**, and **support planning** and **decision-making**. In AI, world models are commonly learned from data and are used in areas such as reinforcement learning, robotics, autonomous systems, and generative AI to improve efficiency and adaptability.

The concept of world models has roots in cognitive science and psychology, where researchers proposed that **humans and animals maintain internal mental models of the world**. A major early influence was **Kenneth Craik**, who introduced the idea of **internal mental models** in his **1943 book The Nature of Explanation**. In AI, the term gained widespread recognition through the **2018 paper World Models** by **David Ha** and **Jürgen Schmidhuber**, published as an arXiv preprint on **2018**. Their work demonstrated how a neural network could learn a compressed model of an environment and use it to train an agent efficiently within a simulated world, making the paper a foundational milestone in modern model-based AI research.

constructed representations. The Stanford Encyclopedia of Philosophy's overview of AI traces this connection among logic, computation, knowledge representation, search, learning, and philosophical theories of mind[2].

Symbolic Program

To understand what a symbolic program is, it helps to contrast it with a **numerical program**. A standard calculator or a neural network primarily manipulates continuous numbers and statistical weights. A symbolic program, on the other hand, **manipulates discrete symbols**, **logical structures**, and **explicit rules** to perform reasoning. It **does not *understand* the physical world**; it only understands the representations it has been given. Here are three concrete examples of symbolic programs:

Example # 1: Logic Programming (e.g., Prolog[3])

Prolog is the classic historical example of symbolic AI. It **represents knowledge as formal facts and logical rules**, and the **program** (**Figure 1**) is simply a query that the system must **mechanically prove**.

```
% 1. KNOWLEDGE REPRESENTATION (Facts)
parent(tom, bob).
parent(tom, liz).
parent(bob, ann).

% 2. FORMAL RULES (Logic)
% "X is a grandparent of Y IF X is a parent of Z AND Z is a parent of Y."
grandparent(X, Y) :- parent(X, Z), parent(Z, Y).

% 3. MECHANIZED REASONING (The Query)
% ?- grandparent(tom, ann).
```

Figure 1: A Prolog code snippet illustrating the core components of symbolic AI: Knowledge Representation (facts), Formal Rules (logic), and Mechanized Reasoning (queries). Each fact has the form: parent(Parent, Child). The symbol :- means "is true if". ?- tells Prolog "can you prove this". Prolog has no stored grandparent(tom, ann) fact; it derives that conclusion from stored facts and a rule.

[2] Selmer Bringsjord and Naveen Sundar Govindarajulu, *Artificial Intelligence*, Stanford Encyclopedia of Philosophy, 2018.

[3] **Prolog** (short for **PROgramming in LOGic**) is a logic programming language and one of the classic examples of **symbolic AI**, where knowledge is represented as facts and rules, and conclusions are derived through logical inference. It was developed in **1972** by French computer scientist **Alain Colmerauer** and **Philippe Roussel** with important theoretical contributions from **Robert Kowalski**. Prolog became a foundational language for AI research, particularly in expert systems, natural language processing, and automated reasoning.

The machine does not know who "Tom" or "Ann" is. It **simply searches** its **formal state space**, matches the symbols against the explicit rules, and mechanically deduces that the query is True.

Example # 2: An Expert System or Rule Engine (e.g., Python[4])

Expert systems were a massive branch of 1980s symbolic AI. They **separate** the **knowledge (the rules)** from the **reasoning engine (the code that applies them)**. Figure 2 shows a simple symbolic rule engine for medical diagnosis:

```python
# 1. KNOWLEDGE REPRESENTATION (Symbols representing the world)
patient_symptoms = {"fever", "cough", "fatigue"}

# 2. EXPLICIT CONDITIONS (The rules)
medical_rules = [
    {"if": {"fever", "cough", "shortness_of_breath"}, "then": "Pneumonia"},
    {"if": {"fever", "cough", "fatigue"}, "then": "Flu"},
    {"if": {"runny_nose", "sneezing"}, "then": "Allergies"}
]

# 3. THE REASONING ENGINE (Mechanized execution)
def diagnose(symptoms, rules):
    for rule in rules:
        # The machine mechanically checks if the explicit conditions are met
        if rule["if"].issubset(symptoms):
            return rule["then"]
    return "Unknown condition"

# Execution
print(diagnose(patient_symptoms, medical_rules))
# Output: Flu
```

Figure 2: A Python code snippet illustrating a symbolic rule engine (expert system). It demonstrates the separation of knowledge representation (symptoms as sets), explicit conditions (if-then rules), and the reasoning engine (mechanical execution via subset checking) to deduce a diagnosis. Instead of storing a sentence, the program stores the symptoms as a set. A Python set is useful because order does not matter, duplicate values aren't allowed, and checking membership is very fast. The medical rules are written by humans. The computer **does not discover** these relationships. It simply follows them. Reasoning engine is also referred to as the inference engine. Its job is to compare the patient's symptoms with every rule. The program will exit if it already found a matching diagnosis.

[4] **Python** is a high-level, interpreted programming language known for its simple, readable syntax and wide range of applications, including web development, data analysis, automation, and artificial intelligence. It was created by **Guido van Rossum** and was first released on **February 20, 1991**.

The program reasons over the **constructed representation** (the **set of symptoms**). It applies **explicit conditions** to move from an **initial state** (symptoms) to a **goal state** (a diagnosis).

Example # 3: Symbolic Mathematics and Theorem Proving (e.g., SymPy[5]*)*
Unlike standard math libraries that just crunch numbers (e.g., calculating that $2.5 \times 2.5 = 6.25$), symbolic math libraries **manipulate the algebraic symbols** themselves to prove theorems (**Figure 3**).

```python
import sympy as sp

# 1. Define symbols (Variables, not numbers)
x, y = sp.symbols('x y')

# 2. Construct symbolic expressions
expr1 = (x + y)**2
expr2 = x**2 + 2*x*y + y**2

# 3. MECHANIZED THEOREM PROVING
# To prove expr1 == expr2, the system mechanically simplifies their difference.
proof = sp.simplify(expr1 - expr2)

print(proof)
# Output: 0
```

Figure 3: A Python code snippet using the SymPy library illustrating symbolic mathematics and mechanized theorem proving. It demonstrates defining abstract symbols (variables), constructing symbolic expressions, and mechanically simplifying their difference to prove algebraic equivalence (resulting in 0). SymPy can work with unknown variables. It creates mathematical objects representing variables. SymPy performs algebraic transformations automatically. The computer ***does not understand*** the theorem like a mathematician. Instead, it has rules for manipulating mathematical expressions and checks whether both sides reduce to the same canonical form.

The system applies **formal algebraic rules** (like the **distributive property**) to manipulate the symbols. Because the final representation evaluates to 0, the system has mechanically proven that the two expressions are logically equivalent.

[5] **SymPy** is an open-source Python library for symbolic mathematics that allows users to perform algebra, calculus, equation solving, and other mathematical computations exactly rather than approximately. SymPy was started by **Ondřej Čertík** in **2006**; **Aaron Meurer** subsequently became a major developer and project leader.

In all of these examples, the machine is not learning patterns from data like a modern language model. Instead, **intelligence is strictly bounded by the representation**. If you do not provide the symbol, the fact, or the rule, the machine cannot reason about it. This perfectly illustrates the philosophical lesson of symbolic AI: *reasoning is just computation over structured representations*.

Probability and the problem of uncertain knowledge

Formal logic is powerful when **propositions and rules** are **known with certainty**. Real environments, however, contain noise, ambiguity, incomplete observations, measurement error, and changing conditions.

Probability theory[6] provided a **language for reasoning** when **certainty is unavailable**. Statistical inference[7] later supplied methods for learning from finite samples and distinguishing observed patterns from population-level claims[8].

Example # 4: Diagnosing a medical condition from symptoms

Imagine a doctor trying to determine whether a patient has a particular disease. **In a world of perfect certainty, formal logic would be enough**: *If symptom A and symptom B are present, then the patient has disease X*. The **rules would be fixed**, the **observations would be accurate**, and the **conclusion would always follow**.

In reality, medicine is rarely that simple. Symptoms can be caused by many different conditions, patients may not report every symptom, tests can

[6] **Probability** is the branch of mathematics that deals with **measuring and predicting the likelihood of events** occurring under **conditions of uncertainty**. It starts with a known model or set of assumptions and determines the chances of possible outcomes. For example, probability can be used to calculate the chance of getting a particular result when rolling a die or the likelihood of a future event based on known patterns.

[7] **Statistical inference** uses data from a sample to make conclusions, predictions, or decisions about a larger population. **Unlike probability, which moves from assumptions to outcomes**, statistical inference works in the opposite direction by **using observed data to estimate unknown parameters**, **test hypotheses**, or **build models about the population**. For example, it can be used to estimate the average height of a population by studying a smaller sample of individuals.

[8] Distinguishing observed patterns from population-level claims is an important concept in statistical reasoning. An **observed pattern** refers to a **trend**, **relationship**, or **result** found within the **specific data that has been collected**, while a **population-level claim** extends that conclusion **beyond the sample to a larger group**. Because samples **may not perfectly represent the populations they come from**, statistical inference is needed to determine whether an observed pattern is likely to reflect a true underlying effect or could have occurred due to random variation. Careful analysis helps avoid overgeneralizing sample findings and ensures that conclusions are supported by appropriate evidence.

produce false positives or false negatives, and diseases can vary across individuals. The **doctor must reason with uncertainty**: *Given the symptoms, test results, and patient history, **how likely is it** that this person has the disease?*

Probability theory provides the language for expressing this uncertainty – for example, estimating that a patient has an 80% chance of having a condition given the available evidence. **Statistical inference then helps doctors learn from data collected across thousands of patients**: *Does this test reliably predict the disease? How accurate is it in the broader population?*

This introduced a different conception of intelligence:

- not merely applying known rules;
- but learning uncertain relationships from evidence;
- updating beliefs when new information becomes available;
- quantifying confidence;
- and selecting actions under risk.

Modern machine learning inherits much of this statistical foundation. **Parameters are estimated from data**, **models are evaluated on samples**, and **predictions are understood as uncertain statements** rather than infallible facts.

Control, feedback, and cybernetics

Norbert Wiener's *Cybernetics*[9] connected **communication**, **feedback**, and **control** in animals and machines. In a **feedback system**, the **consequences of previous actions** are observed and used to **modify future behavior**. This was a foundational step toward thinking about intelligent systems as **dynamic**, **adaptive**, and **embedded** in environments rather than as isolated calculators. Examples of feedback-oriented intelligence include:

- a thermostat correcting temperature deviations;

[9] Norbert Wiener, *Cybernetics or Control and Communication in the Animal and the Machine*, MIT Press, 2019. *originally published in 1948; MIT Press open-access edition/reissue, 2019*.

Cybernetics is the interdisciplinary study of communication, control, and feedback systems in machines, living organisms, and social systems. It was introduced as a formal field by **Norbert Wiener**, who defined it as the study of *control and communication in the animal and the machine*. The term and field were developed in his book Cybernetics: Or Control and Communication in the Animal and the Machine, published in **1948**.

- a robot adjusting movement after observing its position;
- a recommendation system learning from user interaction;
- a fraud system changing thresholds after new attacks;
- a medical monitoring system updating risk as measurements arrive;
- a reinforcement-learning agent adapting its policy through rewards.

Feedback also creates risks. Once predictions influence the environment, future training data may partly reflect the system's earlier decisions. This can produce **self-reinforcing bias**, **selective labels**, **performative effects**, and **feedback loops**.

Example # 5: Predictive policing and self-reinforcing crime data

Imagine a police department uses a machine-learning system to **predict areas where crimes are most likely to occur**. The system is trained on historical crime reports and concludes that certain neighborhoods have a higher risk of crime. Police then increase patrols in those areas.

Because there are more officers present, more minor incidents are detected and recorded in those neighborhoods. The new data now shows even higher crime activity there, so the system learns that its original prediction was correct. The cycle continues:

- Historical data suggests a neighborhood is high-risk.
- The system sends more resources there.
- Increased observation produces more recorded incidents.
- The new data reinforces the original prediction.
- The model becomes increasingly confident in the same pattern.

The problem is that the **data no longer represents only the underlying level of crime**; it **also reflects the system's previous decisions** about where to look. The **model has changed the environment** it is trying to predict. This illustrates several risks of feedback:

- **Self-reinforcing bias:** Existing patterns in historical data become amplified over time.
- **Selective labels:** The system only observes outcomes in places or cases where attention was directed, not the full reality.

- **Performative effects:** A prediction influences behavior and creates conditions that make the prediction appear accurate.
- **Feedback loops:** The output of one prediction becomes part of the input for future predictions, potentially locking the system into a harmful cycle.

The broader lesson is that **intelligent systems are not passive observers**. When their **predictions affect human decisions and environments**, they **become participants in the system they are modeling**. Good AI design must therefore consider not only whether predictions are accurate, but also **how those predictions reshape future data and outcomes**.

Information as a mathematical object

Claude Shannon's[10] 1948 theory of communication **formalized information**, **uncertainty**, **coding**, and **transmission**. Although information theory is not identical to AI, it supplied concepts that now appear throughout machine learning, including **entropy**, **cross-entropy**, **mutual information**, **compression**, **channel capacity**, and **noisy communication**.

A profound consequence was that **information could be measured and manipulated mathematically**. Images, speech, text, sensor readings, and biological signals could all be **encoded and processed as data**. Yet an important philosophical distinction remains:

Information is not automatically meaning.

A dataset may contain billions of values while failing to represent the phenomenon of interest. **Meaning depends** on how variables were **defined**, **measured**, **collected**, **labeled**, and **interpreted**.

Example # 6: Teaching an AI system to recognize emotions from facial images

Suppose researchers want to build an AI system that can identify whether a person is happy, sad, or angry from a photograph. **Modern information theory allows the image to be represented mathematically**: millions of pixel values can be **encoded**, **compressed**, **transmitted**, and **processed by a computer**.

[10] **Claude Shannon** was an American mathematician and electrical engineer who developed information theory in his landmark **1948** paper, *A Mathematical Theory of Communication*. His work provided a mathematical framework for understanding information, uncertainty, coding, and the efficient transmission of messages, forming the foundation of modern digital communication and data science.

The image becomes a **structured collection of numbers** that a machine-learning model can analyze.

However, the numbers themselves do not contain meaning. A pixel value does not inherently represent *happiness* or *sadness*. **Meaning comes from the way the data was created**:

- How were emotions defined?
- Who labeled the images?
- Were the labels based on genuine feelings, facial expressions, or human judgments?
- Did the dataset include diverse cultures, ages, lighting conditions, and contexts?

For example, if an AI system is trained mostly on images where smiling faces are labeled as *happy*, it may learn that a smile equals happiness. But a **smile** can also represent **politeness**, **nervousness**, **discomfort**, or **social expectation**. The model may achieve high accuracy on its dataset while misunderstanding the actual phenomenon of human emotion. This illustrates the distinction:

- **Information theory:** The image can be represented as measurable information (pixels, patterns, signals).
- **Machine learning:** The model can find statistical relationships in that information.
- **Meaning:** Requires understanding what the variables actually represent in the real world.

A large dataset may contain **enormous amounts of information**, but **without careful definitions**, **measurements**, and **interpretation**, it may encode patterns that are precise yet misleading. The challenge of AI is therefore not only processing information but **ensuring that the information corresponds to meaningful aspects of reality**.

1.1.2 Turing and the operational question of intelligence

In 1950, Alan Turing[11,12,13,14,15,16,17,18] reframed the vague question **Can machines think?** into an **operational test** based on **observable interaction**. Rather than first settling the metaphysical definition of thinking[19,20,21], Turing asked whether a **machine's conversational performance** could become **indistinguishable** from that of a person under specified conditions. This move remains influential because AI evaluation is still often operational:

- Can the system classify correctly?
- Can it solve a planning problem?
- Can it answer questions?
- Can it generate coherent text?
- Can it control a vehicle?
- Can it recommend useful items?
- Can it outperform a reference baseline?

However, behavioral success does not settle deeper philosophical questions:

- Does the system understand?
- Is it merely reproducing statistical regularities? [22]
- Does intelligence require consciousness? [23]
- Can linguistic performance be separated from grounding in the world?

---

[11] Graham Oppy and David Dowe, The Turing Test, Stanford Encyclopedia of Philosophy, 2021.

[12] Cameron R. Jones and Benjamin K. Bergen, Large Language Models Pass the Turing Test, arXiv, 2025.

[13] Ricardo Restrepo Echavarría, ChatGPT-4 in the Turing Test, Minds and Machines, 2025.

[14] Tim Bayne and Iwan Williams, The Turing test is not a good benchmark for thought in LLMs, Nature Human Behaviour, 2023.

[15] Bernardo Goncalves, In Defense of the Turing Test and its Legacy, arXiv, 2025.

[16] Bernardo Goncalves, Can machines think? The controversy that led to the Turing test, AI and Society, 2023.

[17] Georgios Mappouras, Turing Test 2.0: The General Intelligence Threshold, arXiv, 2025.

[18] Bernardo Goncalves, The Turing Test Argument, Routledge, 2023.

[19] The **metaphysical definition of thinking** determines whether AI can ever truly think or merely simulate thought. If **thinking is defined functionally** as information processing, symbol manipulation, or computational reasoning, then machines that perform these operations are genuinely thinking. However, if **thinking is defined as requiring subjective conscious experience** (*qualia*), immaterial substance, or existential *being-in-the-world*, then **no amount of computational sophistication can produce genuine thought – only the appearance of it**. This distinction is not merely academic; it has profound practical implications for AI ethics, legal responsibility, and the attribution of rights to artificial systems.

[20] John Searle, Minds, Brains, and Programs, Behavioral and Brain Sciences, 1980.

[21] Hubert Dreyfus, What Computers Still Can't Do: A Critique of Artificial Reason, MIT Press, 1992.

[22] Emily M. Bender, Timnit Gebru, Angelina McMillan-Major, and Margaret Mitchell, On the Dangers of Stochastic Parrots: Can Language Models Be Too Big? Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency, 2021.

[23] David Chalmers, The Conscious Mind: In Search of a Fundamental Theory, Oxford University Press, 1996.

- Should human-like behavior be the standard for machine intelligence?

These questions distinguish **engineering tests of capability** from **philosophical claims about mind and understanding**.

1.1.3 The Dartmouth proposal and the naming of AI

The 1955 proposal for the 1956 Dartmouth Summer Research Project[24] used the term artificial intelligence and proposed studying whether aspects of learning and intelligence could be described precisely enough for machines to simulate them. Its themes included **language**, **abstraction**, **problem solving**, **self-improvement**, and **neural mechanisms**.

The proposal reflected considerable optimism: **intelligence was treated as an object** that might be **decomposed into computationally manageable components**. The workshop helped consolidate, name, and legitimize these research traditions:

- symbolic reasoning;
- search and planning;
- machine learning;
- natural-language processing;
- computer vision;
- robotics;
- knowledge representation;
- automated theorem proving.

1.1.4 Symbolic AI, statistical learning, and modern hybrids

The symbolic view

Symbolic AI represents knowledge explicitly through symbols, rules, logical statements, or structured states. Newell and Simon argued that physical symbol systems were central to intelligent action[25]. Symbolic approaches

[24] John McCarthy, Marvin L. Minsky, Nathaniel Rochester, and Claude E. Shannon, A Proposal for the Dartmouth Summer Research Project on Artificial Intelligence: August 31, 1955, AI Magazine, 2006.

[25] Allen Newell and Herbert A. Simon, Computer science as empirical inquiry: symbols and search, Communications of the ACM, Volume 19, Issue 3, 1976.

were particularly influential in theorem proving, game playing, planning, and expert systems. Their strengths include:

- explicit representations;
- inspectable reasoning chains;
- incorporation of domain rules;
- compositional structures;
- strong performance when the state space and rules are well specified.

Their limitations include:

- difficulty acquiring and maintaining knowledge;
- brittleness under ambiguity;
- poor handling of noisy perception;
- combinatorial explosion;
- dependence on manually encoded representations.

Example # 7: A self-driving car approaching a busy intersection

Suppose we try to build the car using only a symbolic AI system. The system relies on explicit rules such as:

- **IF** the traffic light is green **THEN** proceed.
- **IF** a pedestrian is in the crosswalk **THEN** stop.
- **IF** the vehicle ahead is braking **THEN** reduce speed.

At first glance, these rules seem sufficient. However, real-world situations quickly expose the limitations of the symbolic approach.

- **Difficulty acquiring and maintaining knowledge:** Thousands of rules would be needed to cover unusual situations, such as construction zones, emergency vehicles, or pedestrians behaving unpredictably. Continuously updating this rule base is costly and error-prone.
- **Brittleness under ambiguity:** Imagine a pedestrian standing on the curb and looking at their phone. Are they about to cross or simply waiting? A symbolic system requires a clear symbolic state ("crossing" or "not crossing"), but reality is ambiguous.
- **Poor handling of noisy perception:** Rain, fog, glare, or partially occluded traffic signs can make sensor data unreliable. If the perception module incorrectly identifies a stop sign as a speed-limit sign, the symbolic

reasoning process begins with incorrect symbols and may produce dangerous decisions.

- **Combinatorial explosion:** The number of possible combinations of road conditions, weather, traffic density, pedestrian behavior, and vehicle interactions grows exponentially. Writing rules for every possible combination becomes infeasible.
- **Dependence on manually encoded representations:** Engineers must explicitly define concepts such as "safe following distance," "aggressive driver," or "hazardous road condition." These concepts vary with context and are difficult to capture completely using hand-crafted symbolic representations.

This example illustrates why **purely symbolic AI struggles in complex, uncertain environments**. Modern autonomous vehicles therefore combine symbolic reasoning with machine learning. Deep learning models interpret noisy sensor data (e.g., recognizing pedestrians and traffic signs), while symbolic or rule-based components enforce traffic laws, safety constraints, and high-level planning. This **hybrid approach** leverages the **strengths of both paradigms** while **mitigating the limitations** of a purely symbolic view.

The statistical view

Statistical machine learning instead **learns relationships from examples**. Rather than programming every rule, a developer specifies a **model class**, **objective**, **data representation**, and **training procedure**. Its strengths include:

- learning from high-dimensional observations;
- tolerance of noisy inputs;
- adaptation from examples;
- strong performance in perception, prediction, and generation.

Their limitations include:

- dependence on data quality;
- limited causal interpretation;
- potential opacity;
- vulnerability to distribution shift;
- difficulty guaranteeing behavior outside the observed data regime.

Example # 8: AI-assisted pneumonia diagnosis

A hospital trains a deep learning model on hundreds of thousands of labeled chest X-ray images. The model achieves **98% accuracy** on the test data and appears ready for deployment. However, when it is **used in a different hospital**, several limitations of the statistical approach become apparent.

- **Dependence on data quality:** If the training data contains mislabeled X-rays or underrepresents certain patient groups (e.g., children or elderly patients), the model learns incorrect or biased patterns, reducing its reliability.
- **Limited causal interpretation:** The model may learn that portable X-rays are strongly associated with pneumonia because severely ill patients are more likely to receive portable scans. It predicts based on this correlation, not because it understands the medical cause of pneumonia.
- **Potential opacity:** When the AI predicts that a patient has pneumonia, it may simply output a probability (e.g., 97%) without a clear explanation of which medical features led to the decision. Physicians may find it difficult to trust or verify the prediction.
- **Vulnerability to distribution shift:** The model was trained using images from one hospital's equipment. When deployed in another hospital with different X-ray machines, imaging protocols, or patient demographics, its accuracy drops because the new data differs from the training distribution.
- **Difficulty guaranteeing behavior outside the observed data regime:** Suppose a new respiratory disease emerges or a rare lung condition appears that was absent from the training data. Since the model has never encountered such cases, its predictions may become unreliable or even dangerously incorrect.

This example shows that **although statistical machine learning excels** at learning complex patterns from large datasets, it **does not inherently understand** why those patterns exist or how to reason about situations beyond its training experience. As a result, modern AI systems increasingly **combine statistical learning** with **causal reasoning**, **domain knowledge**, **uncertainty estimation**, and **rule-based**

safeguards to improve **robustness**[26], **interpretability**[27], and **reliability**[28] in real-world applications.

Contemporary AI is often hybrid

Modern systems frequently combine:

- learned perception with rule-based constraints;
- neural representations with search;
- language models with retrieval;
- statistical prediction with optimization;
- learned policies with safety controllers;
- machine-generated recommendations with human review.

Therefore, **symbolic versus statistical** should not be treated as a permanent binary. The practical question is which **representations** and **computational mechanisms** are appropriate for the task.

Example # 9: An autonomous warehouse robot

A robot in a fulfillment center receives an order to pick up a package from Shelf A and deliver it to the shipping area. **No single AI approach is sufficient to perform this task reliably**. The robot combines several AI techniques:

- **Learned perception:** A deep learning model identifies shelves, packages, barcodes, and people from camera images, even under varying lighting conditions.
- **Rule-based constraints:** The robot follows explicit safety rules such as *never exceed the speed limit*, *always stop for a person*, and *do not enter restricted zones*.
- **Neural representations with search:** A neural network estimates traversable paths and obstacles, while a search algorithm computes the shortest safe route to the destination.

[26] **Robustness** refers to a system's ability to **maintain acceptable performance** when exposed to **unexpected perturbations**, **noise**, **distribution shifts**, or **adversarial inputs**, distinguishing it from reliability by emphasizing **resilience under challenging** or **changing conditions** rather than consistent operation under expected conditions.

[27] **Interpretability** measures the degree to which a **human can understand** the **internal logic**, **decision process**, or **factors** influencing a system's outputs, distinguishing it from related concepts by **focusing on cognitive transparency** and **human comprehensibility** rather than solely on **operational performance**.

[28] **Reliability** refers to a system's ability to **consistently perform** its **intended function accurately** and **dependably** over time **under expected operating conditions**, distinguishing it from robustness by emphasizing sustained performance during normal operation rather than resilience against unexpected perturbations, failures, or adversarial conditions.

- **Language models with retrieval:** If a worker asks, *where is item X?*, a language model answers using information retrieved from the warehouse inventory database, ensuring the response reflects the latest stock information.
- **Statistical prediction with optimization:** The system predicts future warehouse traffic based on historical data and optimizes the robot's route to minimize delivery time while avoiding congestion.
- **Learned policies with safety controllers:** A reinforcement learning policy determines smooth navigation actions, but an independent safety controller overrides those actions whenever a collision risk is detected.
- **Machine-generated recommendations with human review:** If the robot encounters a damaged package, it recommends whether to discard or inspect it, but a human supervisor makes the final decision.

This example illustrates that **neither symbolic AI nor statistical machine learning alone is sufficient**.

- A **purely symbolic system** would struggle to recognize objects and interpret noisy camera images.
- A **purely statistical system** might recognize objects well but could violate safety rules or make unpredictable decisions in unfamiliar situations.

By combining **learning-based methods for perception** with **symbolic reasoning**, **search**, **optimization**, **safety rules**, and **human oversight**, the robot becomes more **accurate**, **reliable**, and **trustworthy**.

Hence, the **most effective AI systems** are often **hybrid systems**, integrating **multiple computational approaches** so that **each compensates for the limitations** of the others. Consequently, the practical question is not whether an AI system should be symbolic or statistical, but which **combination of representations and computational mechanisms** best fits the problem being solved.

Four Central Philosophical Questions for AI

The development of artificial intelligence raises questions that are **not only technical** but **also philosophical**. These questions concern the **nature of intelligence**, the **relationship between prediction and understanding**, the **role of social and physical contexts** in shaping intelligent behavior, and the **allocation of responsibility** for AI-assisted decisions. Addressing these issues helps clarify both the capabilities and the limitations of AI systems while providing a **foundation for responsible research**[29], **deployment**[30], and **governance**[31]. The following four questions highlight some of the most influential philosophical debates that continue to shape the theory and practice of artificial intelligence.

1.2.1 What counts as intelligence? Defining artificial intelligence remains one of the most enduring challenges in computer science and philosophy, precisely because **intelligence** is **not a monolithic trait** but a **multifaceted spectrum of capabilities**. Rather than relying on a single, rigid criterion, researchers and practitioners often characterize AI by the specific **functional capacities** a system demonstrates. When attempting to articulate what it means for a machine to exhibit intelligence, the most practical approach is to identify the **discrete cognitive** or **operational tasks** it can perform. Possible answers include the ability to:

- reason correctly;
- learn from experience;
- solve unfamiliar problems;
- use language;
- form plans;
- act toward goals;
- adapt to changing conditions;

[29] **Responsible research** focuses on embedding **ethical considerations**, **safety protocols**, and **bias mitigation** into the **foundational design and development phases** of a technology, distinguishing it from deployment and governance by prioritizing the **intrinsic creation process** over real-world application or external regulation.

[30] **Responsible deployment** involves the **careful**, **monitored introduction** of a technology into real-world environments to ensure its actual use **aligns with intended benefits** and **minimizes harm**, distinguishing it from research and governance by focusing on **practical execution** and **user-facing impact** rather than initial creation or overarching policy.

[31] **Responsible governance** establishes the overarching **legal**, **institutional**, and **policy frameworks** that mandate **accountability** and set **boundaries for technological advancement**, distinguishing it from research and deployment by providing **external regulatory oversight** and **structural rules** rather than the hands-on creation or practical application of the technology.

- understand context;
- interact socially;
- create new artifacts.

No single definition covers every legitimate AI system. A route-planning algorithm, an anomaly detector, a surgical robot, and a language model exhibit different forms of computational competence.

1.2.2 Is successful prediction the same as understanding?

A system can achieve high predictive accuracy **without actually comprehending** the underlying **causal mechanisms** of the phenomena it models. Instead of identifying true **cause-and-effect relationships**, algorithms often exploit **statistical shortcuts**, **proxy variables**, **dataset artifacts**, or **historical regularities**. For instance, a model might predict a patient's disease risk based on hospital-specific administrative markers rather than actual biological pathology or forecast a student's academic success using **socioeconomic proxies** without understanding how a specific educational intervention would change the outcome. This reveals a fundamental distinction in computational reasoning:

- **Prediction** merely answers the question: *What is likely to happen?*
- **Causal reasoning**[32] addresses a deeper, **counterfactual inquiry**[33]: *What would happen if a specific intervention were applied?*

As Judea Pearl's[34] causal framework[35] demonstrates, establishing causal relationships requires explicit **structural assumptions**[36] and **mechanistic models**[37]. Because these causal structures generally **cannot be derived** from **observational associations** alone without additional assumptions or interventions, a system's ability to accurately predict an outcome does not

[32] **Causal reasoning** is the **analytical process** of identifying and evaluating **direct cause-and-effect relationships** to understand how specific actions actively produce changes in a system, rather than merely observing statistical correlations.

[33] **Counterfactual inquiry** is the analysis of **hypothetical scenarios** that ask what would have happened if circumstances or actions had been different.

[34] Judea Pearl, Causal inference in statistics: An overview, Statistical Surveys, Volume 3, pp 96 – 146, 2009.

[35] Victor Chernozhukov, Christian Hansen, Nathan Kallus, Martin Spindler, and Vasilis Syrgkanis, Applied Causal Inference Powered by ML and AI, arXiv, 2024.

[36] **Structural assumptions** are the **foundational theoretical constraints** that define the **directional pathways**, **dependencies**, and **underlying logic** connecting variables within a formal causal framework.

[37] **Mechanistic models** are mathematical or computational representations that explicitly map the underlying **physical**, **biological**, or **logical processes** and **interactions** that generate a system's observable outcomes.

necessarily imply that it understands the underlying causal processes that produced it.

Example # 10: Student attendance and exam performance

A university trains an AI model to predict whether students will pass a final exam. After analyzing several years of student data, the model finds that **students with high attendance are much more likely to pass** than those with low attendance. As a result, it predicts exam outcomes with high accuracy.

- From a **predictive standpoint**, the model is successful.
- However, does it truly understand **why** some students perform better?

Not necessarily. High attendance may simply be a **proxy** for other underlying factors, such as motivation, prior knowledge, effective study habits, or family support. The model has learned a **statistical relationship** but **not the causal mechanisms** behind academic success.

Now consider the following intervention: **What would happen if the university required every student to attend every lecture?**

A predictive model **cannot reliably answer this question**. Simply increasing attendance does not guarantee higher grades if students remain **disengaged**, **lack prerequisite knowledge**, or **do not study outside class**. The intervention may improve performance somewhat, but not to the extent suggested by the historical correlation.

In contrast, a causal analysis would investigate **whether attendance itself improves learning** or whether the **observed relationship is primarily explained by other factors**. This highlights the distinction:

- **Prediction:** *Students with high attendance are likely to pass the exam*.
- **Causal reasoning:** *If we increase a student's attendance, how much will their probability of passing actually improve?*

Accurate prediction identifies **who is likely to succeed**, whereas causal reasoning helps determine **which actions will actually improve success**. This distinction is crucial for making informed decisions in education and many other real-world domains.

Example # 11: Counterfactual inquiry, structural assumptions, mechanistic models

Counterfactual inquiry deals with *What would happen if…?* For instance,

- Would the patient have recovered faster if they had received Drug A instead of Drug B?
- Would crop yields have increased if farmers had used drip irrigation?
- Would the student have passed the exam if they had attended all lectures?
- Would traffic congestion decrease if a new subway line were introduced?
- Would carbon emissions fall if the city banned diesel vehicles?
- Would the company have made a profit if it had reduced prices by 10%?
- Would the wildfire have spread as rapidly if stronger firebreaks had been in place?
- Would crime rates decrease if street lighting were improved?

Structural assumptions deal with *assumptions about how variables are causally connected*. For instance,

- Smoking increases the risk of lung cancer.
- Rainfall influences crop production.
- Exercise improves cardiovascular health.
- Education affects future income.
- Vaccination reduces the probability of infection.
- Higher temperatures increase electricity demand.
- Poor air quality contributes to respiratory illness.
- Traffic volume affects travel time.

Mechanistic models explain *how a process works*. For instance,

- A weather model simulates how atmospheric pressure and temperature produce storms.
- A climate model simulates how greenhouse gases trap heat and warm the planet.
- A pharmacokinetic model describes how a drug is absorbed, distributed, metabolized, and eliminated.
- A cardiac model simulates how electrical impulses propagate through the heart.

- An epidemic model simulates how infectious diseases spread through a population.
- An economic model explains how supply and demand determine market prices.
- A combustion model describes how fuel reacts with oxygen to produce energy.
- A traffic flow model simulates how individual vehicle interactions lead to traffic congestion.

These examples highlight the distinction:

- **Counterfactual inquiry** asks *What if we changed something?*
- **Structural assumptions** specify *which variables directly influence others.*
- **Mechanistic models** explain *the underlying process by which those influences occur***.**

1.2.3 Can intelligence be separated from embodiment and society? While the mechanics of intelligence can be studied in the abstract, deployed AI systems inevitably operate within **complex physical** and **institutional environments**. Their outputs do not exist in a vacuum; rather, they are interpreted by **human users**, integrated into **existing workflows**, and bounded by **legal frameworks**, **resource constraints**, **social norms**, and **economic incentives**. Consequently, an AI system cannot be reduced to its underlying algorithm. It is most accurately understood as a socio-technical composite (Figure 4).




Figure 4: A socio-technical diagram illustrating that a deployed AI system is not merely an isolated algorithm, but an integrated composite of the Model, Data Infrastructure, Interface, Human Workflow, and Institutional Rules.

Example # 12: AI recruitment screening system

Suppose a company develops an AI model that ranks job applicants based on their resumes. The algorithm is trained on historical hiring data and achieves high accuracy in predicting which candidates are likely to be selected by recruiters. At first glance, the AI system appears to be only a mathematical model. However, its real-world impact depends on a much larger socio-technical system.

- **Model:** The AI uses machine learning to identify patterns associated with successful applicants.
- **Data infrastructure:** The training data may reflect past hiring decisions, including historical biases. If previous hiring favored certain universities, locations, or demographic groups, the AI may learn and reproduce those patterns.
- **Interface:** Recruiters interact with the AI through dashboards and ranking lists. The way results are displayed can influence whether humans critically evaluate recommendations or simply accept the AI's ranking.
- **Human workflow:** Hiring managers decide how much authority to give the AI. A company that treats the AI score as a final decision tool creates different outcomes from one where the AI is only used as a supporting recommendation.
- **Institutional rules:** Employment laws, fairness policies, organizational goals, and ethical standards determine how the system can be used and monitored.

The same algorithm can therefore produce very different outcomes depending on the surrounding social and institutional context. A technically accurate model may still create unfair hiring practices if the data, workflow, or governance mechanisms are poorly designed.

1.2.4 Who is responsible for an AI decision?

It is a common **misconception** to **attribute agency to the algorithm** itself. In reality, an AI model is a computational system that **does not** possess **intent**, **judgment**, or **moral agency**; it does not independently choose its training data, define its objectives, curate its labels, or determine the context in which it is deployed.

Instead, these **decisions are shaped** by **developers**, **organizations**, and **stakeholders** throughout the AI lifecycle. Furthermore, **operational parameters**, such as decision thresholds, confidence scores, human-review triggers, and escalation policies for edge cases, are **explicitly configured** by **developers**[38] and **stakeholders**[39]. Consequently, every output generated by an AI system reflects a **chain of human and institutional decisions**, **assumptions**, and **governance choices** that precede its deployment and use.

Because the **risks** and **biases** of AI are deeply embedded in these upstream and downstream[40] human decisions, achieving **Responsible AI**[41] cannot be solved merely by engineering an **ethical algorithm**[42] or tweaking the underlying code. Instead, it requires **comprehensive governance** that spans the entire **socio-technical lifecycle** of the system, from **initial conceptualization** and **data collection** to **deployment**, **continuous monitoring**, and **eventual decommissioning**.

To operationalize this holistic approach, organizations often rely on structured guidelines such as the **National Institute of Standards and Technology** (NIST) **AI Risk Management Framework** (AI RMF)[43]. The NIST framework organizes the complex task of AI oversight into four core, interconnected functions:

---

[38] **Developers** are the technical professionals directly responsible for designing, coding, and building the system, distinguishing them from stakeholders by their primary focus on engineering execution and technical implementation rather than broader organizational outcomes.

[39] **Stakeholders** are the individuals or groups who have an interest in, invest in, or are affected by the system's outcomes, distinguishing them from developers by their focus on strategic value, requirements, and real-world impact rather than the technical mechanics of its creation.

[40] **Upstream** refers to the **early-stage human decisions** made during the design, data collection, and training phases of an AI system, where **foundational choices** about objectives, datasets, and model architecture are established before the system is built.
Downstream refers to the **later-stage consequences** and **impacts** that occur **after** an AI system is **deployed**, encompassing how its outputs are interpreted, acted upon, and experienced by users and society in real-world contexts.

[41] **Responsible AI** is the holistic practice of ensuring artificial intelligence systems are **designed**, **deployed**, and **governed** to **align with human values**, **ethical principles**, and **societal well-being**. The concept emerged as a collective framework during the late **2010s**, driven by advances in AI and growing concerns about fairness, accountability, transparency, privacy, and safety. One of the earliest comprehensive academic treatments was provided by **Virginia Dignum** in her **2019** book, *Responsible Artificial Intelligence: How to Develop and Use AI in a Responsible Way*, which helped establish Responsible AI as a coherent discipline.

[42] An **ethical algorithm** is a computational system explicitly designed to incorporate **social values**, **fairness constraints**, and **privacy guarantees** directly into its decision-making and optimization processes. The concept draws on decades of research in algorithmic fairness, privacy, and computer ethics and was comprehensively articulated by **Michael Kearns** and **Aaron Roth** in their **2019** book, *The Ethical Algorithm: The Science of Socially Aware Algorithm Design*.

[43] NIST AI 100-1, *Artificial Intelligence Risk Management Framework (AI RMF 1.0)*, 2023.

- **Govern:** Establishing the organizational culture, accountability structures, and policies necessary to manage AI risk.
- **Map:** Identifying, contextualizing, and understanding the specific risks associated with the AI system and its operational environment.
- **Measure:** Assessing, analyzing, and tracking the identified risks using both quantitative and qualitative metrics.
- **Manage:** Prioritizing and acting upon the risks, allocating resources to mitigate, transfer, or accept them effectively.

Through the execution of these functions, the framework aims to ensure that AI systems are developed and deployed in a way that **upholds** the essential **characteristics** of **trustworthiness**: **valid and reliable**[44], **safe**[45], **secure and resilient**[46], **accountable and transparent**[47], **explainable and interpretable**[48], **privacy-enhanced**[49], and **fair** with **harmful bias managed**[50].

Example # 13: AI-based loan approval system

A bank deploys an AI model that predicts whether a loan applicant is likely to repay a loan. The model analyzes information such as **credit history**, **income**, **employment records**, and **previous financial behavior**. If the system rejects an applicant, it may appear that *the AI denied the loan*. However, the decision is not solely the result of the algorithm. **The outcome is shaped by a chain of human and institutional choices**:

- **Training data choices:** Bank employees decide which historical loan records are used for training. If past lending decisions contained unfair patterns, the model may learn and reproduce those biases.

---

[44] **Validity** refers to the degree to which an AI system **accurately and reliably** performs its intended function under expected conditions **without producing erroneous or misleading** results.

[45] **Safety** is the assurance that an AI system will **not cause unacceptable physical**, **psychological**, or **environmental harm** to humans, property, or ecosystems during its operation.

[46] **Security** involves **protecting an AI system** and its underlying data from **malicious attacks**, **unauthorized access**, **manipulation**, and **exploitation** by external threat actors.

[47] **Transparency** is the practice of **openly disclosing information** about an AI system's overall design, capabilities, limitations, and operational context to its users and stakeholders.

[48] **Explainability** is the capacity to **clearly articulate and understand** the **internal logic**, **causal factors**, and **specific reasoning** behind an AI system's individual output or decision.

[49] **Privacy** ensures that an AI system **respects user confidentiality** by properly managing, protecting, and minimizing the collection and use of personal and sensitive data.

[50] **Fairness** is the quality of an AI system that **ensures** its outputs and decisions are **free from unjust bias**, **discrimination**, or **disparate impact** against specific individuals or demographic groups.

- **Objective definition:** Developers and business stakeholders decide what the AI should optimize. A model designed to maximize repayment rates may unintentionally disadvantage applicants who have limited credit histories.
- **Feature selection:** Humans choose which variables the model can consider. Including location, employment type, or other proxy variables may introduce unintended discrimination.
- **Decision thresholds:** Managers decide how much risk is acceptable. For example, choosing a stricter approval threshold may reduce financial losses but also reject more legitimate applicants.
- **Human workflow:** Loan officers determine whether the AI recommendation is final or whether applicants can request human review.
- **Institutional rules:** Banking regulations, fairness requirements, and organizational policies determine how the system is monitored and corrected.

Now consider a case where the system **systematically rejects applicants from a particular community**. The responsible question is not simply: *Why did the algorithm make a biased decision?* Instead, the investigation must examine:

- Who selected the training data?
- Who defined success for the model?
- Who approved the deployment?
- Who monitored performance after deployment?
- What safeguards existed for affected individuals?

Applying the NIST AI Risk Management Framework via the four governance functions:

- **Govern:** The bank establishes accountability, assigns responsibility, and creates policies for responsible AI use.
- **Map:** The organization identifies risks such as unfair outcomes, privacy concerns, and impacts on applicants.
- **Measure:** The bank evaluates accuracy, bias across groups, security risks, and explainability of decisions.
- **Manage:** The bank mitigates identified risks by improving data, adjusting processes, adding human review, or discontinuing unsafe uses.

An AI system **does not independently** decide who receives a loan; it produces outputs **within a system designed and operated by people**. Responsibility therefore belongs **across the entire socio-technical lifecycle** – from data collection and model development to deployment, oversight, and governance.

The AI and Data Science Landscape

Having explored the philosophical foundations and historical roots of **mechanized reasoning**[51], we now turn to the **contemporary reality** of artificial intelligence and data science. As these technologies have transitioned from **abstract theoretical constructs** to **ubiquitous systems** shaping **global infrastructure**, establishing a precise, shared vocabulary is essential. Before we can rigorously evaluate their governance, ethics, or societal impact, we must first establish a **foundational understanding** of what these systems actually are and how they **function in practice**. This section anchors that understanding by examining the most widely accepted **international definitions** of AI, unpacking the **precise mechanics** of how these systems operate, what they **aim to achieve**, and why their **outputs fundamentally matter**.

Artificial intelligence **may be** defined as[52,53,54]:

The scientific and engineering discipline concerned with constructing computational systems that perceive or receive information, form useful representations, reason or learn from evidence, and select actions or outputs in pursuit of specified objectives under uncertainty and constraints.

1.3.1 AI is both a science and an engineering discipline: As a **science**, AI studies questions such as:

- What is intelligence?
- How can knowledge be represented?
- How can a system infer conclusions from evidence?
- How can an agent learn from experience?
- How should decisions be made under uncertainty?
- What computational resources are required for intelligent behavior?

---

[51] **Mechanized reasoning** is the automated process of **deriving logical conclusions** from **formalized premises** by systematically applying **predefined rules** and **algorithms without human intervention**.

[52] OECD Artificial Intelligence Papers, Explanatory Memorandum on the Updated OECD Definition of an AI System, 2024.

[53] The **updated OECD definition** (**2023**) is: *An AI system is a machine-based system that, for explicit or implicit objectives, infers, from the input it receives, how to generate outputs such as predictions, content, recommendations, or decisions that can influence physical or virtual environments. Different AI systems vary in their levels of autonomy and adaptiveness after deployment*.

[54] https://oecd.ai/en/ai-principles.

As an **engineering discipline**, AI is concerned with constructing systems that perform useful tasks:

- recognizing objects,
- predicting risks,
- allocating resources,
- recommending content,
- detecting anomalies,
- generating language or images,
- planning routes,
- controlling machines,
- assisting human decisions.

The distinction matters because an AI system **can be practically useful** without reproducing human cognition. A weather model **does not need to think like a meteorologist** if it produces reliable forecasts. Similarly, a diagnostic classifier may recognize patterns **without possessing a human-like understanding of disease**.

1.3.2 Four classical ways of thinking about AI: Russell and Norvig organize traditional definitions of AI around four broad perspectives[55].

Systems that think like humans

This approach asks whether a computational system **reproduces human cognitive processes** such as **memory**, **reasoning**, **language**, **perception**, and **learning**. Its intellectual roots lie in:

- cognitive psychology[56],
- neuroscience[57],
- linguistics[58],
- philosophy of mind[59],

[55] Stuart Russell and Peter Norvig, Artificial Intelligence: A Modern Approach, 4th US edition, 2022.

[56] **Cognitive psychology** is the scientific study of **internal mental processes**, such as memory, perception, and problem-solving, to understand how humans acquire, process, and store information.

[57] **Neuroscience** is the multidisciplinary scientific study of the **structure**, **function**, and **development** of the **nervous system** to understand the **biological basis** of **behavior** and **cognition**.

[58] **Linguistics** is the scientific study of language, encompassing its **structure**, **meaning**, and **context**, to understand how humans communicate and represent knowledge.

[59] **Philosophy of mind** is the branch of philosophy that investigates the **fundamental nature** of **consciousness**, **mental states**, and their **relationship** to the **physical body** and the **external world**.

- computational modeling[60].

The central research question is not merely whether the system produces the right answer, but whether it **arrives at that answer** through **mechanisms resembling human cognition**.

Systems that act like humans

This behavioral perspective defines intelligence in terms of **observable behavior** rather than internal mental processes. In his landmark 1950 paper, Alan Turing reframed the philosophical question, *Can machines think?*, into a practical one: *Can a machine's conversational behavior be indistinguishable from that of a human?* This became known as the **Turing Test**. Turing's key contribution was shifting the focus from **unverifiable claims** about whether a machine *thinks* to the **measurable question** of whether it can **exhibit behavior** that **humans perceive as intelligent**.

Systems that think rationally

This tradition attempts to **formalize** correct reasoning through **logic**. A rational conclusion is one that follows validly from stated premises. This approach supports:

- theorem proving,
- rule-based expert systems,
- knowledge representation,
- logical inference,
- constraint reasoning.

Its limitation is that **real environments are rarely complete, deterministic, or perfectly formalized**. Rational reasoning therefore often requires **probability**, **decision theory**, and **approximation** in addition to deductive logic.

Systems that act rationally

[60] **Computational modeling** is the practice of creating **mathematical** and **algorithmic representations** of **complex systems** to simulate, analyze, and predict their behavior under various conditions.

A rational agent **selects actions** expected to advance its **objectives**, given its **information and constraints**. This perspective is especially useful for modern AI because it accommodates:

- uncertainty,
- incomplete information,
- limited computational resources,
- competing objectives,
- interaction with an environment,
- delayed consequences,
- trade-offs between exploration and exploitation.

Rational action does not mean perfect action. It means selecting an **appropriate action** relative to the information, objectives, and resources available.

1.3.3 Intelligence, autonomy, and agency:

The capacity of an AI system to act independently is not a binary trait; rather, it exists on a **broad spectrum of agency**. We can categorize these systems based on their **level of human oversight** and their ability to execute actions in the real world.

Passive analytical systems

These systems function strictly as **informational engines**. They process and transform raw data into descriptive insights or predictive probabilities, but they lack the mechanism to execute physical or operational actions.

Example # 14: A dashboard forecasting monthly sales trends; a diagnostic model estimating the probability of a specific disease; an algorithm predicting imminent equipment failure.

Decision-support systems

Operating at the next level of agency, these systems **analyze scenarios** and propose **specific courses of action**. However, the final authority and execution remain strictly in human hands.

Example # 15: A clinical tool recommending whether a patient requires a specialist referral; a financial model ranking loan applications for manual underwriter review; an asset management system suggesting maintenance priorities to field engineers.

Semi-autonomous systems

These systems operate with a hybrid model of agency. They are **authorized** to **execute actions** automatically in **routine**, **low-risk scenarios**, but are programmed to escalate **ambiguous**, **complex**, or **high-stakes** situations to human operators.

Example # 16: Fraud detection systems that instantly block clearly suspicious transactions while routing borderline cases to human investigators; medical screening tools that automatically clear low-risk patients and refer complex anomalies to specialists.

Autonomous systems

At the highest end of the agency spectrum, these systems **independently perceive** their **environment**, **make decisions**, and **execute actions** with little to no immediate human intervention.

Example # 17: Robotic control systems in manufacturing; automated navigation and sorting in warehouses; algorithmic high-frequency trading and bidding systems; closed-loop industrial process controls.

Crucially, **autonomy must not be conflated with intelligence**. A simple **thermostat** *operates autonomously* within a narrow, predefined loop, yet it possesses *no general intelligence*. Conversely, a **highly advanced large language model** may *exhibit profound linguistic intelligence and reasoning* capabilities, yet it remains *entirely devoid of agency*, lacking the authority or mechanism to act upon the physical or institutional world without human mediation.

Understanding the AI Ecosystem

Navigating the modern technological landscape requires a **precise vocabulary**, as *artificial intelligence* is frequently deployed as a catch-all term for a wide array of computational disciplines. In reality, the AI ecosystem is a **constellation of interconnected but distinct fields**, each with its own **methodological focus**, **historical roots**, and **practical objectives**. While machine learning, data science, statistics, and automation frequently overlap in practice, **conflating them obscures** how different **systems are built** and what they are **fundamentally designed to achieve**. To clarify this complex landscape, it is essential to distinguish these disciplines by their **central driving questions**, their **typical outputs**, and their **structural relationship** to the broader concept of AI. **Table 1** provides a foundational taxonomy of these overlapping, yet non-interchangeable, domains.

Table 1: A comparative taxonomy of the AI ecosystem, outlining the central questions, typical outputs, and structural relationships of key computational, statistical, and data-driven disciplines.

Field	Central Question	Typical Outputs	Relationship to AI
Artificial Intelligence	How can machines perform tasks involving perception, reasoning, learning, planning, language, decision-making, or adaptive action?	Predictions, plans, decisions, generated content, control actions	Broad umbrella
Machine Learning	How can a system improve a task-related function by learning patterns or parameters from data or experience?	Predictive models, representations, policies, scores	Major approach within AI
Data Science	How can data be acquired, prepared, analyzed, modeled, interpreted, and communicated to produce knowledge or decisions?	Analyses, models, data products, experiments, reports	Broader lifecycle that may or may not use AI

Statistics	What can be inferred about a population or process from uncertain, variable, or incomplete observations?	Estimates, tests, intervals, models, uncertainty statements	Mathematical and inferential foundation
Analytics	What happened, why did it happen, what may happen, and what action should be considered?	Dashboards, reports, forecasts, decision recommendations	Decision-oriented use of data
Optimization	Which feasible choice minimizes or maximizes an objective?	Optimal or approximately optimal decision variables	Used in model training, planning, allocation, and control
Automation	How can a predefined process be executed with limited human intervention?	Rules, workflows, robotic or software actions	May contain no learning or intelligence
Generative AI	How can a model produce new content conditioned on data, prompts, or context?	Text, images, audio, video, code, molecular structures	A family of AI capabilities, not a synonym for all AI
Data Engineering	How can data be collected, represented, validated, transformed, governed, delivered, and monitored reliably at scale?	Pipelines, schemas, stores, feature systems, lineage, data contracts	Infrastructure on which data-driven AI depends

1.4.1 AI is not synonymous with machine learning: While machine learning dominates contemporary discourse, it represents only one subset of the broader artificial intelligence landscape. Many robust, high-stakes AI systems operate entirely without learning from data, relying instead on classical, symbolic, or algorithmic paradigms. These include:

- Search algorithms (e.g., navigating complex state spaces or game trees);
- Formal logic and automated reasoning;
- Constraint satisfaction and mathematical optimization;
- Automated planning and scheduling;

- Structured knowledge bases and expert systems;
- and manually engineered control rules.

Ultimately, **machine learning** is merely one powerful methodology for **achieving intelligent behavior**, not the exclusive definition or sole mechanism of artificial intelligence.

1.4.2 Machine learning is not synonymous with deep learning: Deep learning is a specific class of machine learning methods defined by its **reliance on multi-layer artificial neural networks**. However, it represents only a fraction of the broader machine learning landscape. The field of machine learning encompasses a diverse array of foundational algorithms that operate without deep neural architectures. Prominent examples of machine learning techniques that are not deep learning include:

- Linear regression and kernel machines;
- Decision trees and random forests;
- Nearest-neighbor methods;
- and Bayesian probabilistic models.

Consequently, while all deep learning is machine learning, the vast majority of machine learning algorithms are not deep learning.

1.4.3 Data science is not simply "training a model": The popular perception of data science often reduces it to the technical act of training machine learning algorithms. However, the discipline is vastly broader, encompassing a wide spectrum of **analytical**[61], **investigative**[62], and **strategic**[63] activities. A comprehensive data science initiative may produce a diverse array of valuable outputs, including:

[61] **Analytical** activities involve **systematically examining data** to identify **patterns**, **trends**, and **relationships**, such as calculating customer lifetime value or determining the correlation between website load times and user bounce rates.

[62] **Investigative** activities focus on **probing data** to **uncover root causes**, **anomalies**, or **quality issues**, such as tracing the source of a sudden revenue drop or identifying and correcting missing values in a clinical dataset.

[63] **Strategic** activities **translate data-driven insights** into **high-level business planning** and **long-term decision-making**, such as using market trend forecasts to guide a new product launch or optimizing supply chain networks to reduce annual operational costs.

- **Causal estimates**[64] and **experimental designs**[65] to estimate cause-and-effect relationships under stated assumptions and study designs.
- **Exploratory analyses**[66] and **data-quality investigations** to uncover underlying patterns and ensure data integrity.
- **Statistical reports** and **data visualizations** to translate complex findings into actionable insights for stakeholders.
- **Forecasting systems** and **operational machine-learning models** to predict future trends and automate decision-making.

Ultimately, model training is just one tool in the data scientist's toolkit. The true scope of data science lies in its ability to extract, validate, and communicate actionable knowledge from data in many different forms.

1.4.4 Statistics and machine learning have different emphasis but overlap deeply: While statistics and machine learning share a deep mathematical foundation and frequently overlap in practice, they traditionally prioritize different objectives. **Statistics** is fundamentally rooted in **inference** – seeking to understand the underlying data-generating process. It commonly emphasizes:

---

[64] A **causal estimate** is a **quantitative estimate** of the **effect** of a **specific intervention**, **treatment**, or **exposure** on an outcome under a **defined set** of **assumptions**, aiming to **distinguish causal relationships** from **statistical associations** by **accounting** for **confounding factors** and **alternative explanations**. Examples include estimating the reduction in blood pressure attributable to a new drug while accounting for patient characteristics and lifestyle factors or measuring the increase in sales caused by a marketing campaign while separating its effect from seasonal trends and other influences.

A **confounding variable** is an **extraneous factor** that influences both the **independent variable (the intervention)** and the **dependent variable (the outcome)**, thereby creating a **spurious association** or **masking** the true causal relationship, such as age confounding the observed link between exercise frequency and heart disease risk, or socioeconomic status confounding the correlation between ice cream sales and drowning incidents.

[65] **Experimental designs** are the **structured methodologies** used to plan and execute **controlled tests** that isolate the true effect of an intervention by **manipulating variables** and **controlling for confounders**, such as running an **A/B test** to compare two website checkout flows or conducting a **randomized controlled trial** to measure a new drug's efficacy against a placebo.

A **randomized controlled trial (RCT)** is a rigorous **scientific experiment** in which participants or experimental units are **randomly assigned** to an **intervention group** or a **control group** to estimate the **causal effect** of a **treatment** or **intervention** while **reducing selection bias** and **balancing** potential **confounding factors**. Examples include testing a new cardiovascular drug by assigning one group to receive the medication and another to receive a placebo or evaluating a new educational curriculum by randomly assigning schools or students to either the new program or the standard syllabus.

[66] **Exploratory analyses** are the **preliminary investigative processes** used to **summarize**, **visualize**, and **understand** the **underlying structure** of a dataset to discover **patterns**, spot **anomalies**, or test **assumptions** before formal modeling, such as generating histograms to examine the distribution of customer ages or creating scatter plots to identify correlations between marketing spend and sales revenue.

- **Sampling**[67] and **population inference**[68] to draw valid conclusions about a broader group.
- Quantifying **uncertainty**[69] and rigorously validating **model assumptions**.
- **Estimation**[70], **identifiability**[71], and formal **hypothesis testing**[72].

Example # 18: Evaluating a new public health intervention
Imagine a city wants to know if a new subsidized air filtration program actually reduces asthma-related hospitalizations. A pure machine learning approach might build a highly accurate model to *predict* which neighborhoods will have high hospitalization rates based on historical pollution and demographic data. However, **prediction alone cannot tell policymakers** if the filtration program is actually working.

This is where the statistical emphasis on **inference** becomes critical. A statistician will design a study by **sampling** specific neighborhoods to receive the filters (treatment) while others do not (control). Instead of just outputting a prediction, the statistician uses **estimation** to calculate the exact reduction in hospitalizations attributable to the program. They then apply **formal**

---

[67] **Sampling** is the statistical process of **selecting a representative subset** of data or individuals from a **larger population** to estimate its characteristics **without measuring every single member**, such as surveying 1,000 randomly selected voters to predict a national election outcome or testing 50 microchips from a manufacturing batch of 10,000 to estimate the overall defect rate.

[68] **Population inference** is the statistical process of **using data collected from a sample** to make **generalizations**, **estimates**, or **probabilistic conclusions** about the **characteristics** of the **entire**, **unobserved population**, such as calculating the average household income of a country based on a census sample or concluding that a new medical treatment improves recovery times for all patients based on a clinical trial of a few hundred participants.

[69] **Uncertainty** is the **quantifiable measure** of **doubt** or **variability** regarding a model's predictions or parameter estimates – encompassing both **inherent data noise** and **incomplete knowledge** – such as calculating a 95% confidence interval around a predicted house price to account for unmeasured market factors, or a medical AI outputting a low-confidence probability score when evaluating a rare condition it has rarely encountered in its training data.

[70] **Estimation** is the statistical process of using sample data to calculate an **approximate value or range** for an **unknown population parameter**, such as calculating the sample mean to estimate the average income of a city's residents or using **maximum likelihood estimation** to determine the optimal weights of a predictive model.

[71] **Identifiability** is a mathematical property of a statistical model ensuring that its **underlying parameters** can be **uniquely** and **unambiguously determined** from the **observed data distribution**, such as ensuring that in a Gaussian mixture model, the distinct clusters have unique means and variances so their parameters cannot be mathematically swapped without altering the overall output.

[72] **Formal hypothesis testing** is a rigorous statistical inference method used to **evaluate** whether **observed data** provides **sufficient evidence** to **reject a default null hypothesis** in favor of an alternative, such as performing a *t*-test to determine if a new drug's recovery time is statistically significantly shorter than a placebo's or using a chi-square test to verify if two categorical variables are independent.

A **null hypothesis** is the **default statistical assumption** that there is **no significant effect**, **difference**, or **relationship** between the **variables being tested**, serving as the **baseline to be challenged by empirical evidence**, such as assuming a new drug performs no differently than a placebo in lowering blood pressure, or assuming a new website layout has no impact on user conversion rates compared to the original design.

hypothesis testing to assess whether the **observed reduction** is **statistically significant** and unlikely to have occurred due to random variation alone, using evidence from the data to determine whether the null hypothesis should be rejected. Finally, they **quantify uncertainty** by reporting a confidence interval (e.g., *The program reduces hospitalizations by 15%, with a 95% confidence interval of 10% to 20%*). This process allows the city to make **evidence-based population inferences** by estimating the **likely effect** across the **broader population**, provided that the **sampled neighborhoods** are **representative** and the study design supports generalization, before committing millions of dollars to a full rollout.

Machine learning, conversely, is fundamentally rooted in **prediction** – seeking to accurately map inputs to outputs. It commonly emphasizes:

- Maximizing **predictive performance** and ensuring **generalization**[73] to unseen data.
- Handling **high-dimensional inputs**[74] and achieving **computational scalability**[75].
- Learning complex data **representations**[76] and performing **automated function approximation**[77].

---

[73] **Generalization** is the ability of a machine learning model to **accurately predict** outcomes on **new**, **unseen data** by capturing the **true underlying patterns** rather than **merely memorizing** the training set, such as a spam filter correctly flagging a novel phishing email it has never encountered before, or a medical imaging model accurately diagnosing a condition from a scan taken at a different hospital using different equipment.

[74] **High-dimensional inputs** refer to datasets where each observation is **characterized** by a **massive number of features** or **variables**, often requiring specialized algorithms to avoid the **curse of dimensionality**, such as analyzing millions of gene expression measurements in genomic or transcriptomic datasets, or representing every pixel in a high-resolution image as a separate feature dimension for machine learning analysis.

The curse of dimensionality is the phenomenon in which the **rapid growth** of **feature-space volume** as **dimensions increase** causes data points to become **increasingly sparse**, **reducing** the **effectiveness** of many algorithms and making **distance-based measures less informative**. Examples include a k-nearest neighbors classifier struggling because distances between data points become increasingly similar in high-dimensional spaces, or a predictive model **overfitting** when trained on thousands of features with only a limited number of observations.

[75] **Computational scalability** is the ability of an algorithm or system to **maintain efficient performance** and **manageable resource consumption** as the **volume of data** or **problem complexity grows**, such as a distributed gradient descent algorithm training a neural network on billions of records across hundreds of GPUs, or an indexing structure allowing a search engine to query millions of documents in milliseconds.

[76] **Representations** in machine learning refer to **transformed**, often **structured** or **lower-dimensional feature spaces** derived from raw data to make **underlying patterns more explicit** and **computationally tractable**, such as converting raw text into dense semantic word embeddings or transforming raw image pixels into hierarchical edge and shape detectors within a neural network.

[77] **Automated function approximation** is the process by which a machine learning algorithm **automatically learns** the underlying **mathematical mapping from inputs to outputs** by adjusting its internal parameters, rather than relying on

Ultimately, these fields are not mutually exclusive. A mature AI practitioner **cannot rely on just one paradigm**; they must synthesize both **predictive thinking** (from machine learning) and **inferential thinking** (from statistics) to build systems that are not only highly accurate but also reliable, robust, and interpretable[78].

Example # 19: Automated medical image analysis

Imagine a hospital deploying an AI system to detect early-stage tumors in 3D MRI scans.

- **High-dimensional inputs:** A single 3D MRI scan contains millions of voxels (3D pixels), creating a massively complex, high-dimensional input space that traditional statistical methods struggle to process.
- **Complex representations and automated function approximation:** Instead of a human programmer manually writing rigid rules for what a tumor looks like, a deep learning model performs automated function approximation. It automatically learns complex data representations, **discovering hierarchical patterns** from **simple edges and textures** in the early layers to **intricate**, **irregular tumor shapes** in the deeper layers.
- **Computational scalability:** To learn these patterns, the system must process tens of thousands of massive 3D scans. Computational scalability ensures the training algorithms can efficiently distribute this heavy mathematical workload across multiple GPUs without crashing or taking years to complete.
- **Prediction and generalization:** The ultimate goal is predictive performance. The model must **not just memorize** the training scans but generalize to unseen data; accurately predicting the presence of a tumor on

explicitly programmed analytical formulas, such as a neural network learning the **complex non-linear relationship** between housing features and sale prices or a regression tree automatically partitioning data to approximate a continuous physical process.

[78] Statistician **Leo Breiman** highlighted the distinction between two approaches to statistical modeling in his seminal **2001** paper, *Statistical Modeling: The Two Cultures*. He contrasted the traditional **data modeling culture**, which emphasizes **assumptions** about **data-generating processes** and **statistical inference**, with the **algorithmic modeling culture**, which emphasizes **predictive accuracy** through **computational** methods.

Building on this broader convergence of statistics and machine learning, researchers such as **Michael I. Jordan** have contributed to the development of **statistical machine learning**, a field that integrates **computational methods** with **statistical reasoning**. The importance of combining **predictive** and **inferential perspectives** has also been emphasized in data science education, including the work of Ani Adhikari, John DeNero, and Michael I. Jordan, *Interleaving Computational and Inferential Thinking: Data Science for Undergraduates at Berkeley*, Harvard Data Science Review, 2021.

a brand-new scan from a completely different hospital, even if the scanner's resolution or contrast settings are slightly different.

1.4.5 Optimization does not determine the right objective: Mathematical optimization is a **powerful computational engine** capable of **efficiently minimizing** a specified **loss function**, such as the **empirical risk**[79]:

$$\hat{R}(\theta) = \frac{1}{n}\sum_{i=1}^{n} L(f_\theta(x_i), y_i)$$

However, optimization is **ethically**[80] and **epistemically blind**[81]. It operates **purely** as a **mechanical solver** and cannot determine whether:

- y_i **is the correct target:** The label may be **biased**, **mis-specified**, or an **inappropriate proxy** for the true goal.
- **The sample represents the deployment population:** The training data may systematically **exclude** or **under-represent critical groups**.
- **The loss function reflects real harm:** Minimizing mathematical error **may not align** with minimizing actual human or societal damage.
- **The model should be deployed:** A model can be mathematically optimal **yet socially harmful** or **operationally inappropriate**.

[79] **Empirical risk** is the **average loss** calculated over a **finite training dataset**, serving as a **computable proxy** for the model's **true expected error** across the **entire underlying data distribution**, such as calculating the mean squared error of a housing price model across 1,000 historical sales records or computing the average cross-entropy loss of an image classifier on a batch of 10,000 labeled training images.

[80] **Ethically blind** means that mathematical optimization **lacks moral agency** and **cannot evaluate** the **fairness**, **justice**, or **societal harm** of its outcomes, such as an algorithm efficiently minimizing hiring costs by systematically discriminating against a protected demographic, or a recommendation engine maximizing user engagement by amplifying harmful misinformation.

[81] **Epistemically blind** means that mathematical optimization **cannot assess** the **real-world validity**, **truthfulness**, or **contextual soundness** of its **underlying data** and **assumptions**, such as blindly minimizing error on a dataset where the target labels are **fundamentally flawed proxies**, or optimizing a predictive model without knowing that the training data is **unrepresentative** of the actual deployment **population**.

- **The decision is ethically acceptable:** Optimization has **no concept** of **fairness**[82], **justice**[83], or **moral permissibility**[84].

Example # 20: Algorithmic bias in healthcare resource allocation

Imagine a large hospital network deploys an AI system to identify patients who would benefit most from a *high-risk care management* program.

- **The optimization:** The developers set the target variable (y_i) to be *future healthcare costs* and train the model to minimize the prediction error (empirical risk) of these costs. Mathematically, the optimization engine succeeds brilliantly, achieving **high accuracy** in predicting which *patients will cost the hospital the most money* next year.
- **The blindness in practice:**
  - **The wrong target:** The developers assumed *high cost* was a perfect proxy for *high health need* but it is not.
  - **Unrepresentative reality:** Due to historical and systemic barriers to healthcare access, Black patients with the same level of chronic illness as White patients historically generated lower healthcare costs.
  - **Loss function vs. real harm**[85]**:** By blindly minimizing cost-prediction error, the model learned that Black patients were *lower risk*. Consequently, it systematically denied them entry into the care management program, causing direct, real-world harm to their health outcomes.
  - **Inappropriate deployment:** The model was mathematically optimal for predicting *financial expenditure*, making it entirely **inappropriate and dangerous** to deploy as a *clinical triage*[86] tool.

---

[82] **Fairness** is the **algorithmic property** ensuring that a model's predictions do not **systematically disadvantage** specific **individuals** or **demographic groups**, such as ensuring a loan approval algorithm has equal false-positive rates across different racial groups or using demographic parity to encourage equal selection rates for a hiring tool.

[83] **Justice** refers to the broader **systemic obligation** to ensure that an AI system's deployment promotes **equitable outcomes**, **rectifies historical biases**, and **aligns with legal and human rights** frameworks, such as designing a predictive policing tool that actively mitigates historical over-policing in marginalized neighborhoods or ensuring an automated benefits system does not disproportionately deny aid to vulnerable populations.

[84] **Moral permissibility** is the **ethical evaluation** of whether an **AI system's actions** or **objectives** align with fundamental **human values**, **rights**, and **societal norms**, such as refusing to deploy an autonomous weapon system that targets humans without meaningful human control or rejecting a facial recognition system used for mass surveillance because it violates the fundamental right to privacy.

[85] Ziad Obermeyer, Brian Powers, Christine Vogeli, and Sendhil Mullainathan, *Dissecting racial bias in an algorithm used to manage the health of populations*, Science, 366(6464), pp 447-453, 2019.

[86] **Clinical triage** is the systematic **medical process** of **prioritizing patients** for **treatment or resource allocation** based on the **severity** of their condition and **likelihood of benefit**, such as routing emergency room patients with life-

- **Lack of ethical acceptability:** The optimization algorithm had no concept of fairness, justice, or medical ethics. It simply found the most efficient mathematical path to minimize the specified loss function, **inadvertently automating** and **amplifying** historical healthcare **disparities**.

Optimization solves the objective that was specified. It does not validate the objective. This critical distinction places the **burden of responsibility** squarely on **human designers** to ensure that the goals we ask machines to pursue are themselves sound, just, and **aligned with human values**.

1.4.6 Automation may be deterministic: It is crucial to distinguish between the **mechanical execution** of tasks and the **cognitive capacity to reason**. Many automated systems are **entirely deterministic**, relying on **rigid**, **pre-programmed rules** rather than **adaptive** learning. A payroll processing script, a scheduled database backup, or a simple rule-based approval workflow are all examples of automation, but they possess **no inherent intelligence**.

Conversely, the **deployment of AI** does not necessarily mean a process is fully automated. An AI system can be **highly sophisticated** while remaining **strictly advisory**, providing analysis, predictions, or recommendations without directly executing actions or making final decisions. For example, a machine learning model may analyze complex medical data and generate a diagnostic recommendation, while a physician retains responsibility for the final diagnosis and treatment decision. Ultimately, **automation concerns how tasks are executed**, whereas **AI concerns how information is analyzed, patterns are inferred, and decisions are supported**.

Example # 21: Financial fraud detection

Consider how a bank handles suspicious credit card transactions.

- **Automation without intelligence:** A legacy banking system uses a *deterministic*, *rule-based script*: *If a transaction exceeds $10,000 and originates from a new IP address, automatically freeze the account and send a generic rejection email*. This is pure **automation**. It executes a task

threatening symptoms to immediate care while directing minor injuries to a waiting area, or prioritizing scarce ICU beds and organ transplants for those with the highest medical urgency.

mechanically, but it **possesses no reasoning**. It **cannot adapt to context**, leading to frustrating false positives when a legitimate customer makes a large, planned purchase while traveling.

- **Intelligence without full automation:** Conversely, the bank deploys a modern machine learning model to analyze the same transaction. The AI evaluates **hundreds of dynamic**, **complex features** – such as the user's **historical spending patterns**, **device fingerprinting**, **geolocation consistency**, and **merchant risk scores**. However, instead of automatically freezing the account, the AI acts in a **strictly advisory capacity**. It outputs a **nuanced risk assessment** (e.g., *85% probability of fraud, but matches known behavior for this user's upcoming vacation*) and routes the case to a **human fraud analyst**.

In this scenario, the AI provides the **intelligence** (deriving a sophisticated, context-aware decision from complex data), while the human analyst retains control over the **execution** (making the final call to approve the transaction or call the customer). This perfectly illustrates that **advanced cognitive reasoning** *does not require*, *nor does it guarantee*, the **removal of human oversight from the final action**.

1.4.7 Generative AI is one region of the AI landscape: While highly visible, generative AI represents only a specific subset of the broader artificial intelligence ecosystem. Fundamentally, **generative systems** operate by **learning** and **approximating** the **underlying probability distributions** or structural patterns of a dataset, enabling them to **synthesize** entirely new, original outputs[87] – such as text, images, audio, or code. This stands in sharp contrast to **discriminative systems**, which are primarily tasked with **analyzing existing data** to classify, rank, score, or **predict specific outcomes** without creating new content.

Because of its **unique creative capabilities**, generative AI introduces a distinct and complex set of challenges. The National Institute of Standards and

[87] Generative AI generates new output instances **sampled** or **decoded** from **learned distributions**, which **may contain memorized** or **derivative** material.

Technology (NIST)[88] addresses this in its **Generative AI Profile**, which treats generative models as a specialized domain requiring targeted **risk management** within the broader AI lifecycle. This framework highlights **unique vulnerabilities** inherent to generative systems, including:

- **Confabulation (Hallucinations):** Generating plausible but factually incorrect or fabricated information.
- **Harmful Content:** Producing toxic, biased, or dangerous outputs.
- **Information Integrity:** Threats to the authenticity and trustworthiness of digital media (e.g., deepfakes).
- **Intellectual Property and Privacy:** Infringing on copyrighted material or leaking sensitive training data.
- **Misuse:** The potential for malicious actors to exploit the system for fraud, disinformation, or cyberattacks.

Ultimately, while generative AI shares foundational mechanics with other machine learning approaches, its ability to **create novel content** necessitates its **own specialized governance** and **risk mitigation strategies**.

Example # 22: Legal research and document drafting[89,90,91,92]

Consider how a large law firm might deploy AI to handle contract analysis and legal drafting.

- **Discriminative AI (analyzing existing data):** The firm uses a machine learning model to scan 50,000 historical contracts. The system's sole job is to classify and score **clauses**, **flagging** any that contain **high-risk liability** terms. It **does not write anything new**; it **simply predicts** whether a given block of text is *safe* or *risky* based on patterns it has seen before.
- **Generative AI (synthesizing new content):** The firm then deploys a large language model (LLM) to **draft** a new, custom **non-disclosure agreement** (NDA)[93] based on a few bullet points provided by a lawyer.

---

[88] Chloe Autio, Reva Schwartz, Jesse Dunietz, Shomik Jain, Martin Stanley, Elham Tabassi, Patrick Hall, and Kamie Roberts, *Artificial Intelligence Risk Management Framework: Generative Artificial Intelligence Profile*, NIST Trustworthy and Responsible AI, Gaithersburg, MD, 2024.

[89] Mata v. Avianca, Inc., *United States District Court for the Southern District of New York*, New York, NY, 2023.

[90] Andrea Bucher, *Navigating the Power of Artificial Intelligence in the Legal Field*, Houston Law Review, Houston, TX, 2025.

[91] Relativity, Responsible AI in E-Discovery: A Framework for Preserving Lawyer Judgment, Relativity, Chicago, IL, 2024.

[92] Deloitte, *The Future of Legal Work? The Use of Generative AI by Legal Departments*, Deloitte Insights, New York, NY, 2024.

[93] A **non-disclosure agreement** (NDA) is a **legally binding** contract that establishes a **confidential relationship** between parties, strictly prohibiting the recipient from **disclosing**, **using**, or **disseminating proprietary** or **sensitive information**

While the generative tool is highly productive, it introduces the **exact suite of specialized risks** highlighted by the NIST framework:

- **Confabulation:** The model confidently drafts a clause citing a specific, non-existent court precedent to justify its legal reasoning (a **hallucination**[94]).
- **Intellectual Property and Privacy**[95]**:** Because the model was trained on the firm's entire historical database, it **inadvertently reproduces** verbatim, **highly sensitive** financial terms from a **confidential**, **copyrighted** settlement agreement involving a different client.
- **Information Integrity:** The generated NDA looks so professionally formatted and authoritative that a junior associate accepts it as fact without performing independent verification, polluting the firm's standard of care.
- **Misuse and Harmful Content:** A malicious actor could intentionally prompt the system with deceptive instructions (**jailbreaking**[96]) to generate a legally binding but **intentionally exploitative** clause designed to defraud a counterparty.

Legal departments are **actively segregating** their AI tools: using **predictive, discriminative** models for **low-risk**, **high-volume tasks** (like contract clause extraction), while applying **heavy governance**, **privacy sandboxes**, and **mandatory human review** to generative drafting tools due to the risk of sensitive training data leakage.

---

to **unauthorized third parties**, such as a tech startup requiring investors to sign one before revealing proprietary source code, or an employer requiring a new hire to sign one to **protect trade secrets** and **client databases**.

[94] **Hallucination** in generative AI is the phenomenon where a model generates **plausible sounding** but **factually incorrect**, **fabricated**, or **ungrounded outputs** that lack a basis in its training data or the provided context, such as a legal research tool confidently **inventing non-existent** court case citations or a chatbot fabricating a detailed but entirely false historical biography.

[95] **Intellectual property** refers to the **legally protected rights** over **creations of the mind** – such as inventions, literary works, designs, and trademarks – which in the context of AI raises critical compliance issues when models are trained on copyrighted material without authorization or generate outputs that substantially mimic protected works, such as an image generator reproducing a trademarked corporate logo or a language model outputting verbatim excerpts from a copyrighted textbook.

[96] **Jailbreaking** is the technique of **crafting adversarial prompts** or **inputs** designed to **bypass** a large language model's **safety guardrails** and **alignment training**, thereby **coercing it to generate** restricted or **policy-violating outputs**, such as using a *do anything now* role-playing scenario to trick the system into providing instructions for **synthesizing illegal substances** or **encoding a malicious** request in Base64 to evade content filters and generate hate speech.

AI as an End-to-End Pipeline

To understand how AI systems operate in the real world, we adopt a **comprehensive systems view**. Rather than focusing solely on the algorithm, we treat AI as an **end-to-end pipeline** comprising eight interconnected stages (**Figure 5**).




Figure 5: Artificial intelligence systems are represented as an interconnected sequence of eight stages: problem formulation, data acquisition and preparation, representation, model development, evaluation, decision-making, deployment, and monitoring. Continuous feedback from deployed systems enables iterative refinement of earlier stages, supporting reliability, adaptability, and sustained real-world performance. Note: It is only a pedagogical framework; other standards may divide the lifecycle differently.

Crucially, this pipeline is **not a rigid**, **one-directional waterfall**. In practice, AI engineering is highly iterative and cyclical. Insights gained during the **monitoring** phase often **reveal flawed assumptions**, **data drift**, or **performance degradation**, which can **trigger feedback loops** to any preceding stage. A failure in production might require the team to **revisit** data collection and labeling, **engineer** new feature representations, **retrain** the model, or even fundamentally redefine the original business problem.

1.5.1 Problem formulation: The foundation of any successful AI initiative does not begin with the question, *Which algorithm should we use?* Instead, it must start with a much more **fundamental inquiry**: *Which **real-world decision, operational need, or strategic capability are we trying to improve**?*

A robust problem statement moves beyond technical jargon to clearly define the operational context. It should explicitly identify:

- The **target population** and the **decision-maker**.

- The specific **decision to be supported** and the exact **time** at which that decision occurs.
- The **desired outcome** and the **available alternatives** (including the baseline or status quo).
- The **consequences of errors** (e.g., the cost of false positives versus false negatives).
- The **operational** and **ethical constraints** governing the system's use.

The impact of framing

To understand the difference this makes, consider the contrast between a poorly defined task and a comprehensively framed problem:

Poor framing: *Build an AI model to predict hospital readmission*.
Remarks: This statement is **vague**, **lacks operational context**, and **ignores the downstream impact** of the model's predictions.

Better framing: *At the time of discharge, estimate the probability of an unplanned 30-day readmission among adult medical patients so that the discharge team can allocate a limited number of follow-up appointments, while measuring calibration, subgroup performance, preventability, and the consequences of false alerts*.
Remarks: The second formulation transforms a vague technical task into a **precise**, **actionable directive**.

It successfully specifies:

- **When** the prediction occurs (at the time of discharge).
- **Who** will use the output (the discharge team).
- **What action** follows the prediction (allocating follow-up appointments).
- **What resource** is constrained (a limited number of appointment slots).
- **Which patients** are included (adult medical patients).
- **What outcome period** matters (unplanned 30-day readmission).
- **What risks** must be rigorously examined (model calibration, subgroup fairness, and the real-world consequences of false alerts).

By defining the problem with this **level of granularity**, the data science team is equipped to build a solution that is **not just mathematically sound**, but **genuinely valuable** and **safe** in a real-world clinical environment.

1.5.2 Data: Data are not automatically **neutral** or **context-free**; rather, they are **observations** generated by **specific processes**, **systems**, and **human behaviors**. Understanding the context of data generation is just as critical as the data itself. To properly contextualize the data, practitioners must **rigorously interrogate** its **origins** and **characteristics**. Critical questions include:

- **Provenance**[97] **and Purpose:** Who or what produced the data, and for what original purpose was it collected?
- **Definitions and Proxies**[98]**:** Under which definitions were variables established? Which variables are direct measurements, and which are merely proxies?
- **Completeness and Consistency**[99]**:** Which cases are missing, and was the outcome recorded consistently across the dataset?
- **Temporal and Relational Integrity**[100]**:** What has changed over time? Are timestamps reliable, and can records be linked correctly?
- **Governance:** Are the data legally and ethically permissible to use for this specific objective?

Typical data artifacts

A mature data pipeline produces a **suite of standardized artifacts** to ensure **transparency**, **reproducibility**, and **governance**.

---

[97] **Provenance** is the **comprehensive metadata** and **chronological documentation** that records the **origin**, **custody**, **transformations**, and **processing history** of data or models **throughout their lifecycle**, such as tracking a patient's medical record from an initial hospital admission system through an anonymization pipeline to a research data lake, or logging the exact dataset version, code commit, and hyperparameters used to generate a deployed machine learning model.

[98] A **proxy** is an **observable**, **measurable variable** used to **represent an unobservable**, **latent**, or **difficult-to-measure** underlying **construct of interest**, such as using healthcare costs as a proxy for actual patient health needs, using zip codes as a proxy for socioeconomic status, or using website click-through rates as a proxy for genuine user engagement.

[99] **Completeness** is the **data quality metric** measuring the extent to which **all expected records**, **attributes**, and **values are present** in a dataset **without missing** or **null entries**, such as a patient health record missing crucial lab results for 20% of its entries or a retail transaction database lacking the shipping address field for a subset of orders.

Consistency is the **data quality metric** assessing whether **data values are uniform**, **logically coherent**, and **free from contradictions** across different records, systems, or time periods, such as a customer's date of birth being recorded as 1990 in the billing system but 1992 in the CRM, or a time-series dataset where a user's account status illogically flips from *active* to *closed* and back to *active* on consecutive days.

[100] **Temporal and relational integrity** ensure that data **accurately reflects logical chronological sequences** and maintains **valid**, **unbroken links** between distinct entities, such as **verifying** that a patient's surgery timestamp strictly precedes their post-operative recovery records (temporal), and that every transaction in a sales database correctly and exclusively maps to an existing, valid customer ID without orphaned or misattributed records (relational).

Typical data artifacts include:

- Raw data inventories and source-system documentation.
- Data dictionaries and precise label specifications.
- Provenance records and dataset quality reports.
- Consent, licensing, and access-control policy documentation.
- Clearly defined train-validation-test partitions.
- Comprehensive dataset datasheets.

Datasheets for Datasets

A cornerstone of modern data governance is the **Datasheet for Datasets**[101] framework. Inspired by the **datasheets** used in electronics to document component specifications, this practice recommends **comprehensive documentation** of a dataset's **motivation**, **composition**, **collection methods**, **preprocessing steps**, **recommended uses**, and **inherent limitations**.

By formalizing this documentation, the **implicit assumptions**, **biases**, and **constraints** surrounding the data are made **explicitly visible**. This **empowers** model developers and downstream users to understand the **data's boundaries**, reducing misuse and ensuring that models are built on a **foundation of transparency and informed consent**.

Example # 23: Skin lesion image dataset

A research team creates a dataset containing 100,000 images of skin lesions to train an AI model for detecting skin cancer. The model **performs exceptionally well during testing** and is later adopted by hospitals.

Several months after deployment, clinicians discover that the **model performs much worse** for patients with **darker skin tones** than for those with **lighter skin tones**. An investigation reveals several important facts about the dataset:

- Nearly **90% of the images were collected from fair-skinned patients**.
- Most images came from **specialized dermatology clinics** in one country.

[101] Timnit Gebru, Jamie Morgenstern, Briana Vecchione, Jennifer Wortman Vaughan, Hanna Wallach, Hal Daumé III, and Kate Crawford, *Datasheets for Datasets*, arXiv, 2018.

- Images were captured using **high-end clinical cameras**, whereas many hospitals use **smartphone cameras**.
- The labels were assigned by individual dermatologists **without independent verification**.

Unfortunately, none of these characteristics were documented. As a result, **developers assumed** the dataset was **representative of all patients** and suitable for **widespread clinical use**. Now imagine that the dataset had been accompanied by a Datasheet for Datasets documenting:

- **Motivation:** To support skin cancer detection research in dermatology clinics.
- **Composition:** 100,000 dermoscopic images, primarily from fair-skinned adults.
- **Collection process:** Images collected from five hospitals using specialized imaging equipment.
- **Preprocessing:** Images resized and color-normalized before release.
- **Recommended uses:** Research on dermoscopic image classification in clinical settings.
- **Limitations:** Underrepresentation of darker skin tones, children, and smartphone images; not validated for primary care or consumer applications.

With this documentation, downstream developers would immediately recognize that the dataset **is not representative of the intended deployment population**. They could collect additional data, evaluate fairness across demographic groups, or restrict deployment until the limitations were addressed.

1.5.3 Representation: Representation is the **critical bridge** between the **physical world** and **computational models**. It is the process of **translating** real-world entities, observations, and concepts into **structured mathematical forms** that an algorithm can process and learn from. Common examples of data representation include:

- Translating a **person** into a structured feature vector of *demographic* and *behavioral attributes*.

- Converting a **digital image** into a multi-dimensional *numerical tensor of pixel intensities*.
- Transforming a **text document** into sequences of *discrete tokens*[102] or *dense semantic embeddings*[103].
- Modeling a **road network** as a *mathematical graph* of *interconnected nodes and edges*.
- Structuring a **customer's purchase history** as a *chronological event sequence*.
- Capturing a **dynamic physical process** using a *continuous state-space*[104] *model*.
- Encoding **categorical variables**[105] through *one-hot encoding*[106] or *learned embedding layers*[107].

The choices made during this stage are foundational. Representation **dictates exactly** which **information is visible** to the model, ultimately determining which **patterns**, **relationships**, and **distinctions** will be easy or difficult for the algorithm to learn.

Representation risks

Poor or **thoughtless representation** choices can introduce severe vulnerabilities into an AI system. Key risks include:

---

[102] **Discrete tokens** are the **individual**, **countable units** (such as words, subwords, or characters) into which text is segmented and mapped to **unique integer indices** from a **fixed vocabulary**, such as breaking the word *unhappiness* into the subword tokens ["un", "happi", "ness"] or splitting a sentence into a sequence of word-level integers.

[103] **Dense semantic embeddings** are **continuous**, **high-dimensional numerical vectors** that represent tokens by capturing their **contextual meaning** and **linguistic relationships** in a shared vector space, such as mapping the words *king* and *queen* to (for instance) 768-dimensional arrays where their mathematical proximity reflects their similar semantic roles and gender distinction.

[104] **State-space** is a mathematical framework that models a dynamic system using a **sufficiently informative set of variables** – known as the **state** – required to **fully describe its current condition** and predict its **future evolution**, such as defining the current angle and angular velocity of a swinging pendulum or tracking an aircraft's three-dimensional position and velocity to forecast its future trajectory.

[105] **Categorical variables** are **qualitative data attributes** representing **distinct**, **mutually exclusive categories** without inherent numerical magnitude or continuous ordering, such as classifying a vehicle's color as red, blue, or silver, or categorizing a user's subscription tier as basic, premium, or enterprise.

[106] **One-hot encoding** is a **binary vectorization technique** that transforms a **categorical variable** into a **sparse array** where **each unique category** is represented by a vector containing a **single 1** at its specific index and **0's everywhere else**, such as representing the colors red, green, and blue as $[1, 0, 0]$, $[0, 1, 0]$, and $[0, 0, 1]$ respectively.

[107] **Learned embedding layers** are **trainable neural network components** that map discrete categorical inputs into **dense**, **continuous**, **lower-dimensional vectors**, *optimizing their spatial relationships* during training to capture underlying semantic similarities, such as representing words in a vocabulary as 300-dimensional vectors where *king* and *queen* are positioned closer together than *king* and *apple*, or mapping user IDs in a recommendation system to capture latent purchasing preferences.

- **Loss of Context:** Reducing a complex, dynamic entity (such as a patient's medical history) to a static, fixed-length vector may strip away crucial temporal progressions or nuanced clinical context.
- **Proxy Encoding:** Using seemingly neutral features (like a postal code or IP address) can inadvertently encode and amplify sensitive, protected attributes such as socioeconomic status, race, or ethnicity.
- **Aggregation Bias:** Summarizing complex data through simple averages or totals can mask critical variations, hiding distinct patterns or disparities within specific subgroups.
- **Temporal Leakage (Data Leakage):** Inadvertently including a feature that contains information recorded after the moment the prediction is supposed to be made, which artificially inflates training accuracy but causes the model to fail in real-world deployment.
- **Identity Errors:** Flaws in entity resolution where records from multiple distinct individuals are incorrectly merged, or a single individual is fragmented into multiple conflicting identities.
- **Train-Serving Mismatch:** Discrepancies between the data transformations and preprocessing pipelines applied during model training versus those applied during live inference, leading to silent and often catastrophic performance degradation in production.

Example # 24: AI-powered ICU sepsis prediction

Imagine a hospital deploying an AI system designed to predict **which Intensive Care Unit** (ICU) patients are at **high risk of developing sepsis**[108] in the next 6 hours, triggering an **early alert for the nursing** staff. If the data representation phase is rushed or thoughtless, the system can fail catastrophically across multiple dimensions:

- **Loss of Context:** The engineers represent a patient's vital signs as a *24-hour average heart rate*. This static, fixed-length representation strips away the crucial temporal progression – **masking a dangerous, rapid spike in heart rate** that occurred just an hour ago, which is the actual early warning sign of sepsis.

[108] **Sepsis** is a life-threatening medical emergency caused by the body's extreme, dysregulated response to an infection, which triggers widespread inflammation, tissue damage, and potentially fatal organ failure.

- **Proxy Encoding:** The model includes the patient's *home zip code* as a feature intended to represent *baseline environmental health*. However, this inadvertently acts as a **proxy for socioeconomic status and race**. The model learns to systematically **deprioritize alerts** for patients from **marginalized neighborhoods**, falsely attributing their symptoms to *chronic baseline conditions* rather than acute, life-threatening infection.
- **Aggregation Bias:** The model's performance is evaluated using a single, hospital-wide average accuracy of 92%. This aggregate metric **masks severe aggregation bias**: the model works well for adult medical patients but **fails catastrophically for pediatric patients** or those with **pre-existing autoimmune diseases**, hiding **critical disparities** in care.
- **Temporal Leakage:** The feature *total doses of broad-spectrum antibiotics administered* is included in the training data. In the hospital's historical records, this count is often updated **after the physician officially logs the sepsis diagnosis**. The model *cheats* by learning to simply wait for the doctor's order, achieving 99% accuracy in testing, but failing completely in real-time deployment because the **antibiotic count** is **unavailable** or **systematically different** at the exact moment the 6-hour prediction is required.
- **Identity Errors:** Due to flawed entity resolution in the Electronic Health Record (EHR) system, a patient transferred from an outside hospital is assigned a new, temporary ID. The representation **fragments this single individual** into **two conflicting identities**: one with a clean history and one with severe, sudden symptoms. The model fails to connect the dots, missing the rapid deterioration trend.
- **Train-Serving Mismatch:** During model training, the data science team handled **missing** *blood pressure* readings by **imputing them** with the **specific ICU ward's** historical median. However, the software engineering team building the live deployment pipeline programmed it to impute **missing blood pressure** with a 0. In production, the model receives a 0 blood pressure reading, **triggering a massive flood** of **nonsensical**, **high-priority false alarms** that cause *alert fatigue* and force the nurses to ignore the system entirely.

This scenario illustrates that a model can be built with state-of-the-art algorithms yet **still fail dangerously** in the **real world** due to **flawed representation**. Rigorous **data governance**, careful **feature engineering**, and **strict alignment** between training and production environments are required to prevent these **invisible vulnerabilities** from harming patients.

1.5.4 Model: At its core, a model is a **mathematical function** that maps **structured input representations** to a **desired output**. Formally, this is expressed as

$$f_\theta : X \to Y$$

where the algorithm learns the **optimal parameters**[109] (θ) to transform the **feature space** (X) into the **target predictions** or **decisions** (Y). The landscape of available models is vast, ranging from simple, transparent algorithms to highly complex, adaptive systems. Depending on the problem, a model may take the form of:

- **Classical & Statistical approaches:** Linear functions, decision trees, nearest-neighbor procedures, or probabilistic graphical models.
- **Deep Learning architectures:** Multi-layer neural networks.
- **Algorithmic & Rule-based systems:** Search algorithms, mathematical optimization programs, or explicit sets of deterministic rules.
- **Hybrid systems:** Neuro-symbolic architectures that seamlessly blend learned neural components with explicit, logical symbolic rules.

Model selection criteria

Selecting the right model is a **strategic engineering decision**, not merely a technical one. The choice should never be based on hype; rather, it must be driven by a **careful evaluation** of **operational**, **technical**, and **business constraints**:

- **Data Characteristics:** The size, dimensionality, and inherent nonlinearity of the dataset.

[109] An optimization algorithm is **not**, in general, **guaranteed** to find the **globally optimal** solution. Depending on the **problem's characteristics** and **computational constraints**, it may instead converge to a **local optimum**, a **near-optimal (approximate) solution**, or a **regularized solution** that deliberately **trades optimality** for improved **generalization**, **stability**, or **robustness**.

- **Task Requirements:** The specific nature of the problem (e.g., classification, regression, ranking) and the need for probabilistic calibration[110].
- **Operational Constraints:** Strict latency[111], memory, and computational limits required for real-time inference.
- **Governance and Trust:** The level of **interpretability**[112], **explainability**[113], and **robustness**[114] required by stakeholders, users, or regulators.
- **Lifecycle Costs:** The long-term maintenance burden and the specific machine learning expertise available within the team.

Ultimately, a foundational principle of applied machine learning is that **the most complex model is not automatically the best model.** A simpler, **highly interpretable model** that perfectly **aligns** with the **operational constraints** and **data realities** will consistently outperform an **over-engineered** *black-box* model that is **unnecessarily complex**[115] for the task at hand.

Example # 25: Automated loan underwriting

---

[110] **Probabilistic calibration** is the property of a machine learning model where its **predicted output probabilities accurately match** the **true empirical frequencies** of the observed outcomes, such as a weather forecasting system predicting a 30% chance of rain actually experiencing rain on exactly 3 out of 10 days it makes that prediction, or a credit risk model estimating a 5% default probability seeing exactly 5 defaults out of 100 loans in that specific risk tier.

[111] **Latency** is the **time delay** between a **system receiving** an input and **generating a corresponding output**, which in real-time machine learning inference must be **strictly minimized** to ensure **timely decision-making**, such as an autonomous vehicle processing sensor data in milliseconds to execute an emergency braking maneuver or a payment gateway evaluating a credit card transaction in under 200 milliseconds to approve a purchase at the point of sale.

[112] **Interpretability** is the **inherent property** of a machine learning model that **allows humans** to directly **understand** its **internal mechanics** and how **specific** input features **influence its predictions** without needing external tools, such as a linear regression model showing exactly how much each additional year of age increases predicted income, or a decision tree explicitly mapping the step-by-step logical rules used to approve a loan.

[113] **Explainability** is the capability to **generate post-hoc**, **human-understandable justifications** for a specific model prediction, **often using external techniques** to interpret complex black-box systems, such as using **SHAP** (SHapley Additive exPlanations) values to highlight **which features most contributed** to a neural network's denial of a mortgage application, or generating a visual heatmap to show which pixels in an X-ray led an image classifier to identify a tumor.

[114] **Robustness** is the ability of a machine learning model to **maintain consistent performance**, **reliability**, and **safety** when exposed to **noisy data**, **unexpected distribution shifts**, or **malicious adversarial attacks**, such as a self-driving car's vision system correctly identifying a stop sign even when partially obscured by graffiti, or a spam filter continuing to accurately block phishing emails when attackers slightly alter the wording to evade detection.

[115] **Occam's Razor**, attributed to William of Ockham in the **early 14th century**, is the **principle of parsimony**, which states that among **competing models** with **equivalent predictive** performance, the **simplest model** requiring the **fewest assumptions** or **parameters** should generally be preferred. In machine learning, this principle helps **reduce overfitting** and **improve interpretability** – for example, choosing a **simple logistic regression** model over a deep neural network for a small tabular dataset, or preferring a **shallow decision tree** to a large random forest when **both achieve comparable** predictive accuracy in a regulated credit-scoring application.

Imagine a mid-sized bank deploying an AI system to automatically approve or deny personal loan applications in real-time.

- **The Complex Model (The Trap):** The data science team builds a massive Deep Neural Network (DNN) that ingests thousands of features, including complex behavioral data and non-linear interactions. In offline testing, this highly complex model achieves a 94% accuracy rate in predicting loan defaults.
- **The Simple Model (The Pragmatic Choice):** A competing team builds a Logistic Regression model using only 15 highly curated, traditional financial features (e.g., debt-to-income ratio, credit score, employment length). In offline testing, it achieves a 91% accuracy rate.

At first glance, the complex DNN seems like the obvious winner. However, when evaluating the model against the **operational** and **business constraints**, the **simpler model is chosen for deployment**. Here is why:

- **Interpretability Requirements (The Dealbreaker):** By law (such as the Equal Credit Opportunity Act[116] in the U.S.), if the bank denies a loan, it **must provide** the applicant with specific **adverse action reasons** (e.g., *Your debt-to-income ratio is too high*).

  The *DNN* is a black box; extracting legally compliant, stable explanations requires complex, computationally heavy post-hoc tools (like SHAP[117]) that can sometimes yield contradictory or unstable reasons.

[116] Sponsored primarily by **Representative Bella Abzug** and **Senator Bill Brock** and enacted by the **U.S. Congress** in **1974**, the Equal Credit Opportunity Act (ECOA) is a federal statute **prohibiting creditors** from **discriminating** against applicants based on **protected characteristics** (such as race, sex, or marital status), which **operationally mandates** that institutions provide specific, **non-discriminatory adverse action reasons** when denying credit, such as explicitly stating *debt-to-income ratio is too high* rather than issuing a vague refusal, or preventing a lender from denying a mortgage simply because a female applicant uses her maiden name.

[117] Proposed by **Scott M. Lundberg** and **Su-In Lee** in **2017**, SHAP (**SHapley Additive exPlanations**) is a **game-theoretic framework** that explains the output of any machine learning model by assigning each feature a **mathematically fair importance value** for a specific prediction based on **Shapley values**, such as calculating exactly how much a borrower's high debt-to-income ratio decreased their loan approval probability or identifying which specific pixels in a medical scan contributed most to a neural network's tumor detection.

Formulated by **Lloyd Shapley** in **1953**, **Shapley values** are a **solution concept** in **cooperative game theory** that **fairly distributes** a total payoff among players by **averaging each player's marginal contribution** across all **possible coalitions**. In machine learning, Shapley values underpin SHAP, an explainability method that attributes a model's prediction to individual input features; for example, estimating how much a borrower's credit score and income each contributed to a particular loan denial, or quantifying the contribution of individual pixels to an image classifier's confidence score.

The *Logistic Regression*[118] model provides direct, provides **mathematically interpretable coefficients**, making its **predictions transparent** and readily **explainable**, which **aligns well** with regulatory requirements for **interpretability**, **auditability**, and **accountability**.

- **Data Size:** The bank only processes about 50,000 loan applications a year. This dataset is far too small to reliably train a massive DNN **without severe overfitting**, whereas it is the perfect size for a Logistic Regression model.
- **Maintenance Cost:** When **macroeconomic**[119] **conditions shift** (e.g., an inflation spike), the **underlying data distribution** and **relationships** between variables may **change**, causing the deep neural network's predictive **performance to degrade**. Detecting and addressing this model drift typically requires specialized ML engineers to **continuously monitor**, **validate**, **recalibrate**, and **periodically retrain** the model. The simple model's behavior is **easily understood** and can be **maintained and updated** by **standard risk analysts**[120] using **standard statistical tools**.
- **Latency:** While both models can process a request in milliseconds, the DNN requires **significantly more computing** resources (e.g., CPUs, GPUs) to maintain that speed at scale, whereas the Logistic Regression model runs **effortlessly on standard**, **low-cost** CPUs.

Example # 26: Diagnosing a patient with multiple symptoms

A patient arrives with **persistent cough**, **fever**, **weight loss**, and **joint pain**. A physician applies Occam's principle (*prefer the simplest explanation*) and concludes that **tuberculosis alone** explains all the symptoms.

---

[118] Formalized by **Joseph Berkson** in **1944** (building on **Pierre François Verhulst's 1838** logistic function), **logistic regression** is a statistical classification algorithm that models the **probability of a binary outcome** by applying a sigmoid function to a linear combination of input features, yielding mathematically transparent coefficients that directly quantify variable impact, such as calculating the exact increase in disease odds for every one-unit rise in blood pressure or determining the precise weight assigned to a borrower's credit score in predicting loan default.

[119] **Macroeconomic** refers to the **broad**, **aggregate factors** and **systemic trends** that **influence** an **entire national** or **global economy** rather than individual markets or specific agents, such as nationwide inflation rates, central bank interest rate policies, overall gross domestic product (GDP) growth, or economy-wide unemployment levels.

[120] **Standard risk analysts** are **financial professionals** specialized in **evaluating**, **quantifying**, and **mitigating potential economic losses** (such as credit, market, or operational risks) using domain expertise and traditional statistical methods, such as a bank's credit risk team adjusting loan approval thresholds based on historical default rates, or an insurance underwriter calculating premium adjustments using actuarial tables and standard spreadsheet models.

However, further testing reveals that the patient actually has **both tuberculosis**[121] and **rheumatoid arthritis**[122]. The joint pain is caused by rheumatoid arthritis, while the cough, fever, and weight loss are caused by tuberculosis.

By insisting on the simplest single explanation, the physician overlooked the possibility of **multiple coexisting diseases**, delaying the correct diagnosis and treatment.

Why this is a misuse of Occam's principle? Occam's principle is a **heuristic**, **not a law**. It advises choosing the simplest model **only when competing explanations fit the evidence equally well**. It **does not** imply that reality itself is always simple. In this case:

- A **simpler model:** *one disease explains everything*.
- A **more complex model:** *two independent diseases explain the symptoms*.

Because the more complex model better matches the evidence, it is the appropriate choice despite having greater complexity.

Occam's principle should encourage **avoiding unnecessary complexity**, not **ignoring necessary complexity**. When additional complexity is supported by evidence, a more complex model is preferable to an oversimplified one.

1.5.5 Evaluation: The fundamental question of the evaluation stage is whether the AI system is **sufficiently reliable**, **safe**, and **effective** for its specific intended use. Answering this requires moving far beyond the simplistic practice of reporting a single, aggregate accuracy metric.

Comprehensive evaluation dimensions

A rigorous evaluation must assess the system across multiple, often competing, dimensions to ensure it is fit for purpose. Key dimensions include:

- **Predictive Performance:** *Discrimination* (the model's ability to correctly separate positive from negative cases) and *calibration* (whether a **predicted** 80% **risk** actually **translates** to an 80% **observed frequency**).

[121] **Tuberculosis** is a contagious, airborne infectious disease caused by the bacterium *Mycobacterium tuberculosis* that primarily attacks the lungs, characterized by chronic cough, fever, night sweats, and potential systemic spread if left untreated.

[122] **Rheumatoid arthritis** is a chronic, systemic autoimmune disorder in which the body's immune system mistakenly attacks the synovial lining of the joints, leading to progressive inflammation, severe pain, and eventual joint deformity.

- **Fairness and Robustness:** *Subgroup performance* (ensuring equitable accuracy across different demographics), *robustness* (resilience to noisy data or distribution shifts), and *interpretability* (the ability to understand and trust the model's outputs).
- **Operational Viability:** *Computational cost*, *inference latency*, and *stability* (**consistent performance** across **different times**, **environments**, and **deployment sites**).
- **Real-World Impact:** *Decision utility* (does the output actually help the end-user?), *comparison with meaningful baselines* (does it beat the status quo or a simple heuristic?), and *human-system performance* (how well do humans and the AI perform when working together?).

Example # 27: AI-powered emergency department (ED) triage system

Imagine a hospital deploying an AI system to triage incoming emergency room patients, predicting the risk of rapid clinical deterioration within the next 4 hours to prioritize nursing attention.

- **The Naive Evaluation:** The data science team evaluates the model on a randomly split historical dataset and reports a single, aggregate metric: *Our model achieves 92% accuracy in predicting deterioration*. Based on this, they declare the system ready for live deployment.
- **The Rigorous Evaluation:** A responsible AI governance team rejects the single-metric approach and forces a comprehensive evaluation across all required dimensions before deployment:
    - **Predictive Performance:** They check **discrimination** (the model successfully ranks high-risk patients above low-risk ones) but also check **calibration**. They discover that when the model outputs an *80% risk score*, the **actual observed deterioration rate** is only 45%. The model is **overconfident**, which would lead to dangerous resource misallocation.
    - **Fairness and Robustness:** They evaluate **subgroup performance** and discover the model's accuracy drops significantly for elderly patients and non-English speakers due to **underrepresentation** in the **training data**. They also **test robustness** by simulating missing sensor data,

finding the model crashes or outputs garbage when a single vital sign is temporarily unavailable.

- **Operational Viability:** They measure **inference latency** and find that the complex model takes 15 seconds to generate a prediction per patient due to **heavy data preprocessing**, which is **too slow** for a **fast-paced triage desk**. They also check **stability** and find the model's performance degrades on night shifts when different, older monitoring equipment is used.
- **Real-World Impact:** They compare the AI against a **meaningful baseline** (the hospital's existing, simple Modified Early Warning Score) and find the AI only offers a marginal 2% improvement. Finally, they run a **prospective assisted-use pilot trial** to assess human-system performance, discovering that the model generates so many **false alarms** that **nurses** experience **alert fatigue** and begin actively ignoring its recommendations, destroying its **decision utility**.

This illustrates that **rigorous**, **multi-dimensional evaluation** is essential for demonstrating that an AI system is safe, effective, and fit for its intended real-world purpose.

Aligning evaluation with deployment claims

A critical rule of AI evaluation is that **the testing methodology must strictly match the system's deployment claims.** You cannot validate a claim with the wrong type of test:

- **Temporal Claims**[123]**:** If a model is intended to predict *future events*, it should be evaluated using **temporal validation** (trained on past data and evaluated on strictly future data), rather than using **randomly shuffled cross-validation** that would **leak future information** into the training process.
- **Geographic Claims**[124]**:** If a model is intended to be deployed in *new hospitals* or *regions*, it must undergo rigorous **external validation** using data from *entirely different sites*.

[123] Suraj Kapoor and Arvind Narayanan, *Leakage and the reproducibility crisis in machine learning*, Patterns, 2023.

[124] Andrew Wong, Eamon Otles, John P. Donnelly, et al., *External Validation of a Widely Implemented Proprietary Sepsis Prediction Model in Hospitalized Patients*, JAMA Internal Medicine, 2021.

- **Equity Claims**[125]**:** If a model is intended to serve *different demographic groups*, it must be explicitly evaluated for **subgroup performance**[126] to identify and mitigate *hidden disparities*.
- **Probabilistic Claims**[127]**:** If a model is intended to output *reliable probabilities* (e.g., for risk stratification), its **calibration** must be rigorously assessed, not just its ranking ability.
- **Decision Claims**[128]**:** If a model is intended to *improve human decisions*, it cannot be evaluated in a **static**, **offline vacuum**; it must be assessed within the actual **decision workflow** (e.g., through simulated environments or prospective clinical trials).

Example # 28: AI-powered hospital readmission predictor

Imagine a healthcare network purchasing an AI system designed to predict the 30-day risk of patient readmission, with the goal of helping **discharge nurses prioritize post-discharge follow-up calls**. The vendor makes five specific deployment claims. Here is how a naive evaluation fails, and how a rigorous evaluation aligns the testing methodology with those exact claims:

- **Temporal Claims (Predicting the future)**
  - **The Claim:** The model will predict readmissions for patients discharged next month.
  - **The Naive Test:** The team uses random 80/20 cross-validation, mixing patients from 2021, 2022, and 2023 in both the training and testing sets. The model achieves 85% accuracy.
  - **The Rigorous Test (Temporal Validation):** The team trains the model strictly on patients discharged in 2022, and tests it only on patients discharged in January 2023.

---

[125] Ziad Obermeyer, Brian Powers, Christine Vogeli, and Sendhil Mullainathan, *Dissecting racial bias in an algorithm used to manage the health of populations*, Science, 2019.

[126] **Subgroup performance** is the practice of **disaggregating** a machine learning model's **evaluation metrics** across **specific demographic** or **categorical slices** of a population to identify **hidden biases** and **disparate impacts**, such as discovering that a facial recognition system has a 99% accuracy rate for white males but only 80% for dark-skinned females, or finding that a medical diagnostic tool yields significantly higher false-negative rates for elderly patients compared to younger adults.

[127] Ben Van Calster, David J. McLernon, Maarten van Smeden, et al., *Calibration: the Achilles heel of predictive analytics*, BMC Medicine, 2019.

[128] Sandeep Reddy, Stephen Allan, Sean Coghlan, and Paul Cooper, A governance model for the application of AI in health care, Journal of the American medical informatics association, Volume 27, No. 3, pp 491-497, 2020.

    - **The Discovery:** Accuracy drops to 68%. The model had secretly learned a specific billing code that was only used for three months in 2021 and then discontinued. Random splitting leaked this *future knowledge* into the past; **temporal validation exposed the flaw**.

- **Geographic Claims (Deploying to new sites)**
    - **The Claim:** The model will be deployed across all 50 clinics in the regional health network.
    - **The Naive Test:** The team evaluates the model using data exclusively from the flagship urban academic hospital, where it performs brilliantly.
    - **The Rigorous Test (External Validation):** The team tests the model using data from three entirely different, rural community clinics that were not involved in training.
    - **The Discovery:** The model fails in the rural clinics because it relied heavily on a specific type of advanced lab test that is only available at the urban flagship hospital. **External validation prevented a catastrophic rollout.**

- **Equity Claims (Serving all demographics)**
    - **The Claim:** The tool will be used to allocate scarce nursing resources fairly across the entire patient population.
    - **The Naive Test:** The team looks only at the aggregate Area Under the Curve (AUC) for the whole hospital, which is a healthy 0.82.
    - **The Rigorous Test (Subgroup Performance):** The team disaggregates the evaluation metrics by patient demographics (e.g., race, primary language, insurance type).
    - **The Discovery:** While the aggregate AUC is 0.82, the model's performance for non-English speaking patients drops to an AUC of 0.55 (barely better than a coin flip) because the electronic health record notes for these patients were poorly translated and lacked clinical nuance.

- **Probabilistic Claims (Outputting reliable probabilities)**
    - **The Claim:** The model will output a precise *20% risk* or *80% risk* score so nurses know exactly how urgent a case is.

    - **The Naive Test:** The team only measures *discrimination* (ranking ability) – checking if the model can successfully put high-risk patients above low-risk patients.
    - **The Rigorous Test (Calibration Assessment):** The team plots a calibration curve to check if the predicted probabilities match reality.
    - **The Discovery:** The model is highly overconfident. When it predicts an *80% risk* of readmission, the actual observed readmission rate is only 35%. If deployed as-is, nurses would waste time over-treating low-risk patients while under-treating the truly high-risk ones.

- **Decision Claims (Improving human decisions in a workflow)**
    - **The Claim:** Using this AI will improve the nurses' triage decisions and reduce overall readmission rates.
    - **The Naive Test:** The team evaluates the model in a static, offline vacuum, proving it has high mathematical accuracy on a historical dataset.
    - **The Rigorous Test (Decision Workflow Assessment):** The team runs a *prospective assisted-use pilot trial*. They give AI's recommendations to nurses in real-time and measure the actual clinical outcomes and nurse behavior.
    - **The Discovery:** Because the model flags 60% of patients as *high risk* (due to the miscalibration mentioned above), the nurses experience severe alert fatigue. They stop trusting the tool and revert to their old spreadsheet method. The AI's high offline accuracy did not translate into improved real-world decisions.

By strictly aligning the evaluation methodology with the specific deployment claims, **critical vulnerabilities** were uncovered before the system reached the bedside, proving that how you test an AI is just as important as what you test.

Transparent documentation

To ensure accountability, these evaluation results should be formally documented using **standardized frameworks** like **Model Cards**[129,130]. A comprehensive Model Card **explicitly records** the model's **intended use**, the **specific evaluation procedures** applied, the **conditions** under which it performs well, **detailed subgroup results**, and its **known limitations**, providing downstream users with a clear, honest picture of the **system's capabilities** and **boundaries**.

1.5.6 Decision: A machine learning prediction is **not** a **decision**. While a model outputs a probability, a decision requires concrete action. Suppose a model outputs a **risk probability**[131] for a given input x:

$$\hat{p} = \hat{P}(Y = 1|X = x)$$

Translating this continuous probability into a discrete action requires a **decision rule**, such as:

$$a(x) = \begin{cases} \text{intervene}, & \hat{p} \geq t \\ \text{do not intervene}, & \hat{p} < t \end{cases}$$

Calibrating the decision threshold

The threshold t is the **critical bridge** between **prediction** and **action**. It should **never be arbitrarily set** (e.g., at a default 0.5). Instead, it must be **carefully calibrated** to reflect the specific **operational**, **clinical**, or **business realities**:

- **Asymmetric Error Costs:** The relative harm or financial cost of false positives versus false negatives[132].

---

[129] **Model Cards**, introduced in **2019** by **Margaret Mitchell**, **Timnit Gebru**, and collaborators, are short, standardized documents providing transparency into machine learning models' performance, intended use, and limitations. They, along with tools like **FactSheets**, serve as critical, actionable documentation for promoting accountability and ethical AI development.

FactSheets, introduced by IBM Research in **2018** through the work of researchers including **Sarah Holland** and **Michael Hind**, are structured documentation artifacts designed to improve **transparency**, **provenance**, **accountability**, and **trustworthiness** of AI services by **recording information** about their **purpose**, **performance**, **limitations**, **training data**, and usage considerations.

[130] Margaret Mitchell, Simone Wu, Andrew Zaldivar, Parker Barnes, Lucy Vasserman, Ben Hutchinson, Elena Spitzer, Inioluwa Deborah Raji, and Timnit Gebru, *Model Cards for Model Reporting*, Proceedings of the conference on fairness, accountability, and transparency, pp. 220-229, 2019.

[131] **Risk probability** is the estimated likelihood (typically between 0 and 1) that a **specific target** or **adverse event** will occur given a set of **observed input features**, such as a medical AI predicting a 15% chance of 30-day hospital readmission for a specific patient or a financial model assigning an 8% probability of default to a particular loan applicant.

[132] **False positives** versus **false negatives** contrasts the **distinct real-world consequences** of a **Type I error** (incorrectly predicting an event that did not occur) and a **Type II error** (failing to predict an event that actually occurred), highlighting scenarios where their costs are highly asymmetric, such as in cancer screening where a false negative (**missing a**

- **Intervention Capacity:** The physical or operational limits on how many interventions the system or staff can actually handle.
- **Uncertainty and Expected Benefit:** The tangible value gained from a correct intervention versus the risk of acting on uncertain predictions.
- **Fairness Requirements:** Ensuring the chosen threshold does not disproportionately trigger false alarms or missed detections for specific demographic subgroups.
- **Human-in-the-Loop:** The availability and reliability of downstream human review to catch errors.

Example # 29: Activating a hospital rapid response team (RRT)

Imagine a hospital deploys an AI model to monitor general ward patients[133,134]. For a given patient x, the model outputs a continuous risk probability $\hat{p}$ that the patient will suffer a severe clinical deterioration (e.g., cardiac arrest) within the next 24 hours.

The hospital must translate this probability into a discrete decision rule: *Activate the Rapid Response Team (RRT) if $\hat{p} \geq t$, otherwise continue standard monitoring*.

A **naive** data science team might **arbitrarily set** the default threshold at $t = 0.5$. However, a **rigorous** clinical operations team **recalibrates** this threshold by evaluating the five real-world decision constraints:

- **Asymmetric Error Costs:** The cost of a False Negative (failing to activate the RRT for a deteriorating patient) is a preventable death or code blue. The cost of a False Positive (activating the RRT for a stable patient) is minor: a brief clinical assessment and a few unnecessary lab tests. Because the

malignant tumor) is **potentially fatal** compared to a false positive (an **unnecessary but safe follow-up** biopsy), or in corporate email filtering where a false positive (quarantining a critical client message) is far more damaging to business operations than a false negative (letting a promotional spam email reach the inbox).

CAUTION: Describing a follow-up biopsy as merely *unnecessary but safe* **dangerously minimizes the reality** that it is an **invasive medical procedure** carrying tangible physical risks (such as infection or bleeding), **severe psychological distress**, and **substantial financial burdens** for the patient.

[133] Richard T. Sutton, David Pincock, Daniel C. Baumgart, et al., *An Overview of Clinical Decision Support Systems: Benefits, Risks, and Strategies for Success*, NPJ Digital Medicine, 2020.

[134] Heather M. Giannini, Jennifer C. Ginestra, Corey Chivers, Michael Draugelis, Asaf Hanish, William D. Schweickert, Barry D. Fuchs, Laurie Meadows, Michael Lynch, Patrick J. Donnelly, Kimberly Pavan, Neil O. Fishman, C. William Hanson, and Craig A. Umscheid, *A Machine Learning Algorithm to Predict Severe Sepsis and Septic Shock: Development, Implementation, and Impact on Clinical Practice*, Critical Care Medicine, Volume 47, No. 11, pp 1485-1492, 2019.

cost of a False Negative is vastly higher, the threshold t should be **pushed lower** than 0.5 to cast a wider safety net.

- **Intervention Capacity:** The hospital only has *two* RRT nurses on duty during the night shift. If the threshold is set too low (e.g., $t = 0.2$), the AI might flag 40 patients simultaneously, **completely overwhelming the nurses and causing the system to collapse**. The threshold t must be raised just enough to ensure the number of alerts **does not exceed the physical capacity of the staff** to respond effectively.
- **Uncertainty and Expected Benefit:** For patients with a borderline risk (e.g., $\hat{p}$ between 0.35 and 0.45), the AI is highly uncertain[135]. The **expected benefit of a full, disruptive RRT activation is low**. Instead of a binary rule, the decision workflow is adjusted: in this *uncertainty band*, the decision is not to activate the RRT, but to **trigger a lower-acuity action**[136], such as increasing the frequency of vital sign checks by the floor nurse.
- **Fairness Requirements:** An audit reveals that, **because of historical biases** in the documentation of symptoms, the model **systematically underestimates** the risk of deterioration for non-English-speaking patients. As a result, using a **single global decision threshold** (e.g., $t = 0.4$) produces an **unacceptably high false-negative rate** for this subgroup. To improve fairness, the hospital may **recalibrate the model**, improve the **representativeness** of the training data, **retrain** the model to reduce bias, or, where **clinically and legally appropriate**, **adjust decision thresholds** to achieve comparable clinical performance and patient protection across demographic groups.
- **Human-in-the-Loop: Human-in-the-Loop:** The hospital decides that an RRT activation is **not a fully automated action**, but a **soft alert** presented on the primary nurse's dashboard for a brief (e.g., two-minute) **clinical review** before the team is dispatched. Because a clinician **evaluates** the **alert before action** is taken, the hospital may **safely adopt a lower**

[135] This is a synthetic example. A **moderate risk** probability is **not necessarily epistemic** uncertainty; the model may be confident that the patient's risk is approximately 40%.

[136] **Lower-acuity action** is a **targeted clinical** or **operational intervention** calibrated for **less severe**, **stable**, or **uncertain conditions** that requires **fewer immediate resources** and carries **less systemic disruption** than a critical emergency response, such as increasing the frequency of routine vital sign monitoring by a floor nurse instead of activating a full rapid response team, or scheduling a routine telehealth follow-up instead of directing a patient to the emergency department.

decision threshold (e.g., $t = 0.3$) to **improve sensitivity**[137] and **detect more** patients at risk, provided that the resulting increase in **false positives remains manageable** and **does not** create **unacceptable alert fatigue** or workflow **disruption**.

By treating the threshold t not as a mathematical default, but as a **tunable policy lever**, the hospital **aligns the AI's output with clinical reality**. They **avoid the twin disasters** of missing dying patients (by respecting asymmetric costs and fairness) and **overwhelming their staff** (by respecting intervention capacity and human-in-the-loop dynamics). This perfectly illustrates that a prediction is just a number; the **decision** is where **human values** and **operational constraints** are actually applied

The Decision-Cost function

To formalize these trade-offs, we can define a **conceptual decision-cost function** that the system aims to minimize:

$$C(t) = c_{\text{FP}}P(\text{FP}|t) + c_{\text{FN}}P(\text{FN}|t) + c_{\text{delay}}\mathbb{E}[D|t] + c_{\text{workflow}}(t)$$

In this equation, c represents the **specific costs** (financial, clinical, or operational) associated with:

- $\boldsymbol{P(\text{FP}|t)}$**:** The probability of a false positive at threshold t.
- $\boldsymbol{P(\text{FN}|t)}$**:** The probability of a false negative at threshold t.
- $\boldsymbol{\mathbb{E}[D|t]}$**:** The expected delay or downstream friction caused by the decision.
- $\boldsymbol{c_{\text{workflow}}(t)}$**:** The broader operational cost of integrating this threshold into the existing human workflow.

This mathematical formulation highlights a foundational principle of applied AI: **the optimal decision threshold is rarely the one that simply maximizes overall accuracy.** Instead, the best threshold is the one that minimizes real-world costs and maximizes the operational utility of the decision.

---

[137] **Sensitivity** (also called **true positive rate** or **recall**) is a performance metric that measures a **model's ability to correctly identify all actual positive cases**, calculated as the proportion of true positives among all real positives: $\text{Sensitivity} = \frac{\text{TP}}{\text{TP+FN}}$. In other words, it answers the question: *of all cases where the condition truly exists, how many did the system successfully detect?* For example, in a hospital deterioration prediction system, a sensitivity of 90% means the model correctly identifies 90% of patients who will actually deteriorate while missing 10% (false negatives). Similarly, in fraud detection, a highly sensitive model catches most fraudulent transactions, while in cancer screening, high sensitivity reduces the chance of missing patients who have the disease.

Example # 30: AI-assisted airport baggage screening

Imagine a national aviation authority deploys an AI model to analyze X-ray images of carry-on luggage at security checkpoints[138,139]. The model outputs a probability $\hat{p}$ that a **bag contains a prohibited item** (e.g., a weapon or explosive). The decision rule is: *Send the bag to the manual search lane if* $\hat{p} \geq t$*, otherwise let it pass.*

A naive approach would be to tune the threshold t to **maximize overall mathematical accuracy** on a test dataset. However, a rigorous operations team uses the **decision-cost function** $C(t)$ to find the threshold that minimizes real-world systemic harm:

$$C(t) = c_{\text{FP}} P(\text{FP}|t) + c_{\text{FN}} P(\text{FN}|t) + c_{\text{delay}} \mathbb{E}[D|t] + c_{\text{workflow}}(t)$$

Here is how the team evaluates the components to set the optimal threshold:

- **False Positives $\boldsymbol{c_{\text{FP}} P(\text{FP}|t)}$:** If t is **set too low**, the AI **flags thousands** of clean bags. The cost c_{FP} includes the wasted time of TSA[140] agents, the frustration of passengers having their bags manually searched, and the potential for passengers to miss their flights.
- **False Negatives $\boldsymbol{c_{\text{FN}} P(\text{FN}|t)}$:** If t is **set too high**, the AI **misses actual** weapons. The cost c_{FN} is **catastrophic** (a potential security breach or loss of life). Because c_{FN} is astronomically high, it **pushes the threshold t down** to cast a wider safety net.
- **Delay and Friction $\boldsymbol{c_{\text{delay}} \mathbb{E}[D|t]}$:** If the threshold t is **pushed too low** to catch every possible threat, the **manual search queue explodes**. The **expected delay** $E[D|t]$ for *every single passenger in the airport* **spikes** because the entire checkpoint slows to a crawl. The cost c_{delay} (the

[138] Adam T. Biggs and Stephen R. Mitroff, *Improving the Efficacy of Security Screening Tasks: A Review of Visual Search Challenges and Ways to Mitigate Their Adverse Effects*, Applied Cognitive Psychology, Volume 29, No. 1, pp 142-148, 2015.

[139] Transportation Security Administration, *Various Reports on Automated Target Recognition*, U.S. Department of Homeland Security, 2023.

[140] The **Transportation Security Administration** (TSA) is a United States federal agency under the Department of Homeland Security responsible for securing the nation's transportation systems, most notably by screening airline passengers and baggage for prohibited items, such as operating X-ray machines at airport security checkpoints or managing the TSA PreCheck trusted traveler program.

economic and social value of passengers' lost time) **forces the threshold t back *up*** to prevent gridlock[141].

- **Workflow Integration $c_{\text{workflow}}(t)$:** The physical airport terminal only has two manual search stations per checkpoint. If the threshold t results in 40% of all bags requiring manual searches, the **physical workflow completely breaks down**. The cost $c_{\text{workflow}}(t)$ becomes **unsustainably high** because the airport would have to physically redesign the terminal or **hire an unfeasible number of additional staff** just to handle the AI's output.

If the team simply **maximized accuracy**, the math might dictate a threshold of $t = 0.4$, which correctly classifies 96% of bags. However, at $t = 0.4$, the **false positive rate is so high** that the **manual search lines wrap around** the terminal, causing massive delays (c_{delay}) and **physically breaking the checkpoint's operational capacity** (c_{workflow}).

By **minimizing the decision-cost function** $C(t)$ instead, the team selects a **higher threshold** of $t = 0.7$. This **slightly lowers** the overall **mathematical accuracy** to 94%, but it **drastically reduces** the **false positive rate**. The optimal threshold *keeps the manual search lines moving*, **preserves the physical workflow**, and ensures that the AI's predictions are actually actionable in the real world.

1.5.7 Deployment: Deployment is the critical phase where a trained machine learning model is **transitioned** from a **controlled development environment** and **embedded** into a **live**, **operational ecosystem**. This stage transforms a theoretical mathematical asset into a **functional**, **real-world product**.

Moving from a sandbox[142] to production requires answering a rigorous set of engineering, operational, and governance questions:

---

[141] **Gridlock** is a state of **severe systemic paralysis** where a network, process, or physical space becomes **completely congested** because the **volume of pending tasks** or **entities exceeds** the available processing capacity, such as an airport security checkpoint where manual search queues back up into the main terminal halting all passenger flow, or a computing system where competing processes indefinitely block each other from accessing shared resources, bringing the entire application to a standstill.

[142] **A sandbox** is a **fully isolated**, **controlled testing environment** in software and machine learning engineering where code, models, or configurations can be **executed** and **evaluated safely** without impacting live production systems, real user data, or end-users, such as a developer testing a new database schema migration in an isolated cloud instance to ensure it doesn't crash the live customer database, or a data scientist evaluating a newly trained fraud detection model in a staging server using historical shadow data before deploying it to the live payment processing pipeline.

- **Infrastructure and Performance**
  - Where will inference physically occur (e.g., centralized cloud, edge device, on-premise server)?
  - What is the maximum acceptable latency for the use case?
  - What specific data features will actually be available to the model in real time?
- **Resilience and Failure Handling**
  - What is the protocol when expected input data is missing, delayed, or corrupted?
  - Can the system safely abstain from making a prediction if its confidence is too low?
  - What is the defined fallback procedure if the system encounters an unrecoverable error?
  - Can the model be instantly rolled back to a previous stable version in an emergency?
- **Human-System Interaction**
  - Who is the end recipient of the model's output (e.g., an end-user, a downstream API, a clinician)?
  - How will the model's reasoning, predictions, or uncertainties be explained to them?
- **Governance and MLOps**[143,144]
  - How will model versions, code, and data pipelines be strictly controlled and tracked?

The concept of sandboxing evolved from earlier work in operating system isolation, **software fault isolation**, and **secure execution environments**. A major contribution was made by **Robert Wahbe**, **Steven Lucco**, **Thomas E. Anderson**, and **Susan L. Graham** in their **1993** paper, *Efficient Software-Based Fault Isolation*, which formalized important techniques for isolating and safely executing untrusted code. Modern **sandboxing** later expanded through technologies such as virtual machines, containers, browser security sandboxes, and cloud-based isolated environments.

[143] **MLOps (Machine Learning Operations)** is a set of engineering practices that combines machine learning, DevOps, and data engineering to automate and manage the end-to-end lifecycle of machine learning systems, including development, deployment, version control, monitoring, retraining, and governance. Common MLOps tools include **MLflow** for experiment tracking and model management, **Kubeflow** for machine learning workflow orchestration, **Apache Airflow** for data and pipeline automation, and **TensorFlow Extended (TFX)** for production ML pipelines.

The concept has no single inventor; rather, it evolved from the convergence of DevOps, software engineering, and machine learning operations practices and was widely popularized through industry guidance such as Google's **2020** white paper, *MLOps: Continuous Delivery and Automation Pipelines in Machine Learning*.

[144] Dominik Kreuzberger, Niklas Kühl, and Sebastian Hirschl, *Machine Learning Operations (MLOps): Overview, Definition, and Architecture*, IEEE Access, Volume 11, pp. 31866-31879, 2023.

- Who holds ultimate accountability for ongoing monitoring, retraining, and maintenance?

Ultimately, a **highly accurate model** sitting in a Jupyter notebook is **not a deployed AI system**. True deployment requires **engineering the system** to **survive**, **scale**, and **deliver value** in the **messy**, **constrained reality** of the real world.

Example # 31: Deploying a real-time mobile banking fraud detector

Imagine a fintech company has developed a highly accurate machine learning model to detect fraudulent credit card transactions. In the data science sandbox, the model achieves a stellar 99.5% accuracy.

- **The Naive Approach:** The lead data scientist simply exports the model as a `.pkl` file, wraps it in a basic Python script, and pushes it to a single cloud server, declaring the project *deployed*.
- **The Rigorous Approach:** The platform engineering team recognizes that a model in a notebook is not a deployed system. Before going live, they rigorously address the four deployment pillars:
  - **Infrastructure and Performance:** The team realizes that routing every transaction to a centralized cloud server **introduces a 2-second latency**, which will cause the **payment to time out** at the physical point-of-sale terminal[145]. To meet the **strict sub-50-millisecond latency** requirement, they **deploy** the model to a **distributed edge-computing environment**[146] closer to the payment gateways. They also verify that the real-time transaction stream actually contains the specific merchant data fields the model expects.

[145] **Physical point-of-sale (POS) terminal** is a **dedicated hardware device** at a **customer transaction location** that **enables electronic payments** by collecting payment information, communicating with payment networks, and completing purchases through methods such as cards, mobile wallets, or contactless payments. Examples include a retail store's card reader, a restaurant's payment tablet, a supermarket checkout scanner, or a self-service kiosk that processes customer transactions.

[146] **Distributed edge-computing environment** is a computing architecture in which data processing, storage, and AI model inference are performed on **geographically distributed devices** or **servers** located close to the data source or end user rather than relying entirely on a centralized cloud data center. This **reduces network latency**, **improves real-time responsiveness**, and can **enhance reliability** when connectivity is limited. Examples include deploying a fraud-detection model on servers located near payment gateways, running AI inference on factory machines for real-time quality inspection, or processing autonomous vehicle sensor data directly on the vehicle's onboard computers rather than sending all data to a remote cloud.

- **Resilience and Failure Handling:** In the sandbox, data was always perfect. In production, the **real-time geolocation API occasionally times out**[147]. The team programs a strict fallback protocol: if the geolocation feature is missing, the model **gracefully imputes** a default value or **abstains** from predicting, safely routing the transaction to the **legacy rule-based system**[148]. Furthermore, they implement an automated circuit breaker: if the model's transaction decline rate spikes by more than 5% in a 10-minute window, the **system instantly rolls back to the previous stable model version** to prevent locking out legitimate customers.
- **Human-System Interaction:** Instead of just silently declining flagged transactions, the system is **integrated into the customer app**. If the model predicts an 85% fraud probability, it triggers an **interactive push notification**[149]: *Was this you?* If the customer confirms, the transaction proceeds. If they **deny** it, the **transaction is blocked** and routed to a **human fraud analyst**. Crucially, the system passes SHAP values to the analyst's dashboard[150], explicitly explaining *why* the transaction was

[147] **Real-time geolocation API timeout** occurs when a **software application requests** location information from an **external geolocation service**, but the **service does not return a response** within the **required time** limit due to **network delays**, **server overload**, **connectivity problems**, or **service failures**. In real-time AI systems, such failures can interrupt model inputs and require fallback handling strategies. Examples include a fraud-detection system failing to retrieve a customer's current device location from a geolocation service within 500 milliseconds, a navigation application not receiving GPS-enhanced location data from a mapping service, or a banking application temporarily unable to verify a transaction's geographic origin.

[148] **Legacy rule-based system** is an **older decision-making system** that relies on **manually defined rules**, **conditions**, and **thresholds** created by domain experts **rather than statistical learning** from data. These systems typically use **explicit logic statements** such as IF-THEN rules and are often **retained as reliable fallback mechanisms** when newer AI models fail or require validation. Examples include a fraud detection system that declines transactions when a purchase exceeds a fixed amount or occurs in a high-risk country, an insurance system that applies predefined underwriting rules, or a credit screening system that automatically rejects applications based on fixed eligibility criteria.

[149] **Interactive push notification** is a real-time message delivered by a mobile or web application to a user's device that not only provides information but also allows the user to take immediate actions or provide input directly within the notification interface. In AI-enabled systems, interactive push notifications are often used to incorporate human feedback, verification, or approval into automated decision workflows. Examples include a banking app sending a *Was this you?* fraud alert with buttons to confirm or deny a transaction, a healthcare app prompting a patient to confirm a medication reminder, or a security application asking a user to approve a login attempt from a new device.

[150] **Analyst's dashboard** is a **specialized user interface** that **consolidates relevant data**, **system outputs**, **explanations**, and **operational controls** to help a human expert **monitor**, **interpret**, and **act** on **automated system decisions**. In AI systems, dashboards often display model predictions, confidence scores, alerts, historical context, and explainability information such as feature contributions or SHAP values. Examples include a fraud analyst dashboard showing a flagged transaction's amount, location, customer history, fraud probability score, and the features that most influenced the model's decision; a healthcare dashboard displaying patient risk scores and contributing clinical factors; or a cybersecurity dashboard presenting detected threats and their severity indicators for security analysts.

flagged (e.g., *unusual foreign merchant* and *high velocity*), enabling the human to make a rapid, informed decision.

- **Governance and MLOps:** The team abandons manual model updates. They build an **automated MLOps** pipeline using MLflow[151] and Kubernetes[152]. Every time a new model is trained, it is **automatically tested against a holdout dataset** and deployed in **prospective assisted-use pilot trials** (scoring live traffic without taking action) for 48 hours. The Head of Fraud Risk is designated as the **accountable owner**, receiving **automated alerts** if **data drift**[153] is detected (e.g., fraudsters suddenly shifting to a new type of crypto scam), triggering the retraining pipeline.

The data science team's 99.5% accurate notebook model would have caused **massive customer friction**, **crashed during API timeouts**, and **silently degraded** over time. By treating deployment as a **comprehensive engineering** and **governance challenge** – optimizing for latency, building resilient fallbacks, designing human-in-the-loop workflows, and automating MLOps – the company transformed a fragile mathematical experiment into a **robust**, **scalable**, and **secure** real-world product.

[151] **MLflow** is an open-source machine learning **lifecycle management platform** introduced by **Databricks** in **2018** that provides **tools for tracking experiments**, managing **model versions**, **packaging models**, and **deploying** machine learning systems across different environments. It was developed to address the challenges of reproducibility, collaboration, and governance in machine learning workflows. Examples include recording hyperparameters and performance metrics for competing fraud detection models, storing and versioning approved model artifacts before production deployment and maintaining an audit trail of which model version is currently serving customer transactions.

[152] **Kubernetes** is an open-source **container orchestration platform** originally created at **Google** and released in **2014**, with its design influenced by Google's internal cluster management systems such as Borg. It was later donated to and became a flagship project of Cloud Native Computing Foundation. Kubernetes automates the deployment, scaling, networking, and management of containerized applications across distributed computing environments. Examples include automatically scaling fraud detection model-serving containers during peak transaction periods, restarting failed inference services, rolling out a new model version gradually, or reverting to a previous stable deployment if monitoring detects performance degradation.

[153] **Data drift** is the **change** in the **statistical distribution** of **input data** between the data used to **train** a machine learning model and the data encountered during **production deployment**. It occurs when **real-world conditions change**, causing the **features provided** to the model to **no longer match the patterns** or **assumptions learned** during training, potentially reducing predictive performance. Examples include a fraud detection model experiencing data drift when transaction patterns shift from traditional credit card fraud to new cryptocurrency scams, a medical diagnosis model encountering changes in patient demographics or hospital testing practices, or a recommendation system facing changes in user behavior after the introduction of a new product category.

1.5.8 Monitoring: Unlike traditional software systems, machine learning models **can degrade over time** not because the underlying code fails, but because the **environment**, **data patterns**, or **user behavior** around them **changes**. **Continuous monitoring** is therefore not merely an optional post-deployment activity; it is **a critical operational requirement** for detecting when a model's assumptions **no longer align** with real-world conditions.

Comprehensive monitoring dimensions

A **robust monitoring strategy** must extend beyond basic system availability and performance checks. It requires **continuous observation** across **multiple dimensions** to ensure that the deployed system remains accurate, reliable, safe, and fair.

- **Input Quality:** Monitoring the quality and validity of incoming data by detecting **missing values**, **invalid ranges**, **unexpected formats**, and sudden **schema changes**. For example, a mobile application update may alter the structure of incoming telemetry data, causing failures or unexpected model behavior.
- **Input Distribution (Data Drift):** Tracking changes in the **statistical characteristics** of input data, such as shifts in user **demographics**, **device types**, **geographic regions**, **language patterns**, or overall **case distribution**. These changes may indicate that the model is operating in an environment different from the one it was trained on.
- **Concept and Label Drift:** Monitoring changes in the **relationship** between **input variables** and **outcomes**, as well as changes in the **distribution** of **target labels**. For example, fraud detection models may become less effective as attackers develop new strategies and behaviors.
- **Feature Pipelines:** Observing **upstream data processing** systems for **transformation errors**, **delayed data joins**[154], **missing updates**, and **stale features**[155] that may reduce model effectiveness.

[154] **Data joins** are database operations that **combine records** from **multiple data sources** or **tables** by **matching** related **fields** (known as **keys**) to create a **unified dataset** for analysis or machine learning. In feature pipelines, joins are used to assemble the complete set of inputs required by a model from different systems. Examples include combining customer transaction records with account information using a customer ID, merging hospital patient records with laboratory test results using a patient identifier, or joining e-commerce browsing history with purchase data to generate recommendation features.

[155] **Stale features** are machine learning input variables whose values are **outdated** because they have **not been refreshed** according to the **required update frequency** or because the underlying data source has **stopped providing current**

- **Model Outputs:** Analyzing **prediction distributions**, **confidence scores**, **uncertainty estimates**, and **abstention rates**[156] to identify unusual patterns or changes in model behavior.
- **Predictive Performance:** Measuring model **effectiveness** as **new ground-truth outcomes** become available. Relevant metrics may include **error rates**, **calibration quality**, **precision**, **recall**, **F_1-score**, **regression errors**, and **subgroup-specific performance** indicators depending on the application.
- **Ground Truth Outcomes:** Tracking the **availability**, **accuracy**, and **timeliness** of **production labels**. Ground-truth data is essential for evaluating whether the model continues to meet its intended performance objectives.
- **Operational Health:** Ensuring system **reliability** and **efficiency** by monitoring **inference latency**, **uptime**[157], **throughput**[158], and infrastructure **resource usage**, including CPU, GPU, memory, and storage consumption.

---

information. Stale features can cause a model to make decisions based on inaccurate representations of the current state of the world. Examples include a fraud detection model using a customer's spending pattern from six months ago instead of recent transactions, a credit risk model relying on an outdated income estimate, or a recommendation system using old user preferences that no longer reflect current interests.

[156] **Abstention rate** is the **proportion of cases** in which an AI model **intentionally declines to make a prediction** or **decision** because its **confidence** is **insufficient**, **uncertainty is too high**, or **predefined safety criteria are not satisfied**. Abstention is a **risk-control mechanism** that allows a system to **defer difficult cases to human review** or an alternative process rather than producing **potentially unreliable outputs**. Examples include a medical diagnosis model refusing to classify a rare disease case when confidence is below a safety threshold and referring it to a specialist, a fraud detection system routing ambiguous transactions to human investigators instead of automatically approving or declining them, or an autonomous vehicle system transferring control to a human operator under uncertain road conditions.

[157] **Uptime** is the **percentage of time** that a software system, service, or infrastructure component **remains operational**, **available**, and **capable of responding to requests** during a defined period. It is a **key reliability metric** used to measure **service availability** and is often expressed as a percentage (e.g., 99.9% uptime means the system is unavailable for approximately 8.8 hours per year). Examples include a fraud detection API remaining available 99.99% of the time so payment transactions can be continuously evaluated, a healthcare AI system maintaining availability for clinicians accessing patient risk predictions, or a cloud-based recommendation service remaining operational during peak shopping periods.

[158] **Throughput** is the **rate** at which a system can **process and complete tasks**, **requests**, or **data units** within a **given time period**, typically measured as requests per second, transactions per second, or data processed per second. In machine learning systems, throughput measures **how many predictions** or **inference requests** a model can **handle while maintaining acceptable performance**. Examples include a fraud detection model processing 10,000 transaction evaluations per second during peak payment periods, a natural language processing service analyzing thousands of documents per hour, or an image classification system processing millions of images per day in a manufacturing quality-control pipeline.

- **Human-System Interaction:** Evaluating how **users interact** with AI-driven decisions, including **override rates**[159], **acceptance of recommendations**, **user corrections**, and potential **automation bias**[160,161], where users may rely on AI outputs without sufficient independent judgment.
- **Harm, Fairness, and Safety:** Continuously assessing whether the system produces **unequal error rates** across **relevant groups**, generates **harmful outcomes**, **violates safety expectations**, or produces patterns that **require human intervention**.
- **Feedback Loops:** Identifying situations where model **predictions influence the future data** used for decision-making or retraining. For example, a predictive policing system that influences where officers are deployed may generate additional enforcement data in selected areas, reinforcing the model's original assumptions and potentially amplifying existing biases.

Combating hidden technical debt

Comprehensive monitoring is essential for addressing the **hidden technical debt**[162] in machine learning systems. Unlike traditional software debt, ML systems **accumulate** additional **complexity** through **evolving** data

[159] **Override rate** is the **proportion of AI-generated recommendations**, **predictions**, or **decisions** that are **rejected**, **modified**, or **replaced by a human user** or a **downstream decision process**. It is a **human-system interaction metric** used to evaluate user trust, model usefulness, workflow alignment, and potential issues with AI performance. Examples include physicians overriding an AI-generated diagnosis recommendation in 15% of cases after reviewing additional clinical information, loan officers rejecting an AI-generated credit risk recommendation when they identify missing context, or fraud analysts reversing automated transaction blocks after manual investigation.

[160] **Automation bias** is the **tendency of humans** to place **excessive trust in automated systems** and **accept** their outputs **without sufficient independent evaluation**, even when the system's recommendations are incorrect or inappropriate. It is a **cognitive bias** that can cause users to **ignore contradictory evidence**, **reduce critical judgment**, or **fail to detect AI errors**. Examples include a physician accepting an AI diagnostic suggestion despite conflicting patient symptoms, a pilot failing to recognize an incorrect aircraft automation decision, or a financial analyst approving a high-risk transaction because an AI system incorrectly marked it as safe.

[161] Ihsan Ayyub Qazi, Ayesha Ali, Asad Ullah Khawaja, Muhammad Junaid Akhtar, Ali Zafar Sheikh, and Muhammad Hamad Alizai, Automation bias in large language model–Assisted diagnostic reasoning among physicians trained in AI literacy—A randomized clinical trial, NEJM-AI, Volume 3, Issue 5, 2026.

[162] **Hidden technical debt** in machine learning systems refers to the **accumulation of latent engineering**, **data**, and **operational problems** that are **not immediately visible** in the model code itself but **gradually increase system complexity**, **maintenance costs**, and **risk over time**. The concept was formalized in machine learning by **D. Sculley** and colleagues in their influential **2015** paper, *Hidden Technical Debt in Machine Learning Systems*, which described how ML systems **accumulate unique forms of technical debt** through **data dependencies**, **feedback loops**, **configuration complexity**, **entangled components**, and **changing external environments**. Examples include a fraud detection model becoming unreliable because upstream transaction data schemas silently change, a recommendation system degrading because user behavior shifts over time, or a production model failing because undocumented feature-engineering logic no longer matches the training pipeline.

dependencies, **tightly coupled** components, **feedback loops**, **configuration challenges**, and **undocumented changes** in surrounding infrastructure.

Without **continuous**, **multi-dimensional monitoring**, these hidden dependencies can lead to **silent failures**[163], **declining** predictive **performance**, **fairness issues**, and **increased operational risk**. Effective monitoring therefore serves as a fundamental mechanism for maintaining the reliability, safety, and long-term value of machine learning systems after deployment.

Example # 32: The "silent decay" of an AI-driven collections system

Imagine a large fintech[164] company deploys a machine learning model to predict customer loan default risk. Based on the prediction, the system automatically routes customers to different repayment strategies: *Standard* (automated email), *Watchlist* (soft phone call), or *Aggressive* (hard collections and automated SMS demands).

- The Naive Approach (accumulating hidden debt): The data science team only monitors the model's offline accuracy (AUC) and assumes the system is healthy. Over 18 months, the surrounding infrastructure changes, silently accumulating massive technical debt.
- **The Rigorous Approach (combating debt via monitoring):** An MLOps team implements the comprehensive monitoring strategy, actively hunting for the specific types of hidden debt identified by Sculley and colleagues.

Here is how the hidden debt accumulates, and how the monitoring strategy combats it:

- **Undeclared Consumers and Data Dependencies**
  - **The hidden debt:** The backend engineering team updates the *transaction timestamp* format in the core database from UTC to local

[163] **Silent failures** are failures in which a machine learning system **continues to operate and produce outputs** without generating **obvious errors** or **triggering system alerts**, while its predictions, decisions, or overall performance have **degraded in ways** that may **not be immediately visible**. These failures are particularly dangerous because the system **appears healthy from an operational perspective** (e.g., it is running and responding to requests) while becoming **increasingly inaccurate**, **biased**, or **unreliable**. Examples include a fraud detection model continuing to approve transactions normally while fraud patterns evolve and detection accuracy declines, a medical risk prediction model producing predictions after a hospital changes its data-recording practices and key input features become unreliable, or a recommendation system continuing to generate suggestions after user preferences shift, causing engagement to gradually decrease without a technical outage.

[164] **FinTech (financial technology)** is the use of technology to deliver, improve, and automate financial services such as payments, banking, lending, investing, and insurance.

time to fix a minor UI bug. They don't notify the ML team. The ML pipeline **silently ingests this change**, shifting all time-based features (like *hours since last payment*) by several hours, completely breaking the model's temporal logic.

  - **Combating it via monitoring:** The team **monitors input quality** and feature pipelines. They implement **strict schema validation** and **sanity checks** on incoming data. The moment the timestamp distribution shifts anomalously, an **automated alert fires**, pausing the pipeline before the corrupted data reaches the model.

- **Self-reinforcing feedback loops**
  - **The hidden debt:** The model starts **routing borderline customers** to the **Aggressive SMS** collection flow. Because these automated SMS demands are **highly effective at extracting immediate payments** out of customer fear, the system logs these accounts as *successfully repaid*. The model's training data now shows that *high-risk* customers **always pay when sent an SMS**. The model learns to **over-predict default risk** simply to trigger the SMS flow, creating a **self-fulfilling prophecy** that severely **miscalibrates** the actual financial risk.
  - **Combating it via monitoring:** The team monitors **feedback loops and outcomes**. Instead of just looking at the final *repaid* label, they **track the intervention applied versus the outcome**. They discover the aggressive SMS flow is **artificially inflating** the success rate of high-risk predictions. To fix this, they implement **counterfactual logging**[165] and adjust the training pipeline to account for the intervention bias.

- **System entanglement and configuration complexity**
  - **The hidden debt:** The marketing team launches a new *90-day grace period* **promotional feature**. The ML model is **entirely unaware** of this

[165] **Counterfactual logging** is a data collection and monitoring technique that **records not only the actions taken** by an AI system and their **observed outcomes**, but also **information about alternative actions** that **could have been taken** and their **potential outcomes**. It is used to **reduce bias from feedback loops** and estimate **what might have happened** under **different decisions** or **interventions**. Counterfactual logging is especially important in systems where **AI decisions influence future data**, because **observed outcomes** may **reflect** the **effect of the intervention** rather than the **original prediction quality**. Examples include a fraud detection system recording whether a transaction was blocked, approved, or reviewed by a human along with the eventual fraud outcome, a recommendation system logging alternative items that could have been shown to a user and whether they would have resulted in engagement, or a healthcare model recording both the treatment assigned to a patient and relevant outcomes to estimate what might have occurred under a different treatment strategy.

business logic. When customers use the grace period, the model **interprets the delayed payment** as *severe financial distress* and **downgrades** their credit score. Furthermore, the team has 14 different, **unversioned configuration files**[166] controlling how features are scaled and normalized, making it **impossible** to accurately **roll back**[167] the model when it starts failing.

  - **Combating it via monitoring:** The team monitors **input distribution** and **model outputs**. When the distribution of the *days since last payment* feature **suddenly spikes**, they correlate it with the marketing team's release calendar, realizing the model is **misinterpreting the grace period**. Simultaneously, they **eliminate configuration complexity** by **migrating all feature transformations** into a centralized, **version-controlled** feature store (like Feast or Tecton), ensuring the training and serving **environments** are **perfectly synchronized**.

- **Complex data dependencies (Glue Code)**
  - **The hidden debt:** To connect the ML model to the **legacy collections dashboard**, a previous engineer wrote 2,000 lines of **brittle**[168], **undocumented** *glue code*[169] that **manually maps** the model's output

---

[166] **Unversioned configuration files** are system configuration files that **lack systematic tracking** of their **historical changes**, **ownership**, and **previous states** through a **version-control mechanism** such as Git or another configuration management system. In machine learning systems**, configuration files often define critical operational settings** such as feature transformations, model parameters, data sources, thresholds, and deployment settings. Without versioning, teams **cannot reliably determine** what configuration produced a specific model behavior or **reproduce earlier** system states. Examples include a credit-risk model using an undocumented feature normalization setting that changes from month to month, a recommendation system where ranking parameters are manually edited without records, or a fraud detection pipeline where decision thresholds are modified without maintaining previous versions.

[167] **Roll back** is the process of **reverting** a **software system**, **machine learning model**, **configuration**, or **deployment environment** to a **previously known stable version** after detecting failures, performance degradation, or unexpected behavior. Rollbacks are a key **reliability mechanism in production systems** because they allow teams to quickly **restore service** while investigating the underlying issue. Examples include reverting a fraud detection model from version 3.2 to version 3.1 after false declines increase sharply, restoring a previous feature-processing pipeline after a faulty data transformation causes prediction errors, or returning a web application to an earlier release after a production deployment introduces critical bugs.

[168] **Brittle** refers to a software component that is **highly fragile** and **likely to fail** when **small**, **unexpected changes** occur in its **inputs**, **environment**, **dependencies**, or **surrounding systems**. Brittle systems often **lack flexibility**, **validation**, **error handling**, or **modular design**, making **maintenance and upgrades difficult**. Examples include a machine learning pipeline that breaks when a data column is renamed, an application that fails after a minor API response format change, or a manually configured deployment script that stops working after an infrastructure update.

[169] **Glue code** is software written to **connect separate systems**, **applications**, **libraries**, or **components** that were **not originally designed to work together**. Although often **necessary** for **integration**, **excessive** or **poorly maintained** glue code can create **technical debt** because it may contain **custom assumptions**, **duplicated logic**, and **undocumented dependencies**. Examples include code that converts a machine learning model's probability outputs into categories

probabilities to the dashboard's **rigid UI categories**[170]. When the model is updated to output a new confidence score, the **glue code silently fails**, defaulting all users to the *Standard* bucket, rendering the AI entirely useless without throwing a single error.

- **Combating it via monitoring:** The team monitors **operations** and **human-system Interaction**. By **tracking** the actual **distribution** of the model's **final routed decisions** (e.g., the percentage of users sent to *Aggressive* vs *Standard*), they notice the *Aggressive* bucket has **dropped to 0%**. This **triggers an immediate investigation**, uncovering the **broken glue code** before it causes millions in lost revenue.

If the team had only **monitored** the model's mathematical accuracy **in a vacuum**, they would have been **blindsided** by a 30% spike in **actual financial losses**, *with no idea why*. By treating the ML model as just one tiny component of a **massive**, **fragile system**, and applying **multi-dimensional monitoring**, they successfully **identified** and **neutralized** the **hidden technical debt**. This proves that in production ML, monitoring the environment and the system's behavior is just as critical as monitoring the model's math.

required by a legacy business dashboard, scripts that transform data formats between two databases, or middleware that translates messages between a payment processor and an accounting system.

[170] **Rigid UI categories** are **fixed user-interface classifications** or **display options** that **cannot easily adapt** to new data structures, model outputs, or business requirements **without manual changes** to the software. They can **limit the flexibility** of an AI system when the model produces more detailed or continuous outputs than the interface can represent. Examples include a customer-risk dashboard that only accepts three categories (*low*, *medium*, and high) while a new model produces a continuous risk score from 0 to 100, a medical dashboard that supports only predefined diagnosis labels while an AI system generates probabilistic predictions, or a customer support system restricted to a fixed set of issue types despite new emerging categories.

An Instructive Example of a Model Card

In this example, we illustrate how a Model Card can be used to provide **transparency** for a machine learning model designed to **predict the likelihood of heart disease**. By **documenting critical aspects** such as data sources, performance metrics, and fairness considerations, the Model Card helps users understand the **model's behavior**, its **potential biases**, and its **limitations**. This structured approach ensures that the model is **used ethically** and **in alignment** with its intended purpose, while promoting **accountability** and **trust** among stakeholders.

4.8.1 Model Card: Heart Disease Prediction Model

Model Overview

- **Model Name:** Heart Disease Prediction Model
- **Purpose:** The model is designed to predict the likelihood of heart disease in patients based on their medical history, lifestyle factors, and clinical measurements.
- **Type:** Binary Classification (heart disease: Yes/No)
- **Model Architecture:** Random Forest Classifier trained on patient data (age, blood pressure, cholesterol levels, etc.)
- **Intended Use:** The model is intended to assist healthcare professionals by providing an additional tool to help identify high-risk patients who may require further diagnostic testing or preventive care.

Data Description

- **Data Source:** The dataset is derived from a publicly available heart disease dataset (e.g., Cleveland Heart Disease dataset) consisting of 300 records from a hospital database.
- **Features:** The model uses features such as age, gender, blood pressure, cholesterol levels, maximum heart rate, and the presence of chest pain, among others.
- **Data Preprocessing:** Missing values were imputed using the mean or mode for numerical and categorical data, respectively.
- **Exclusions:** The model does not include information on race, ethnicity, or genetic predisposition, as those factors were not part of the dataset.

Performance Metrics

- **Overall Accuracy:** 85%
- **Precision:** 0.80
- **Recall:** 0.75
- **F_1 Score:** 0.77
- **Performance by Subgroup**
  - **Male Patients:** Precision $= 0.83$, Recall $= 0.78$
  - **Female Patients:** Precision $= 0.75$, Recall $= 0.70$
  - **Patients with High Cholesterol:** Precision $= 0.85$, Recall $= 0.80$
  - **Patients with Normal Blood Pressure:** Precision $= 0.78$, Recall $= 0.72$
- **Fairness Observations:** The model performs better on male patients compared to female patients, indicating potential gender bias. The model also tends to miss heart disease predictions in women with normal blood pressure.

Known Limitations

- **Bias in Data:** The dataset includes fewer female patients, potentially leading to biased performance in predicting heart disease for women.
- **Generalizability:** The model was trained on a dataset that may not fully represent all global populations. Its performance might vary with different demographics and health conditions not present in the training data.
- **Feature Limitations:** Certain relevant features such as family history and lifestyle factors (e.g., smoking, diet) were not included in the dataset, which may affect the model's accuracy in predicting heart disease risk.

Intended and Inappropriate Uses

- **Intended Use:** The model is intended to support medical professionals in identifying patients at higher risk of heart disease. It should not be used as the sole basis for a diagnosis but as an additional decision support tool.
- **Inappropriate Use:** The model should not be used for predicting heart disease risk in populations that were not represented in the training data (e.g., certain ethnic groups). It should not replace clinical judgment or comprehensive diagnostic testing.

Ethical Considerations

- **Fairness:** The model has potential gender and demographic biases, which should be addressed before full-scale deployment. Regular audits should be conducted to ensure fair treatment of all patient subgroups.

- **Impact of Misuse:** Misuse of the model, particularly in settings with underrepresented groups, could lead to harm. For example, under-predicting heart disease in women could delay necessary interventions, exacerbating health inequalities.

Additional Considerations

- **Future Work:** There is an opportunity to improve the model by integrating additional features such as family history, smoking status, and genetic markers. A more diverse dataset should also be used to mitigate bias and improve the model's fairness and generalizability.

Takeaways from the Model Card

- **Data Transparency:** Users can see where the data came from, what it includes, and what is excluded (such as race and family history).
- **Performance by Group:** The model's performance is evaluated not just on overall accuracy but also broken down by subgroups (e.g., gender), which helps identify potential fairness issues.
- **Known Limitations:** The document highlights known biases in the dataset, such as gender imbalance, and sets expectations about the model's generalizability.
- **Ethical Guidance:** Clear guidelines are given on appropriate use, emphasizing that the model should not replace medical expertise or be used for underrepresented groups.

This Model Card provides transparency around the heart disease prediction model, helping stakeholders understand its strengths, weaknesses, and fairness considerations. It ensures that the model is used ethically and responsibly, reducing the risk of harmful consequences, such as biased healthcare decisions.

Types of AI Problems

AI problems can be grouped according to the **type of output required**, the **structure of the underlying decision process**, and the **way success is measured**. Although many real-world systems combine multiple problem types, identifying the dominant **problem formulation** helps determine the **appropriate modeling approach**, **evaluation strategy**, and **potential failure modes**. Table 2 summarizes the major categories of AI problems, their typical objectives, representative applications, common evaluation measures, and frequent framing mistakes that can lead to misleading conclusions or ineffective solutions.

Table 2: Major types of AI problems, their desired outputs, representative applications, evaluation metrics, and common framing errors.

Problem Type	Desired Output	Representative Example	Typical Evaluation	Common Framing Error
Classification	Discrete class	Benign vs malignant lesion	Accuracy, sensitivity, specificity, F_1, AUROC, AUPR	Treating all errors as equally costly
Regression	Continuous value	Predicting energy demand	MAE, RMSE, R^2, interval coverage	Ignoring skew, heteroscedasticity, or asymmetric cost
Ranking	Ordered items	Ordering search results by relevance	NDCG, MAP, precision@k	Evaluating items independently of list position
Recommendation	Personalized items or actions	Recommending courses of products	Recall@k, NDCG, utility, diversity	Optimizing clicks rather than long-term benefit
Clustering	Unlabeled groups	Discovering customer segments	Silhouette, stability, domain validity	Treating clusters as objectively *real* categories
Search	Relevant state, path, or document	Route finding or document retrieval	Relevance, path cost, success rate, latency	Defining an incomplete search space

Planning	Sequence of actions	Robot task planning	Goal success, cumulative cost, constraint violations	Assuming a static or fully known environment
Control	Sequential feedback action	Maintaining a drone's trajectory	Stability, tracking error, safety, energy	Ignoring delayed or noisy feedback
Anomaly Detection	Outlier or anomaly score	Detecting fraudulent transactions	Precision-recall, detection delay, false-alarm rate	Assuming all rare cases are harmful
Generation	New content	Generating text, images, codes, or designs	Human evaluation, factuality, task success, safety	Equating fluency with truth
Forecasting	Time-indexed future values	Predicting traffic volume	MAE, RMSE, MASE, interval coverage	Randomly splitting temporally ordered data
Causal Estimation	Effect of an intervention	Effect of tutoring on learning	Bias, interval coverage, sensitivity analysis	Interpreting correlation as intervention effect
Decision Optimization	Recommend feasible action	Allocating ambulances or inventory	Expected utility, regret, constraint satisfaction	Optimizing an inaccurate or incomplete objective

1.6.1 Classification: Classification predicts one or more discrete categories. For **binary classification**, the response variable $Y \in \{0, 1\}$. Examples include fraud versus legitimate transaction, disease versus no disease, and spam versus non-spam. In **multiclass classification**, the response variable $Y \in \{1, \cdots, K\}$. Exactly one class is selected, such as identifying a handwritten digit.

In **multilabel classification**, the response variable $Y \subseteq \{1, \cdots, K\}$. Multiple labels may be present, such as assigning several diagnoses to a clinical record.

The class definition must be **operationally meaningful**. A label such as *high risk* is incomplete unless the event, time horizon, and threshold are specified.

1.6.2 Regression: Regression predicts a **numeric quantity**: $Y \in \mathbb{R}$. Examples include price, temperature, remaining useful life, length of stay, and energy consumption. The choice of loss encodes an assumption about error. $L_{\text{MSE}}(y, \hat{y}) = (y - \hat{y})^2$ **penalizes large errors heavily**, while $L_{\text{MAE}}(y, \hat{y}) = |y - \hat{y}|$ is **more robust to large deviations**. The correct loss should reflect the application, not merely convention.

1.6.3 Ranking and recommendation: Ranking produces an **ordered list**. Recommendation commonly **combines ranking** with **personalization** and **availability constraints**. A recommendation system is not simply predicting what a user will click. It selects what the user will be shown, thereby **influencing future preferences** and **behavior**. This creates a feedback loop:

Past exposure → Observed interaction → Training data → Future exposure

Consequently, observed clicks are not pure measures of preference; they are **conditional on previous rankings**, **interface design**, **position**, and **availability**.

1.6.4 Clustering: Clustering searches for **structure without preassigned outcome** labels. Examples include grouping molecular profiles, segmenting customers, organizing documents, and discovering sensor operating regimes. A mathematically compact partition may still be scientifically meaningless. Therefore, clustering requires:

- stability analysis;
- sensitivity to representation and scaling;
- inspection of cluster composition;
- domain validation;
- caution against reifying algorithmic groups as natural categories.

1.6.5 Search, planning, and control: These are classical AI problem types. **Search** explores a **space of states** or **candidates**. It requires an **initial state**, **actions** or **transitions**, a **goal test**, a **path cost**, and possibly a **heuristic**[171,172,173].

Planning identifies a **sequence of actions** expected to **achieve a goal** while **satisfying constraints**.

Control repeatedly observes a system and **selects actions over time**:

$$x_{t+1} = F(x_t, u_t, w_t)$$

where x_t is the **state**, u_t is the **control action**, and w_t represents **disturbances** or **uncertainty**. Unlike static prediction, control changes the process being predicted.

1.6.6 Anomaly detection: Anomaly detection identifies **observations** that **differ from a reference pattern**. An anomaly may indicate **fraud**, **equipment failure**, **cyberattack**, **rare disease**, **data corruption**, and **legitimate novelty**. The central challenge is that *unusual* is not the same as *undesirable*. An anomaly detector **requires an investigation** or **response policy**; otherwise, it merely produces *unusualness scores*[174].

---

[171] **Heuristic** is a **problem-specific rule**, **strategy**, or **evaluation function** that **guides** a **search** or **optimization** algorithm toward **promising solutions** by estimating **which choices are most likely to lead to the goal**, thereby **reducing computational effort** *without guaranteeing an optimal solution*. The broader concept of heuristic problem solving was popularized by mathematician **George Pólya** in his influential **1945** book *How to Solve It*, which presented **practical strategies for solving mathematical problems**. In artificial intelligence, heuristic search was formally introduced by **Allen Newell**, **John Clifford Shaw**, and **Herbert A. Simon** in **1956** through the **Logic Theorist**, the first AI program to use heuristics for automated theorem proving.

Today, heuristics remain fundamental in AI search and planning and are also widely used in machine learning to describe **simple**, **hand-crafted rules** or **baseline methods** against which learned models are compared. Examples include the straight-line (Euclidean) distance heuristic used by the A* search algorithm for route planning, selecting the chess move that captures the highest-value opponent piece first to reduce the search space, or using a simple fraud detection heuristic that flags all transactions exceeding a fixed monetary threshold before comparing its performance with a trained machine learning model.

[172] **Allen Newell**, **John Clifford Shaw**, and **Herbert A. Simon**, *Elements of a theory of human problem solving*, Psychological review, 1958.

[173] Leo Gugerty, *Newell and Simon's Logic Theorist: Historical Background and Impact on Cognitive Modeling*, Proceedings of the human factors and ergonomics society annual meeting, Volume 50, No. 9, pp. 880-884, 2006.

[174] **Unusualness score** (also called an **anomaly score** or **outlier score**) is a numerical measure assigned by an anomaly detection algorithm that **quantifies the degree** to which an **observation deviates** from the **normal patterns learned** from a **reference dataset**. **Higher scores** indicate that an observation is more anomalous, **but they do not**, by themselves, **determine whether the observation is harmful**, **fraudulent**, or **requires intervention**. Examples include a fraud detection system assigning a transaction an anomaly score of 0.97 because its amount, location, and timing differ markedly from a customer's historical behavior; a predictive maintenance system giving a vibration sensor reading a high anomaly score because it deviates from normal operating conditions; or a network intrusion detection system assigning elevated anomaly scores to unusual traffic patterns that may warrant investigation but could also reflect legitimate changes in user activity.

1.6.7 Generation: Generative systems **create new instances conditioned** on **prompts**, **examples**, or **context**. Applications include **language generation**, **image synthesis**, **software generation**, **molecular design**, **music**, **simulation**, and **synthetic data**. Three separate evaluation questions are necessary:

- **Plausibility:** Does the output resemble valid examples?
- **Grounded correctness:** Is the content supported by evidence or constraints?
- **Utility and safety:** Does it help the intended user without unacceptable risk?

A fluent output[175] can still be false, unsafe, biased, or irrelevant.

1.6.8 Forecasting: Forecasting predicts future values while accounting for temporal ordering and dependence.

$$\hat{y}_{t+h|t} = \mathbb{E}[Y_{t+h}|\mathcal{I}_t]$$

where h is the **forecast horizon** and $\mathcal{I}_t$ represents the **information available** at time t. Examples include **predicting electricity demand**, **forecasting hospital admissions**, **estimating future sales**, **predicting traffic volume**, **forecasting weather** or **equipment failure**.

Forecasting may produce **point estimates**[176], **prediction intervals**[177], **quantiles**[178], or **complete probability distributions**. Typical evaluation

[175] **Fluent output** is **AI-generated content** that is **grammatically correct**, **coherent**, **well-structured**, and **stylistically natural**, giving the **appearance** of being written or produced by a **competent human**. Fluency evaluates the **quality of the presentation** rather than the **factual accuracy**, **correctness**, **usefulness**, or **safety of the content**. Consequently, a highly fluent output may still contain **hallucinations**, **factual errors**, **logical inconsistencies**, or **harmful recommendations**. Examples include a large language model generating a well-written but factually incorrect explanation of a historical event, an AI coding assistant producing syntactically correct software that contains subtle logical bugs, or an image generation model creating a photorealistic image of a person or event that never actually existed.

[176] **Point estimate** is a **single numerical prediction** of an unknown quantity or future outcome produced by a statistical or machine learning model. Unlike interval or probabilistic forecasts, a point estimate provides one best estimate without explicitly expressing uncertainty. Examples include forecasting tomorrow's electricity demand as 12,500 MW, predicting next month's sales to be $2.4 million, or estimating that a patient has a 72% probability of developing a disease.

[177] **Prediction interval** is a **range of values** within which a **future observation** is **expected to fall** with a **specified probability**, accounting for **uncertainty in the prediction**. Unlike a **confidence interval**, which **quantifies uncertainty about a population parameter**, a **prediction interval quantifies uncertainty** about an **individual future outcome**. Examples include forecasting that tomorrow's temperature will be 25°C, with a 95% prediction interval of 22°C to 28°C, or predicting that next week's sales will fall between $95,000 and $110,000 with 90% confidence.

[178] **Quantile** is a value that **divides a probability distribution** or dataset into **specified proportions**, indicating the **point below which a given percentage of observations falls**. Quantile forecasts summarize different parts of the predictive

measures include MAE, RMSE, MASE, interval coverage, and interval width. Because time order matters, **randomly splitting observations** can **leak future information** into training. Evaluation should instead use **temporal holdouts**[179] or **rolling-origin validation**[180]. Important considerations include:

- trend and seasonality;
- autocorrelation and lagged effects;
- forecast horizon;
- external predictors;
- structural changes and distribution shift;
- uncertainty in future outcomes.

A forecasting model should be compared with appropriate naive or seasonal baselines and monitored because relationships learned from the past may not remain stable.

1.6.9 Causal estimation: Causal estimation asks how an intervention changes an outcome:

$$\tau = \mathbb{E}[Y(1) - Y(0)]$$

where $Y(1)$ and $Y(0)$ denote **potential outcomes** under **treatment** and **no treatment** respectively[181]. The fundamental difficulty is that both potential

distribution rather than providing only a single prediction. Examples include forecasting the 10th, 50th (median), and 90th percentiles of electricity demand, estimating that there is only 10% chance sales will fall below $80,000, or reporting the median predicted travel time instead of the mean.

[179] **Temporal holdout** is a model evaluation strategy in which a **forecasting model** is **trained using historical observations** and **tested exclusively** on **chronologically later data**, thereby **preserving** the **natural ordering of time** and preventing information from the future from influencing model training. Examples include training a retail sales forecasting model on data from 2019–2024 and evaluating it on 2025 data or training a hospital admissions forecasting model on the first three years of patient records and testing it on the fourth year.

[180] **Rolling-origin validation** (also called **walk-forward validation**, **forward-chaining validation**, or **rolling forecasting origin**) is a time-series model evaluation method in which the **training dataset** is **repeatedly expanded** or **moved forward through time**, with the model **evaluated** on the **next unseen time period** at each step. This approach provides a realistic assessment of forecasting performance while **preserving temporal order** and **preventing information leakage** from the future into the training data. The method has long been used in forecasting and was formally described and popularized by **Rob J. Hyndman** and **George Athanasopoulos** in the first edition of *Forecasting: Principles and Practice* (**2013**). Examples include training a retail sales forecasting model on January–June data and testing it on July, then retraining on January–July and testing on August, or repeatedly updating an electricity demand forecasting model as each new month of observations becomes available.

[181] The **Neyman-Rubin Potential Outcomes Framework**, originally introduced by **Jerzy Neyman (1923)** and later formalized and extended by **Donald Rubin (1974)**, is a foundational framework for causal inference that defines causal effects by **comparing an individual's potential outcomes** under **different treatment conditions**. For each unit (e.g., a person, patient, or organization), the framework assumes two potential outcomes: one if the unit receives the treatment, denoted as $Y(1)$, and another if it does not, denoted as $Y(0)$. The causal effect is defined as the difference between these two potential outcomes. However, because only one of these outcomes can be observed for any individual while the other remains counterfactual, the true individual causal effect cannot be directly measured – a challenge known as

outcomes cannot be observed for the same unit at the same time. Causal inference therefore depends on design and assumptions such as:

- randomization;
- exchangeability;
- positivity;
- consistency;
- correct temporal ordering;
- control of confounding.

A highly accurate predictor of treatment assignment or outcome is not automatically a valid estimator of treatment effect.

1.6.10 Decision optimization: Decision optimization selects the best feasible action under objectives, uncertainty, costs, and constraints:

$$a^* = \arg\max_{a \in \mathcal{A}} \mathbb{E}[\mathcal{U}(a, Y)|X = x]$$

where $\mathcal{A}$ is the **set of feasible actions** and $\mathcal{U}(a, Y)$ represents the **utility of taking action** a. Examples include **allocating ambulances**, **scheduling staff**, **determining inventory levels**, **selecting treatment actions**, **optimizing delivery routes**, and **assigning limited interventions**. Prediction and optimization answer different questions:

- **Prediction:** What is likely to happen?
- **Decision optimization:** What should be done?

A highly accurate prediction **does not necessarily produce** the best decision. **Decision quality** also depends on **error costs**, **intervention benefits**, **resource limits**, **safety requirements**, **fairness**, and **uncertainty**. Typical evaluation criteria include:

- expected utility;

---

the *fundamental problem of causal inference*. Consequently, the framework focuses on estimating average treatment effects across groups using randomized experiments or statistical methods designed to account for confounding in observational data.

The **fundamental problem of causal inference** refers to the impossibility of directly observing the causal effect of a treatment on an individual. For any unit, only one potential outcome can be observed: either the outcome under treatment $Y(1)$ or the outcome under control $Y(0)$. **The missing outcome – the counterfactual – can never be observed for the same individual at the same time.** Therefore, causal inference relies on estimating causal effects by comparing groups, using methods such as randomized controlled trials or statistical adjustment techniques to approximate the unobserved counterfactual outcome.

- total cost;
- regret;
- constraint violations;
- resource utilization;
- safety and fairness outcomes.

Common errors include optimizing an **incomplete proxy objective**, treating **risk as equivalent to intervention benefit**, **ignoring operational constraints**, and evaluating predictive accuracy **without evaluating the resulting actions**.

Translating Real Problems into AI Tasks

AI systems are most valuable when they are **designed as solutions** to **meaningful decisions**, *not as exercises in fitting patterns to available data*. The central challenge in applied AI is **not selecting an algorithm** or **maximizing a benchmark score** but translating a real-world need into a clearly defined task with **appropriate inputs**, **outputs**, **constraints**, and **evaluation criteria**. This requires understanding the **context in which decisions** are made, the **people affected by those decisions**, and the **consequences of system errors**. Problem framing is therefore the foundation of reliable AI; it determines **what should be predicted**, **what evidence is relevant**, **what success means**, and whether a model is the right tool at all.

1.7.1 Begin with the decision, not the dataset: A pervasive failure pattern in applied machine learning is the ***solution looking for a problem*** approach. This data-first trap typically unfolds as follows:

- Acquire a convenient, novel, or easily accessible dataset.
- Arbitrarily select an *interesting* target variable to predict.
- Train multiple algorithms to maximize a mathematical metric (such as AUC, accuracy, or F_1 score).
- Report the highest-performing model.
- **Only then** search backward for a business, clinical, or operational use case to justify the work.

This approach frequently results in **highly accurate mathematical curiosities** that **deliver zero real-world value** because they **do not actually solve a meaningful problem**.

A defensible, **value-driven AI lifecycle** rigorously *reverses this sequence*, **anchoring** every **technical choice** to a **specific operational need**:

- **Identify the Decision:** Pinpoint the exact operational choice, workflow bottleneck, or unmet capability that requires improvement.
- **Determine Information Needs:** Ascertain what specific foresight, risk assessment, or information would actually make that decision better.
- **Select the Analytical Paradigm:** Decide whether the problem requires *prediction* (forecasting an outcome), *causal inference* (estimating the

effect of an intervention), *optimization* (allocating resources efficiently), or *automation* (executing a routine task).

- **Define the Operating Context:** Explicitly define the target population, the physical or digital environment, and the operational constraints under which the system will function.
- **Source Purpose-Built Data:** Collect, construct, or curate data specifically tailored to answer the defined question, rather than forcing a question to fit a convenient dataset.
- **Evaluate Against the Decision:** Build and evaluate the system *against its actual ability* to improve the target decision in the real world, rather than just optimizing an abstract, offline mathematical metric.

Effective AI systems are built by starting with a meaningful decision, action, or operational outcome—not by searching for problems inside available data. Data, algorithms, and metrics should be selected because they support a clearly defined objective, not because they are convenient or interesting. A technically excellent model that does not improve a real-world decision is merely a statistical artifact.

Example # 33: Medical AI

A medical AI system designed to **detect cancer from X-rays** should **not be evaluated only** by its **accuracy score** on a test dataset. While a high accuracy rate may show that the AI can identify patterns in images, the **real measure** of success is whether it helps doctors **make better decisions** and **improves patient outcomes** in practice. For example, the system should be evaluated on whether it helps **detect cancer earlier**, **reduces missed diagnoses**, **supports doctors' workflows**, and **ultimately leads to better treatment** and **survival rates for patients**. This means the AI should be judged by its *impact on real-world medical decisions*, not just by an *offline mathematical performance metric*.

1.7.2 A comprehensive problem-framing canvas: Before writing a single line of code, the problem must be **anchored to a specific**, **actionable outcome**. Frame the project by asking the following critical questions:

- **The Decision:** What specific decision will be altered, informed, or automated by this system?
- **The Actor:** Who (or what) is the decision-maker responsible for executing this choice?
- **The Actions:** What concrete interventions or actions are actually available to the decision-maker once the output is generated?
- **The Necessity of AI:** Is a complex machine learning model actually required to solve this problem?
- **The Simpler Alternatives:** Could the objective be achieved more effectively, cheaply, or reliably using a deterministic rule, a checklist, a basic statistical summary, or simply a process redesign?

Ultimately, a model that **does not change a decision** or **trigger a concrete action** has **zero operational value**, regardless of how high its mathematical accuracy score might be.

Example # 34: The "high-accuracy" employee attrition model that changed nothing

Imagine a large corporate HR department wants to reduce employee turnover. They hire a data science team to solve the problem.

- **The Naive Approach:** The data science team takes a convenient dataset of historical employee records (salary, tenure, performance reviews, commute distance). They train a complex Gradient Boosting model to predict *which employees will quit in the next 12 months*. The model achieves an impressive 88% AUC. The team proudly hands the HR Director a list of 500 *high-risk* employees. The HR Director asks, *Okay, so what do we do with them?* The company has no budget to give 500 people raises, and managers don't have time to intervene with 500 people. The **model is abandoned**, having **delivered zero operational value** despite its high accuracy.
- **The Framed Approach (applying the canvas):** A rigorous AI product manager **stops the team before they write any code** and forces them to fill out the **problem-framing canvas** for the decision and action:
    - **The decision:** *Which specific employees should be targeted for retention interventions?*

- **The actor:** *Mid-level department managers*. (Not the central HR team, because managers are the ones who actually influence daily employee satisfaction).
- **The actions:** *What can the manager actually do?* The manager has a strict budget. They can only offer one of three things to a maximum of five employees per quarter: a *one-time* $2,000 retention bonus, a *shift to a 4-day workweek*, or a *formal stay interview*.
- **The necessity of AI and simpler alternatives:** *Do we need a complex ML model to rank 10,000 employees to find the top 5?* The team realizes that a highly complex, uninterpretable neural network might actually be detrimental here, as managers will refuse to use a *black box* to allocate scarce financial bonuses.
- **The Pivot:** The team tests a **simpler alternative**; a basic, transparent SQL heuristic that **simply flags employees** who (a) *haven't had a base salary increase in 24 months*, AND (b) *have reported to more than two different managers in the last year*.

The simple heuristic rule identified 80% of the actual churners that the complex ML model found. More importantly, because the rule was based on **transparent**, **logical business criteria**, the managers actually **trusted** it. They were willing to take concrete **actions** (*offering the 4-day workweek or the bonus*) to the flagged employees.

1.7.3 Population and unit of analysis:

Every machine learning project must begin by explicitly defining the **unit of analysis** – the **fundamental**, **independent entity** the model is **evaluating**, **predicting for**, or **learning from**. Depending on the domain, this unit must be strictly identified as:

- **An individual:** (e.g., patient, customer, household)
- **An event or interaction:** (e.g., hospital visit, transaction, time window)
- **An object or artifact:** (e.g., image, device, document)
- **A spatial entity:** (e.g., geographic region, store location)

The danger of unit confusion

Failing to respect the boundaries of the unit of analysis during data partitioning is a primary cause of **data leakage** and **invalid evaluation**. If instances of the same unit bleed across the training and testing sets, the model will artificially

inflate its performance by memorizing unit-specific quirks rather than learning generalizable patterns.

Example # 35: Medical AI (again)

Consider a medical imaging model designed to detect anomalies in chest X-rays. The **true unit of analysis** for real-world deployment is the **patient**, not the individual **image**. If a single patient has five X-rays, and these images are randomly split so that three go to the training set and two go to the testing set, the **model will simply memorize** that specific **patient's unique anatomical baseline**. It will score highly on the test set, but it has completely failed to learn how to generalize to entirely new, unseen patients.

1.7.4 Index time: (or prediction origin) is the **exact**, **specific moment** in the **real world** at which the model is **required to make its prediction**. The absolute rule of feature engineering is that **every single input feature must be strictly available at or before this index time**.

- **The trap of hindsight:** For a hospital deterioration system, if the index time is the moment of patient admission, the model cannot use a critical laboratory result that was ordered or finalized 48 hours later. Using that result **does not constitute early prediction**; it is merely hindsight.
- **The core warning:** This highlights the most dangerous trap in predictive modeling i.e., **target leakage**. A feature may **appear incredibly predictive** precisely because it **contains future information**. If a model relies on data that has **not yet occurred at the index time**, it is **leaking the future**, not demonstrating intelligence.

1.7.5 Prediction horizon: The **prediction horizon** defines the exact **temporal window into the future** within which the **target outcome must occur**. It explicitly answers the question: *How far ahead is the system actually trying to look?* Depending on the operational context, this horizon can vary drastically:

- **Immediate/Real-time:** Detecting fraud at the exact millisecond of the current transaction.
- **Short-term:** Predicting critical equipment failure within the next 24 hours.

- **Medium-term:** Estimating the risk of hospital readmission within 30 days of patient discharge.
- **Long-term:** Forecasting customer churn within the next three months.
- **Environmental:** Predicting flood occurrence within the next six hours.

The impact of the horizon

The chosen horizon is **not merely a minor parameter**; it **fundamentally alters** the physics of the machine learning problem:

- **Tasks and Labels:** A 24-hour horizon requires entirely different feature engineering and label definitions than a 30-day horizon.
- **Baselines:** The naive baseline (e.g., *always predict the historical average*) shifts depending on the time window being evaluated.
- **Intervention Possibilities:** Most importantly, the **prediction horizon** must strictly **align** with the **operational window** available to **act**. Predicting a flood six hours in advance allows time for evacuation; predicting it six minutes in advance is useless. The horizon must be explicitly chosen to **provide enough lead time** for the decision-maker to **actually execute a meaningful intervention**.

Example # 36: Predicting wind turbine gearbox failure

Imagine a renewable energy company deploying an AI system to **predict wind turbine gearbox failures**. A **naive** data science team might define the prediction horizon as *failure within the next 24 hours*, achieving 96% accuracy by **simply detecting obvious**, **immediate vibration spikes**.

However, this is **operationally useless** because maintenance crews require 48 to 72 hours to **source specialized parts and deploy** heavy-lift cranes to remote sites. By rigorously realigning the prediction horizon to *failure within the next 14 to 30 days* to **match the actual physical intervention window**, the entire machine learning problem fundamentally changes: the model is forced to learn **subtle**, **long-term degradation patterns** rather than **immediate catastrophic signals**.

This single adjustment transforms the system from a **mathematically accurate but practically useless** 24-hour alarm into a **highly valuable**

strategic planning tool that provides the exact lead time needed to prevent costly, unplanned downtime.

1.7.6 Inputs: A machine learning model is **only as robust as the data feeding it**. Before any feature is passed to an algorithm, it must be **strictly cataloged** to **prevent silent failures**, **data leakage**, and **compliance violations**. For every proposed input variable, the team must create a rigorous specification documenting the following:

- **Definition and source:** What exactly does this variable measure in the real world, and which specific system, database, or sensor generates it?
- **Unit and type:** What is the exact unit of measurement (e.g., mg/dL, USD, milliseconds) and the data type (e.g., continuous, categorical, binary)?
- **Update frequency and missingness:** How often is the underlying data refreshed (e.g., real-time, daily batch), and what is the historical rate and pattern of missing or null values?
- **Timestamp semantics:** What does the attached timestamp actually represent (e.g., time of event occurrence vs. time of database entry)? This is critical to ensure the feature does not leak future information.
- **Availability at inference:** Will this feature realistically be accessible in the live production environment at the exact index time the prediction must be made?
- **Privacy classification:** What is the regulatory sensitivity of the data (e.g., PII[182], PHI[183], GDPR-protected[184]) and what security protocols are required?
- **Transformation:** What specific preprocessing, normalization, encoding, or aggregation has been applied to the raw data?
- **Known Biases:** What historical, measurement, or sampling biases are known to exist in how this data was collected?

[182] **PII (Personally Identifiable Information):** Any data that can be used on its own or in combination with other information to identify, contact, or locate a specific individual, such as a full name, Social Security number, or IP address.

[183] **PHI (Protected Health Information):** Any individually identifiable information regarding a person's past, present, or future physical or mental health, healthcare provision, or payment for healthcare, as strictly regulated under laws like the US HIPAA.

[184] **General Data Protection Regulation (GDPR):** Any personal data relating to an identified or identifiable natural person within the European Union, governed by strict regulations that mandate explicit consent, data minimization, purpose limitation, and the user's right to erasure.

Treating features as **undocumented**, **interchangeable columns** in a spreadsheet is a primary cause of **deployment failure**. Rigorous feature documentation transforms raw data from a *black box* into a **transparent**, **auditable**, and **operationally viable** component of the AI system.

1.7.7 Output: The model's output must be explicitly defined to match the exact needs of the downstream decision-maker. Depending on the problem framing, the output can take various forms:

- **Predictive and probabilistic:** A discrete class label, a continuous scalar value, a probability score, or a confidence/prediction interval.
- **Comparative and diagnostic:** A ranked list of alternatives, an anomaly score, or a risk tier.
- **Prescriptive and generative:** A specific recommendation, an operational plan, a direct automated action, or a generated artifact (e.g., text, image, code).
- **System behavior:** An explicit abstention (the model's deliberate choice to decline making a prediction when its confidence is too low).

The strategic value of probabilities

Whenever possible, **outputting a continuous probability** is vastly **superior** to **outputting a rigid, hard class label** (e.g., a simple *Yes/No* or *Fraud/Not Fraud*). A probability preserves the model's **underlying uncertainty**, providing the decision-maker with the **flexibility** to **dynamically adjust** the action threshold. This allows the organization to **calibrate the system's behavior** in real-time based on the asymmetric costs of errors[185], current intervention capacity, and shifting operational constraints.

1.7.8 Labels and ground truth: In supervised machine learning, a model is only **as good as** its **ground truth**. However, in real-world applications, **labels are**

[185] **Asymmetric costs of errors** mean that the real-world consequences of a **False Positive (Type I error)** and a **False Negative (Type II error)** are rarely equal, with **one type of mistake** almost always being far **more damaging** or **expensive** than the other. For example, in medical screening, a false negative (missing a malignant tumor) carries a catastrophic cost, making a false positive (an *unnecessary* but *safe* follow-up biopsy) the preferable error. Conversely, in corporate email filtering, a false positive (quarantining a critical client contract) is far more damaging than a false negative (letting a promotional spam email reach the inbox). This is precisely why outputting a continuous probability is superior to a rigid *yes/no* label. It **preserves the model's uncertainty**, allowing human operators to **set custom decision thresholds** that **actively minimize** the more **expensive** or **dangerous error** based on their specific operational realities.

rarely objective, **pristine facts**; they are **proxies constructed by humans**, **systems**, or **historical events**.

Sources of ground truth

Depending on the domain, labels are generated through various mechanisms:

- **Objective measurement:** Direct physical or sensor measurements (e.g., blood glucose levels, server CPU temperature).
- **Human evaluation:** Expert clinical judgment, consensus review panels, or manual human annotation.
- **System and administrative records:** Administrative coding (e.g., ICD-10 billing codes[186]), recorded user behavior (e.g., clicks, purchases), or timestamps of later events (e.g., hospital readmission within 30 days).
- **Derived proxies:** A proxy variable (e.g., using *prescribed medication* as a proxy for *having a disease*) or the output of another legacy algorithm.

The reality of labels

In practice, **labels are rarely perfect**. They are **frequently noisy**, **inconsistent**, **delayed**, **selectively recorded**, and **heavily dependent** on the specific institution or process that generated them.

Critical interrogation

Before training a model, the team must rigorously interrogate the labels by asking:

- **Construct validity:** Does the label actually represent the true underlying phenomenon we care about, or just a convenient, flawed proxy?
- **Access bias:** Is the label confounded by a user's or patient's access to services? (For example, *a disease label only exists if the patient could afford to visit a doctor to get diagnosed in the first place*).

[186] **ICD-10 billing codes** are standardized alphanumeric codes from the **International Classification of Diseases, 10th Revision (ICD-10)** used by healthcare providers, insurers, and public health organizations to classify, document, and communicate diagnoses, diseases, injuries, symptoms, and health conditions for clinical records, billing, reimbursement, and statistical analysis. The system was developed by the **World Health Organization (WHO)** and adopted internationally beginning in **1992**, with country-specific clinical modifications such as **ICD-10-CM (Clinical Modification)** used in the United States for medical billing. Examples include **E11.9** for type 2 diabetes mellitus without complications, **I10** for essential (primary) hypertension, **J45.909** for unspecified asthma, and **S72.001A** for a fracture of an unspecified part of the femur during an initial encounter.

- **Measurement disparities:** Was the label generated using different criteria, thresholds, or levels of scrutiny across different demographic or geographic groups?
- **The meaning of "negative":** Are the unlabeled or *negative* cases genuinely free of the condition, or are they simply unobserved, missing, or under-reported?
- **Status quo bias:** Is the model merely learning to reproduce historical, potentially biased institutional decisions rather than discovering an objective, optimal truth?

A machine learning model **cannot learn a truth that isn't in the data**. If the ground truth is **flawed**, **biased**, or **misaligned** with the **actual operational goal**, the model will **flawlessly** and **efficiently reproduce** those **exact flaws at scale**.

1.7.9 Constraints: Real-world AI systems **do not exist in a vacuum** of pure mathematical accuracy. They must **operate** within a **complex web of physical**, **financial**, **ethical**, and **legal boundaries**. Before a model is deployed, the team must explicitly define and respect the following categories of constraints:

- **Technical and infrastructure:** Latency (maximum acceptable inference time), throughput (required request volume), memory footprint, computational limits (CPU/GPU availability), and energy consumption (carbon footprint or battery limits for edge devices).
- **Resource and operational:** The financial budget for continuous training and inference, and the human staffing capacity required to monitor and manage the system.
- **Trust and usability:** Explainability (the need for stakeholders to understand the model's logic) and accessibility (ensuring the system's interface and outputs are usable by all intended populations, including those with disabilities).
- **Governance, ethics and compliance:** Privacy protections, informed consent, strict regulatory compliance (e.g., HIPAA[187], GDPR), safety

[187] **HIPAA (Health Insurance Portability and Accountability Act)** is a United States federal law enacted in **1996** that establishes requirements for protecting the privacy, security, and confidentiality of individuals' **protected health**

(preventing physical or digital harm), robustness (resilience to edge cases, noise, or adversarial inputs), and data residency (legal requirements to keep data within specific geographic or jurisdictional borders).

In applied machine learning, **mathematical accuracy** is just **one of many competing objectives**. A **slightly less accurate** model that is **interpretable**, **computationally inexpensive**, **legally compliant**, and **seamlessly deployable** will almost always deliver **more real-world value** than a mathematically perfect *black box* that violates operational constraints and ultimately sits on a shelf.

1.7.10 Stakeholders: A machine learning system's **impact radiates far beyond** the immediate **model developers or operators**. A comprehensive problem-framing canvas must **explicitly map the entire ecosystem** of individuals and entities impacted by the system.

The stakeholder ecosystem

Depending on the use case, the relevant stakeholders typically include:

- **The subjects:** The individuals whose historical data was used to train the model.
- **The targets:** The people directly subjected to the model's decisions (e.g., patients, loan applicants, job candidates).
- **The operators and experts:** The domain professionals, data providers, and system operators who build, maintain, interpret, or act upon the model's outputs.
- **The broader ecosystem:** Regulators, downstream institutions, local communities, and individuals who may be indirectly affected by the system's broader externalities.

The core tension: conflicting objectives

information (PHI) and regulating how healthcare organizations, insurers, and their business partners collect, use, store, and transmit health data. HIPAA includes the **Privacy Rule**, which governs the use and disclosure of PHI, and the **Security Rule**, which requires administrative, physical, and technical safeguards to protect **electronic protected health information (ePHI)**. Examples include a hospital encrypting electronic patient records, restricting access to medical data based on employee roles, obtaining authorization before sharing a patient's diagnosis with third parties, or requiring an AI company processing medical records to implement appropriate security controls and data protection agreements.

These stakeholders rarely share perfectly aligned incentives. Optimizing a system for one group often introduces friction or harm to another.

Example # 37: Fraud detection system

A **highly aggressive** fraud detection system may successfully minimize financial losses for the bank (**satisfying the operator**), but **simultaneously impose severe friction**, **payment delays**, and **unequal false-positive burdens** on legitimate customers (**harming the target**).

A **defensible AI system** cannot blindly optimize for a single metric that benefits only the model operator. It **requires explicitly acknowledging** these **competing interests**, mapping the potential harms, and designing the system's constraints and thresholds to balance these conflicting objectives fairly and transparently.

1.7.11 Cost of error: In binary classification, every prediction results in one of four outcomes. Rather than viewing these merely as abstract mathematical metrics, they must be understood as concrete operational events with real-world consequences:

- **True positive (Hit):** Correctly taking a positive action (e.g., flagging, treating, or blocking) when a condition is actually present.
- **False negative (Miss):** Taking a negative action (e.g., ignoring, clearing, or approving) when a condition is actually present.
- **False positive (False Alarm):** Taking a positive action when a condition is actually absent.
- **True negative (Correct Rejection):** Correctly taking a negative action when a condition is actually absent.

The reality of asymmetric costs

In applied machine learning, the **penalty for a False Negative** is **rarely equal** to the **penalty for a False Positive**. Optimizing a model for overall *accuracy* **blindly ignores this critical asymmetry**:

- **Healthcare:** A false negative in cancer screening delays life-saving treatment (**catastrophic**), while a false positive causes temporary anxiety and unnecessary follow-up testing (**manageable**).

- **Finance:** A false fraud alert blocks a legitimate customer transaction, causing **immediate friction**, **reputational damage**, and **lost revenue**.
- **Safety and infrastructure:** A **false reassurance** (a false negative) in structural monitoring – such as an AI declaring a fatigued bridge component safe – can lead to catastrophic physical failure and loss of life.

Beyond financial metrics: non-financial costs

The true cost of an error is rarely just a line item on a corporate balance sheet. AI systems frequently impose **profound human**, **social**, and **operational costs**, including:

- Loss of personal autonomy or freedom.
- Social stigma or reputational damage.
- Delayed access to essential services, care, or opportunities.
- Increased cognitive or operational workload for human operators reviewing the errors.
- Systemic inequity and the amplification of historical biases.
- Psychological harm or distress to the end-user.
- The long-term erosion of public trust in the institution deploying the AI.

A machine learning model should **never be evaluated solely** on its **aggregate accuracy**. It must be **explicitly tuned** and **thresholded** to minimize the **specific type of error** that carries the **highest real-world cost**, ensuring the system's mathematical objectives are **perfectly aligned with human** well-being, safety, and operational reality.

1.7.12 Baseline and counterfactual: A machine learning model's **value is entirely relative**. To **prove** its **operational worth**, it must be **rigorously benchmarked** against the **actual alternative** it is **meant to replace or augment**, rather than just being compared to a naive statistical baseline.

Defining the true baseline

In the real world, the **counterfactual** – what would have happened if the AI had not been deployed – is **rarely random guessing**. Depending on the operational context, the true baseline might be:

- **Current professional judgment:** The unassisted decision-making of human experts or clinicians.

- **A simple heuristic:** A basic threshold, checklist, or linear scoring system currently in use.
- **The status quo:** No intervention at all (maintaining current operations).
- **A legacy system:** A previous, older machine learning model or algorithmic rule.
- **Alternative policies:** Random allocation of resources or a different, non-AI resource-prioritization protocol.

The paradigm shift in evaluation

This rigorous comparison forces a critical shift in how organizations evaluate AI success. It demands that **we stop asking**: *Is the model's accuracy or AUC statistically impressive in a vacuum?* **And instead demand the answer to:** *Does deploying this complete AI system actually improve real-world outcomes compared to the best available alternative?*

A **mathematically brilliant**, **highly complex model** that **performs worse** than a **simple**, **existing checklist** is a **failure**. True AI value is **not measured by statistical novelty** or **algorithmic complexity**, but by the **measurable**, **positive delta** between the AI-assisted workflow and the best available alternative.

1.7.13 Evaluation plan: Before a single line of training code is written, the team **must lock in a comprehensive**, **rigorous evaluation plan**. This plan **defines exactly** how the **model will be judged**, ensuring the **assessment is objective**, **reproducible**, and **strictly aligned** with operational goals. The pre-specified plan must explicitly define the following components:

- **Performance metrics:** The *primary metric* (the ultimate measure of business or clinical success) and *secondary metrics* (guardrail metrics to ensure the model isn't optimizing one dimension at the expense of another, such as maximizing recall without destroying precision).
- **Validation strategy:** The specific *validation design*, including *external* or *temporal testing* (evaluating on out-of-distribution or future data) and *prospective evaluation* (simulating real-world deployment conditions).
- **Reliability and fairness:** *Subgroup analyses* (checking for disparate performance across demographics or edge cases), *calibration assessment*

(ensuring predicted probabilities match actual real-world frequencies), *uncertainty analysis*, and *robustness tests* (resilience to noise, missing data, or adversarial inputs).

- **Operationalization and governance:** The specific *decision thresholds* for triggering action, the strict *acceptance criteria* (the minimum performance bar required to approve going live), and the post-deployment *monitoring plan*.

The danger of post-hoc evaluation

Locking in these criteria before training is a **critical defense** against **metric shopping**[188] and **data dredging**[189]. If a team is allowed to train multiple models, look at the results, and then choose the evaluation metric, they will **inevitably select the metric that makes their preferred model look best**. This creates a **dangerous illusion of performance** that will inevitably shatter when the model encounters the real world.

An evaluation plan **written after the fact** is merely a **retrospective justification for deployment**. A rigorous evaluation plan **written before training** is a **binding contract for quality**, ensuring the model is judged by the **uncompromising rules** of the real world, not the convenience of the data scientist.

---

[188] **Metric shopping** is the practice of evaluating a model or analysis using **multiple possible performance metrics** and **selectively reporting the metric** that produces the **most favorable result**, rather than choosing evaluation criteria in advance based on the intended objective and risks. It can create a **misleading impression of model quality** by **emphasizing measures that hide weaknesses** in other dimensions of performance. Examples include selecting accuracy as the primary metric for a fraud detection model despite severe class imbalance where recall is more important, reporting only a model's high overall accuracy while ignoring poor performance for minority groups, or choosing a forecasting metric that favors a preferred model after observing the results from several alternatives.

[189] **Data dredging** (also called **data fishing** or p**-hacking** in statistical contexts) is the practice of **repeatedly searching through datasets**, **variables**, **models**, or **analytical approaches** until **statistically significant** or **favorable patterns** are discovered, **without a pre-specified hypothesis** or **appropriate correction for multiple comparisons**. It increases the likelihood of finding patterns that appear meaningful but are actually due to chance. Examples include testing hundreds of demographic variables until finding one that appears correlated with a disease outcome by coincidence, trying many machine learning architectures and feature combinations until one produces the best validation score on a limited dataset or repeatedly analyzing historical financial data until discovering a trading strategy that performs well only because of random fluctuations.

Multiple comparisons is the statistical problem that occurs when **many hypotheses**, **variables**, **models**, or **outcomes** are **tested simultaneously**, increasing the probability of obtaining **apparently significant results purely by chance** unless appropriate corrections are applied. Examples include testing 1,000 genetic markers to find disease associations where some appear significant randomly, comparing dozens of machine learning models and selecting the best validation score by chance, or analyzing many customer segments until one shows an apparently strong marketing effect.

1.7.14 Problem-framing worksheet: A project team should be able to complete the statement in **Figure 6**. If this statement cannot be completed clearly, model development should not begin.




Figure 6: Problem-Framing Worksheet for AI System Development. The worksheet formalizes an AI problem by specifying the decision time, target population or unit, available data, required output, prediction horizon, intended decision-maker and action, evaluation baseline and metrics, and relevant error costs, subgroup risks, operational constraints, and governance requirements. Model development should proceed only when each component can be defined clearly and unambiguously.

Applications Across Domains

AI systems are increasingly **deployed in settings** where **predictions** must be **translated into real-world decisions**, **interventions**, and **resource allocations**. Although the underlying machine-learning methods may differ, **many applications share the same fundamental challenge** i.e., connecting **imperfect**, **evolving data** to **high-stakes operational actions**. The following cross-domain examples illustrate how AI tasks, data requirements, risks, and data-engineering dependencies interact across healthcare, finance, business, public policy, climate, education, and engineering. They highlight that **successful deployment** depends **not only on model performance**, but also on whether the **surrounding data infrastructure** can **support reliable**, **timely**, and **responsible decision-making**.

Figure 7 illustrates how AI problems vary across application domains while retaining a common operational structure: each system transforms domain-specific data into predictions or recommendations that support a concrete action, but its real-world reliability depends on managing both application-specific risks and the corresponding data-engineering dependencies.

Domain	AI task	Data	Operational action	Central risk	Data-engineering dependency
Healthcare	Predict clinical deterioration	Vital signs, laboratory values, medication and encounter history	Escalate monitoring or review	Alert fatigue, delayed labels, site shift	Temporal joins, patient identity, unit harmonization, prospective availability
Finance	Detect transaction fraud	Transactions, merchant, device, account history	Block, challenge, or review	False declines, adaptive attackers	Streaming ingestion, low latency, event ordering, feedback labels
Business	Forecast product demand	Sales, promotions, prices, holidays, inventory	Replenish stock	Stockouts or excess inventory	Historical versioning, calendar alignment, promotion data
Public policy	Identify households needing support	Administrative and survey data	Prioritize outreach	Exclusion, proxy discrimination, due-process concerns	Entity resolution, consent, provenance, access controls
Climate	Forecast flood risk	Rainfall, terrain, river gauges, satellite data	Issue warning or deploy resources	Missed events or false alarms	Geospatial alignment, sensor quality, timeliness, missing-data handling
Education	Estimate disengagement risk	Attendance, assessments, LMS activity	Offer support	Stigmatization, surveillance, self-fulfilling labels	Student identity, timestamp semantics, access inequities
Engineering	Predict equipment failure	Sensor streams, maintenance logs, operating conditions	Schedule maintenance	Unnecessary shutdown or catastrophic failure	Sensor calibration, units, synchronization, streaming reliability

Figure 7: Illustrative AI problem domains, operational risks, and data-engineering dependencies.

Why AI Projects Fail

AI projects **rarely fail** because the **underlying algorithms are incapable of learning**. More often, **failure arises** from **weaknesses in problem definition**, **data foundations**, **evaluation practices**, **deployment assumptions**, or the **broader systems** in which models operate. A successful AI system must **align technical** performance with **real-world objectives**, **reliable evidence**, **human workflows**, and **long-term operational conditions**. The following failure modes illustrate why building an effective AI system requires more than selecting a model and measuring accuracy.

1.9.1 Failure 1 – Solving the wrong problem: A technically accurate model may fail because its **target** is **disconnected** from the **desired outcome**. Examples include:

- predicting hospital costs when the real objective is preventable morbidity;
- optimizing click-through rate when the desired outcome is long-term user welfare;
- predicting student failure without an effective support intervention;
- detecting risk when no one has the capacity to act.

Problem framing is therefore a form of system design, not administrative preparation.

1.9.2 Failure 2 – Poor data quality: Poor data may involve:

- incorrect values;
- missing records;
- inconsistent units;
- duplicate identities;
- delayed updates;
- changing coding practices;
- unrepresentative samples;
- unreliable labels;
- undocumented preprocessing.

More data *do not* automatically solve these problems. **Large quantities** of **systematically biased data** can create **highly confident** but **invalid models**.

1.9.3 Failure 3 – Data Leakage: Leakage occurs when training or evaluation uses information unavailable at genuine prediction time or when information crosses partitions improperly. Common forms include:

- **Target leakage:** a feature directly or indirectly reveals the outcome.
- **Temporal leakage:** future information is used to predict the past.
- **Group leakage:** records from the same individual, household, device, or site occur in both training and testing.
- **Preprocessing leakage:** scaling, imputation, or feature selection is fitted using the full dataset.
- **Label leakage:** annotation procedures expose outcome-related information. Benchmark contamination: evaluation examples appear in training data.

Leakage **often** produces **unusually impressive results**. It must therefore be **actively investigated** rather than treated as an accidental edge case.

1.9.4 Failure 4 – Weak evaluation: A model may perform well on average yet fail for particular sites, populations, devices, or time periods. Weak evaluation includes:

- reporting only accuracy;
- selecting a convenient test set;
- ignoring class imbalance;
- tuning repeatedly on the test set;
- omitting confidence intervals;
- failing to compare against a simple baseline;
- ignoring calibration;
- omitting subgroup analysis;
- using random splits for temporal deployment;
- testing only under conditions similar to training.

Leakage **often** produces **unusually impressive results**. It must therefore be **actively investigated** rather than treated as an accidental edge case.

1.9.5 Failure 5 – Underspecification: It occurs when **several models satisfy** the **same training and validation requirements** but behave **differently** under **deployment-relevant changes**. Models with nearly identical in-distribution (IID) test performance may rely on **different features**, **shortcuts**, or **inductive biases**. Held-out accuracy alone may therefore be insufficient to determine which model is safe or stable[190]. Mitigation includes:

- stress testing[191];
- multiple training runs;
- evaluation under shifts;
- causal or mechanistic checks[192];
- subgroup and environment-specific evaluation;
- model-selection criteria beyond average accuracy.

1.9.6 Failure 6 – Distribution shift: Deployment data may differ from training data because of:

- population changes;
- new devices;
- policy changes;
- seasonal effects;
- user adaptation;
- economic shocks;
- new clinical practice;
- adversarial behavior;
- changes in the data pipeline.

---

[190] Alexander D'Amour et al., *Underspecification Presents Challenges for Credibility in Modern Machine Learning*, Journal of Machine Learning Research, 2022.

[191] **Stress testing** is the **systematic evaluation** of a machine learning model under **extreme**, **rare**, or **intentionally challenging conditions** to assess its **robustness**, **reliability**, and **failure modes beyond normal operating scenarios**. Examples include evaluating an autonomous driving model in heavy rain or dense fog, testing a fraud detection model against novel attack patterns, or assessing a medical AI system using data from hospitals with different patient populations and imaging devices.

[192] **Causal or mechanistic checks** are evaluations that determine whether a **model bases its predictions** on **genuine causal mechanisms** or **scientifically meaningful relationships** rather than **spurious correlations** or **dataset-specific shortcuts**. Examples include verifying that a pneumonia detection model relies on lung abnormalities instead of hospital-specific image markers, confirming that a credit risk model responds appropriately to changes in income while holding other factors constant, or testing whether a biological prediction model remains valid when known causal pathways are experimentally perturbed.

A fixed model **assumes some stability** in the relation among inputs, labels, and decisions. **Monitoring** is needed to determine when that assumption no longer holds.

1.9.7 Failure 7 – Ignoring workflow and human factors: An accurate model may fail because:

- alerts arrive too late;
- users do not trust the score;
- explanations are inadequate;
- there are too many alerts;
- the interface encourages automation bias;
- responsibility is unclear;
- recommended actions are infeasible;
- the system increases rather than reduces workload.

AI performance must therefore be evaluated at both the model and system levels.

1.9.8 Failure 8 – No deployment or monitoring plan: A model may degrade silently if:

- upstream schemas change;
- feature computations fail;
- labels become delayed;
- input distributions shift;
- thresholds are altered;
- new subpopulations appear;
- the model version is not recorded;
- outcome data are unavailable.

Production ML research has shown that data and system dependencies can create substantial maintenance burdens beyond the model code itself.

Why Data Engineering Is Inevitable

Modern AI is often presented as a **problem of models** and **algorithms**, but every model **ultimately depends** on the **quality**, **meaning**, **movement**, and **governance of data**. Before a system can learn, predict, or be evaluated, **data must be collected**, **interpreted**, **transformed**, **delivered**, and **maintained** across **changing operational environments**. As AI systems grow in **scale** and **complexity**, these responsibilities become **indispensable engineering problems** rather than **administrative tasks**. Data engineering therefore emerges not as a supporting discipline, but as a foundational component of every reliable AI system.

1.10.1 What data engineering means in AI: Data engineering is the discipline of designing and operating the systems through which data traverses as shown in Figure 8.




Figure 8: Data Lifecycle Flow. Data progress through eight interconnected stages: generation, capture, validation, storage, transformation, serving, observation, and governance. Together, these stages form a continuous lifecycle that supports data quality, accessibility, reliability, monitoring, accountability, and responsible use across operational and analytical systems.

Its artifacts include:

- ingestion pipelines;
- databases and data lakes;
- event streams;
- schemas;
- data contracts;
- validation tests;
- metadata catalogs;
- lineage systems;

- feature pipelines;
- training datasets;
- versioned transformations;
- access policies;
- monitoring dashboards.

1.10.2 The model depends on a data-generating and data-delivery system: A trained model does not consume abstract data. It consumes values created by real systems:

- sensors;
- surveys;
- transactional applications;
- clinicians;
- users;
- laboratory instruments;
- public agencies;
- labeling teams;
- other algorithms.

Each source has its own:

- semantics;
- sampling process;
- timestamp conventions;
- error modes;
- update schedule;
- access controls;
- incentives.

Therefore, **Reliable model $\not\Rightarrow$ Reliable AI system** unless the **surrounding data processes are reliable**.

1.10.3 Data semantics must be engineered: Consider a variable called temperature. It is incomplete without knowing:

- Celsius or Fahrenheit;
- body, room, or device temperature;

- measurement site;
- sensor type;
- timestamp;
- missing-value code;
- calibration status;
- whether the value is raw or corrected.

Similarly, a field called `diagnosis_date` may mean:

- date symptoms began;
- date first documented;
- date confirmed by a specialist;
- date entered into a database;
- date used for billing.

AI systems fail when identical column names **conceal different meanings** or when **different names** represent the **same concept**.

1.10.4 Temporal correctness must be engineered: Time determines:

- what was known at prediction;
- which events belong in a feature window;
- whether an outcome follows an input;
- whether records are stale;
- whether train and test periods overlap;
- whether delayed data are mistakenly treated as real time.

For a prediction at time t, **a feature should generally satisfy**

$$t_{\text{feature availability}} \leq t$$

It is **not sufficient** for the **event to have occurred earlier**; it **must also have** been **recorded and available** to the operational system **by prediction time**.

1.10.5 Training-serving consistency must be engineered: A common failure occurs when the feature pipeline used in training differs from live inference. Examples include:

- categories encoded differently;
- missing values handled differently;
- a data source unavailable in production;

- numerical units changed;
- a feature computed over a different time window;
- a library version altered preprocessing;
- batch and streaming pipelines produce different results.

Shared, **versioned transformations** and **automated tests** reduce this mismatch.

1.10.6 Reproducibility requires lineage: A reproducible model requires more than saved weights. The team should be able to identify:

- source data version;
- extraction query;
- transformation code;
- label definition;
- partition logic;
- random seed;
- library versions;
- model configuration;
- evaluation data;
- approval status;
- deployment version.

Without lineage, a result **cannot be reliably audited**, **reconstructed**, **compared**, or **rolled back**.

1.10.7 Scale and timeliness are data problems: A predictive model may require:

- millions of records;
- continuous sensor streams;
- low-latency features;
- geographically distributed sources;
- real-time identity resolution;
- delayed outcomes;
- large unstructured files.

Model accuracy alone does not guarantee that the **necessary data** can be **delivered** within the **required latency**, **cost**, and **reliability envelope**.

1.10.8 Governance must be implemented in infrastructure: Privacy and governance cannot remain policy statements alone. They require mechanisms such as:

- role-based access;
- encryption;
- retention limits;
- de-identification;
- consent tracking;
- audit logs;
- purpose restrictions;
- geographic controls;
- deletion workflows;
- incident response.

The NIST AI RMF treats **governance as a cross-cutting function** rather than a final-stage checklist.

1.10.9 Monitoring depends on new data: A deployed model can only be monitored if the system captures:

- inputs;
- predictions;
- model versions;
- human responses;
- eventual outcomes;
- relevant subgroup information;
- operational metadata.

Thus, **even model monitoring** is fundamentally a **data-engineering problem**.

1.10.10 The inevitability argument: Data engineering becomes unavoidable because:

- every AI model requires data with defined meaning;
- data must be delivered consistently to training and production;
- labels and outcomes must be linked over time;

- model behavior must be monitored after deployment;
- decisions must be audited;
- privacy and access rules must be enforced;
- changes in data sources must be detected;
- failures must be reproducible and reversible.

Data engineering is therefore **not merely what happens before** machine learning. **It is the connective tissue of the complete AI lifecycle**.

Principles for Students

Before selecting algorithms or tuning models, an AI project **must first be framed as a well-defined problem**. Many failures arise **not from inadequate machine learning** methods, but from **unclear objectives**, **poorly specified data**, **unrealistic evaluation**, or the **absence of deployment planning**. The principles presented in this chapter summarize the fundamental ideas developed throughout this monograph and provide a **practical framework** for formulating AI problems that are scientifically valid, operationally feasible, and aligned with real-world decision-making (Figure 9).




Figure 9: The framework summarizes ten foundational principles for defining AI projects before model development, emphasizing decision-centered framing, explicit specification of the target population and prediction horizon, prevention of information leakage, recognition of label uncertainty, deployment-aligned evaluation, subgroup and operational assessment, comparison with meaningful baselines, advance planning for deployment and monitoring, transparent documentation of assumptions, and treatment of AI as a sociotechnical system embedded within human and institutional contexts.

Three Illustrative Case Studies

We now discuss three case studies utilizing the concepts, principles, and practices studied in this module.

1.12.1 Google Flu Trends – When Scale Could Not Replace Measurement

Context and objective

Google Flu Trends attempted to **estimate influenza activity** using the **frequency of internet search queries** associated with **flu-related behavior**. The project appeared to illustrate a compelling big-data proposition: search activity was available rapidly and at massive scale, whereas official disease-surveillance reports were delayed. The intended pipeline is (approximately) presented in **Figure 10**:




Figure 10: The pipeline illustrates a four-stage workflow for estimating influenza activity from search behavior: raw search queries are collected, influenza-relevant terms are selected, a statistical model is fitted to the selected signals, and the resulting model output is used to estimate population-level influenza activity.

The project raised an important possibility: **could digital traces provide faster epidemiological surveillance?**

Why the problem appeared suitable for AI

The basic hypothesis was plausible:

- people experiencing symptoms may search for related information;
- aggregated search volume may correlate with influenza prevalence;
- search data arrive faster than traditional reports;
- a model may map search patterns to surveillance estimates.

This was a prediction problem involving a proxy:

Search behavior ≈ Disease activity

Search behavior is not disease. It is affected by **symptoms**, **media coverage**, **public anxiety**, **search-engine design**, **internet access**, and **user habits**.

What went wrong

Lazer and colleagues reported that in February 2013, **Google Flu Trends** produced **estimates exceeding the contemporaneous CDC** estimate by **more than a factor of two**. They also found that, beginning in August 2011, the system overestimated flu prevalence in 100 of 108 weeks[193]. The authors identified two broad causes:

- **Big-data hubris**
  - Large-volume **data were treated** as though they **could substitute** for **traditional measurement** and **domain knowledge**.
  - The **model-development process** reportedly **searched approximately** 50 million candidate terms **against only** 1,152 weekly observations. This creates **considerable opportunity for chance correlations** and **overfitting**. The final term set was not fully documented, limiting reproducibility and external scrutiny.
- **Algorithm dynamics**
  - The **search platform** and **user behavior changed** over time. Search suggestions, media attention, interface changes, and user adaptation **altered the relationship** between **search terms** and **actual influenza prevalence**.
  - The **input distribution** was therefore **not generated** by a **stationary measurement instrument**. It was generated partly by a **changing platform**.
  - The paper describes this as a problem of **algorithm dynamics**: **modifications** to the underlying **search environment** changed the **data-generating process**.

[193] David Lazer, Ryan Kennedy, Gary King, and Alessandro Vespignani, *The Parable of Google Flu: Traps in Big Data Analysis*, Science, 2014.

Data-engineering interpretation

The failure can be reconstructed as a data-lifecycle problem.

- **Proxy instability**

  The model relied on a **behavioral proxy** whose **meaning changed** over time. A data-engineering system should maintain:

  - source-version metadata;
  - query-definition versions;
  - platform-change logs;
  - media-event indicators;
  - geographic coverage information;
  - data-quality and missingness reports.

- **Missing lineage**

  Without full documentation of the selected search terms and transformations, external investigators could not fully reproduce the model. A robust pipeline would version as depicted in **Figure 11**.




Figure 11: A reproducible pipeline should version not only the fitted model but also the upstream data and processing components on which its outputs depend, including the raw query stream, term dictionary, filtering rules, aggregation procedure, and calibration dataset. Versioning these artifacts preserves provenance, supports auditing and rollback, and enables results to be reproduced when data definitions, preprocessing logic, or model behavior change.

- **Inadequate ground-truth anchoring**
  - Digital traces were **treated too independently** from **established surveillance**.
  - Lazer and colleagues showed that a **combined model** using both Google Flu Trends and lagged CDC information **achieved lower mean absolute error** than either source alone: approximately 0.232 for the

combined model, compared with 0.486 for Google Flu Trends and 0.311 for the lagged CDC model.

This demonstrates that **novel data sources** should **often complement rather than replace** established **measurement systems**.

- **Insufficient drift monitoring**
  The system required monitoring of:
  - residual error over time;
  - calibration;
  - search-term frequency;
  - relationship between search terms and surveillance data;
  - regional performance;
  - sensitivity to media events;
  - source-platform changes.

  A **persistent increase in residuals** should have **triggered recalibration** or **suspension**.

A redesigned architecture

A more defensible surveillance architecture would contain:

- **Source layer**
  - traditional public-health surveillance;
  - search trends;
  - pharmacy or medication-purchase indicators;
  - absenteeism;
  - laboratory reports;
  - weather and seasonal covariates.
- **Data-quality layer**
  - schema checks;
  - completeness checks;
  - geographic coverage;
  - timestamp validation;
  - source-version tracking;
  - anomaly detection.
- **Modeling layer**

- interpretable baseline;
- seasonal epidemiological model;
- digital-trace model;
- ensemble or data-fusion model;
- uncertainty intervals.

- **Evaluation layer**
  - rolling-origin temporal validation;
  - region-specific evaluation;
  - calibration assessment;
  - comparison with seasonal baselines;
  - sensitivity analysis around high-media periods.

- **Monitoring layer**
  - residual drift;
  - input drift;
  - source availability;
  - platform changes;
  - retraining triggers;
  - human epidemiologist review.

Central lessons

A more defensible surveillance architecture would contain:

- Volume **does not remove** measurement bias.
- A proxy is **only useful while its relationship** with the target remains stable.
- Platforms are **active parts** of the data-generating process.
- Reproducibility **requires documentation** of features and transformations.
- Hybrid systems **may outperform attempts to replace** trusted measurement entirely.
- Monitoring **must test the continuing validity** of the proxy-target relationship.
- Data engineering **is indispensable** because the **main risk** was not merely the **regression algorithm**; it was the **changing meaning** and **provenance** of the data.

The Google Flu Trends experience remains a **foundational warning** against assuming that more data automatically produce better knowledge.

1.12.2 Epic Sepsis Model – High-Stakes Prediction Requires Workflow-Aware Validation

Context

Sepsis is a serious clinical condition in which timely recognition and treatment may be critical. **Electronic health records (EHR)** contain **laboratory values**, **vital signs**, **medications**, **diagnoses**, and **encounter histories** that could potentially support earlier risk detection. The **Epic Sepsis Model** was integrated into electronic health-record workflows and used routinely available clinical data to generate sepsis risk scores. This appeared to be an attractive AI application:

Clinical observations → Risk score → Alert → Clinical review

External evaluation

A 2021 study evaluated the model using 27,697 patients and 38,455 hospitalizations. Sepsis occurred in 2,552 hospitalizations, approximately 7% of the evaluated sample. Risk scores were calculated every 15 minutes[194]. The reported hospitalization-level area under the ROC curve was approximately: $\mathrm{AUROC} = 0.63$, with a 95% confidence interval of approximately $0.62 - 0.64$. **At a score threshold of six or greater**:

- 6,971 of 38,455 hospitalizations – about 18% – would have generated alerts;
- 1,709 of the 2,552 sepsis cases – about 67% – were not detected at that threshold;
- only 183 sepsis cases were identified among patients not already receiving timely antibiotics.

The study concluded that the model **produced relatively poor discrimination**, **substantial alert burden**, and **failure to identify** many patients with sepsis before clinical recognition.

Why the evaluation was more complicated than AUROC

- **What exactly was the label?**
  Sepsis definitions can depend on:

[194] Andrew Wong, Erkin Otles, John P. Donnelly, et al., *External Validation of a Widely Implemented Proprietary Sepsis Prediction Model in Hospitalized Patients*, JAMA Internal Medicine, Volume 181, No. 8, 2021.

- clinical criteria;
- laboratory evidence;
- organ dysfunction;
- antibiotic administration;
- culture orders;
- documentation practices;
- timing conventions.

A label built partly from clinician actions may encode practice patterns rather than a purely biological state.

- **When should the model predict?**
  A system intended for early detection must predict before clinicians already recognize and treat the condition. A model that predicts sepsis after:
  - antibiotics have been ordered;
  - cultures have been taken;
  - critical laboratory tests have returned;
  - an escalation process has begun.

  may be accurate but operationally unhelpful. This is why index time and feature availability are central data-engineering requirements.

- **What happens after an alert?**
  An alert only creates value when:
  - it reaches the right professional;
  - at the right time;
  - with adequate context;
  - and a feasible response pathway.

  If too many alerts are generated, clinicians may become desensitized.

Data-engineering challenges

- **Temporal alignment**
  Each feature should have:
  - event time;
  - recording time;
  - availability time;

- correction time.

For example, a laboratory specimen may be collected at 10:00, entered at 10:15, verified at 11:00, and displayed at 11:05. A retrospective dataset that uses the 10:00 collection time may mistakenly make the result appear available earlier than it was.

- **Patient and encounter identity**

  The same patient may have:
  - multiple admissions;
  - emergency and inpatient encounters;
  - transferred episodes;
  - duplicate records;
  - records across institutions.

  Improper splitting can allow information from one hospitalization to leak into another.

- **Missingness**

  Clinical values are not measured randomly. A laboratory test may be ordered because a clinician already suspects deterioration. Thus

  $$P(\text{measurement observed} \mid \text{clinical condition}) \neq P(\text{measurement observed})$$

  Missingness itself can be predictive, but it **may encode clinician behavior** that differs among hospitals.

- **Site variation**

  Hospitals differ in:
  - patient mix;
  - measurement frequency;
  - coding practice;
  - laboratory systems;
  - treatment protocols;
  - alert workflows.

  External validation is therefore necessary before local deployment.

Alert burden and decision utility

Suppose a model has a **modest false-positive rate**. In a **low-prevalence setting**, the number of **false alerts can still be large**. The operational effect depends on:

$$\textbf{Alert volume} = \textbf{Number of eligible encounters} \times P(\hat{p} \geq t)$$

Evaluation should report:

- alerts per patient-day;
- positive predictive value;
- cases detected before clinical recognition;
- time gained;
- clinician response rate;
- unnecessary interventions;
- workload;
- patient outcomes.

A threshold should be selected jointly with clinical capacity and risk tolerance.

A stronger development and deployment plan

- **Phase 1: Problem formulation**
  Specify whether the objective is:
  - early recognition;
  - mortality reduction;
  - prioritization for review;
  - support for less experienced clinicians;
  - detection of missed deterioration.

  These are not identical objectives.

- **Phase 2: Label design**
  Use expert-reviewed, temporally precise definitions. Conduct sensitivity analyses across plausible sepsis definitions.

- **Phase 3: Data construction**
  Create a feature store with:
  - strict event-time semantics;
  - validated units;
  - site-specific mappings;
  - missingness indicators;

- versioned code;
- patient-level partitioning.

- **Phase 4: Validation**
  Use:
  - temporal holdout;
  - external hospital validation;
  - calibration analysis;
  - subgroup analysis;
  - prospective silent evaluation;
  - comparison with clinical scores and current practice.

- **Phase 5: Workflow simulation**
  Estimate:
  - alert count per shift;
  - staff capacity;
  - response time;
  - escalation pathways;
  - expected benefit;
  - alert suppression rules.

- **Phase 6: Controlled prospective deployment**
  Begin with a silent or advisory phase, measure human interaction, and maintain a rollback mechanism.

- **Phase 7: Monitoring**
  Monitor:
  - input completeness;
  - feature latency;
  - score distribution;
  - calibration;
  - alert volume;
  - sepsis prevalence;
  - time to intervention;
  - subgroup performance;
  - overrides;
  - adverse events.

Central lessons

- High-stakes AI requires external and prospective validation.
- The label must match the intended clinical event.
- Predictive timing is as important as predictive accuracy.
- Features must be available before the intended decision.
- Alert volume is a system-level metric.
- Human workflow determines whether a prediction creates value.
- Local data infrastructure and clinical practice affect transportability.
- Data engineering is inevitable because temporal alignment, event availability, identity resolution, unit consistency, and outcome linkage determine whether the model is genuinely predictive.

1.12.3 TensorFlow Extended – Data Engineering as the Architecture of Production AI

Motivation

Machine-learning experimentation often begins with a compact script:

- load a dataset;
- transform features;
- train a model;
- compute metrics;
- save the model.

Production systems are much more demanding. They must repeatedly:

- ingest new data;
- validate schemas;
- identify anomalies;
- reproduce transformations;
- retrain models;
- evaluate candidate versions;
- prevent regressions;
- deploy safely;
- monitor operation;
- preserve lineage.

Google developed TensorFlow Extended, or TFX, as a production-scale platform for repeatable end-to-end machine-learning pipelines. The system was presented in a peer-reviewed KDD publication as an architecture for bringing models from experimentation into reliable production workflows[195].

The production problem

A manually constructed ML workflow can fail in many ways:

- the training query changes;
- a new category appears;
- an upstream field disappears;
- feature logic differs between training and serving;
- a model is deployed without comparison against the current version;
- a data anomaly causes silent degradation;
- a result cannot be reproduced; retraining requires manual intervention.

The challenge is not merely to train once. It is to create a repeatable system.

Pipeline architecture

A production-oriented pipeline is shown in **Figure 12**:




Figure 12: The workflow depicts nine sequential stages required to operationalize an AI system: data ingestion, statistical profiling, schema definition, data validation, transformation, model training, performance evaluation, model-level release validation, and production serving. The figure emphasizes that deployment-ready AI depends on coordinated data engineering, quality assurance, model assessment, approval controls, and serving infrastructure rather than on model training alone.

- **Data ingestion**

[195] Denis Baylor, Eric Breck, Heng-Tze Cheng, Noah Fiedel, Chuan Yu Foo, Zakaria Haque, et al., *TFX: A TensorFlow-Based Production-Scale Machine Learning Platform*, Proceedings of the 23rd ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, 2017.

The pipeline reads source data using a defined and versioned specification. Required controls include:

- source identifiers;
- partition information;
- extraction time;
- record counts;
- checksums;
- access controls.

- **Data statistics**

  The system computes statistics such as:

  - feature distributions;
  - missingness;
  - cardinality;
  - ranges;
  - category frequencies;
  - label balance.

  These statistics support both schema inference and change detection.

- **Schema**

  A schema specifies expectations such as:

  - data type;
  - allowed range;
  - required status;
  - categorical domain;
  - expected presence;
  - shape.

  A schema turns implicit assumptions into machine-checkable contracts.

- **Data validation**

  New data are compared with the schema and reference distributions. Validation may detect:

  - missing columns;
  - new categories;
  - unexpected ranges;

- excessive missingness;
- distribution shifts;
- malformed records.

- **Transformation**
  Feature transformations are defined once and applied consistently to both training and serving. This reduces training-serving skew.

- **Training**
  Training should record:
  - code version;
  - data version;
  - hyperparameters;
  - hardware environment;
  - random seeds;
  - model artifacts.

- **Model evaluation**
  A candidate model is evaluated on held-out data and compared with the existing production model.

- **Model validation**
  Deployment can be blocked when:
  - a required metric decreases;
  - subgroup performance worsens;
  - fairness constraints fail;
  - latency exceeds limits;
  - the model artifact is incompatible;
  - data validation fails.

- **Serving and monitoring**
  An approved model is deployed with version metadata, logging, performance monitoring, and rollback capability.

Reported operational value

The TFX publication described how reusable components and standardized pipelines reduced the time required to place models into production from months to weeks in some applications. A Google Play application described in

associated material used recurring model updates and improved data/model analysis, with a reported increase in app installations of approximately 2%. The important point is not the exact percentage in isolation. It is that business value emerged from the complete system:

- fresh data;
- repeatable transformation;
- continuous evaluation;
- reliable deployment;
- iterative improvement.

Why this is a data-engineering case study

TFX illustrates that production AI is largely a problem of controlled data movement and validated state transitions. Model dependencies are shown in **Figure 13**.




Figure 13: A deployed model depends not only on the learned parameters themselves but also on the versioned data, schema definition, transformation logic, training configuration, evaluation procedure, and approval process that collectively determine how the model is built, assessed, and released. The figure emphasizes that model behavior is a product of the entire surrounding pipeline and governance context, not of the model artifact alone.

Removing any of these components **weakens reliability**.

- **Without schema validation**
  A source change may silently corrupt features.
- **Without transformation consistency**
  The model may see different representations in training and production.
- **Without lineage**

A result cannot be reproduced or audited.

- **Without automated evaluation**
  A newly trained model may be worse than the deployed model.
- **Without orchestration**
  Tasks may execute in the wrong order or with incompatible inputs.
- **Without monitoring**
  Failures may remain invisible until users report them.

Applying the architecture outside large technology companies

A university, hospital, bank, public agency, or engineering firm may not need Google-scale infrastructure. The same principles still apply. A lightweight implementation could use:

- version-controlled SQL and Python;
- scheduled orchestration;
- object storage;
- schema-validation tools;
- data-quality tests;
- an experiment tracker;
- a model registry;
- containerized inference;
- monitoring dashboards;
- documented approval procedures.

The scale of the technology can vary. The need for reproducibility, validation, lineage, and monitoring does not disappear.

Central lessons

- A model-training script is not a production system.
- Reusable pipeline components reduce duplicated and inconsistent logic.
- Schemas make data assumptions explicit.
- Automated validation prevents bad data from silently reaching models.
- Shared transformations reduce training-serving skew.
- Candidate models should be compared with the current production system.

- Lineage enables audit, rollback, and reproducibility.
- Continuous improvement requires continuously engineered data.
- Data engineering is not merely supportive of AI production; it constitutes much of the production architecture.

Reading List

To support students in furthering their understanding of the topics covered in this module, here's a curated reading list organized by topic. This list includes books and research papers that delve deeper into each of the key areas discussed in this module.

Historical and Philosophical Roots of Artificial Intelligence

- A. M. Turing, *Computing Machinery and Intelligence*, *Mind*, 59(236), pp. 433–460, 1950.
- J. McCarthy, M. L. Minsky, N. Rochester, and C. E. Shannon, *A Proposal for the Dartmouth Summer Research Project on Artificial Intelligence*, *AI Magazine*, 27(4), 2006; original proposal written in 1955.
- A. Newell and H. A. Simon, *Computer Science as Empirical Inquiry: Symbols and Search*, *Communications of the ACM*, 19(3), pp. 113–126, 1976.
- C. E. Shannon, *A Mathematical Theory of Communication*, *Bell System Technical Journal*, 27(3–4), pp. 379–423 and 623–656, 1948.
- N. Wiener, *Cybernetics: Or Control and Communication in the Animal and the Machine*, MIT Press, 1948; open-access edition, 2019.
- S. Bringsjord and N. S. Govindarajulu, *Artificial Intelligence*, *Stanford Encyclopedia of Philosophy*, 2018, substantive revision 2024.
- G. Oppy and D. Dowe, *The Turing Test*, *Stanford Encyclopedia of Philosophy*, 2021.

Machine Intelligence, Understanding, Mind, and Meaning

- J. R. Searle, *Minds, Brains, and Programs*, *Behavioral and Brain Sciences*, 3(3), pp. 417–424, 1980.
- H. L. Dreyfus, *What Computers Still Cannot Do: A Critique of Artificial Reason*, MIT Press, 1992.
- D. J. Chalmers, *The Conscious Mind: In Search of a Fundamental Theory*, Oxford University Press, 1996.
- E. M. Bender, T. Gebru, A. McMillan-Major, and M. Mitchell, *On the Dangers of Stochastic Parrots: Can Language Models Be Too Big?* Proceedings of the ACM Conference on Fairness, Accountability, and Transparency, pp. 610–623, 2021.
- B. C. Smith, *The Promise of Artificial Intelligence: Reckoning and Judgment*, MIT Press, 2019.
- M. A. Boden, *AI: Its Nature and Future*, Oxford University Press, 2016.

Symbolic AI, Statistical Learning, and Hybrid Intelligence

- S. Russell and P. Norvig, *Artificial Intelligence: A Modern Approach*, 4th ed., Pearson, 2021.
- C. M. Bishop, *Pattern Recognition and Machine Learning*, Springer, 2006.
- I. Goodfellow, Y. Bengio, and A. Courville, *Deep Learning*, MIT Press, 2016.
- J. Pearl, *Probabilistic Reasoning in Intelligent Systems: Networks of Plausible Inference*, Morgan Kaufmann, 1988.
- L. Breiman, *Statistical Modeling: The Two Cultures*, *Statistical Science*, 16(3), pp. 199–231, 2001.
- A. S. d'Avila Garcez, L. C. Lamb, and D. M. Gabbay, *Neural-Symbolic Cognitive Reasoning*, Springer, 2009.

Machine Learning, Data Science, Statistics, and Automation Ecosystem

- OECD, *Explanatory Memorandum on the Updated OECD Definition of an AI System*, OECD Artificial Intelligence Papers, 2024.
- G. Shmueli, *To Explain or to Predict? Statistical Science*, 25(3), pp. 289–310, 2010.
- R. Parasuraman, T. B. Sheridan, and C. D. Wickens, *A Model for Types and Levels of Human Interaction with Automation*, *IEEE Transactions on Systems, Man, and Cybernetics, Part A*, 30(3), pp. 286–297, 2000.
- J. Reis and M. Housley, *Fundamentals of Data Engineering*, O'Reilly Media, 2022.
- M. Kleppmann, *Designing Data-Intensive Applications*, O'Reilly Media, 2017.

Causal Reasoning, Counterfactuals, and Interventions

- J. Pearl, *Causal Inference in Statistics: An Overview*, *Statistics Surveys*, 3, pp. 96–146, 2009.
- J. Pearl and D. Mackenzie, *The Book of Why: The New Science of Cause and Effect*, Basic Books, 2018.
- M. A. Hernán and J. M. Robins, *Causal Inference: What If*, Chapman and Hall/CRC, 2020.
- J. Kleinberg, H. Lakkaraju, J. Leskovec, J. Ludwig, and S. Mullainathan, *Human Decisions and Machine Predictions*, *Quarterly Journal of Economics*, 133(1), pp. 237–293, 2018.
- Z. Obermeyer, B. Powers, C. Vogeli, and S. Mullainathan, *Dissecting Racial Bias in an Algorithm Used to Manage the Health of Populations*, *Science*, 366(6464), pp. 447–453, 2019.
- G. W. Imbens and D. B. Rubin, *Causal Inference for Statistics, Social, and Biomedical Sciences*, Cambridge University Press, 2015.

AI as a Socio-Technical System: Responsibility, Fairness, and Governance

- A. D. Selbst, D. Boyd, S. A. Friedler, S. Venkatasubramanian, and J. Vertesi, *Fairness and Abstraction in Sociotechnical Systems*, Proceedings of the ACM Conference on Fairness, Accountability, and Transparency, pp. 59–68, 2019.
- National Institute of Standards and Technology, *Artificial Intelligence Risk Management Framework 1.0*, NIST AI 100-1, 2023.
- V. Dignum, *Responsible Artificial Intelligence: How to Develop and Use AI in a Responsible Way*, Springer, 2019.
- M. Kearns and A. Roth, *The Ethical Algorithm: The Science of Socially Aware Algorithm Design*, Oxford University Press, 2019.
- S. Reddy, S. Allan, S. Coghlan, and P. Cooper, *A Governance Model for the Application of AI in Health Care*, *Journal of the American Medical Informatics Association*, 27(3), pp. 491–497, 2020.
- B. Friedman and D. G. Hendry, *Value Sensitive Design: Shaping Technology with Moral Imagination*, MIT Press, 2019.
- OECD, *OECD Principles on Artificial Intelligence*, OECD, adopted 2019 and updated 2024.

AI as an End-to-End Lifecycle and Problem-Formulation Process

- S. Amershi, A. Begel, C. Bird, R. DeLine, H. Gall, E. Kamar, N. Nagappan, B. Nushi, and T. Zimmermann, *Software Engineering for Machine Learning: A Case Study*, Proceedings of the IEEE/ACM International Conference on Software Engineering: Software Engineering in Practice, pp. 291–300, 2019.
- D. Sculley, G. Holt, D. Golovin, E. Davydov, T. Phillips, D. Ebner, V. Chaudhary, M. Young, J. F. Crespo, and D. Dennison, *Hidden Technical Debt in Machine Learning Systems*, *Advances in Neural Information Processing Systems*, 28, 2015.
- E. Breck, S. Cai, E. Nielsen, M. Salib, and D. Sculley, *The ML Test Score: A Rubric for ML Production Readiness and Technical Debt Reduction*, Proceedings of the IEEE International Conference on Big Data, pp. 1123–1132, 2017.
- D. Baylor, E. Breck, H. T. Cheng, N. Fiedel, C. Y. Foo, Z. Haque, S. Haykal, M. Ispir, V. Jain, L. Koc, C. Y. Koo, L. Lew, C. Mewald, A. Modi, N. Polyzotis, S. Ramesh, S. Roy, S. E. Whang, M. Wicke, J. Wilkiewicz, M. Zhang, and M. Zinkevich, *TFX: A TensorFlow-Based Production-Scale Machine Learning Platform*, Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pp. 1387–1395, 2017.
- N. Polyzotis, S. Roy, S. E. Whang, and M. Zinkevich, *Data Management Challenges in Production Machine Learning*, Proceedings of the ACM SIGMOD International Conference on Management of Data, pp. 1723–1726, 2017.

- A. Ng, *Machine Learning Yearning: Technical Strategy for AI Engineers in the Era of Deep Learning*, deeplearning.ai, 2018.

Problem Framing: Decisions, Objectives, Labels, Constraints, and Costs of Error

- B. E. Frischmann and E. Selinger, *Re-Engineering Humanity*, Cambridge University Press, 2018.
- S. Barocas, M. Hardt, and A. Narayanan, *Fairness and Machine Learning: Limitations and Opportunities*, MIT Press, 2023.
- S. Corbett-Davies, E. Pierson, A. Feller, S. Goel, and A. Huq, *Algorithmic Decision Making and the Cost of Fairness*, Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pp. 797–806, 2017.
- M. Hardt, E. Price, and N. Srebro, *Equality of Opportunity in Supervised Learning*, *Advances in Neural Information Processing Systems*, 29, 2016.
- B. Green and Y. Chen, *The Principles and Limits of Algorithm-in-the-Loop Decision Making*, *Proceedings of the ACM on Human-Computer Interaction*, 3(CSCW), Article 50, 2019.
- C. O'Neil, *Weapons of Math Destruction: How Big Data Increases Inequality and Threatens Democracy*, Crown, 2016.

Data Provenance, Representation, Proxies, and Dataset Documentation

- T. Gebru, J. Morgenstern, B. Vecchione, J. W. Vaughan, H. Wallach, H. Daumé III, and K. Crawford, *Datasheets for Datasets*, *Communications of the ACM*, 64(12), pp. 86–92, 2021.
- E. M. Bender and B. Friedman, *Data Statements for Natural Language Processing: Toward Mitigating System Bias and Enabling Better Science*, *Transactions of the Association for Computational Linguistics*, 6, pp. 587–604, 2018.
- N. Sambasivan, S. Kapania, H. Highfill, D. Akrong, P. Paritosh, and L. M. Aroyo, *Everyone Wants to Do the Model Work, Not the Data Work: Data Cascades in High-Stakes AI*, Proceedings of the CHI Conference on Human Factors in Computing Systems, 2021.
- H. Suresh and J. V. Guttag, *A Framework for Understanding Sources of Harm throughout the Machine Learning Life Cycle*, Proceedings of the ACM Conference on Equity and Access in Algorithms, Mechanisms, and Optimization, 2021.
- S. Kapoor and A. Narayanan, *Leakage and the Reproducibility Crisis in Machine-Learning-Based Science*, *Patterns*, 4(9), Article 100804, 2023.
- A. Paullada, I. D. Raji, E. M. Bender, E. Denton, and A. Hanna, *Data and Its Discontents: A Survey of Dataset Development and Use in Machine Learning Research*, *Patterns*, 2(11), Article 100336, 2021.

Representation Risks, Distribution Shift, and Underspecification

- A. Torralba and A. A. Efros, *Unbiased Look at Dataset Bias*, Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition, pp. 1521–1528, 2011.
- R. Geirhos, J. H. Jacobsen, C. Michaelis, R. Zemel, W. Brendel, M. Bethge, and F. A. Wichmann, *Shortcut Learning in Deep Neural Networks*, *Nature Machine Intelligence*, 2, pp. 665–673, 2020.
- A. D'Amour, K. Heller, D. Moldovan, B. Adlam, B. Alipanahi, A. Beutel, C. Chen, J. Deaton, J. Eisenstein, M. D. Hoffman, F. Hormozdiari, N. Houlsby, S. Hou, G. Jerfel, A. Karthikesalingam, M. Lucic, Y. Ma, C. McLean, D. Mincu, A. Mitani, A. Montanari, Z. Nado, V. Natarajan, C. Nielson, T. F. Osborne, R. Raman, K. Ramasamy, R. Sayres, J. Schrouff, M. Seneviratne, S. Sequeira, H. Suresh, V. Veitch, M. Vladymyrov, X. Wang, K. Webster, S. Yadlowsky, T. Yun, X. Zhai, and D. Sculley, *Underspecification Presents Challenges for Credibility in Modern Machine Learning*, *Journal of Machine Learning Research*, 23(226), pp. 1–61, 2022.
- P. W. Koh, S. Sagawa, H. Marklund, S. M. Xie, M. Zhang, A. Balsubramani, W. Hu, M. Yasunaga, R. L. Phillips, I. Gao, T. Lee, E. David, I. Stavness, W. Guo, B. A. Earnshaw, I. S. Haque, S. Beery, J. Leskovec, A. Kundaje, E. Pierson, S. Levine, C. Finn, and P. Liang, *WILDS: A Benchmark of In-the-Wild Distribution Shifts*, Proceedings of the International Conference on Machine Learning, pp. 5637–5664, 2021.
- Y. Ovadia, E. Fertig, J. Ren, Z. Nado, D. Sculley, S. Nowozin, J. Dillon, B. Lakshminarayanan, and J. Snoek, *Can You Trust Your Model's Uncertainty? Evaluating Predictive Uncertainty under Dataset Shift*, *Advances in Neural Information Processing Systems*, 32, 2019.

Model Selection, Interpretability, Explainability, and Model Documentation

- M. Mitchell, S. Wu, A. Zaldivar, P. Barnes, L. Vasserman, B. Hutchinson, E. Spitzer, I. D. Raji, and T. Gebru, *Model Cards for Model Reporting*, Proceedings of the ACM Conference on Fairness, Accountability, and Transparency, pp. 220–229, 2019.
- C. Rudin, *Stop Explaining Black Box Machine Learning Models for High Stakes Decisions and Use Interpretable Models Instead*, *Nature Machine Intelligence*, 1, pp. 206–215, 2019.
- M. T. Ribeiro, S. Singh, and C. Guestrin, *Why Should I Trust You? Explaining the Predictions of Any Classifier*, Proceedings of the ACM SIGKDD International Conference on Knowledge Discovery and Data Mining, pp. 1135–1144, 2016.
- S. M. Lundberg and S. I. Lee, *A Unified Approach to Interpreting Model Predictions*, *Advances in Neural Information Processing Systems*, 30, 2017.

- F. Doshi-Velez and B. Kim, *Towards a Rigorous Science of Interpretable Machine Learning*, arXiv technical report, 2017.
- D. Gunning and D. Aha, *DARPA's Explainable Artificial Intelligence Program*, *AI Magazine*, 40(2), pp. 44–58, 2019.

Evaluation, Calibration, Robustness, and External Validation

- B. Van Calster, D. J. McLernon, M. van Smeden, L. Wynants, and E. W. Steyerberg, *Calibration: The Achilles Heel of Predictive Analytics*, *BMC Medicine*, 17, Article 230, 2019.
- A. Wong, E. Otles, J. P. Donnelly, A. Krumm, J. McCullough, O. DeTroyer-Cooley, J. Pestrue, M. Phillips, J. Konye, C. Penoza, M. Ghous, and K. Singh, *External Validation of a Widely Implemented Proprietary Sepsis Prediction Model in Hospitalized Patients*, *JAMA Internal Medicine*, 181(8), pp. 1065–1070, 2021.
- E. W. Steyerberg, *Clinical Prediction Models: A Practical Approach to Development, Validation, and Updating*, 2nd ed., Springer, 2019.
- D. G. Altman and P. Royston, *What Do We Mean by Validating a Prognostic Model? Statistics in Medicine*, 19(4), pp. 453–473, 2000.
- S. M. Lundberg, B. Nair, M. S. Vavilala, M. Horibe, M. J. Eisses, T. Adams, D. E. Liston, D. K. W. Low, S. F. Newman, J. Kim, and S. I. Lee, *Explainable Machine-Learning Predictions for the Prevention of Hypoxaemia during Surgery*, *Nature Biomedical Engineering*, 2, pp. 749–760, 2018.
- M. A. Riley, P. C. Snell, J. Ensor, D. L. Burke, F. E. Harrell Jr., K. G. M. Moons, and G. S. Collins, *Minimum Sample Size for Developing a Multivariable Prediction Model*, *Statistics in Medicine*, 38(7), pp. 1262–1275, 2019.

From Prediction to Decision: Thresholds, Utility, and Human Oversight

- R. T. Sutton, D. Pincock, D. C. Baumgart, D. C. Sadowski, R. N. Fedorak, and K. I. Kroeker, *An Overview of Clinical Decision Support Systems: Benefits, Risks, and Strategies for Success*, *npj Digital Medicine*, 3, Article 17, 2020.
- H. Raiffa and R. Schlaifer, *Applied Statistical Decision Theory*, MIT Press, 1961.
- J. O. Berger, *Statistical Decision Theory and Bayesian Analysis*, 2nd ed., Springer, 1985.
- M. L. Cummings, *Automation Bias in Intelligent Time Critical Decision Support Systems*, Proceedings of the AIAA Intelligent Systems Technical Conference, 2004.
- K. L. Mosier and L. J. Skitka, *Human Decision Makers and Automated Decision Aids: Made for Each Other?* in *Automation and Human Performance: Theory and Applications*, Lawrence Erlbaum Associates, 1996.

Deployment, MLOps, Monitoring, and Hidden Technical Debt

- D. Kreuzberger, N. Kühl, and S. Hirschl, *Machine Learning Operations: Overview, Definition, and Architecture*, *IEEE Access*, 11, pp. 31866–31879, 2023.
- M. Treveil, N. Omont, C. Stenac, K. Lefevre, D. Phan, J. Zentici, A. Lavoillotte, M. Miyazaki, and L. Heidmann, *Introducing MLOps: How to Scale Machine Learning in the Enterprise*, O'Reilly Media, 2020.
- E. Breck, N. Polyzotis, S. Roy, S. E. Whang, and M. Zinkevich, *Data Validation for Machine Learning*, Proceedings of the Conference on Machine Learning and Systems, 2019.
- L. Baier, F. Jöhren, and S. Seebacher, *Challenges in the Deployment and Operation of Machine Learning in Practice*, Proceedings of the ACM Symposium on Applied Computing, pp. 1067–1076, 2020.
- J. Klaise, A. Van Looveren, G. Vacanti, and A. Coca, *Monitoring and Explainability of Models in Production*, ICML Workshop on Challenges in Deploying and Monitoring Machine Learning Systems, 2020.
- A. Paleyes, R. G. Urma, and N. D. Lawrence, *Challenges in Deploying Machine Learning: A Survey of Case Studies*, *ACM Computing Surveys*, 55(6), Article 114, 2023.

Classification, Regression, Ranking, Recommendation, and Clustering

- G. James, D. Witten, T. Hastie, R. Tibshirani, and J. Taylor, *An Introduction to Statistical Learning: With Applications in Python*, Springer, 2023.
- T. Hastie, R. Tibshirani, and J. Friedman, *The Elements of Statistical Learning: Data Mining, Inference, and Prediction*, 2nd ed., Springer, 2009.
- C. D. Manning, P. Raghavan, and H. Schütze, *Introduction to Information Retrieval*, Cambridge University Press, 2008.
- F. Ricci, L. Rokach, and B. Shapira, eds., *Recommender Systems Handbook*, 3rd ed., Springer, 2022.
- C. C. Aggarwal, *Recommender Systems: The Textbook*, Springer, 2016.
- A. K. Jain, *Data Clustering: 50 Years beyond K-Means*, *Pattern Recognition Letters*, 31(8), pp. 651–666, 2010.

Planning, Control, Reinforcement Learning, and Decision Optimization

- S. M. LaValle, *Planning Algorithms*, Cambridge University Press, 2006.
- R. S. Sutton and A. G. Barto, *Reinforcement Learning: An Introduction*, 2nd ed., MIT Press, 2018.
- D. P. Bertsekas, *Dynamic Programming and Optimal Control*, 4th ed., Athena Scientific, 2017.

- K. J. Åström and R. M. Murray, *Feedback Systems: An Introduction for Scientists and Engineers*, Princeton University Press, 2008.
- M. L. Puterman, *Markov Decision Processes: Discrete Stochastic Dynamic Programming*, Wiley, 1994.
- S. Boyd and L. Vandenberghe, *Convex Optimization*, Cambridge University Press, 2004.

Anomaly Detection, Forecasting, and Generation

- C. C. Aggarwal, *Outlier Analysis*, 2nd ed., Springer, 2017.
- V. Chandola, A. Banerjee, and V. Kumar, *Anomaly Detection: A Survey*, *ACM Computing Surveys*, 41(3), Article 15, 2009.
- R. J. Hyndman and G. Athanasopoulos, *Forecasting: Principles and Practice*, 3rd ed., OTexts, 2021.
- I. Goodfellow, J. Pouget-Abadie, M. Mirza, B. Xu, D. Warde-Farley, S. Ozair, A. Courville, and Y. Bengio, *Generative Adversarial Nets*, *Advances in Neural Information Processing Systems*, 27, 2014.
- D. P. Kingma and M. Welling, *An Introduction to Variational Autoencoders*, *Foundations and Trends in Machine Learning*, 12(4), pp. 307–392, 2019.

Generative AI, Foundation Models, and Specialized Risks

- National Institute of Standards and Technology, *Artificial Intelligence Risk Management Framework: Generative Artificial Intelligence Profile*, NIST AI 600-1, 2024.
- L. Weidinger, J. Mellor, M. Rauh, C. Griffin, J. Uesato, P. S. Huang, M. Cheng, M. Glaese, B. Balle, A. Kasirzadeh, Z. Kenton, S. Brown, W. Hawkins, T. Stepleton, C. Biles, A. Birhane, J. Haas, L. Rimell, L. A. Hendricks, W. Isaac, S. Legassick, G. Irving, and I. Gabriel, *Taxonomy of Risks Posed by Language Models*, Proceedings of the ACM Conference on Fairness, Accountability, and Transparency, pp. 214–229, 2022.
- Z. Ji, N. Lee, R. Frieske, T. Yu, D. Su, Y. Xu, E. Ishii, Y. J. Bang, A. Madotto, and P. Fung, *Survey of Hallucination in Natural Language Generation*, *ACM Computing Surveys*, 55(12), Article 248, 2023.
- N. Carlini, F. Tramer, E. Wallace, M. Jagielski, A. Herbert-Voss, K. Lee, A. Roberts, T. Brown, D. Song, Ú. Erlingsson, A. Oprea, and C. Raffel, *Extracting Training Data from Large Language Models*, Proceedings of the USENIX Security Symposium, pp. 2633–2650, 2021.
- R. Bommasani, D. A. Hudson, E. Adeli, R. Altman, S. Arora, S. von Arx, M. S. Bernstein, J. Bohg, A. Bosselut, E. Brunskill, E. Brynjolfsson, S. Buch, D. Card, R. Castellon, N. Chatterji, A. Chen, K. Creel, J. Q. Davis, D. Demszky, C. Donahue, M. Doumbouya, E. Durmus, S. Ermon, J. Etchemendy, K. Ethayarajh, L. Fei-Fei, C. Finn, T. Gale, L. Gillespie,

K. Goel, N. Goodman, S. Grossman, N. Guha, T. Hashimoto, P. Henderson, J. Hewitt, D. E. Ho, J. Hong, K. Hsu, J. Huang, T. Icard, S. Jain, D. Jurafsky, P. Kalluri, S. Karamcheti, G. Keeling, F. Khani, O. Khattab, P. W. Koh, M. Krass, R. Krishna, R. Kuditipudi, A. Kumar, F. Ladhak, M. Lee, T. Lee, J. Leskovec, I. Levent, X. L. Li, X. Li, T. Ma, A. Malik, C. D. Manning, S. P. Mirchandani, E. Mitchell, Z. Munyikwa, S. Nair, A. Narayan, D. Narayanan, B. Newman, A. Nie, J. C. Niebles, H. Nilforoshan, J. Nyarko, G. Ogut, L. Orr, I. Papadimitriou, J. S. Park, C. Piech, E. Portelance, C. Potts, A. Raghunathan, R. Reich, H. Ren, F. Rong, Y. Roohani, C. Ruiz, J. Ryan, C. Ré, D. Sadigh, S. Sagawa, K. Santhanam, A. Shih, K. P. Srinivasan, A. Tamkin, R. Taori, A. Thomas, F. Tramèr, R. E. Wang, W. Wang, B. Wu, J. Wu, Y. Wu, S. M. Xie, M. Yasunaga, J. You, M. Zaharia, M. Zhang, T. Zhang, X. Zhang, Y. Zhang, L. Zheng, K. Zhou, and P. Liang, *On the Opportunities and Risks of Foundation Models*, Stanford Center for Research on Foundation Models, 2021.

Why AI Projects Fail: Leakage, Feedback Loops, Weak Evaluation, and Deployment Failure

- D. Lazer, R. Kennedy, G. King, and A. Vespignani, *The Parable of Google Flu: Traps in Big Data Analysis*, *Science*, 343(6176), pp. 1203–1205, 2014.
- D. Ensign, S. A. Friedler, S. Neville, C. Scheidegger, and S. Venkatasubramanian, *Runaway Feedback Loops in Predictive Policing*, Proceedings of the Conference on Fairness, Accountability and Transparency, pp. 160–171, 2018.
- A. Wong, E. Otles, J. P. Donnelly, et al., *External Validation of a Widely Implemented Proprietary Sepsis Prediction Model in Hospitalized Patients*, *JAMA Internal Medicine*, 181(8), pp. 1065–1070, 2021.
- Z. Obermeyer, B. Powers, C. Vogeli, and S. Mullainathan, *Dissecting Racial Bias in an Algorithm Used to Manage the Health of Populations*, *Science*, 366(6464), pp. 447–453, 2019.
- S. Kapoor and A. Narayanan, *Leakage and the Reproducibility Crisis in Machine-Learning-Based Science*, *Patterns*, 4(9), Article 100804, 2023.
- A. D'Amour et al., *Underspecification Presents Challenges for Credibility in Modern Machine Learning*, *Journal of Machine Learning Research*, 23(226), pp. 1–61, 2022.
- D. Sculley et al., *Hidden Technical Debt in Machine Learning Systems*, *Advances in Neural Information Processing Systems*, 28, 2015.

Practice Questions for Quizzes and/or Exams

Please find below a list of **practice questions** to help you review **key concepts** and prepare for quizzes and/or exams.

Historical and Philosophical Roots of AI

1. Why is the history of AI better understood as a history of attempts to formalize intelligence rather than only as a history of faster computers?
2. Identify the major intellectual traditions that contributed to the development of modern AI.
3. Explain how formal logic made the idea of mechanized reasoning possible.
4. What does it mean to say that intelligence requires representation?
5. How does a symbolic program differ from a numerical program?
6. Explain how facts, rules, and queries interact in a Prolog program.
7. How does an expert system separate knowledge representation from the inference engine?
8. How does symbolic theorem proving establish that two algebraic expressions are equivalent?
9. Why is symbolic reasoning bounded by the symbols, facts, and rules supplied to the system?
10. Compare the roles of probability theory and statistical inference in reasoning under uncertainty.

Feedback, Information, and the Operational View of Intelligence

11. How did cybernetics connect communication, feedback, and control in animals and machines?
12. Explain how a feedback loop can make an AI system an active participant in the environment that it models.
13. How can predictive policing produce self-reinforcing bias and selective labels?
14. Distinguish among self-reinforcing bias, selective labels, performative effects, and feedback loops.
15. Why is information not automatically equivalent to meaning?
16. Use facial emotion recognition to explain how a dataset can contain abundant information but represent the target phenomenon poorly.
17. How did Claude Shannon contribute to concepts now used throughout machine learning?

18. How did Alan Turing transform the question of machine thought into an operational evaluation problem?
19. Why does successful performance on a Turing style test not settle whether a machine understands?
20. What role did the Dartmouth proposal play in naming and consolidating the field of AI?

Symbolic AI, Statistical Learning, and Hybrid Systems

21. State the main strengths of symbolic AI.
22. State the main limitations of symbolic AI in complex and uncertain environments.
23. Why would a purely symbolic self-driving system struggle with ambiguity, noisy perception, and combinatorial explosion?
24. State the main strengths of statistical machine learning.
25. State the main limitations of statistical machine learning.
26. How can a pneumonia prediction model learn a hospital-specific shortcut rather than a medically meaningful pattern?
27. What is distribution shift, and why can it reduce performance at a new hospital?
28. Explain why symbolic AI and statistical machine learning should not be treated as a permanent binary choice.
29. Describe how an autonomous warehouse robot can combine learned perception, search, optimization, safety rules, and human review.
30. Under what conditions is a hybrid AI system preferable to a purely symbolic or purely statistical system?

Philosophical Questions, Agency, and Responsibility

31. Why is intelligence better viewed as a spectrum of capabilities than as a single monolithic property?
32. Compare prediction with causal reasoning.
33. Why can accurate prediction fail to answer a question about the effect of an intervention?
34. Distinguish among counterfactual inquiry, structural assumptions, and mechanistic models.
35. Use student attendance and exam performance to explain the difference between correlation and intervention effect.
36. What does it mean to describe a deployed AI system as a socio-technical composite?
37. Explain how data infrastructure, interface design, human workflow, and institutional rules can alter the impact of the same recruitment model.
38. Why should moral agency not be attributed directly to an algorithm?
39. How do upstream and downstream human decisions shape AI outcomes?

40. Explain the Govern, Map, Measure, and Manage functions of the NIST AI Risk Management Framework.

The AI and Data Science Ecosystem

41. Define artificial intelligence as both a scientific discipline and an engineering discipline.
42. Compare systems that think like humans, act like humans, think rationally, and act rationally.
43. What is a rational agent, and why does rational action not imply perfect action?
44. Distinguish among passive analytical systems, decision-support systems, semi-autonomous systems, and autonomous systems.
45. Why should autonomy not be confused with intelligence?
46. Differentiate artificial intelligence, machine learning, data science, statistics, analytics, optimization, automation, generative AI, and data engineering.
47. Why is machine learning not synonymous with artificial intelligence?
48. Why is deep learning not synonymous with machine learning?
49. Why is data science broader than model training?
50. Compare the traditional emphasis of statistics with the traditional emphasis of machine learning.
51. How do inferential thinking and predictive thinking complement each other in a mature AI project?
52. Why is mathematical optimization ethically blind and epistemically blind?
53. Explain why optimization can solve a specified objective without validating whether the objective is appropriate.
54. Distinguish automation without intelligence from intelligence without full automation.
55. Compare generative AI with discriminative AI and identify the distinctive risks of generative systems.

AI as an End-to-End Pipeline

56. List and explain the eight stages of the end-to-end AI pipeline presented in the module.
57. Why should the AI pipeline be viewed as iterative and cyclical rather than as a one-directional waterfall?
58. What elements should a robust AI problem statement define before model development begins?
59. Why is the statement build a model to predict hospital readmission an inadequate problem formulation?
60. What additional details make a hospital readmission problem operationally meaningful?

61. What questions should be asked about data provenance, variable definitions, completeness, temporal integrity, and governance?
62. What is the purpose of a Datasheet for Datasets?
63. How can poor dataset documentation lead to unsafe deployment of a skin lesion classifier?
64. Why is representation described as the bridge between the physical world and computational models?
65. Explain loss of context, proxy encoding, aggregation bias, temporal leakage, identity errors, and train-serving mismatch.
66. What does the mapping $f_\theta: X \to Y$ represent in model development?
67. Which operational, governance, data, and lifecycle criteria should guide model selection?
68. Why can a simpler model be preferable to a more accurate but complex model?
69. Why should the principle of parsimony be treated as a heuristic rather than as a rule that reality must always be simple?
70. What information should a Model Card communicate to downstream users?

Evaluation, Decisions, Deployment, and Monitoring

71. Why is overall accuracy insufficient for evaluating a high-stakes AI system?
72. Distinguish discrimination from calibration.
73. What evaluation dimensions should be assessed in addition to predictive performance?
74. Why must temporal, geographic, equity, probabilistic, and decision claims be matched with appropriate validation methods?
75. Why is a machine learning prediction not the same as a decision?
76. How should asymmetric error costs, intervention capacity, uncertainty, fairness, and human review influence a decision threshold?
77. Interpret the conceptual decision-cost function that combines false positives, false negatives, delay, and workflow cost.
78. What engineering and governance questions must be answered before moving a model from a sandbox into production?
79. What is the role of abstention, fallback procedures, rollback mechanisms, and circuit breakers in deployment?
80. What should be monitored across input quality, drift, feature pipelines, model outputs, predictive performance, operations, human interaction, fairness, and feedback loops?

Types of AI Problems

81. Distinguish binary, multiclass, and multilabel classification.

82. Why must a classification label such as high risk include an event definition, threshold, and time horizon?
83. Compare mean squared error and mean absolute error for regression tasks.
84. Why should the regression loss function reflect the real application rather than convention alone?
85. How do ranking and recommendation differ from ordinary classification?
86. Why are observed clicks not pure measures of user preference in a recommendation system?
87. Why should clusters not automatically be treated as objectively real categories?
88. What components are required to formulate a search problem?
89. Compare search, planning, and control as classical AI problem types.
90. Explain the main framing risks in anomaly detection, generation, forecasting, causal estimation, and decision optimization.

Problem Formulation and Common Failure Modes

91. Why should an AI project begin with a decision or capability rather than with an available dataset?
92. What questions are included in a comprehensive problem-framing canvas?
93. Define the target population, unit of analysis, index time, prediction horizon, inputs, outputs, labels, constraints, stakeholders, and cost of error.
94. Why must every feature be available at or before the index time?
95. How should a project team define a meaningful baseline and an evaluation plan before training begins?
96. Explain how solving the wrong problem, poor data quality, data leakage, weak evaluation, underspecification, distribution shift, ignored workflow, and absent monitoring can cause AI failure.

Data Engineering and Illustrative Case Studies

97. Why is data engineering described as the connective tissue of the complete AI lifecycle?
98. How do semantics, temporal correctness, training-serving consistency, lineage, governance, and monitoring make data engineering unavoidable?
99. What lessons about proxies, drift, lineage, and ground-truth anchoring can be learned from Google Flu Trends and the Epic Sepsis Model?
100. How does TensorFlow Extended demonstrate that production AI depends on ingestion, statistics, schemas, validation, transformation, training, evaluation, model validation, serving, monitoring, and lineage?

Below is a list of **scenario-based questions** designed to help students apply the concepts from this module to real-world AI systems.

S1: University Student Support System

A university plans to build an AI system to identify students who may fail a course. The initial proposal states: *Build a machine learning model that predicts student failure*. The available data include attendance, assignment grades, learning-platform activity, prior academic performance, financial-aid status, and final examination results. The university intends to use the predictions to allocate a limited number of tutoring appointments. However, the proposal does not specify when the prediction will be made, which students will be included, how failure will be defined, or how many tutoring appointments are available.

Questions

- Why is the original problem statement inadequately formulated?
- Rewrite the problem statement by specifying the target population, index time, prediction horizon, outcome, decision-maker, and intended action.
- Which variables may create temporal leakage if the prediction is required during the first four weeks of the semester?
- What are the likely consequences of false-positive and false-negative predictions?
- Should the university evaluate only predictive accuracy, or should it also measure calibration, subgroup performance, and decision utility? Explain briefly.

S2: Hospital Sepsis Prediction

A hospital develops a model to predict sepsis within the next six hours. During training, missing blood-pressure values are replaced with the median value for the relevant hospital ward. In production, the software team replaces missing values with zero.

The training data also include the number of broad-spectrum antibiotic doses administered. In many records, this value is updated after a physician has already suspected or diagnosed sepsis. The model achieves 98 percent accuracy during development but produces a large number of false alerts after deployment.

Questions

- Identify the train-serving mismatch in this case.
- Explain why the antibiotic-dose feature may introduce temporal leakage.
- Why can high offline accuracy coexist with poor real-world performance?
- Which data validation checks should be placed between data ingestion and model inference?
- What fallback action should occur when critical clinical inputs are missing or invalid?

S3: Automated Loan Underwriting

A bank compares two models for predicting loan default: (a) *A deep neural network with 94% accuracy* (b) A logistic regression model with 91% accuracy.

The deep neural network uses thousands of behavioral features and requires substantial computing resources. Its explanations vary when different post-hoc methods are applied. The logistic regression model uses 15 established financial variables, runs on standard hardware, and provides directly interpretable coefficients.

The bank must provide applicants with clear reasons for rejected applications and has limited machine-learning engineering capacity.

Questions

- Which model should the bank consider for deployment, and why?
- Why is the model with the highest predictive accuracy not automatically the best operational choice?
- Which criteria beyond accuracy should guide model selection?
- How do interpretability, latency, maintenance cost, and governance requirements affect the decision?
- What information should be documented in a Model Card before deployment?

S4: AI Based Recruitment Ranking

A company trains a ranking model using ten years of historical recruitment data. The model gives higher scores to applicants from a small group of universities because candidates from these institutions were hired more frequently in the past.

Recruiters receive a dashboard containing a ranked list of applicants. The interface highlights the top ten candidates in green, while all remaining candidates appear in grey. Recruiters are instructed to review all applications, but most interview invitations are sent only to the highlighted candidates.

After one year, the company retrains the model using the new hiring data generated under this process.

Questions

- Why should this system be understood as a socio-technical system rather than only as a ranking algorithm?
- How may historical hiring data encode institutional bias?
- How can the dashboard design influence human decisions and create automation bias?
- Explain how retraining on the new hiring data may create a self-reinforcing feedback loop.
- Which stakeholders should be responsible for governing, measuring, and managing the risks of this system?

S5: Smart Warehouse Robot

A warehouse deploys a robot that identifies packages using cameras, calculates routes through the facility, and transports items to shipping stations. The robot uses:

- A deep learning model for package and obstacle recognition
- A search algorithm for route selection
- An optimization procedure for reducing travel time
- Explicit rules that prohibit entry into restricted areas
- A safety controller that stops the robot when collision risk becomes high
- Human review when damaged packages are detected

During peak season, the layout of the warehouse changes, new packaging materials are introduced, and the number of workers in the facility increases. The robot begins taking longer routes and occasionally fails to recognize reflective packages.

Questions

- Why is this system an example of hybrid AI?
- Which components are statistical, symbolic, search-based, optimization-based, and human-controlled?
- What types of data drift or environmental change are present?
- Which operational indicators should be monitored after deployment?
- Under what conditions should the robot abstain, stop, use a fallback procedure, or request human review?

These are **take-home reflection questions** intended to encourage **deep thinking and planning**. There are no single correct answers. Each question can't be answered in a couple sentences. It will push you to think deeply about the concepts, principles, and practices in this module.

R1: National Early Warning System for Disease Outbreaks

A national public health agency proposes an AI system to identify emerging infectious disease outbreaks before hospitals become overwhelmed. The proposed system will combine hospital admission records, pharmacy sales, laboratory test orders, school absenteeism, internet search activity, weather conditions, and social media posts. The project team initially defines the objective as follows: *Use AI to detect disease outbreaks as early as possible*.

A machine learning model performs well when tested retrospectively. However, several concerns emerge. Internet search activity changes after media reports about a disease. Laboratory testing is more frequent in wealthy urban areas than in rural regions. Pharmacy sales include purchases made for prevention rather than illness. Social media activity is

concentrated among younger populations. The system may also influence future data because issuing an outbreak warning can increase testing, hospital visits, online searches, and public concern.

Questions

- **Reformulate the problem comprehensively.** Define the target population, unit of analysis, index time, prediction horizon, output, decision-maker, intended intervention, resource constraints, and acceptable delay. Explain whether the primary task should be classification, anomaly detection, forecasting, causal estimation, or a hybrid of several problem types.
- **Examine the meaning of the available data.** For every major source, discuss what phenomenon it directly measures, what it only approximates, and how the data-generation process may differ across regions and populations. Identify the proxies, missing populations, selective labels, and possible measurement biases.
- **Design an evaluation strategy that matches the deployment claims.** Explain how temporal validation, geographic validation, calibration assessment, subgroup analysis, detection delay, false-alarm rate, and comparison with existing epidemiological surveillance should be incorporated. Discuss why a random train-test split would be inadequate.
- **Analyze the feedback loop created by deployment.** Explain how an alert could change testing, reporting, public behavior, and future training data. Propose a logging, monitoring, and retraining strategy that distinguishes changes in actual disease prevalence from changes caused by the warning system itself.
- **Develop a governance plan.** Allocate responsibility across public health officials, data engineers, epidemiologists, model developers, hospitals, communication teams, and government leaders. Apply the Govern, Map, Measure, and Manage functions to determine when the system should issue a warning, abstain, request expert review, or be suspended.

R2: Adaptive Traffic Management for a Large City

A city plans to replace fixed traffic-light schedules with an AI-based traffic-management system. The system will use road cameras, vehicle sensors, mobile-phone location data, public-transport schedules, emergency-service requests, weather information, and historical traffic records.

The stated goal is to minimize average travel time. The optimization system learns to give longer green signals to roads with the largest traffic volumes. After deployment, average travel time decreases by 12 percent, but buses become less reliable, pedestrian waiting times increase, cyclists report more dangerous crossings, and traffic is redirected through low-income residential areas.

The city argues that the system is successful because it achieved the objective that engineers specified.

Questions

- **Critique the objective function.** Explain why minimizing average vehicle travel time may be mathematically clear but socially incomplete. Propose a multi-objective formulation that accounts for public transport, pedestrians, cyclists, emergency vehicles, air pollution, neighborhood disruption, safety, and equity.
- **Distinguish prediction, planning, optimization, and control within this system.** Identify the role played by each component and explain why the complete system cannot be described merely as a traffic-prediction model.
- **Analyze the representation of the city.** Discuss which road users are visible to the data infrastructure and which may be poorly represented. Explain how mobile-phone ownership, camera placement, sensor coverage, and historical planning decisions could produce aggregation bias or proxy encoding.
- **Propose a decision-cost framework.** Identify the costs of false congestion alarms, missed congestion, delayed emergency vehicles, pedestrian risk, pollution, and workflow failure. Explain how these costs should influence real-time control decisions rather than relying only on average accuracy or travel time.
- **Treat the system as a socio-technical composite.** Analyze how the model, data infrastructure, public interface, traffic-control workflow, transport policy, legal rules, and public accountability mechanisms jointly determine outcomes. Explain who should have authority to modify objectives, thresholds, and safety constraints.

R3: Generative AI Adviser for University Students

A university introduces a generative AI adviser to help students select courses, understand degree requirements, prepare study plans, and identify academic-support services. The system uses curriculum documents, course descriptions, student records, prerequisite rules, historical enrolment data, and university policies.

During a pilot, students report that the adviser is fluent, patient, and available at all hours. However, it occasionally invents course prerequisites, recommends classes that are not being offered, exposes information from another student record, and presents outdated academic regulations with high confidence. Some students begin following its recommendations without consulting faculty advisers.

University leadership proposes allowing the system to register students automatically in order to reduce administrative workload.

Questions

- **Locate this system within the AI landscape.** Explain which parts involve generative AI, information retrieval, symbolic rules, search, recommendation, optimization,

automation, and human decision support. Develop a hybrid architecture that uses each approach only where it is appropriate.

- **Define the boundary between intelligence and autonomy.** Discuss whether the adviser should remain passive, operate as decision support, execute routine actions semi-autonomously, or be permitted to register students without immediate human approval. Justify different autonomy levels for low-risk and high-risk actions.
- **Design mechanisms for grounding and reliability.** Explain how retrieval from authoritative university sources, rule-based prerequisite checking, source citation, uncertainty communication, abstention, version control, and human escalation could reduce confabulation and outdated advice.
- **Examine human-system interaction risks.** Discuss automation bias, overreliance, interface design, unequal access to human advisers, and the possibility that professionally written but incorrect advice may be accepted without verification. Propose interface features that encourage critical review.
- **Develop an end-to-end monitoring plan.** Specify indicators for factual accuracy, privacy violations, outdated knowledge, student overrides, human escalations, harmful recommendations, subgroup differences, response latency, system availability, and real-world academic outcomes. Explain what events should trigger rollback or temporary suspension.

R4: AI for Climate-Smart Agricultural Support

An agricultural ministry wants to help smallholder farmers decide when to irrigate, fertilize, plant, and harvest. The proposed system combines satellite images, weather forecasts, soil sensors, crop records, market prices, and farmer-reported observations. It generates personalized recommendations through a mobile application.

Most historical data come from large commercial farms with reliable irrigation, high-quality sensors, and stable internet connectivity. Small farms often have incomplete records, different crop varieties, irregular access to water, and limited ability to act on recommendations. The model predicts crop yield accurately, and the ministry assumes that following its recommendations will therefore increase yield.

Questions

- **Separate prediction from causal reasoning.** Explain why accurately predicting yield does not prove that a recommended intervention will improve yield. Formulate the counterfactual questions that must be answered before recommending irrigation, fertilizer, or planting changes.
- **Evaluate the target population and data representativeness.** Compare the historical training population with the intended deployment population. Discuss distribution shift, missingness, sensor inequality, regional variation, and whether a Datasheet for Datasets would reveal limitations before deployment.

- **Design a meaningful representation of the farming process.** Explain whether static feature vectors are sufficient or whether temporal sequences, spatial maps, weather uncertainty, resource constraints, and mechanistic crop models are required. Discuss the costs of losing temporal or local context.
- **Choose an appropriate combination of computational methods.** Consider statistical learning, weather forecasting, optimization, rule-based agronomic constraints, causal estimation, and human expert review. Explain why a single highly complex model may be inferior to a transparent hybrid system.
- **Assess the broader decision workflow.** A recommendation is useful only if the farmer has water, credit, fertilizer, labor, transport, and market access. Explain how these constraints should affect problem formulation, evaluation, interface design, and claims of system success.

R5: Automated Prioritization of Social-Welfare Applications

A government agency receives more social-welfare applications than its staff can process quickly. It proposes an AI system that assigns each applicant a priority score based on income, employment history, family size, location, housing status, prior benefit use, and administrative records.

The model is trained to predict which applications were approved historically. It achieves high accuracy and is used to place applicants into three queues:

- Immediate processing
- Standard processing
- Low priority processing

After deployment, applicants from informal employment sectors and remote areas are frequently assigned low priority because their records are incomplete. These cases are reviewed less often, so fewer positive outcomes are observed for these groups. The agency later retrains the model using the newly collected decisions.

Questions

- **Determine whether the label represents the real objective.** Discuss the difference between predicting historical approval and identifying present need or eligibility. Explain how historical administrative decisions may encode policy choices, documentation inequality, resource constraints, and institutional bias.
- **Analyze the emerging feedback loop.** Explain how low-priority assignment reduces review, how reduced review creates selective labels, and how retraining on these outcomes may make the model increasingly confident in its original decisions.
- **Reformulate the problem around a decision or capability.** Define the real operational need, target population, index time, prediction horizon, decision alternatives, capacity constraints, and consequences of delay. Consider whether

prioritization should be based on need, eligibility uncertainty, urgency, expected benefit, or review complexity.

- **Design an evaluation and fairness framework.** Identify appropriate measures beyond aggregate accuracy, including false-negative rates, waiting time, calibration, subgroup performance, appeal outcomes, human override rates, and harm caused by delayed assistance. Discuss how evaluation should account for incomplete ground truth.
- **Assign responsibility across the socio-technical lifecycle.** Explain the responsibilities of policy designers, data collectors, software developers, model developers, caseworkers, agency leaders, auditors, and appeal bodies. Propose safeguards such as human review, explanation requirements, an appeal channel, abstention for incomplete records, monitoring, and decommissioning criteria.

Below is a list of **application problems** designed to help students translate the concepts into concrete planning, documentation, evaluation, and governance artifacts. They reflect the end-to-end view of AI presented in this module, including problem formulation, data documentation, model selection, deployment, monitoring, and failure analysis.

A1: Formulating an AI Problem

Scenario: Reducing Unplanned Hospital Readmissions

A regional hospital reports that many adult patients return to the hospital shortly after discharge. Hospital leadership proposes the following project: *Build an AI model that predicts which patients will be readmitted*.

The hospital has access to demographic information, diagnoses, medications, laboratory results, previous admissions, discharge summaries, appointment history, insurance status, and future claims data. Predictions could be generated at admission, during hospitalization, at discharge, or several days after discharge.

The hospital has only 100 follow-up appointment slots each week. The discharge team must decide which patients should receive an early follow-up appointment, a telephone call, standard discharge instructions, or no additional intervention.

Task

Develop a complete AI problem formulation for this project. Your response must specify:

- The real-world decision or operational capability to be improved.
- The target population and exclusion criteria.
- The unit of analysis.
- The index time at which the prediction will be generated.
- The prediction horizon.
- The precise outcome definition.
- The information available at the index time.

- The decision-maker who will receive the output.
- The actions that may follow from the prediction.
- The current baseline or status quo.
- The consequences of false positives and false negatives.
- The intervention-capacity constraint.
- The primary performance and calibration measures.
- The subgroup and fairness analyses required.
- The conditions under which the system should abstain or request human review.
- A final problem statement written as one precise paragraph.

Also identify any variables in the proposed data that could produce temporal leakage.

A2: Preparing a Model Card

Scenario: Heart Disease Risk Prediction Model

A hospital has developed a random forest model to estimate the probability that an adult patient has clinically significant heart disease. The following information is available:

- Training data: 12,000 patient records from two urban hospitals
- Evaluation data: 3,000 records collected later from the same hospitals
- Inputs: age, sex, blood pressure, cholesterol, chest pain category, maximum heart rate, diabetes status, body mass index, and electrocardiogram findings
- Output: probability of heart disease
- Overall accuracy: 86 percent
- Precision: 0.82
- Recall: 0.74
- F_1 score: 0.78
- Recall for male patients: 0.80
- Recall for female patients: 0.62
- Recall for patients younger than 40 years: 0.55
- The predicted probabilities are moderately overconfident
- Family history, smoking status, ethnicity, and genetic information are unavailable
- The model has not been externally validated
- The intended use is clinical decision support
- Some administrators have proposed using the model to automatically reject requests for further cardiac testing

Task

Prepare a complete Model Card for this system. The Model Card must contain:

- Model name, version, type, and architecture.
- Purpose and intended clinical role.
- Intended users.
- Inputs and outputs.
- Training and evaluation data.
- Preprocessing and missing-value handling.

- Overall performance measures.
- Subgroup performance.
- Calibration findings.
- Fairness observations.
- Known limitations.
- Appropriate uses.
- Inappropriate or prohibited uses.
- Human-review requirements.
- Potential harms resulting from false positives and false negatives.
- Generalizability limitations.
- Monitoring requirements after deployment.
- Conditions that should trigger recalibration, retraining, rollback, or withdrawal.
- Future work required before broader deployment.

Conclude the Model Card with a clear deployment recommendation: approve, conditionally approve, or do not approve.

A3: Preparing a Datasheet for a Dataset

Scenario: Crop Disease Image Dataset

An agricultural research institute releases a dataset for developing AI systems that identify crop diseases from leaf images. The dataset contains:

- 80,000 images
- Four crops: wheat, maize, tomato, and potato
- Twelve disease categories and one healthy category
- Images collected from 35 commercial farms
- Seventy percent of the images collected from two regions
- Most images captured during daylight using high-resolution cameras
- Only 5 percent captured using low-cost mobile phones
- Disease labels assigned by field technicians
- Ten percent of labels independently reviewed by plant pathologists
- Diseased plants photographed more frequently than healthy plants
- Images resized to 512 by 512 pixels
- Backgrounds not removed
- Farm identifiers replaced with coded values
- No images collected during drought conditions
- No data from smallholder farms
- No formal procedure for adding future disease categories
- Intended use described only as crop disease AI research

Task

Prepare a Datasheet for this dataset. The datasheet must document:

- Motivation for creating the dataset.
- Dataset creators, funders, and responsible maintainers.

- Dataset composition.
- Unit of observation.
- Geographic and seasonal coverage.
- Crop and disease distributions.
- Data-collection process.
- Sampling procedure.
- Label definitions.
- Labeling and verification procedures.
- Preprocessing and transformations.
- Known missing populations and conditions.
- Potential proxies and dataset artifacts.
- Possible class imbalance and selection bias.
- Consent, privacy, licensing, and access considerations.
- Recommended uses.
- Uses that are not supported.
- Risks associated with mobile-phone deployment.
- Generalization limitations.
- Maintenance, correction, versioning, and retirement procedures.

Conclude by explaining whether the dataset is suitable for training a system intended for smallholder farmers using low-cost mobile phones.

A4: Deciding Which Model to Deploy

Scenario: Predictive Maintenance in a Manufacturing Plant

A manufacturing company wants to predict whether a critical machine will fail within the next 24 hours. The system must generate a prediction every minute using vibration, temperature, pressure, load, and maintenance-history data. Three models have been evaluated (**Table 3**).

Additional constraints include:

- The production controller requires a response within 100 milliseconds.
- The plant has no GPU infrastructure.
- Engineers require understandable reasons before stopping a machine.
- Every unnecessary shutdown costs 20,000 dollars.
- A missed failure can cost more than 1 million dollars and may injure workers.
- The internal team has experience with statistical models and tree-based systems but limited deep-learning expertise.

Task

Select the model that should be deployed and justify the decision. Your analysis must consider:

- Predictive performance.
- Failure recall.

- Calibration.
- False-positive and false-negative costs.
- Latency.
- Hardware and memory requirements.
- Robustness to missing sensor values.
- Interpretability and explanation needs.
- External validation.
- Maintenance burden.
- Available team expertise.
- Long-term lifecycle cost.
- Monitoring and retraining requirements.
- Whether the selected model should operate automatically or as decision support.
- Whether a hybrid arrangement involving more than one model would be preferable.

Do not select a model solely because it has the highest accuracy.

Table 3: Major types of AI problems, their desired outputs, representative applications, evaluation metrics, and common framing errors.

Criterion	Model A: Logistic Regression	Model B: Random Forest	Model C: Deep Neural Network
Accuracy	88 percent	92 percent	94 percent
Failure recall	76 percent	87 percent	90 percent
Calibration	Good	Moderate	Poor
Inference latency	5 milliseconds	35 milliseconds	240 milliseconds
Explanation	Direct coefficients	Feature importance and local explanations	Unstable post-hoc explanations
Memory requirement	Very low	Moderate	High
Specialist maintenance	Low	Moderate	High
Performance with missing sensors	Moderate	Good	Poor
External-site validation	Completed	Completed	Not completed
Retraining frequency	Every six months	Every three months	Every month

A5: Identifying Hidden Technical Debt

Scenario: Food Delivery Recommendation System

A food delivery company uses a machine-learning model to rank restaurants for each customer. The system has operated for three years. The following conditions are discovered during an internal review:

- Customer, restaurant, payment, location, and promotion data are joined through several undocumented scripts.
- The mobile application team recently renamed several event fields without informing the machine-learning team.
- Training uses one implementation of restaurant distance, while production uses another.
- Fifteen separate configuration files contain ranking weights and thresholds.
- Some configuration files are edited manually on production servers.
- More than twenty internal services consume model scores, but no central list of consumers exists.
- The recommendation interface accepts only five fixed restaurant categories.
- The new model produces twelve categories and a continuous relevance score.
- A large block of custom glue code maps the new outputs into the old interface.
- User clicks are treated as direct measures of preference.
- Restaurants shown near the top receive more clicks and therefore appear more frequently in future training data.
- Promotion teams modify ranking scores after model inference.
- Feature definitions are duplicated across training, testing, and production pipelines.
- Restaurant availability is refreshed every hour, even though many restaurants open and close within minutes.
- No single person owns the complete pipeline.
- Only recommendation click-through rate is monitored.

Task

Prepare a hidden technical debt register. For each identified debt item, record:

- The evidence in the scenario.
- The technical debt category.
- The affected component.
- The likely failure mode.
- The possible business, fairness, or operational consequence.
- The method for detecting the problem.
- The proposed corrective action.
- The person or team that should own the corrective action.
- The urgency level.

Your register should consider at least:

- Undeclared consumers
- Unstable data dependencies
- Train-serving mismatch
- Configuration debt

- Glue-code debt
- Pipeline entanglement
- Stale features
- Feedback loops
- Selective exposure
- Monitoring gaps
- Ownership gaps
- Interface rigidity
- Hidden post-processing

Conclude by identifying the three items that create the greatest production risk.

A6: Completing a Problem-Framing Worksheet

Scenario: University Tutoring Allocation

A university can provide intensive tutoring to only 200 first-year students each semester. University leadership proposes using AI to identify students who are likely to experience serious academic difficulty. Available information includes:

- Admission scores
- Previous academic records
- Programme of study
- Course enrolment
- Attendance
- Weekly quizzes
- Assignment submissions
- Learning-platform activity
- Financial-aid information
- Midterm grades
- Final grades
- Withdrawal records

Tutoring can begin at the end of week 3, week 6, or after the midterm examination. The existing process relies on voluntary student requests and faculty referrals. Some students may not seek help because of stigma, lack of awareness, or scheduling constraints.

Task

Complete the following problem-framing worksheet:

At **[decision time]**, for **[target population or unit]**, using only **[available information]**, produce **[required output]** concerning **[prediction horizon or outcome period]**, so that **[decision-maker]** can **[action]**. The system will be compared with **[baseline]** and evaluated using **[metrics]**, while accounting for **[error costs, subgroup risks, operational constraints, and governance requirements]**.

After completing the statement, explain:

- Why the selected decision time is operationally appropriate.
- Which variables are available at that time.
- Which variables would cause temporal leakage.
- How serious academic difficulty should be defined.
- Whether the output should be a class, probability, ranking, or recommendation.
- How the 200-student capacity limit affects the decision rule.
- The consequences of false positives and false negatives.
- Which student groups require separate performance analysis.
- How students should be informed about the system.
- Whether students should be able to decline, appeal, or request human review.
- How the system should be compared with voluntary requests and faculty referrals.
- What evidence would justify deployment.

A7: Identifying Possible Failures in an AI Project

Scenario: Automated Recruitment Screening

A technology company develops an AI system to rank job applicants. The project has the following characteristics:

- The objective is stated as finding the best applicants.
- Historical hiring decisions are used as ground-truth labels.
- Most previous hires came from five universities.
- Applicants without conventional employment histories are underrepresented.
- Postal code, name, university, and employment gaps are included as features.
- Resume information submitted after the interview is included in the training records.
- All applicant records from the same year are randomly divided into training and testing sets.
- The model achieves 96 percent accuracy.
- Accuracy is the only reported metric.
- No comparison is made with the existing recruiter-review process.
- The model has not been tested on applications from another country or a later hiring year.
- Recruiters receive only a ranked list and no uncertainty information.
- The top ten applicants are highlighted in green.
- Recruiters usually review only the highlighted applicants.
- Applicants cannot request an explanation or appeal.
- The model is automatically retrained every six months using the latest hiring decisions.
- No monitoring is performed for subgroup performance, drift, override rates, or feedback loops.
- No individual or committee has formal responsibility for model governance.

Task

Conduct an end-to-end failure analysis. Identify possible failures associated with:

- Problem definition.
- Target and label selection.
- Data provenance.
- Historical bias.
- Proxy variables.
- Population representativeness.
- Temporal leakage.
- Train-test splitting.
- Evaluation metrics.
- External and temporal validation.
- Calibration and uncertainty.
- Model interpretability.
- Interface design.
- Automation bias.
- Human workflow.
- Appeals and procedural fairness.
- Feedback loops.
- Selective labels.
- Retraining.
- Monitoring.
- Accountability and governance.
- Legal, ethical, and organizational constraints.

For every failure identified, explain:

- Why it is a failure
- Which stage of the AI pipeline it affects
- The harm it could produce
- How it could be detected
- How it should be prevented or mitigated

Conclude with one of the following recommendations and defend it:

- Proceed to a controlled pilot
- Redesign the project before any pilot
- Replace the machine-learning approach with a simpler process
- Cancel the project because the proposed use is not justified