Econ 202A Macroeconomics: Section 5

Kiyea Jin

November 20, 22, 2024

Section 5

Overview

1. Transition Dynamics
   - Permanent shock
2. Andreas's Repository
   - Adaptive Sparse Grid
   - Partial Equilibrium
   - General Equilibrium

Section 5-1: Transition Dynamics

Transition Dynamics

- We have solved for the long-run stationary equilibrium of the Huggett economy under fixed parameters.
- Now, consider a permanent increase in unemployment risk, represented by λ_e.
- Our goal is to analyze the transition dynamics resulting from this parameter change.

Dynamics of Wealth Distribution



Figure 1: Initial and Terminal Wealth Distribution (T=0, ∞)

Dynamics of Wealth Distribution



Figure 2: Dynamics of Wealth Distribution (T=0, 5, 10, ∞)

Time Path of Equilibrium Interest Rate

Go to Savings



Figure 3: Time Path of Equilibrium Interest Rate

System of Equations

The system to be solved is:

$$\rho V_j(a,t) = \max_c \; u(c) + \partial_a V_j(a,t)\left[z_j + r(t)a - c\right] + \lambda_j\left[V_{-j}(a,t) - V_j(a,t)\right] + \partial_t V_j(a,t) \tag{1}$$

$$c_j(a,t) = \left(u'\right)^{-1}\left(\partial_a V_j(a,t)\right) \tag{2}$$

$$s_j(a,t) = z_j + r(t)a - c_j(a,t) \tag{3}$$

System of Equations

The system to be solved is:

$$\rho V_j(a,t) = \max_c \; u(c) + \partial_a V_j(a,t)\left[z_j + r(t)a - c\right] + \lambda_j\left[V_{-j}(a,t) - V_j(a,t)\right] + \partial_t V_j(a,t) \tag{1}$$

$$c_j(a,t) = \left(u'\right)^{-1}\left(\partial_a V_j(a,t)\right) \tag{2}$$

$$s_j(a,t) = z_j + r(t)a - c_j(a,t) \tag{3}$$

$$\partial_t g_j(a,t) = -\partial_a\left[s_j(a,t)g_j(a,t)\right] - \lambda_j g_j(a,t) + \lambda_{-j} g_{-j}(a,t) \tag{4}$$

System of Equations

The system to be solved is:

$$\rho V_j(a,t) = \max_c \; u(c) + \partial_a V_j(a,t)\left[z_j + r(t)a - c\right] + \lambda_j\left[V_{-j}(a,t) - V_j(a,t)\right] + \partial_t V_j(a,t) \tag{1}$$

$$c_j(a,t) = \left(u'\right)^{-1}\left(\partial_a V_j(a,t)\right) \tag{2}$$

$$s_j(a,t) = z_j + r(t)a - c_j(a,t) \tag{3}$$

$$\partial_t g_j(a,t) = -\partial_a\left[s_j(a,t)g_j(a,t)\right] - \lambda_j g_j(a,t) + \lambda_{-j} g_{-j}(a,t) \tag{4}$$

$$0 = \frac{dS(r(t))}{dt} = \int_{\underline{a}}^{\infty} s_e(a,t) g_e(a,t)\, da + \int_{\underline{a}}^{\infty} s_u(a,t) g_u(a,t)\, da \tag{5}$$

Algorithm

1. Solve for the long-run equilibrium for both the initial and terminal states:
   — Set the initial condition $g_j^n(a, 0)$ for all iterations n as $g_j(a)$ from the initial equilibrium.
   — Set the terminal condition $V_j^n(a, T)$ for all iterations n as $V_j(a)$ from the terminal equilibrium.

2. Make an initial guess for the function $r^0(t)$. A good initial value is $r^0(t) = r_T$ for all t, based on the terminal equilibrium.

   For iterations $n = 0, 1, 2, \ldots$

3. Given $r^n(t)$, solve the HJB equation backward in time with the terminal condition $V_j^n(a, T) = V_j(a)$. This yields the time path of $V_j^n(a, t)$ and the implied saving policy function $s_j^n(a, t)$. Ensure that the transition matrix $\mathbf{P}^n$ is computed and stored for each iteration.

4. Using $s_j^n(a, t)$, solve the Kolmogorov-Forward (KF) equation forward in time with the initial condition $g_j^n(a, 0)$ to compute the time path of $g_j^n(a, t)$.

Algorithm

5. Calculate the asset supply for all t:

$$S^n(t) = \int_{\underline{a}}^{\infty} a g_e^n(a,t)\, da + \int_{\underline{a}}^{\infty} a g_u^n(a,t)\, da$$

6. Update the guess for $r(t)$ using:

$$r^{n+1}(t) = r^n(t) - \xi \frac{dS^n(t)}{dt}$$

   where $\xi > 0$ is a step size.

7. Stop the iteration when $r^{n+1}(t)$ is sufficiently close to $r^n(t)$.

(Step 3) Solving the Time-Dependent HJB Equation

Approximate the value function at I discrete points in the wealth dimension and I_t discrete points in the time dimension, and use the shorthand notation $v_{i,j}^{it} = v_j(a_i, t_{it})$ where $i = 1, \cdots, I$ and $it = 0, 1, \cdots, I_t$ with a uniform time step size $\Delta t = t(it+1) - t(it)$. The discrete approximation to the time-dependent HJB (1) is:

$$\rho V_{i,j}^{it} = U(c_{i,j}^{it+1}) + (V_{i,j}^{it})' \left[z_j + r^{it+1} a_i - c_{i,j}^{it+1} \right] + \lambda_j \left[V_{i,-j}^{it} - V_{i,j}^{it} \right] + \frac{V_{i,j}^{it+1} - V_{i,j}^{it}}{\Delta t} \tag{7}$$

with terminal condition $V_{i,j}^{I_t} = V_j(a_i)$.

(Step 3) Solving the Time-Dependent HJB Equation

Given $\mathbf{V}^{\mathbf{it+1}}$, this system can be written in matrix notation as:

$$\rho \mathbf{V}^{\mathbf{it}} = U(\mathbf{c}^{\mathbf{it+1}}) + \mathbf{P}^{\mathbf{it+1}}\mathbf{V}^{\mathbf{it}} + \frac{1}{\Delta t}(\mathbf{V}^{\mathbf{it+1}} - \mathbf{V}^{\mathbf{it}}) \tag{8}$$

where $\mathbf{P}^{\mathbf{it+1}}$ still has the interpretation of the transition matrix of the discretized stochastic process for (a_t, z_t).

(Step 3) Solving the Time-Dependent HJB Equation

Given $\mathbf{V}^{\mathbf{it+1}}$, this system can be written in matrix notation as:

$$\rho \mathbf{V}^{\mathbf{it}} = U(\mathbf{c}^{\mathbf{it+1}}) + \mathbf{P}^{\mathbf{it+1}}\mathbf{V}^{\mathbf{it}} + \frac{1}{\Delta t}(\mathbf{V}^{\mathbf{it+1}} - \mathbf{V}^{\mathbf{it}}) \tag{8}$$

where $\mathbf{P}^{\mathbf{it+1}}$ still has the interpretation of the transition matrix of the discretized stochastic process for (a_t, z_t).

Now each *it* has the interpretation of a time step instead of an iteration on the stationary value function. The reason for this similarity in the algorithm is that intuitively a stationary value function can be found by solving a time-dependent problem and going far enough back in time, i.e., as $t \to -\infty$.

(Step 3) Solving the Time-Dependent HJB Equation

Equivalently, solve the linear system:

$$\mathbf{V}^{\mathbf{it}} = \left((\rho + \frac{1}{\Delta t})\mathbf{I} - \mathbf{P}^{\mathbf{it+1}}\right)^{-1} \left[U(\mathbf{c}^{\mathbf{it+1}}) + \frac{1}{\Delta t}\mathbf{V}^{\mathbf{it+1}}\right] \tag{9}$$

(Step 4) Solving the Time-Dependent Kolmogorov Forward Equation

We approximate the density at I discrete points in the wealth dimension and I_t discrete points in the time dimension, and use the shorthand notation $g^{it}_{i,j} = g_j(a_i, t_{it})$. Given an initial condition $g^0_{i,j} = g_j(a_i)$, the Kolmogorov Forward equation (4) is then easily solved.

One here has the option of using either an explicit method:

$$\frac{\mathbf{g^{it+1}} - \mathbf{g^{it}}}{\Delta t} = (\mathbf{P^{it}})^{\mathbf{T}}\mathbf{g^{it}} \quad \Longrightarrow \quad \mathbf{g^{it+1}} = \Delta t(\mathbf{P^{it}})^{\mathbf{T}}\mathbf{g^{it}} + \mathbf{g^{it}}$$

or an implicit method:

$$\frac{\mathbf{g^{it+1}} - \mathbf{g^{it}}}{\Delta t} = (\mathbf{P^{it}})^{\mathbf{T}}\mathbf{g^{it+1}} \quad \Longrightarrow \quad \mathbf{g^{it+1}} = \left(\mathbf{I} - \Delta t(\mathbf{P^{it}})^{\mathbf{T}}\right)^{-1}\mathbf{g^{it}} \tag{10}$$

Both schemes preserve mass, but the implicit scheme is also guaranteed to preserve the positivity of g for arbitrary time steps Δt.

Section 5-2: Andreas's Repository

Andreas's Repository

- Repository link: https://github.com/schaab-lab/SparseEcon
- Explore this repository to extend the code you've written so far!
- Clone the repository and add the local path to your MATLAB code.

Adaptive Sparse Grids

- This repository provides a toolbox for solving dynamic programming problems in continuous time using **adaptive sparse grids**. The method applies to a wide range of dynamic programming applications across various fields in economics (Schaab and Zhang, 2022).
- If you're interested, read Schaab and Zhang (2022).
- More resources: `https://github.com/schaab-teaching/NumericalMethods`

Adaptive Sparse Grids

- Uniform grids:

  — Points are placed equidistantly across the domain.

  — Suffer from the "curse of dimensionality," where the number of grid points grows exponentially with added dimensions.

Adaptive Sparse Grids

- Uniform grids:

  — Points are placed equidistantly across the domain.

  — Suffer from the "curse of dimensionality," where the number of grid points grows exponentially with added dimensions.

- Adaptive sparse grids:

  — Strategically remove points that contribute minimally to function approximation.

  — Use information like residual approximation error to dynamically refine the grid based on problem-specific needs.

Adaptive Sparse Grids



Figure 4: Adaptive Sparse Grids (Schaab and Zhang, 2022)

Adaptive Sparse Grids



Figure 5: Adaptive Sparse Grids (Schaab and Zhang, 2022)

Adaptive Sparse Grids



Figure 6: Adaptive Sparse Grids (Schaab and Zhang, 2022)

Adaptive Sparse Grids



Figure 7: Adaptive Sparse Grids (Schaab and Zhang, 2022)



Figure 8: Time Path of Saving

Dynamics of Consumption



Figure 9: Time Path of Consumption

References

Schaab, A. and A. Zhang (2022). Dynamic programming in continuous time with adaptive sparse grids. *Available at SSRN 4125702*.