

PROXY CLASSES

Proxy Classes

by Prasanna Ghali

Array Definitions

2

- Array dimensions must be *constant expressions*
- Constant expression's value cannot change and must be evaluated at compile time
- What can be constant expression?
 - ▣ Literal is constant expression
 - ▣ `const` object or `constexpr` object initialized from constant expression

Array Definitions: What is Legal?

3

```
int data1[10][20]; // 2D array: 10 by 20
```

```
int const Rows{10}, Cols{20};  
int data2[Rows][Cols]; // 2D array: Rows by Cols
```

```
constexpr int CRows{10}, CCols{20};  
int data3[CRows][CCols]; // 2D array: CRows by CCols
```

```
enum class HLP1 : int { STUDENT = 10, TEST = 20 };  
int data4[STUDENT][TEST]; // 2D array: STUDENT by TEST
```

Array Definitions: What is Illegal?

4

- ❑ Corresponding constructs using variables as dimension sizes are illegal!!!

```
// error!!! array dimensions must be known at compile time  
int process_input(size_t dim1, size_t dim2) {  
    int data[dim1][dim2];  
    // other irrelevant code here ...  
}
```

```
// error!!! not even legal for heap-based allocations  
int process_input(size_t dim1, size_t dim2) {  
    int *data = new int [dim1][dim2];  
    // other irrelevant code here ...  
}
```

Implementing 2D Arrays

5

- Define class template for 2D arrays to support objects we need but are missing from language proper:

```
template <typename T>
class Array2D {
public:
    Array2D(size_t dim1, size_t dim2);
    // ...
private:
    T *ptr;
    // ...
};
```

```
// now define the arrays we want:
Array2D<int> data(10, 20); // ok
Array2D<float> *data2 =
    new Array2D<float>(10, 20); // ok


void process_input(size_t dim1, size_t dim2) {
    Array2D<int> data(dim1, dim2); // ok
    ...
}
```

Implementing 2D Arrays

6

- Need to declare subscript operator in `Array2D` to let us do this: `std::cout << data[2][3];`
- First impulse is to declare `operator[][]` functions:

```
template <typename T>
class Array2D {
public:
    // declarations that won't compile
    T& operator[][](size_t index1, size_t index2);
    T const& operator[][](size_t index1, size_t index2) const;
    ...
};
```



Won't compile because there is such a thing as `operator[]`
but no such thing as `operator[][]`

Implementing 2D Arrays

7

- We could use parentheses to index into arrays by overloading `operator()`:

```
template <typename T>
class Array2D {
public:
    // declarations that will compile
    T& operator()(size_t index1, size_t index2);
    T const& operator()(size_t index1, size_t index2) const;
    ...
};

// clients could use arrays this way:
Array2D<int> data(20, 20);
std::cout << data(2, 3);
```

Implementing 2D Arrays

8

```
// clients could use arrays this way:  
Array2D<int> data;  
std::cout << data(2, 3);
```



Drawback is that your `Array2D` doesn't look like built-in arrays any more.

In fact, above access to element at row 2 and column 3 of `data` looks like a function call!!!

Implementing 2D Arrays

9

- Thinking more deeply, we analyze why the following code works:

```
int data[10][20];  
...  
cout << data[3][4]; // ok
```

We recall `data` is not really a 2D array at all, it's a 10-element one-dimensional array!!!

So expression `data[3][4]` really means `(data[3])[4]`, i.e., fifth element of array that is fourth element of `data`

In short, value yielded by 1st application of brackets on an array `data` is another array, so 2nd application of brackets gets an element from that secondary array

Implementing 2D Arrays

10

- We should play same game in class `Array2D` by overloading `operator[]` to return object of new class `Array1D`
- Next, we overload `operator[]` again in `Array1D` to return an element in original two-dimensional array

Implementing 2D Arrays

11

```
template <typename T>
class Array2D {
public:
    class Array1D {
    public:
        T& operator[](size_t idx);
        T const& operator[](size_t idx) const;
        ...
    };

    Array1D operator[](size_t idx);
    const Array1D operator[](size_t idx) const;
    // other data members and functions ...
};
```

```
// this is now legal
Array2D<int> data(10, 20);
...
cout << data[3][5]; // ok
```

Proxy Objects and Proxy Classes

12

- Each **Array1D** object stands for a one-dimensional array that is absent from conceptual model used by clients of **Array2D**
- Objects that stand for other objects are called *proxy objects*, and classes that give rise to proxy objects are called *proxy classes*
- **Array1D** is a proxy class – its instances stand for one-dimensional arrays that, conceptually don't exist

Another Simple Solution

13

```
class Matrix {  
    float m_matrix[4][4];  
public:  
    // for statements like matrix[0][0] = 1;  
    float* operator [] (int index) {  
        return m_matrix[index];  
    }  
  
    // for statements like matrix[0][0] = otherMatrix[0][0];  
    float const* operator [] (int index) const {  
        return m_matrix[index];  
    }  
};
```