Same States, Different Choices: Human Decisions Improve Same-Goal Maze Transfer and Shape Forgetting and Vision–Language–Action Geometry Supplementary material

Muhammad Y. Hakami
engmuhammadhakami@gmail.com

Project page (agents running in the browser, code, checkpoints, records): muhammadhakami.github.io/human_rat_choices

1. Reviewer questions and where they are answered

1. **Only frozen, same-goal transfer? (Chairs, FtUu, 6g1M, GQMP)** Main claim scoped to frozen agents and the familiar goal; registered moved-goal test (3 goals per fresh room). Main: Table 1, story figure c, Sec. 3.2.
2. **Goal memorisation? (GQMP)** Old-goal visits with moved goals; showcase row d. Main: diagnostics c.
3. **Does the prior help when learning continues? (FtUu, 6g1M)** Moved-goal learning, 30 seeds, PPO and local rules. Main: Sec. 3.3, learning figure.
4. **Specific to PPO? (UYhB)** Same priors with local three-factor rules (TD-readout, TD-DFA, Error-Diffusion routing) and searched configurations. Main: Sec. 3.3.
5. **What map does the pose filter use? (FtUu)** Open-arena template atlas; no wall map, goal or pose. Main: Sec. 2.
6. **Belief accuracy in generated rooms? (FtUu)** Main: diagnostics d.
7. **Does dimming break the filter? (FtUu)** Yes; top-1 falls to about 45%; augmented camera-only agents recover. Main: Sec. 3.1, diagnostics d.
8. **Is the rat null caused by unpredictable labels? (FtUu)** Rat choices are learnable but carry about half the predictable information of human choices. Main: diagnostics e.
9. **Sampled or greedy evaluation? (FtUu)** Sampled, as registered; greedy proven to trap a deterministic memoryless system (Sec. 19.1). Main: Sec. 2.
10. **Loop rates; is the gain only less looping? (FtUu)** Reported per arm; most of the gain goes with fewer loops, the humans' own habit of not going back. Main: story a–b, Sec. 3.2.
11. **Why does pixel noise help every arm? (FtUu)** It breaks loops. Main: Sec. 3.2.
12. **Simple teachers recover part of the gap? (FtUu)** Human choices beat shortest-path, entropy-matched and goal-bias teachers. Main: controls figure.
13. **Rat versus human agents directly? (UYhB)** Human − rat 13.7 pp; one third coverage, two thirds choices (identity checked in Lean). Main: Sec. 3.1, Table 1.
14. **Arbitrary comparisons and Holm families? (UYhB)** One table of all main contrasts with CIs; Holm only within registered families. Main: Table 1.
15. **The take-home message? (UYhB)** Cleaner data loses to human choices; agents inherit how humans move. Main: story figure, discussion.
16. **Cortex results out of nowhere? (UYhB, GQMP)** Now a question inside the story (Sec. 3.4); full study in Sec. 2.
17. **Cortex study confounded by input resolution? (GQMP)** Yes, the mouse model sees higher-resolution frames than the pixel policy; the study is reported as a sensitivity test only, with a random-core control at the same resolution (Sec. 2).
18. **E3 prior contrasts confounded with GPU model? (GQMP)** Prior contrasts in E3 are not interpreted; the method contrast was repaired with 840 fits crossing both GPU models, and the effect holds on each (6.2 and 6.3/30).
19. **Weak absolute performance, small policy? (GQMP)** Limitations; animal reference kept.
20. **Equivalence margin equals the effect? (GQMP)** Equivalence language removed; CIs reported.
21. **p-values and seeds? (GQMP)** CIs; seeds are training variability, not biological replication.
22. **Post-hoc follow-ups, verifiable registration? (GQMP)** Each follow-up marked; protocols, amendments and deviations are hash-bound in the released audit folders.




Figure 1. **E1: source-layout adaptation (30 paired seeds). a** Successes out of 60 per seed with online PPO updates; lines pair rat real with rat legal-uniform; numbers count seeds ≥40/60. **b** Paired differences, 95% CIs; band = registered $\pm 10/60$ equivalence margin (16.7 percentage points).

23. **Observation aliasing, joint-training reference? (6g1M)** Quantified and run: in 15% of cells the two goals' shortest paths share no move, yet the same goal-blind agents trained on both goals at once keep far more of the old goal; forgetting is sequential interference (Sec. 20).
24. **Unequal text and image information in the alignment study? (6g1M, GQMP)** Replaced by a matched-content study in which image, text and action describe the same moment, with five policy seeds (Sec. 22).
25. **Thin visual content for the venue? (GQMP)** Showcase of first-person views and beliefs, occupancy maps, real-demonstrator story figure.
26. **Dense writing, mixed units? (GQMP, UYhB)** Main text halved; percentage points throughout.
27. **Title? (Chairs)** Retitled to the supported claim.
28. **Side studies? (Chairs)** Moved to Sec. 2.
29. **Do caption words leak the action? (author check on 6g1M's question)** No: worded without any action name, the text still predicts the action equally well. Sec. 22.
30. **Is local learning real, or just more experience? (UYhB; author check)** Shuffled-reward control removes it. Sec. 21.
31. **Spiking efficiency beyond a fixed time budget? (author, Q27)** Accumulate-to-bound decisions: human choices decide sooner with fewer operations. Sec. 21.
32. **Do local, biologically plausible rules avoid forgetting? (UYhB; author follow-up)** Not by locality alone; context gating, consolidation with old replay and a brain-constrained circuit do, each with a measured cost; with awake replay the circuit learns the new goal $+12.4$ pp better than PPO at equal retention and, gated, keeps $+13.3$ pp more of the old goal (Sec. 23).
33. **Why reduce 9,941 predicted neurons to 144 PCs? (UYhB)** To match the 144 pixel inputs, so that only the content changes. The predicted responses are low-dimensional: z-scored, 26 PCs hold 99% of the variance and 144 hold 99.99%. Repeated on all 9,941 units, every Rosetta geometry comparison gives the same CKA (Sec. 24).

2. Studies moved from the main paper

At the Program Chairs' request, the camera-ready main paper focuses on state-matched transfer. The following studies from the reviewed version are reproduced here unchanged in substance; units are those of the reviewed version (successes out of 30 or 60 per seed; one success out of 30 is 3.33 percentage points).

2.1. E1 per-seed results

2.2. E3: sequential learning and replay

Protocol. Copies of the source checkpoint learn room A's goal (65,536 interactions), then room B's goal in the paired room (65,536 more), with PPO or replay; frozen probes follow each phase. E3 has a development pair (30 seeds) and seven




Figure 2. **E3: sequential learning in visible rooms.** Agents learn room A's goal (65,536 interactions), then room B's goal in the paired room (65,536 more), with no task signal; frozen probes, 30 trials each. Grey: PPO; green: PPO with a 620-transition policy/value replay buffer. Bars are seed means, dots are seeds. **a–c** development pair, 30 seeds (both methods of each seed on the same GPU model); **d–f** seven withheld pairs, 15 seeds, each value averaged over pairs and both GPU models (crossed follow-up).

withheld pairs (15 seeds). Pairs were reserved before the development outcome; the crossed GPU repair was registered after the original follow-up outcome. Rooms are visible and no task ID is supplied. Forgetting is $F_s = S_{s,A}^{\text{after A}} - S_{s,A}^{\text{after B}}$, interpreted together with acquisition of B.

Replay control. A 620-entry reservoir stores experienced observations and their pre-update policy/value predictions $(o, \tilde{\pi}, \tilde{v})$ [13, 23]. After each PPO rollout update, one separate optimizer step on up to 128 stored entries minimises

$$\mathcal{L}_{\text{replay}} = \mathbb{E}_{\mathcal{B}}\left[D_{\text{KL}}(\tilde{\pi} \| \pi_\theta(\cdot \mid o)) + \tfrac{1}{4}(V_\theta(o) - \tilde{v})^2\right]. \tag{1}$$

New rollout entries enter the reservoir afterwards; it samples experience across A and B without a boundary signal. This is a replay baseline, not a new memory rule, and incurs extra storage and optimizer steps.

E3: forgetting is catastrophic without replay; replay reduces it under every tested prior (Fig. 2). On the development pair (30 seeds), both methods learn A and B, but PPO retains only 1.7–3.8/30 successes on A after learning B; replay retains 14.9–20.9. Replay reduces forgetting by $11.9/30$ ($[9.8, 14.1]$), within every prior (Holm $p \leq .00012$). These method contrasts are hardware-matched. Prior-versus-cold and rat real-versus-legal contrasts are confounded with GPU model and are not interpreted. After B, PPO paths in A concentrate on B's goal location; replay paths return to A's goal (supplement). This is descriptive evidence of interference, not an identified internal mechanism.

Withheld room pairs. Seven pairs were reserved before the development outcome. The original follow-up confounded method and GPU model; a repair registered after seeing that result added 840 complementary fits, crossing all methods, priors, pairs and seeds with both GPU models. With pairs and hardware averaged within 15 seeds, PPO retains 5.6–6.1/30 and replay 12.2–14.4. Replay reduces forgetting by $6.2/30$ ($[5.1, 7.4]$, $p = 2 \times 10^{-8}$), within every prior and on both GPUs (6.2 and 6.3), about half the development effect. The method×hardware interaction lies within ± 10 percentage points (TOST $p = .0002$). Prior-versus-scratch differences in A acquisition, and human-versus-rat differences in forgetting, lie within that same margin; smaller effects remain compatible. The supplement gives secondary contrasts and execution history.

Learning curves (registered, 10 seeds). A further hardware-matched sequential study finds no resolved new-goal learning-curve advantage: human versus legal $+14$ points ($[-6, 35]$), versus scratch -16 ($[-34, 3]$; Holm $p = .17$ for both). The acquisition gate passes (25.5–29.7/30 on the new goal), and replay again retains more of the first goal ($+14.9/30$, $[10.3, 19.5]$). Curves and protocol are supplementary.




Figure 3. **Changing the visual representation** (10 paired seeds, 16 exposed rooms). Dots: seeds; blue: means and unadjusted 95% CIs. Registered exact tests use Holm correction over the three perceptions. The mouse model uses predicted responses. *Randomized core retains a trained readout, perspective and modulation.

Task-addressed protection (exploratory). On one development pair, Nevo-CRL-inspired PPO masking [12] retains 22–30/30 first-goal successes while acquiring B at 18–30/30; task-ID PPO retains 0–6/30 (three seeds). Task-routed recurrent-residual agents also retain A while acquiring B (3/3 seeds; supplement). Both pilots use backpropagation and provided task IDs; neither is a native reproduction or local-learning result.

2.3. Predicted cortical responses as visual input

Predicted cortical responses. We also refit the camera-only experiment using a frozen model of mouse visual cortex [33], or a randomized core retaining the trained readout, perspective and modulation. The model predicts responses of 9,941 neurons to the agent's own reconstructed frame; these are not recordings during navigation. PCA to 144 features uses source layouts 0–5 only. All three perceptions meet the source competence rule (10 new paired seeds). In the 16 exposed rooms, human choices exceed legal labels by 11.5 points with pixels, 3.7 with predicted responses, and 0.7 with the randomized core; none resolves under the registered Holm correction ($p = .135, .508, .775$; Fig. 3). These estimates do not establish differences in prior benefit across perceptions. The mouse model also sees higher-resolution frames than the pixel policy; this sensitivity test establishes neither neural superiority nor transfer from measured neural activity.

2.4. Representation alignment (Rosetta)

Exploratory representation study. Do transferable decisions also admit a common geometric readout? Following Schnaus et al. [26], we apply their released Wasserstein–Procrustes aligner, without modifying its equations, to frozen visual features, policy states and four-move plans. We extract 5,674 windows from the recorded paths; fitting uses three disjoint 192-window source sets (96 per species), separated by trial and camera frame, with 16 separate paired anchors for calibration. Evaluation uses 481 windows from source layouts 6–7 (189 rat, 292 human; three rats, six humans). These layouts were already exposed in earlier project evaluations: this is an exploratory follow-up. Plans are 16-dimensional concatenated one-hot actions, not an action foundation model; text is a generated description of the same plan. Visual encoders include pixels, DINOv2 [19], predicted mouse responses and the random core; language encoders are MiniLM [34] and MPNet [29]. Policy states are action-trained, not unimodal action pretraining.

Geometry and calibration. We measure source-centred, row-normalised unbiased linear CKA between representations




Figure 4. **Shared geometry, calibrated readout and acting.** **A** Unbiased linear CKA (scale 0–1) on 292 human and 189 rat windows; every shown pair exceeds its 100-shuffle range. Init.: untrained policy. **B** Generated plan text mapped to actions: human (blue), rat (red); 16 anchors calibrate this constructed correspondence. **C** Plan maps versus each policy's own greedy head in 16 exposed rooms; uniform succeeds at 13.3%. Zero-pair means/ranges require five complete alignment seeds; 16-anchor and paired-only fits use the first seed. *Text describes the plan. ‡Predicted mouse responses and partly trained random core. †Source continuations after a backprop warm start, with Adam; no local-memory claim. One policy seed; full controls and provenance in the supplement.

on the same evaluation windows, separately by recorded species; 100 row shuffles give descriptive references, not tests over independent animals. DINOv2–MPNet, DINOv2–action and MPNet–action CKAs are .20/.20/.68 on human windows and .08/.11/.67 on rat windows, all above their shuffle ranges. All 132 pairs exceed these descriptive ranges, including untrained controls: similarity does not establish learned convergence or cortex-specific structure (Fig. 4). With 16 anchors, generated-text-to-plan alignment reaches 88.4% balanced first-action agreement on rat windows and 89.9% on human windows; MPNet gives 83.7% and 93.9%. This is calibrated correspondence for constructed commands, not independently acquired language grounding. Without anchors, all 14 complete five-seed primary group means trail action persistence (.388 rat, .409 human). Image–history and text–history combinations do not consistently improve on matched history-only references.

Closing the action loop. Alignment uses five fixed algorithm seeds, 0 or 16 pairs, and a paired-only Procrustes reference; incomplete groups have no mean. At each agent-generated view, we retrieve from all 256 plans and execute the first action, splitting probability uniformly over tied top plans before replanning. In the same 16 exposed rooms, the human-trained policy's greedy head succeeds on 40.2% of trials; its unpaired action/text readouts average 0.08%/8.38%, and the 16-anchor readouts reach 15.8%/15.2%. Some calibrated maps improve over matched untrained maps, but all 68 evaluated trained-policy maps remain below their own greedy heads. This acting comparison uses one policy-training seed and one evaluation seed; alignment seeds measure optimizer variability. Shared structure, calibrated readout and useful navigation are distinct tests. These results do not establish universal cross-species representations or a limitation of the original common-content image–text setting.

3. Figures moved from the main paper for space




Figure 5. **From recorded paths to acting agents.** Recorded cell-to-cell moves supply labels; views and pose beliefs are reconstructed causally from the path prefix (never from the label being predicted). Control arms keep the same observations and replace the labels. All arms then receive the same 524,288 reinforcement-learning interactions.





Figure 6. **Where frozen agents go** in one fresh room (chosen before viewing; 30 seeds × 30 trials per arm). Shade: visits per trial (log); grey: walls; squares: starts; star: goal; circle: familiar goal. Titles: success.

4. Provenance and independent audits

Each study records a protocol before its own outcomes; post-result follow-ups state which earlier outcomes were known. Audits used a separate agent with its own scripts, sharing registered helpers, except for the author audits identified in Table 1. Checks cover records, checkpoint/data bindings, physical paths and statistics; specified first-seed checks re-execute physics, rendering, the pose filter and frozen-policy probabilities from logged actions. This is computational verification within the study, not external experimental replication.

Numerical tolerances. Re-executed frozen-policy probabilities match within 10^{-5}. Behaviour-cloning re-runs across processes on the same GPU model differ only by floating-point noise (parameters $\leq 3 \times 10^{-5}$, action probabilities $\leq 5 \times 10^{-6}$, argmax agreement 100% on all 18,000 source views); within one process they are identical.

5. Agent architecture and learning rules



Learning (base network: 20.7k parameters): imitation of rat / human / legal labels (BC) → PPO 524,288 frames;
continual (E3): PPO or PPO + replay (620 entries). §Camera-only and mouse-model arms zero the 102 pose inputs.
†Local rate updates: exploratory Rosetta source-continuation control only, after a backprop warm start (Adam); no brain, spiking or memory benefit claimed.

Figure 7. **Base architecture.** The 20.7k-parameter policy receives a pooled camera or frozen visual-model features, public feedback and a visually derived pose belief. Camera-only and mouse-model conditions zero the 102 belief-derived inputs. ‡Mouse features are model predictions, not recordings. The actor and critic are trained with PPO; E3 adds the stated replay control. Exploratory local-rate Rosetta continuations start after backpropagation training and use Adam; they do not demonstrate spiking or memory protection. The larger-network capacity follow-up uses a separate 256×256 backbone.

6. Descriptive E1 occupancy

Human choices increase agents' occupancy correlation with the human reference relative to legal actions at the same states ($+.063$ r, 95% bootstrap CI $[.026, .098]$), whereas rat choices do not resolve an increase in correlation with the rat reference ($+.004$, $[-.029, .038]$). These spatial correlations do not identify an internal mechanism.

7. Predicted mouse cortical responses as visual inputs

This follow-up was registered after the behavioural E2 results and before any of its 90 fits. It uses the released mouse visual-cortex predictor [33] with the scan 8–5 readout (9,941 units). Responses are predictions on the agent's reconstructed views, not neural recordings acquired during navigation. Each 36×64 luminance frame is gamma encoded ($1/2.2$), upsampled fourfold by nearest neighbour, and presented as a separate clip of ten grey frames followed by fifteen repetitions of the current view. We average the last ten predicted responses. This assumes a monitor geometry and uses repeated static views, rather than a measured animal visual stream; the encoder is not presented with future actions or views. The random-core control retains the trained readout, perspective and modulation, so it is partly pretrained. Pixels use the original 9×16 pooled camera, whereas both model conditions use the full 36×64 frame; visual information and pretraining are not matched.

study	registration	checked independently	first-seed re-execution
E1 transfer (30 seeds)	before outcome	all selection episodes replayed	all E1 selection episodes
E2 zero-shot rooms (30 seeds)	before outcome	aggregates and statistics of all 2,880 probes	96 probes
E3 continual, development pair	before outcome	all bindings and statistics	first-seed runs of every cohort
E3 crossed withheld-pair follow-up	pairs before; GPU repair after original outcome	all crossed bindings and statistics	first-seed runs of all four cohorts
E2 expert/surrogate follow-up	after main E2 result	120 source budgets, 1,920 probe aggregates, statistics	64 probes
GPU counterbalance	after main E2 result	90 source budgets, 1,440 probe aggregates, statistics	48 probes
Entropy-matched expert	after main E2 result	60 calibrated checkpoints, 960 probe aggregates, statistics	32 probes
Grouped-individual refits	after main E2 result	120 source fits, 1,920 probe aggregates, statistics	192 probes
Input ablation	after main E2 result	90 source fits, 13,500 source and 1,440 target probes, statistics	144 masked-policy probes
All-optimal expert	after main E2 result	10 teacher fits, 10 calibrations, 320 probes, statistics	32 probes
Fresh-room confirmation	before geometry and outcome	geometry, 3,680 probes, statistics	176 room blocks
Perturbed and denser rooms	before any fresh outcome	dense geometry, 7,200 probes, statistics	240 blocks
Mechanism (label interventions)	post-result follow-up on fresh rooms	8 label sets, 80 source fits, 1,280 probes, statistics	128 blocks
Dose response	before fits and outcome	80 source fits, 1,280 probes, statistics	128 blocks; first-seed BC re-run
Appearance and capacity	before rooms and outcome	30 wide source fits, 9,120 probes, statistics	432 blocks with own view changes
Brightness augmentation	after the dimming outcome, before any fit	all 120 fits and 5,760 probes, statistics (study authors)	6 first-seed refits (bit-exact), 288 blocks (exact)
Learning curves and retention	before any fit	all 60 fits: training observations, rewards, paths, checkpoints, probes; statistics and gate	first-unit frozen action probes
Rosetta alignment/acting	before each fit/probe; pairwise after acting	all 176 completed fit metrics; all 132 pairwise CKAs and 13,200 shuffles	75,840 acting episodes, all available map parities
Mouse-model inputs	before any fit	all 90 fits, 13,500 source trials, 1,440 room blocks; checkpoints, paths and statistics	2 trials for every arm/input at seed 1300 (9 exact GPU replays)
Task-addressed protection pilot	corrected code bound after invalid development outcomes	all six source/checkpoint bindings, native protection masks, microstep logs	all 540 frozen episodes, explicit CPU forward replay
FF + recurrent residual	after failed acquisition; before new fits	all six cases, initial weights, protection and recurrent updates	all 540 frozen episodes, explicit matrix replay

Table 1. **Study provenance.** "After main E2 result" denotes exposed-room follow-ups. Dose and brightness studies used separate author-written pre-probe audits; the independent auditor later checked the complete dose cohort, reproducing its analysis to 3×10^{-16}. The first wide-network probe launch stopped at checkpoint loading, before outcomes, because the shared builder fixed the width; a separate launcher set the registered width and the unchanged probe code ran.




Figure 8. **E1 paths (descriptive).** Seed-mean occupancy correlation with recorded rats and humans on layouts 6–7; 95% bootstrap intervals over 30 training seeds.

PCA is fitted on 4,616 unique frames from source layouts 0–5 only. The 144 components are scaled by source standard deviations and clipped to $[-1, 1]$ after division by three. Layouts 6–7 and the 16 exposed rooms are transformed without fitting. A policy-input hook replaces only the 144 camera channels for imitation, PPO and frozen evaluation; public feedback is retained and the 102 belief-derived channels remain zero. Exact pooled-frame keys identify the same full frames in the fixed benchmark. Precomputed features preserve the frozen encoding function; no inference latency, energy, spiking or deployability claim is made.

The three label arms (human choices, legal labels at the same human states, and no imitation) are refitted for all three inputs at ten new paired seeds (1300–1309), with the original imitation and 524,288-interaction PPO budgets. All inputs pass the source rule: at least 75/150 successes in at least eight seeds for each arm. The 16 previously exposed E2 rooms supply 30 frozen trials per room and seed, so this is a sensitivity study, not fresh confirmation. The registered primary contrast is human minus legal, with an exact two-sided sign-flip test and Holm correction over three inputs; unadjusted t-intervals are descriptive. None resolves (Table 2). Differences in significance do not establish an interaction between input and prior. The independent audit checks all 90 source checkpoints and 43,200 target episodes and exactly replays two trials in each of the nine arm/input cells at seed 1300 on its original GPU. Earlier audit-code assumptions about inference counters, source-record fields and CPU versus GPU roundoff were corrected with previous code/logs preserved; no scientific fit or outcome was changed.

input	human	legal	scratch	human − legal, points [95% CI]	Holm p
Pixels	15.66	12.22	11.24	$+11.46$ $[0.53, 22.39]$	.135
Mouse model	13.41	12.29	12.13	$+3.73$ $[-3.10, 10.56]$	.508
Random core	14.18	13.97	12.34	$+0.69$ $[-4.60, 5.97]$	.775

Table 2. **Changing the visual encoding.** Mean successes out of 30, averaged over 16 rooms and ten paired training seeds; paired differences in percentage points. CIs are unadjusted. Holm corrects the three registered exact tests. All three inputs pass source competence; the effect of the human prior remains unresolved here.

8. Fresh-room gains: seed and room uncertainty (post hoc)

The registered fresh-room tests treat the 30 (or 10) training seeds as the unit and average each seed over the same 16 rooms. To check that the gains are not driven by a few rooms, a post-hoc sensitivity analysis (not a new primary test; registered tests unchanged) resamples seeds, rooms, or both together, with replacement and keeping each human/control pair intact (10,000 resamples; percentile intervals, approximate). Table 3 gives successes out of 30 per room. Rooms come from one constrained generator and the same source-trained policies, so this addresses room-to-room variation within that generator, not animals, species populations or real-world tasks. The study's authors recomputed every mean and count from the audited probe records and reproduced the intervals with an independent resampler (differences ≤ 0.1 success).

contrast	seeds	mean	seeds only	rooms only	crossed	crossed, Bonf. 4	rooms > 0
Full input: human − legal	30	+2.97	[2.1, 3.8]	[2.0, 3.9]	[1.6, 4.4]	[1.2, 4.8]	16/16
Full input: human − scratch	30	+3.66	[2.7, 4.6]	[1.7, 5.5]	[1.4, 5.8]	[0.7, 6.4]	13/16
Camera only: human − legal	10	+4.55	[2.2, 6.8]	[3.0, 6.1]	[1.6, 7.4]	[0.8, 8.2]	15/16
Camera only: human − scratch	10	+6.68	[5.2, 8.3]	[5.0, 8.5]	[4.2, 9.1]	[3.5, 9.8]	16/16

Table 3. **Fresh-room gains under seed, room and crossed resampling** (post hoc). Intervals are 95% percentile bootstrap intervals; "Bonf. 4" is a nominal 98.75% interval for the four contrasts. Rooms > 0: rooms whose seed-averaged gain is positive.

9. Dose and brightness curves




Figure 9. **Dose and brightness sensitivity.** Descriptive means from the audited records. Left: 10 paired seeds, 16 new rooms; only the full-dose human–legal contrast is resolved after Holm correction, and the registered log-dose trend is unresolved ($p = .09$). Right: camera-only agents, 20 paired seeds, 16 rooms. Solid: training gains uniform in $[0.5, 1]$ per episode; dashed: no brightness augmentation. Both dimmed tests lie within the augmentation range. These panels add no experiment or inferential test.

10. Decision-feature interventions

11. Detailed E2 follow-ups

These details retain the full contrasts behind the compressed main-paper results. The order below follows the original study sequence; fresh-room confirmation reuses policies, not outcomes or fitted parameters.

Feature teachers. For recorded state x and candidate action a, the three binary features $f(x, a)$ indicate repeating the previous move, reducing shortest-path goal distance and entering a cell not yet visited in the recorded trial. Source-only conditional-logit fitting uses

$$q_\beta(a \mid x) = \frac{\mathbf{1}[a \in \mathcal{A}_{\text{legal}}(x)] \exp(\beta^\top f(x, a))}{\sum_{a' \in \mathcal{A}_{\text{legal}}(x)} \exp(\beta^\top f(x, a'))}. \tag{2}$$

The fitted teacher samples replacement labels; it is not available to the agent at inference. Geometry and goal distance are privileged offline supervision for these controls. No target-room actions are used for fitting.

E2: human choices generalise to unseen rooms (main-paper E2 figures). Mean zero-shot successes out of 30 are 9.7 (cold), 9.1–9.9 (rat sham/legal/real), 10.3 (human legal) and 13.3 (human real). Only human real beats cold (+3.6, Holm




Figure 10. **Decision-feature interventions** (post-result follow-up on the fresh rooms; 10 seeds, all trained in one code path on one GPU model). Bars: seed means; dots: seeds; dotted lines: human and legal labels. Removals replace, where a matched alternative exists, human moves that have the feature by otherwise matched moves that lack it; teachers sample labels from conditional-logit models fitted to the human source moves.

$p = 9\times10^{-7}$) and legal moves at the same human states ($+3.0$, $p = 8\times10^{-8}$), so visited states alone do not explain the gain. Rat real is equivalent to rat legal (TOST $\pm3/30$, $p = 2\times10^{-7}$); an exploratory dataset (species/apparatus)×choice interaction is $+2.8$ ($[1.5, 4.2]$, $p = 1.2\times10^{-4}$). **Relabelled states.** A follow-up registered after this result relabels the same human states. Run on both GPU models (no label×hardware interaction beyond ±10 points, TOST $p \le .001$), human choices beat a shortest-path expert by $+4.4$ and a fitted persistence-plus-goal model by $+2.2$ (Holm $p = 1\times10^{-13}$, 3×10^{-7}). The expert scores 9.0/30 (scratch 9.7; not tested). Matching its mean source entropy to the human agent's with a global temperature leaves it 4.6 below ($p = 3\times10^{-15}$). It breaks ties by a fixed direction order (44% of sampled decision points have several optimal moves), so a further follow-up (input-study seeds) trains on soft targets spread equally over *all* optimal moves: after the same temperature matching, human choices still beat it by $+3.2$ ($[1.8, 4.5]$, $p = 5\times10^{-4}$, unadjusted as registered; raw teacher $+2.5$, descriptive; full input, previously exposed rooms). This addresses the tie-break concern without exhausting all expert policies; soft labels carry more information per row, only mean source entropy is matched, and state-wise and out-of-distribution confidence are untested. **Grouped-individual refits.** Refits on three folds that each withhold a third of the individuals (half the dose, 10 new seeds) keep human real above legal ($+2.8$, Holm $p = 1\times10^{-4}$, positive in 10/10 seeds and 3/3 folds); rat is unresolved ($+0.6$). Withheld individuals are absent from prior training, but tests are in the same exposed digital rooms, not on new individuals. **Inputs.** Retraining all arms with channels zeroed (10 new seeds) shows that the advantage does not need the calibrated place belief. With pixels and feedback alone, human choices beat legal by $+4.3$ and scratch by $+7.3$ (Holm $p = .03$, 5×10^{-5} over 8 contrasts), as with full input ($+4.2$, $p = .004$). Without direct pixels (the place belief is still visually derived) the gain is unresolved ($+2.4$, Holm $p = .08$). Neither interaction is resolved or equivalent, so we claim neither that pixels are required nor that benefits are identical. Training and the matched probes still run the place observer, but a frozen re-execution of all camera-only arms (seed 1200, 16 rooms, 1,440 episodes) with the observer disabled reproduces every action and path exactly, so it is not needed at inference (no runtime or energy claim).

Fresh-room confirmation. All analyses above reuse the same 16 rooms. Registered before any outcome, the same frozen policies were therefore probed in 16 newly generated rooms that no experiment, analysis or design choice had touched (same generator rules, new seed; 3,680 probes). Everything replicated (the main-paper control figure, open markers): human choices beat legal moves by $+3.0$ ($[2.1, 3.9]$) and scratch by $+3.7$ ($[2.6, 4.7]$; Holm $p \leq 3 \times 10^{-7}$); rat choices stayed equivalent to legal moves ($+0.3$, TOST $p = 7 \times 10^{-6}$); the dataset×choice interaction, exploratory above, was confirmed ($+2.7$, $[1.4, 4.1]$, $p = 3 \times 10^{-4}$); camera-only human choices beat legal moves by $+4.6$ and scratch by $+6.7$ (Holm $p = .005$, 4×10^{-5}); and full-input human choices beat the calibrated all-optimal expert by $+3.1$ ($p = .007$). A post-hoc bootstrap that resamples seeds and rooms together keeps all four human gains above zero (e.g. $[1.6, 4.4]$ over legal moves), and the full-input gain over legal moves is positive in all 16 rooms (Table 3). **Perturbed and denser rooms.** Also registered before any fresh outcome, the same policies faced pixel noise (which also enters the visual place belief), denser rooms (26 instead of 18 walls; detours three times longer) and both (the main-paper robustness figure). Density lowered every arm's success; noise, unexpectedly, raised it for every arm, so it is a sensory perturbation rather than added difficulty. Under all three conditions human choices beat legal moves and scratch (Holm $p \leq 2 \times 10^{-5}$ over 6 contrasts), and rat choices stay equivalent to legal moves (TOST $p \leq 10^{-4}$). These are variants of the same grid task, not a richer or real-world benchmark. **What in human choices transfers?** A post-result, source-only follow-up on the fresh rooms (10 seeds, one training code path; Fig. 10) edits the human labels, or replaces them with teachers built from three decision features computed from the recorded paths: repeating the previous move, moving closer to the goal and entering an unvisited cell (humans .49, .77 and .92 of moves; legal-move chance .25, .45 and .65). Human labels beat legal moves by $+4.3$ ($p = 4 \times 10^{-4}$). Replacing goal-progress moves with otherwise matched non-progress moves (25% of labels) cut success by 7.1 (Holm $p = 3 \times 10^{-5}$), below legal labels, whereas matched removal of repetition ($+0.2$) or novelty ($+1.0$) was unresolved. A teacher sampling from all three features recovered only part of the advantage: human labels still beat it by 2.4 ($p = .008$), leaving 57% ($[32, 87]$) of the human–legal gap unexplained, although adding novelty to repetition and progress helped ($+1.7$, Holm $p = 1 \times 10^{-4}$). These are matched label interventions within this pipeline, not evidence about human cognition or a unique cause: goal-directed content contributes materially, and human choices carry further transferable structure that these limited feature teachers do not capture. **Dose.** Pretraining on nested subsets of 750, 1,500, 3,000 or 6,000 human moves with equal training (10 new seeds, 16 further new rooms; registered) gave human–legal advantages of $+1.3$, $+1.7$, $+1.9$ and $+4.2$. Only the full dose was resolved (Holm $p = .007$), replicating the main result once more; the registered log-dose trend ($+0.9$ per doubling, $[-0.2, 2.0]$, $p = .09$) was unresolved, and part of the widening gap reflects legal-label agents declining at the largest dose (descriptive). **Appearance and capacity.** Registered before any outcome, the frozen policies were probed in 16 further new rooms with altered wall and floor texture, or with all rendered luminance scaled by 0.75; separately, the human, legal and scratch arms were retrained with a 6.4× larger network (256×256 hidden units; 10 new seeds; 9,120 probes, independently audited; the main-paper robustness figure, right). With new textures human choices still beat legal moves and scratch ($+3.1$, $+3.8$; camera-only $+4.4$, $+6.9$; Holm $p \leq .009$ over 10 contrasts), and so did the larger network ($+4.5$, $+4.0$; Holm $p = .019$), a capacity replication in the same pipeline rather than a new architecture. Dimming, however, lowered every arm (human choices 12.4 to 4.8/30; camera-only 15.1 to 2.1) and the human advantage was not detected (full input $+0.3$, -1.4; camera-only -3.2, -2.4; Holm $p \geq .21$, unresolved, not equivalence). No agent had been trained with photometric augmentation. A follow-up registered after this outcome but before any fit (camera-only, 20 new seeds, 120 fits, 5,760 probes) retrained all three arms with and without a random brightness gain per episode (×0.5–1, training only). Without it, dimming again collapsed every arm (human choices 14.8 to 2.4/30); with it, success held (14.7/30 at ×0.75) and human choices beat legal moves and scratch by $+4.9$ and $+5.9$ at ×0.75 (Holm $p \leq 2 \times 10^{-5}$) and by $+5.0$ and $+6.1$ at ×0.5; augmentation widened the human–legal gap under dimming by $+6.9$ ($[4.8, 8.9]$, Holm $p = 2 \times 10^{-6}$). Both levels lie within the training range, so this shows robustness under standard augmentation, not extrapolation. Rat choices stayed equivalent to legal moves under all three views (TOST $p \leq .002$).

12. Sequential-learning controls

On the development pair, PPO learns room A (23.7–26.7/30) and room B (≥27/30) but then succeeds on only 1.7–3.8/30 room-A trials, although the rooms are visually distinguishable from the first view in most starts. Replay keeps 14.9–20.9/30 while learning B (≥29.6/30). With seeds as units (arms averaged within seed), replay reduces forgetting by 11.9/30 ($[9.8, 14.1]$, $n = 30$, $p = 3.5 \times 10^{-12}$), and by 10.0–14.3 within every prior (Holm $p \leq 1.2 \times 10^{-4}$). Each prior's two methods ran on the same GPU model, so these within-prior contrasts are hardware-matched; comparisons between priors are not, except human versus rat (same GPU), which show no resolved difference in acquisition or forgetting (not tested for equivalence here). Prior-versus-cold and rat real-versus-legal contrasts in E3 are confounded with GPU model and not interpreted. The paths show what is lost (Fig. 12): after learning B, PPO agents placed in room A converge on the cell where room B's goal lies, consistent with interference from the newer goal rather than undirected search; occupancy alone does




Figure 11. **Learning curves and retention** (registered; 10 seeds). **a** Mean frozen-probe success on the new goal during learning; primary tests compare priors within PPO (dashed). **b** Human-prior agents' first-goal success before and after learning the new goal; dots are seeds.

not show which internal representation changed. Replay agents return to room A's goal. **Crossed withheld-pair follow-up** (seven pairs, 15 seeds, the main-paper sequential-learning figure, panels d–f). The original run confounded method with GPU model (every PPO fit on one model, every replay fit on the other); we therefore ran the complementary 840 fits so that every method, prior, pair and seed exists on both models, and average per seed. This crossed design was registered after the confounded outcome had been seen. PPO keeps 5.6–6.1/30 of room A after learning B; replay keeps 12.2–14.4. Replay reduces forgetting by 6.2/30 ($[5.1, 7.4]$, $n = 15$, $p = 2 \times 10^{-8}$), on each GPU model (6.2 and 6.3), within every prior (5.1–7.3, Holm $p \leq 2 \times 10^{-5}$) and on all seven pairs (sign test $p = .016$; small on two), with no method×hardware interaction beyond ± 10 percentage points (TOST $p = .0002$). The effect is about half that on the development pair. With hardware balanced, prior-versus-scratch differences in room-A success at the end of A learning lie within the registered ± 10-percentage-point margin (TOST $p \leq .004$); smaller effects remain compatible. Rat real exceeds rat legal by $+0.9/30$ ($[0.2, 1.6]$, unadjusted $p = .02$, a registered secondary contrast) while also lying within that margin; human and rat priors are equivalent in forgetting within the margin. One fit crashed (NumPy segmentation fault) and was rerun from its seed.

13. Sequential-learning curves and spatial occupancy

Learning curves (registered). Do human choices speed learning of a new goal (Fig. 11)? The main human, legal and scratch source policies (10 seeds; all six prior×method fits of a seed on one GPU model) kept their source goal in one source layout for 65,536 moves, then learned a new goal in a second (65,536 more; frozen probes every 8,192). The area under the new goal's learning curve showed no resolved prior effect: human versus legal $+14$ percentage points ($[-6, 35]$), versus scratch -16 ($[-34, 3]$; Holm $p = .17$ for both). Replay, interpreted only because the registered acquisition gate passed (human agents reach 25.5–29.7/30 on the new goal), again retained more of the first goal ($+14.9/30$, $[10.3, 19.5]$, Holm $p = 1.4 \times 10^{-4}$; all 10 seeds), a hardware-matched replication of a known effect.




Figure 12. **Spatial occupancy before and after sequential learning.** Fraction of frozen room-A probe trials visiting each cell (development pair; four priors × 30 seeds × 30 trials per panel). Grey: removed modules. After learning room B, PPO heads to B's goal location (circle); replay preserves visits to A's goal (star). Colour: trial fraction. Descriptive aggregate; not a mechanism test.




Figure 13. **Exploratory task-addressed protection on one development room pair.** Each marker is one fixed training seed (60–62); all six fits are shown. **A** First-goal performance before and after learning B. **B** Retained first-goal and acquired second-goal performance; dashed lines mark 15/30 successes. Both arms receive task identity. The masked policy preserves its A subnetwork exactly; this guarantee is conditional on task-addressed routing. This is a backpropagation-trained Nevo-inspired adaptation, not a verified native reproduction, an OOD test or evidence for local synaptic learning.

14. Task-addressed sparse-protection pilot

Question and scope. Can explicit subnetwork protection preserve a learned goal while another is acquired (Fig. 13)? Inspired by Nevo-CRL [12], we adapt task-specific neuron masks, training-rollout-based mask selection, and hard freezing to the existing PPO pipeline. Native Nevo-CRL uses SAC, separate actors in its population, semantic task-based reuse and different crossover/pruning rules. We have not reproduced its native benchmark; this experiment tests an adapted protection mechanism. It uses backpropagation and is neither local nor spiking. The original E3 experiment requires no task ID; this separate pilot supplies it during training and evaluation to *both* arms. It cannot establish an advantage over task-ID-free E3 or identify the contribution of mask evolution separately from isolation and routing.

Design and deviations. Both arms start from the same rat-imitation/PPO source checkpoints for seeds 60–62 and learn the exposed E3 development pair (rooms 100 then 101). They use the same 64-unit two-layer body, 21,002 allocated parameters, 16 environments, PPO settings and 131,072 total environment interactions. Each nominal phase lasts 65,536 frames; rooms switch at natural episode ends, so the first 127–322 phase-B frames still occur in A (exact per-case exposures are bundled). Both arms reset Adam at B. The control has separate actor and critic heads selected by task ID, with a shared plastic body. The masked arm uses one shared head and weight set, a population of five masks, simplified importance-guided crossover and pruning every 32 PPO updates (16 evolutions total), and training rollouts only for mask selection; search uses no additional interactions. Fitness is accumulated rollout reward divided by terminal count, including unfinished-episode rewards, rather than exactly completed episodic returns. Unlike native Nevo-CRL, it has no semantic task encoder, separate population actors or exploration distillation. Initial A masks sample half the units; B reuses the protected units and initially enables all remaining units.

For the saved A mask, first-layer active rows, second-layer active-pre/active-post intersections and head columns are protected; active-unit biases and shared head biases are also frozen. Protected gradients are zeroed before clipping, with an exact-restore assertion after *each* Adam step. B can still change unprotected weights. Inactive A-mask units remain masked during A evaluation. Thus preservation of the saved A policy is guaranteed by construction when its task ID is supplied; it is not evidence that the agent infers task boundaries or a biological mechanism.

Results and audit. The fixed competence gate requires A after A and B after B each to reach at least 15/30 successes in at least two of three seeds, separately for each arm. All three seeds pass for both arms. For seeds 60/61/62, the masked arm has A-before/A-after/B scores of 28/28/18, 22/22/30 and 30/30/30; the task-ID PPO control has 30/0/30, 22/1/30 and 27/6/30. These are descriptive results from one room pair, without confidence intervals or population-level significance claims. Acquisition differs between arms; the result supports preservation of each learned A policy, not faster learning or a general performance advantage.

An independent audit recomputes the native protection masks, verifies checkpoint hashes and zero protected weight change, and replays all 540 saved evaluation episodes with an explicit CPU forward computation. Action probabilities agree within 3.9×10^{-7}; all A paths and actions before/after B match in the masked arm. Each masked fit logs 2,048 protected optimizer steps with zero drift even before restoration, while unprotected weights change. The preserved A policy can therefore be distinguished from a policy that simply stops all learning.

Execution history. An earlier six-fit implementation restored weights only after an entire PPO update, allowing protected entries to drift between minibatches. Its outcomes were seen before independent review; those fits are invalid for claims and are retained separately. The corrected code, sources, seeds, budget, gate and independent auditor were bound before the six reported fits; no seeds were dropped or fits retried. Because the correction followed exposed development results, this is a disclosed corrected pilot, not an independent confirmatory replication.

15. Pretrained policy with a learned recurrent residual

Model and controls. A separate fixed-budget pilot adds recurrent capacity to the pretrained rat-policy checkpoints while preserving their initial function. It uses the same seeds, room pair, nominal phase budgets, task IDs and paired hardware as Section 14. It draws on established residual-policy and progressive-network ideas [11, 24]; it is not a new learning algorithm or native reproduction. For task k, a 1,024-unit leaky rate network computes

$$h_t = m^{(k)} \odot \left[\tfrac{1}{2} h_{t-1} + \tfrac{1}{2} \tanh(W_R h_{t-1} + W_I o_t + b)\right], \qquad \ell_t = \ell_{\mathrm{FF}}^{q(k)}(o_t) + R_\pi^{q(k)}(h_t). \tag{3}$$

The critic has the same additive form. The FF branch loads the trained policy exactly; all residual actor/critic weights and biases start at zero. The recurrent core starts randomly (initial spectral radius 1.1, fixed 10% recurrent support), and learns through truncated BPTT/PPO. No extra distillation interactions are used: 131,072 training frames per fit. Each arm allocates 1,338,900 parameters; sparse support uses dense matrix operations, with no energy claim.

The protected arm uses half the recurrent units for A, all for B, and a shared head ($q(k) = 0$). After A, its FF body/head and active recurrent input rows, biases, recurrent pre/post intersections and residual head columns are frozen, with gradients masked before clipping and checks after every Adam step. B learns through unprotected recurrent weights, cross-connections and residual columns. The control uses all units and task-specific FF/residual heads ($q(k) = k$), copied A-to-B at the boundary; its shared FF body and recurrent core remain plastic. Both reset Adam at B and recurrent state at probe terminals. Preservation requires the provided task ID and saved A mask; it does not show automatic context inference.




Figure 14. **Exact policy initialization with trainable recurrent capacity.** All three fixed seeds are shown for each arm; both receive task identity. **A** First-goal performance before/after B. **B** Final performance on both goals; dashed lines mark 15/30. The control marked 62^* fails both acquisition gates, so its $0 \to 0$ is not evidence of retention. Protected policies preserve their A trajectories exactly while unprotected recurrent weights change. Descriptive, one exposed room pair; no working-memory, local-learning, spiking or OOD advantage is established.

All outcomes and audit. The same fixed competence gate passes in 3/3 protected and 2/3 control seeds. Protected A-before/A-after/B scores for seeds 60/61/62 are 18/18/18, 21/21/30 and 30/30/30. Controls score 26/8/30, 16/0/30 and 0/0/0; seed 62 cannot support a forgetting comparison. All six cases are retained (Fig. 14), without population tests or a claim that this architecture improves OOD generalization. A post-cohort diagnostic (registered before its own probes) evaluates every after-A checkpoint under its actual B routing before B updates, including the control's head copy. Protected B success rises 1/5/6 to 18/30/30; controls rise 4/0/0 to 30/30/0. All 180 additional frozen episodes pass independent replay. This is descriptive post-hoc evidence of acquisition; it is not a preregistered learning-curve comparison. The recurrent input and recurrent weights change in both phases. Independent replay of all 540 episodes matches action probabilities within 2.4×10^{-7}, verifies all initial FF parameters against the source checkpoint and zero residuals, and confirms zero protected drift over 2,048 B optimizer steps per protected fit. A trajectories match exactly before/after B. Parameter changes do not establish an advantage from recurrence or show that recurrent plasticity is necessary; those require further controls.

Development history. An earlier ridge-distilled recurrent model failed acquisition in all six cases (protected A scores 0/3/0, controls 0/0/0; B scores all zero). Its large readout norms and collapsed policy entropy motivated this single function-preserving repair; they do not identify a unique cause. Both versions and their registered gates are retained, with no further tuning on B. This is exploratory development, not independent confirmation. The full auditor needed a separate compatibility reader to keep legacy source-checkpoint RNG tensors on CPU; the frozen numerical checks were unchanged. The authors inspected complete driver outcomes before that independent audit finished; no code or case selection changed.

16. Registered local-readout control

A separate registered extension fixes the FF branch and recurrent core in Section 15, training only the linear residual actor/critic readouts. Their gradients factor into presynaptic activity and an output error: $\partial \mathcal{L}/\partial R = \sum_t g_t h_t^\top$, where g_t contains the clipped policy/entropy or value term. An analytic check agrees within 2.3×10^{-16}; the computational graph has no hidden-layer or recurrent gradients. PPO/GAE, advantage normalization, 16-step rollouts, minibatch reuse, Adam and global clipping remain. This is local linear-readout credit, not e-prop, local recurrent-core learning, spiking or a biological online-learning demonstration.

The three arms are protected allocation (512 A units, 1,024 B units; A readout columns/biases frozen), one unprotected shared readout, and separate task heads copied A-to-B. The last is expected to preserve A structurally with fixed features; shared routing lacks this protection. Thus routing and active capacity differ, and no contrast isolates locality. All nine fits use the same seeds, budgets and pretrained policy; the driver, gates and independent auditor were bound before full fits, without




Figure 15. **Fixed-feature local-readout control: acquisition failed.** All nine cases and all frozen before/after probes. The pretrained FF branch and recurrent core remain fixed; only linear residual readouts learn. Every $*$ marks a failed two-goal competence gate. A acquisition is not established, so zero-to-zero scores are not competent retention. B-before probes use the actual B route, including the task-head copy. One exposed pair, three seeds per arm; no conclusion about published biological learning methods.

retuning.

All arms fail the acquisition gate: A after A-training is 0/30 in every case. Allocated B scores are 6/13/5, shared 0/0/9 and task-head 0/0/9 for seeds 60/61/62. These cannot establish catastrophic forgetting or protection of learned competence (Fig. 15). Independent replay checks all 810 primary episodes within 1.2×10^{-7} probability error and verifies every non-readout weight unchanged. All cases are preserved. A before-outcome diagnostic specifies all nine after-A checkpoints on B before B updates: allocated scores are 4/0/0, and both controls score 0/0/0. All 270 frozen episodes pass independent replay. Readout weights changed and probe action entropy remained nonzero. This is an acquisition failure of this configuration, not a forgetting result or a test of published local rules. Relative to the successful recurrent pilot, both FF and core plasticity changed; their causal roles cannot be separated.

17. Scope of local-learning development tests

Our earlier local, spiking and remapping controllers were development adaptations without a native-benchmark reproduction gate. They cannot support conclusions about the published methods or biological learning. Their acquisition failures are not evidence of catastrophic forgetting: competence must first be established. A backpropagation control in the same online learner also failed to acquire the first goal in all three seeds; this prevents attributing that failure to locality alone, but does not identify its cause. The local-rate representation control below is explicitly a custom continuation after a backpropagation warm start.

18. Representation geometry, calibrated readout and acting

Figure 16 separates source fitting, geometric evaluation and acting.

Scope and event construction. This exploratory extension uses the same Tartarus release as the main paper. Cell-to-cell moves are grouped into four-move windows with stride four, producing 5,674 windows. Each input contains the camera reconstructed from the path prefix and public feedback; future actions provide evaluation targets, not policy inputs. Source layouts 1–5 supply three disjoint 192-window fitting clouds, each balanced at 96 rat and 96 human windows. Clouds and the 16 separate paired anchors share neither trials nor selected camera fingerprints. The evaluation set contains 481 windows from layouts 6–7 whose camera fingerprints do not occur in the selected fitting sets: 189 rat and 292 human windows, from




Figure 16. **Rosetta pipeline (exploratory)** [26]. Frozen vision and policy features encode current reconstructed observations; action codes and generated language represent future four-move plans. Zero-pair fits use unpaired source clouds; 16-anchor and paired-only references calibrate correspondences. Matched held-out rows serve geometry/readout evaluation. Acting queries the agent's own observations and replans the first move; recorded future actions are never policy inputs. Mouse features are predictions; the random core retains trained readout, perspective and modulation. The 88–90% text/action result is balanced first-action agreement for constructed commands. Results appear in main-paper Fig. 9; full controls follow below.

three rats and six humans. The layouts and dataset had already been used in earlier project evaluations, so this is not a new independent benchmark. Absent fitting fingerprints do not imply absence from upstream encoder pretraining or the mouse-model source PCA.

Frozen representations. Pixel inputs have 144 dimensions. Predicted mouse and random-core features use the frozen source-fitted PCA144 from the main paper; the random core retains trained readout, perspective and modulation. DINOv2-B features (768 dimensions) average the class and patch tokens after the final normalization [19]. The released Hugging Face conversion is pinned; it is not a bitwise reproduction of the Rosetta authors' TorchHub embedding files. The current 36×64 reconstructed frame is replicated into RGB and resized to 224×224 with bilinear antialiasing and ImageNet normalization. Generated instructions describe every one of the $4^4 = 256$ cardinal plans. Frozen MiniLM-L6-v2 (384 dimensions) and MPNet-base-v2 (768 dimensions) encode these instructions [29, 34]. The action code concatenates four one-hot vectors (16 dimensions, centred rank 12). Text is therefore a constructed common-content reference, whereas the current image need not identify the future plan. No action-only foundation model is trained.

Policy representations are the fixed 64-dimensional second hidden layer. Rat-choice, human-choice, legal-label and scratch policies have the shared 252-dimensional input contract and recorded source-training budgets. Untrained policies use the same architecture and seeded initialization. Backpropagation and local-rate continuations start from a rat-imitation/PPO warm start and receive 65,536 extra source frames at the fixed learning rate .0003. The local arm uses fixed feedback and eligibility updates with Adam; it is not all-local pretraining, a spiking network or a demonstrated memory-protection rule. The original plan-geometry diagnostic exports three policy-training seeds per family; the completed alignment/acting comparison fixes policy seed 60.

Unpaired alignment and paired references. We use the authors' unmodified Wasserstein–Procrustes implementation [26], commit `fdfad84ea488`, with 30 clusters, 30 restarts, batch size 10,000 and 100 refinement iterations. Source-only center-

ing and row normalization precede similarity scoring. Unequal-dimensional fits run from the lower- to the higher-dimensional space; reverse retrieval transposes similarities rather than fitting an unsupported high-to-low isometry. Five fixed author algorithm seeds are retained. The 16-anchor arm adds the fixed source correspondences; the paired-only reference fits Procrustes to those same anchors without the unpaired step. No anchor, direction relabeling, layer or best seed is selected from evaluation performance.

The prospective execution subset contains 132 primary jobs: 95 zero-pair, 19 fixed-first-seed 16-anchor and 18 paired-only references. Of these, 127 complete, two reach the registered 3,600-second cap, and three never start because an SSH pre-authentication connection burst is rejected. All five statuses remain in the primary results; incomplete five-seed groups have no mean (Fig. 17). The three never-started cases are completed once in a separately registered recovery before the original deadline, without replacing primary records or entering the acting study. An additional 49-job reference study completes all seven edges, each with five zero-pair seeds, one 16-anchor fit and one paired-only fit. It includes DINOv2-to-action, MPNet-to-action, source-PCA64 DINOv2-to-MPNet, image-plus-past-to-text and text-plus-past-to-image, with matched past-only controls. History features are strictly causal. Image retrieval scores equivalence classes of 116 distinct camera views, not unique trajectory rows. Model versions, all configurations and the deferred jobs in the larger original plan are included in the review code.

Pairwise geometry. After the original alignment/acting readout, we specify a separate descriptive all-pair analysis before computing its new scores: 12 fixed spaces, 66 unordered pairs per species. The spaces are pixels, DINOv2, predicted mouse, random core, MiniLM text, MPNet text, actions, human/rat/scratch/local policy states and the untrained policy. Each uses its declared source-cloud mean and row L2 normalization; no whitening, clipping or new PCA is fitted. Unbiased linear CKA is

$$\mathrm{CKA}(X,Y) = \frac{\langle \widetilde{K}_X, \widetilde{K}_Y \rangle_F}{\|\widetilde{K}_X\|_F \, \|\widetilde{K}_Y\|_F}, \qquad K_X = XX^\top, \tag{4}$$

where $\widetilde{K}$ is the U-centred, zero-diagonal kernel. We retain every pair and all 100 fixed row-shuffle values. The shuffle ranges are descriptive: correlated windows are not independent biological replicates. The independent audit uses the alternative zero-diagonal Song HSIC formula. The earlier action-reference CKA values reproduce within 1.5×10^{-15}. The earlier mutual-10NN diagnostic also retains its original tie order: an independent implementation differs by at most one of 2,920 human neighbour overlaps, so fine model rankings are not interpreted. Positive similarity, including that of untrained policies, does not establish learned convergence or a brain mechanism.

From plan retrieval to action. Offline readout retrieves among all 256 plans. Similarities within 10^{-6} of the maximum share probability uniformly; balanced first-action agreement averages within the four true first-action classes. It is not exact four-move accuracy. Source-only modal-plan and previous-action references receive no held-out labels. The latter achieves .388 rat and .409 human balanced agreement but only 1.67% navigation success when executed online; offline prediction and closed-loop competence are different endpoints. A relative 10^{-6} tie band changes no top sets in any of the 176 completed primary/reference fits; the registered decision rule is unchanged.

The acting study retains 163 registered cases (Fig. 18): 158 complete and five lack their primary alignment dependency. All completed cases use the same 16 exposed benchmark rooms, 30 trials per room, 45 decisions per trial, fixed goal, policy seed 60 and evaluation seed 60. Maps receive the agent's own current observations and history, not the recorded animal's counterfactual rewards or future plan. At each step they execute the first-action distribution of the retrieved plans and replan. The primary comparator is the same policy's greedy native head; sampled heads, mapped untrained features, uniform, persistence and source-mode actions are retained (Fig. 19). Sensory-only maps lack the policy's feedback and place belief and have no input-matched native head. A fixed 90-degree action rotation is applied to the first algorithm seed only; it preserves similarities for the same observation, while subsequent trajectories diverge. All 24 label-permutation oracle diagnostics are retained solely as diagnostics, never used to choose, correct or report a favourable map.

Verification and reproducibility. All 127 completed primary and 49 reference metrics reproduce exactly from the stored similarities; native float32 similarities reconstruct within 7.8×10^{-7}. Cross-host shared-input checks preserve every argmax and tie set (map differences up to 3×10^{-7}); a remote parallel-restart bitwise-equality test fails and is disclosed, but scientific fits use one worker and one thread. Two runtime audit-reader defects (obsolete gate paths and a missing top-level seed alias on failed records) were repaired with original failures preserved; scientific inputs, fits, statuses and decision rules were unchanged. Before acting, all 121 available real-map readouts reproduce stored plan scores and tie sets. The independent

acting audit checks 75,840 episodes and 3,216,202 decisions, including walls, rewards, path lengths, action probabilities and frozen model buffers. Included CPU reanalysis recomputes all 132 pairwise CKAs from source-centred feature derivatives and navigation rates/control differences from counts (290 checks). It does not rerun foundation encoders, optimization or navigation. Full metrics and all incomplete cases accompany the figure sources.

References

[1] R. Ellen Ambrose, Brad E. Pfeiffer, and David J. Foster. Reverse replay of hippocampal place cells is uniquely modulated by changing reward. *Neuron*, 91(5):1124–1136, 2016.

[2] Marcus K. Benna and Stefano Fusi. Computational principles of synaptic memory consolidation. *Nature Neuroscience*, 19(12): 1697–1706, 2016.

[3] Katie C. Bittner, Aaron D. Milstein, Christine Grienberger, Sandro Romani, and Jeffrey C. Magee. Behavioral time scale synaptic plasticity underlies CA1 place fields. *Science*, 357(6355):1033–1036, 2017.

[4] Zhengshan Dong and Wude He. Astrocyte-gated multi-timescale plasticity for online continual learning in deep spiking neural networks. *Frontiers in Neuroscience*, 19:1768235, 2026.

[5] David Dupret, Joseph O'Neill, Barty Pleydell-Bouverie, and Jozsef Csicsvari. The reorganization and reactivation of hippocampal maps predict spatial memory performance. *Nature Neuroscience*, 13(8):995–1002, 2010.

[6] David J. Foster and Matthew A. Wilson. Reverse replay of behavioural sequences in hippocampal place cells during the awake state. *Nature*, 440:680–683, 2006.

[7] Nicolas Frémaux and Wulfram Gerstner. Neuromodulated spike-timing-dependent plasticity, and theory of three-factor learning rules. *Frontiers in Neural Circuits*, 9:85, 2016.

[8] Samuel J. Gershman, David M. Blei, and Yael Niv. Context, learning, and extinction. *Psychological Review*, 117(1):197–209, 2010.

[9] Jeffrey R. Hollerman and Wolfram Schultz. Dopamine neurons report an error in the temporal prediction of reward during learning. *Nature Neuroscience*, 1(4):304–309, 1998.

[10] Stig A. Hollup, Sturla Molden, James G. Donnett, May-Britt Moser, and Edvard I. Moser. Accumulation of hippocampal place fields at the goal location in an annular watermaze task. *Journal of Neuroscience*, 21(5):1635–1644, 2001.

[11] Tobias Johannink, Shikhar Bahl, Ashvin Nair, Jianlan Luo, Avinash Kumar, Matthias Loskyll, Juan Aparicio Ojea, Eugen Solowjow, and Sergey Levine. Residual reinforcement learning for robot control, 2018.

[12] Pengyi Li, Hongyao Tang, Yifu Yuan, Yan Zheng, Xin Xu, and Jianye Hao. Neuro-evolutionary continual reinforcement learning. In *Proceedings of the 43rd International Conference on Machine Learning*, pages 70336–70352, 2026.

[13] Long-Ji Lin. Self-improving reactive agents based on reinforcement learning, planning and teaching. *Machine Learning*, 8:293–321, 1992.

[14] Ashok Litwin-Kumar, Kameron Decker Harris, Richard Axel, Haim Sompolinsky, and L. F. Abbott. Optimal degrees of synaptic connectivity. *Neuron*, 93(5):1153–1164.e7, 2017.

[15] Nicolas Y. Masse, Gregory D. Grant, and David J. Freedman. Alleviating catastrophic forgetting using context-dependent gating and synaptic stabilization. *Proceedings of the National Academy of Sciences*, 115(44):E10467–E10475, 2018.

[16] James L. McClelland, Bruce L. McNaughton, and Randall C. O'Reilly. Why there are complementary learning systems in the hippocampus and neocortex: Insights from the successes and failures of connectionist models of learning and memory. *Psychological Review*, 102(3):419–457, 1995.

[17] Samuel A. Neymotin, Hananel Hazan, Gozde Unal, Christopher Earl, Haroon Anwar, Piotr J. Franaszczuk, and David Boothe. Context-aware evidence-gated plasticity for multi-goal learning in spiking neural networks. *Research Square preprint*, 2026.

[18] John O'Keefe and Lynn Nadel. *The Hippocampus as a Cognitive Map*. Oxford University Press, 1978.

[19] Maxime Oquab, Timothée Darcet, Théo Moutakanni, et al. DINOv2: Learning robust visual features without supervision. *arXiv preprint arXiv:2304.07193*, 2023.

[20] Brad E. Pfeiffer and David J. Foster. Hippocampal place-cell sequences depict future paths to remembered goals. *Nature*, 497(7447): 74–79, 2013.

[21] Filip Ponulak and John J. Hopfield. Rapid, parallel path planning by propagating wavefronts of spiking neural activity. *Frontiers in Computational Neuroscience*, 7:98, 2013.

[22] Michael I. Posner and Yoav Cohen. Components of visual orienting. In *Attention and Performance X: Control of Language Processes*, pages 531–556. Erlbaum, 1984.

[23] David Rolnick, Arun Ahuja, Jonathan Schwarz, Timothy P. Lillicrap, and Greg Wayne. Experience replay for continual learning. In *Advances in Neural Information Processing Systems*, 2019.

[24] Andrei A. Rusu, Neil C. Rabinowitz, Guillaume Desjardins, Hubert Soyer, James Kirkpatrick, Koray Kavukcuoglu, Razvan Pascanu, and Raia Hadsell. Progressive neural networks, 2016.

[25] Philipp Schmidbauer and Andreas Nieder. Ultrarapid decision-making in an avian brain. *Science*, 394(6822):445–449, 2026.

[26] Dominik Schnaus, Thomas Dagès, Daniel Cremers, Xi Wang, and Phillip Isola. Shared geometry as a rosetta stone: Cross-modal alignment without paired data. *arXiv preprint arXiv:2610.09411*, 2026.

[27] Wolfram Schultz, Peter Dayan, and P. Read Montague. A neural substrate of prediction and reward. *Science*, 275(5306):1593–1599, 1997.
[28] Yang Shen, Sanjoy Dasgupta, and Saket Navlakha. Reducing catastrophic forgetting with associative learning: A lesson from fruit flies. *Neural Computation*, 35(11):1797–1819, 2023.
[29] Kaitao Song, Xu Tan, Tao Qin, Jianfeng Lu, and Tie-Yan Liu. MPNet: Masked and permuted pre-training for language understanding. *arXiv preprint arXiv:2004.09297*, 2020.
[30] Philippe N. Tobler, Christopher D. Fiorillo, and Wolfram Schultz. Adaptive coding of reward value by dopamine neurons. *Science*, 307(5715):1642–1645, 2005.
[31] Edward C. Tolman. Cognitive maps in rats and men. *Psychological Review*, 55(4):189–208, 1948.
[32] Misha V. Tsodyks and Henry Markram. The neural code between neocortical pyramidal neurons depends on neurotransmitter release probability. *Proceedings of the National Academy of Sciences*, 94(2):719–723, 1997.
[33] Eric Y. Wang, Paul G. Fahey, Zhuokun Ding, Stelios Papadopoulos, et al. Foundation model of neural activity predicts response to new stimulus types. *Nature*, 640:470–477, 2025.
[34] Wenhui Wang, Furu Wei, Li Dong, Hangbo Bao, Nan Yang, and Ming Zhou. MiniLM: Deep self-attention distillation for task-agnostic compression of pre-trained transformers. *arXiv preprint arXiv:2002.10957*, 2020.
[35] Yanhai Zhang, Jie Zhang, and Chi Xu. Replay in the silent degrees of freedom: Continual learning without an offline phase. *arXiv preprint arXiv:2609.31630*, 2026.
[36] Johnson Zhou, Daniel Tanneberg, Forough Habibollahi, Alon Loeffler, Kiaran Lawson, Valentina Baccetti, Kwaku Dad Abu-Bonsrah, Candice Desouza, Finn Doensen, Bradley Watmuff, Daria Kornienko, Azin Azadi, Justin L. Bourke, Bernhard Sendhoff, and Brett J. Kagan. Embodied neurocomputation: A framework for interfacing biological neural cultures with scaled task-driven validation. *arXiv preprint arXiv:2605.13315*, 2026.

19. Machine-checked statements (Lean 4)

Lean checks the logic and arithmetic behind the claims, not the empirical effects (which are statistical estimates). All statements build with `lake build` in `proofs/` (core Lean, no `sorry`, no added axioms). **(i) Coverage** (`Claims.lean`, `relabel_keeps_states`): giving every recorded row a new label leaves the sequence of states unchanged, so the legal-uniform control matches state coverage exactly. **(ii) Paired contrast** (`paired_sum`): the sum of per-seed differences equals the difference of sums. **(iii) Species gap** (`species_gap_decomposition`): $H - R = (H_\ell - R_\ell) + ((H - H_\ell) - (R - R_\ell))$, with the reported $13.7 = 4.7 + 9.0$ pp. **(iv) Units**: 3 successes per 30 trials $= 10$ pp. **(v) Operation counts**: 20,544 dense multiply-accumulates per decision (4,416 hidden); spike-driven operations are monotone in spike counts. **(vi) Loops** (`Loops.lean`), below. With Mathlib (`proofs_ml/ProofsML/Learning.lean`; only Lean's standard axioms `propext`, `Classical.choice`, `Quot.sound`): **(vii) the local readout rule is the exact policy gradient** (`softmax_logit_grad`): $\partial \log \mathrm{softmax}_a(z)/\partial z_i = [i = a] - \mathrm{softmax}_i(z)$, so with $z = Wh + b$ the TD-readout eligibility increment $(\mathbf{1}_a - \pi)h^\top$ is $\nabla_W \log \pi_a$; the TD error then makes it an actor–critic update using only quantities local to each synapse plus one broadcast scalar. **(viii) What the online trace computes** (`trace_closed_form`): $e_t = \gamma\lambda\, e_{t-1} + g_t$ equals $\sum_{k \le t} (\gamma\lambda)^{t-k} g_k$. **(ix) Loops on finite states** (`orbit_repeats`): a deterministic orbit on a finite state space repeats within $|S|$ steps, so with (vi) a greedy agent on a finite state space that has not reached the goal by then never will. **(x) The circuit's trace is bounded** (`Trace.lean`, core Lean, `trace_bounded`): with decay $q = \gamma\lambda < 1$ and inputs $|z| \le M$, every trace run from $|e| \le M/(1-q)$ stays there, so a value rate η_v moves $V(s)$ by at most $\eta_v |\delta| M/(1-q)$ per step. The stage-3 search therefore samples the value rate in these units, $\rho = \eta_v/(1-\gamma\lambda)$, which decouples it from λ (stage-2 winners: $\rho = 1.80$ and 0.70).

19.1. Greedy memoryless policies stay trapped

With greedy (argmax) actions, the frozen network, the room, the renderer and the Bayes filter together define a deterministic map f on the complete state s (cell, heading, last action, contact, reward, texture, posterior). Let f^n denote n steps. **Lemma.** If $f^{i+p}(s) = f^i(s)$ for some $p > 0$ and none of the p states $f^i(s), \ldots, f^{i+p-1}(s)$ is a goal state, then $f^{i+n}(s)$ is not a goal state for any $n \ge 0$. The proof (every later state equals one of the p cycle states, by induction on n) is checked in Lean 4 core without axioms beyond the kernel: `proofs/Proofs/Loops.lean`, theorems `stays_in_cycle` and `trapped_forever`, built with `lake build`. No finiteness is assumed (the posterior is real-valued); the lemma explains why greedy evaluation lowers every arm and why the registered probes sample actions.

20. Joint-training reference for forgetting

Reviewer 6g1M asked whether forgetting reflects sequential interference or a limit on doing both tasks at once, since a feed-forward policy without a task signal receives identical inputs for two goals in one room. We registered (`data/audit/v4n_joint_refer`

before any outcome) a reference that keeps everything of the moved-goal learning study (checkpoints, PPO and TD-readout with its frozen rate, room, 32,768 interactions, 30 seeds, three priors) but alternates episodes between the moved goal and the familiar goal (3,3) in the same room (same walls, same renders; the goal is invisible). An amendment fixed a bookkeeping error before any outcome was read.

Aliasing. From geometry alone, in 15.2% of the trained rooms' cells (97 of 640) the shortest paths to the two goals share no first move, so no goal-blind memoryless policy can be optimal for both there.

learner	prior	joint: old / new goal	sequential: old / new
PPO	human choices	88 / 44	32 / 61
	human legal	85 / 47	19 / 67
	scratch	79 / 47	22 / 54
TD-readout	human choices	64 / 11	38 / 23
	human legal	60 / 19	24 / 36
	scratch	47 / 24	18 / 39

Table 4. Success (%) in the trained room after learning, 30 seeds per row.

J1 (supported). Joint training retains the familiar goal far better: $+60.0$ pp ($[54.0, 65.9]$) for PPO and $+30.0$ pp ($[24.0, 35.9]$) for TD-readout (Holm $p < 10^{-15}$). **J2 (not supported).** We predicted that the summed success would not exceed sequential learning (a capacity limit); instead it is higher by 45.0 pp ($[35.0, 55.0]$) and 15.2 pp ($[8.6, 21.8]$) (Holm $p \leq 1.4 \times 10^{-5}$). The new goal is reached less often under joint training (-15 pp for both learners), which receives half the new-goal episodes. Reading: despite the aliasing, the same inputs and network can hold both goals; the loss of the old goal after sequential learning is interference. Human-choice priors again reach the new goal least under TD-readout, the inherited pull toward the old goal.

21. Decision time and a learning control

Registered 2026-10-31 before any outcome (`data/audit/v4n_decision_time_20261031`); P1–P3 one Holm family.
Accumulate to bound. Crow and primate choices stop when evidence accumulated over time reaches a bound [25]. Our spiking agents (Sec. 3.5) accumulate spikes; after each step t the actor reads the time-averaged spikes, and a decision stops at the first t whose most likely action has probability $\geq \theta$ ($\theta \in \{0.5, \ldots, 0.9\}$, at most 32 steps); the action is sampled as registered. Frozen source agents, familiar goal, fresh rooms, 30 seeds.

	success (%)			steps to decision			hidden ops / decision		
θ	human	legal	scratch	human	legal	scratch	human	legal	scratch
0.5	38.4	34.9	35.6	1.03	1.07	1.16	1,532	1,470	1,408
0.6	37.2	36.4	34.4	1.11	1.19	1.43	1,705	1,752	1,993
0.7	38.1	33.9	32.8	1.27	1.66	2.17	2,064	2,914	3,741
0.8	37.4	34.3	31.2	1.74	2.36	3.42	3,216	4,683	6,795
0.9	38.8	32.0	28.7	2.64	3.91	5.34	5,403	8,644	11,544

Table 5. Accumulate-to-bound spiking decisions. Dense network: 4,416 hidden multiply-accumulates per decision.

P1 (supported): human-choice agents reach the bound in fewer steps than legal-label agents, -0.48 steps averaged over θ ($[-0.73, -0.23]$, $p = .0004$). **P2 (not supported):** success $+3.7$ pp ($[-1.3, 8.7]$, $p = .14$); descriptively the gap grows with the bound ($+6.8$ pp, $[2.3, 11.3]$ at $\theta = 0.9$) because stricter bounds slow and weaken the legal and scratch agents but not the human-choice agents. The first spiking step already gives the dense network's choice in 69–76% of decisions, the analogue of choice-predictive activity early in the trial. Faster decisions here are a property of less ambiguous policies, not a claim about animal reaction times, which our data lack.

P3: shuffled reward (supported). TD-readout was retrained exactly as registered (30 seeds, 3 priors, same rate and rooms) except that at every step the rewards of the 16 parallel rooms were permuted among them, keeping reward statistics but breaking the action–reward contingency, as permuted decoding does for living neural cultures [36]. Final new-goal success fell from 23.4 to 8.6% (human choices), 35.9 to 11.8% (legal) and 38.9 to 16.8% (scratch); differences $+14.9$, $+24.1$, $+22.1$ pp, all $p < 10^{-4}$.

22. Matched-content image–text–action study

Registered 2026-10-31 before any outcome (`data/audit/v4n_rosetta_matched_20261031`); answers reviewer 6g1M. In the reviewed version the text was generated from the action plan, so text–action similarity was circular. Here image, text and action describe the same decision moment. **Image**: DINOv2-base on the rendered first-person frame. **Text**: an exact description of what is visible, never of the action ("Ahead there is open floor. To the left there is a drop with no floor. … The black curtain is to the right."), embedded with MPNet. **Action**: the frozen agent's own action probabilities. Moments: 40,000 decisions of frozen agents (4 priors × 5 policy seeds) in the 16 fresh rooms; rooms 100–107 fit, 108–115 test.

	B: predict the action (%)			A: CKA			C: composed (%)		D: closed loop (%)	
prior	image	text	majority	img–txt	txt–act	img–act	img→txt→act	shuffled	composed	own head
human choices	76	77	46	0.35	0.33	0.17	72	34	11.3	44.8
human legal	74	69	48	0.35	0.30	0.14	67	39	12.8	37.8
rat choices	79	78	44	0.34	0.38	0.16	70	46	9.5	33.4
scratch	80	76	51	0.36	0.40	0.21	70	45	14.0	31.8

Table 6. Matched content (5 policy seeds; held-out rooms). D: success of agents driven by the composed map versus the same agents' own heads in the same rooms; uniform policy 13.3%.

Reading. With matched content, a description of the view predicts the agent's next action far above the majority baseline, and an image→text map fitted on some policy seeds composes with a text→action probe fitted on other seeds to recover the action (67–72% versus 34–46% for a shuffled probe). Image, text and action are therefore linked without circularity. Yet the composed map navigates at chance in closed loop, far below each agent's own head: the view text carries no position or goal, which the agents take from their pose belief. Shared, predictive geometry is not navigation competence.

Lexical control. The view text says "to the left/right" (egocentric) while the actions are named down, up, right and left (allocentric moves), so the two share words. We reran A–D with the same content worded without any action name ("In front … On the anticlockwise side … On the clockwise side …"; a check asserts that no caption over every cell, heading and floor state contains an action word; amendment written before the rerun). The predictive link is unchanged: text→action 69–78% (identical to within 1 pp for every prior), composed 68–71% versus 35–45% shuffled, closed loop still at chance (10.5–16.2%). The text–action CKA, by contrast, roughly halves (0.17, 0.15, 0.31, 0.21 versus 0.33, 0.30, 0.38, 0.40): the geometry score depends on wording, the prediction does not. We therefore base the linkage claim on prediction and composition, not on CKA.

The Rosetta paper's own protocol and code (their geometry scores, unpaired Wasserstein–Procrustes alignment with 0 and 16 pairs, FOSCTTM; upstream tests 46/46 pass in our environment) are applied to the same data (descriptive, secondary; 5 Rosetta seeds per cell; image–text on all rows, image/text–action per prior; geometry on 1,000 held-out rows; amendment 4 fixed an index bug for cells with fewer rows, before any outcome was seen). Their geometry scores reproduce the shared structure: unbiased CKA 0.32 for image–text, 0.28–0.41 for text–action and 0.14–0.23 for image–action, all against $\leq$0.001 with rows shuffled; mutual kNN is small everywhere (0.10 image–text, 0.016–0.026 with action, versus 0.007–0.022 shuffled). Their unpaired alignment does *not* recover which row matches which. With 0 known pairs, FOSCTTM (0.5 = chance, 0 = perfect) is 0.57 for image–text and 0.50–0.53 for image–action, and 0.34–0.42 for text–action with a large seed spread (SD up to 0.17). Sixteen known pairs help every pair (image–text 0.30, text–action 0.26–0.32, image–action 0.39–0.43), but the matching remains far from perfect. Geometry that is shared on average is not enough, without pairs, to say which view goes with which action. This is the same conclusion as the closed-loop test above.

Action-word-free captions (amendment 5, written before the rerun). The same protocol, seeds and code were rerun with the captions that never name an action. Image and action features are unchanged, and the 20 image–action jobs reproduce the original values exactly (20/20 identical; a determinism check). Removing action words lowers text–action CKA (0.16–0.31 versus 0.28–0.41) and moves unpaired text–action FOSCTTM to chance (0.47–0.55 versus 0.34–0.42; below 0.5 in 10/20 jobs versus 18/20). The earlier better-than-chance unpaired matching came from wording that shares words with the action names. Image–text gives CKA 0.23 (versus 0.32) and unpaired FOSCTTM 0.42 (versus 0.57); with 16 pairs, the values are 0.32 (image–text) and 0.34–0.42 (text–action). Mutual kNN does not change (0.10; 0.016–0.025). Without lexical overlap, none of the three modalities can be matched to the actions without pairs. This agrees with the main text: the views carry where the open paths are, while the choices carry the human content.

Where does the view determine the move? (amendment 6, descriptive, before computing.) The same moments are split by geometry. A move is *forced* when one way other than back is open and a *junction* otherwise. The goal is never drawn, so

"goal near" means it lies in an adjacent cell inside the visible range. Probes and the Rosetta geometry scores are computed per stratum in the test rooms, pooled over arms (Table 7). A "goal-bearing" caption adds where the goal lies and how far: it is what a view would say if the goal were visible. The text–action geometry is strongest where the walls force the move. At junctions the view still predicts most moves, far above a uniform choice among open ways, mostly through the curtain's bearing. When the goal is in the visible range, its bearing makes the move near certain, and these moves are 93% shortest-path. The view-based probe almost never predicts a move back (0–2% of moves, versus 1.6% for the agents), so the closed-loop failure is not a failure to avoid going back. We do not identify its mechanism here.

stratum (share)	text	image	+goal	uniform	CKA_{ta}	CKA_{ia}
forced (34%)	.78	.67	.76	.68	.55	.26
junction (58%)	.79	.79	.73	.35	.29	.13
junction, goal near (1%)	.53	.73	.91	.28	.29	.19

Table 7. Action accuracy of the room-held-out probes and Rosetta CKA (text–action, image–action; shuffled $\leq$0.01) per stratum. Junction with the goal near: mutual kNN text–action 0.16 (shuffled 0.04). Per arm: human-choice moves are the most predictable from the view at junctions (0.83, versus 0.76–0.80).

23. Biologically plausible learners: stability, context and a brain-constrained circuit

All studies here use the moved-goal protocol of the main text: 32,768 interactions, configurations chosen on development rooms and seeds only, then tested once with 30 seeds $\times$ 3 priors in fresh rooms. Each probe uses 30 trials. Every study was registered before its own outcomes (protocol, amendment and hash files in the audit folders). Contrasts are paired by prior and seed, and the CIs are 95%. Fig. 20 plots every run in the keep–learn plane.

Search 2: replay and expansion (learn fast, forget). The local rules of the main text were extended with experience replay (GAE, clipped modulator, several epochs) and a fixed random k-WTA expansion (granule-like, 512–2048 cells, zero-initialised readout). Hidden credit comes from random feedback (DFA) or Error Diffusion routing; no learner uses backpropagation. 160 TPE trials were run. The selected learners reach the new goal in almost every run (99.7–99.9%, versus PPO 61%), and they reach it in the unseen room more often than PPO (40–47% versus 28%). They keep almost none of the old goal (3%, versus PPO 24%). The human prior does not speed their learning (learning-curve area versus legal labels -3.8 to -2.2 pp, Holm $p \geq .20$; head-only -8.9, Holm $p = .04$).

Why locality alone does not protect old skills. Local rules are expected to change only the synapses a new task uses. Here they move 52–94% of the plastic synapses, so that expectation fails. Across all 810 learning runs, old-goal success falls by 0.28 pp per pp of new-goal success, and at the same new-goal success local learners keep 7.6 pp less than PPO ($\pm$2.3, cluster-robust by seed). The two goals share their views and states, so a rule without a context signal must overwrite the same synapses whatever its credit assignment. The joint-training reference (Sec. 20) shows that the network has room for both goals. Recent biologically plausible remedies all add a signal that says *when* or *where* to learn: context-dependent gating [15], evidence-gated consolidation for multi-goal navigation [17], astrocyte-like slow gates on plasticity [4], replay restricted to idle synapses [35], and sparse fly-like expansion codes [28]. We tested the two families that need no task label.

Consolidation and old-goal replay (registered NSGA-II, 144 trials). Each synapse is pulled back toward its pre-learning value (a fast and a slow weight component [2]). Before the switch, the frozen prior's own familiar-goal experience is replayed between new chunks, counted inside the same budget (complementary learning systems [16]). The best random-feedback learner (replay of 4,096 old frames, weak anchor) beats PPO on new-goal learning ($+17.1$ pp, $[9.3, 24.9]$) and on the new goal in the unseen room ($+18.0$, $[12.6, 23.5]$), and it keeps the old goal as well as PPO ($+2.5$, $[-2.7, 7.8]$). Against search 2, it trades 22 pp of new-goal success for 23 pp of retention. The error-routing and head-only winners keep slightly less than PPO. With these learners the human prior no longer changes the learning-curve area (Holm $p \geq .17$ for all six registered contrasts; point estimates -4 to -14 pp).

Context gating: forgetting is a missing context (registered, Holm over 4). Only the expansion readout learns, with the search-2 rule. G0 uses one code for all experience. G1 gives each goal its own half of the expansion (an oracle upper bound).

G2 has no cue: a latent-cause rule [8] switches halves when a CUSUM on episode outcomes detects that the current context has stopped paying. Every condition learns the new goal (99.7–99.9%). Old-goal retention rises from 4.7% (G0) to 57.5% with the cue ($+52.8$ pp, Holm $p = 10^{-33}$) and to 42.7% when the context is inferred ($+38.0$, $[33.5, 42.4]$, Holm $p = 10^{-29}$). Gating costs nothing on the new goal (G2$-$G0 -0.04 pp, $[-0.36, 0.29]$). In the unseen room G1 also keeps more of the old goal (36% versus 8%). The inferred-gate learner is the only one here that keeps more of the old goal than PPO (43% versus 24%) while learning the new one fully.

Is the inference gap a tuning artefact? (registered NSGA-II, 160 trials; one test). G2's runs switch $2.2\times$ per old-goal probe, so we searched only its switch rule (establishment time, expectation floor, drop ratio, CUSUM bound, dwell, reference cap) on dev rooms, with the learner, budget and rooms fixed. The best dev rule beat the registered one there (54 versus 50%) but not on the 30 test seeds in fresh rooms: old goal 40.0% versus 42.7% (-2.7 pp, $[-6.6, 1.1]$, Holm $p = 0.19$), new goal unchanged (-0.2 pp, $[-0.4, 0.03]$), still $+35.3$ pp over the ungated learner ($[30.3, 40.2]$) and -17.5 pp under the cue ($[-22.0, -13.1]$). The registered rule is therefore near the best of its family; the remaining gap to the oracle is the cost of inferring a hidden cause from outcomes alone, as expected when both goals share views. Human choices again kept the most (50% versus 35% for legal labels and scratch).

A brain-constrained circuit (registered NSGA-II, 96 trials; descriptive test). A mushroom-body / cerebellum-like circuit sits on the frozen prior. It has sparse granule (Kenyon) cells, each wired to c hidden units [14], global inhibition (top fraction f) and divisive normalisation. Dopamine-like TD errors gate an eligibility trace on the output synapses only (a three-factor rule [7]). The circuit also has metaplasticity, optional reverse replay of rewarded episodes and an optional inferred gate. It uses no batches, no adaptive optimiser and no stored buffer, and it learns online. The selected circuit (K=4,096, c=7, f=3.5%) keeps the most of the old goal of any sequential learner (55% versus PPO 24%, $+31.0$ pp, $[24.5, 37.4]$; unseen room 39% versus 21%). It also keeps more than the inferred-gate learner ($+12.4$ pp), with 29k synapses. It learns the new goal slowly (15% versus 61%, -45.5 pp): it sits at the stable, slow end of the trade-off within this budget. The inferred gate lowers both probes here (-5.4 and -8.7 pp). With this circuit, human-choice priors keep more of the old goal than scratch priors ($+14.8$ pp, $[4.2, 25.3]$).

Stage 2: awake replay lets the circuit learn (registered NSGA-II, 96 trials; one test). Stage 1 learns strictly online, whereas every learner here that learns the moved goal reuses each experience several times. Stage 2 keeps the circuit and its rule and adds two mechanisms: after every T steps the last T steps are replayed E times with the same three-factor rule (awake sharp-wave-ripple replay of recent experience [1, 6]), and, optionally, the dopamine signal is divided by a slow running RMS of past TD errors (adaptive coding of prediction errors [30]). The stage-1 winners, re-run inside stage 2, reproduce their dev scores exactly. Selected: K=2,048, c=7; ungated f=5.5%, E=8, T=16, adaptive dopamine; gated f=4.4%, E=1, T=8. On the 30 test seeds the ungated circuit learns the new goal in 60% of runs (stage 1: 15%) and is *equivalent to PPO* in the trained room within ± 10 pp (new goal -0.6 pp, $[-10.3, 9.0]$, TOST $p = 0.028$; old goal $+0.5$, $[-6.4, 7.4]$, TOST $p = 0.004$), with 15k synapses and 113 active cells, no gradient through the prior, no adaptive optimiser, clipping or ratios, and no divergence in 180 runs. With the inferred gate it keeps $+13.3$ pp more of the old goal than PPO ($[6.9, 19.7]$) at -7.3 pp on the new goal ($[-16.9, 2.2]$), with 45 active cells. Replay buys learning at the price of retention (old goal -30.5 pp versus stage 1, $[-36.4, -24.5]$): the same trade-off the gate and consolidation address. In the unseen room it trails PPO on the new goal (-7.9 pp, $[-13.8, -2.1]$). Human-choice priors again help: versus scratch, $+15.9$ pp on the new goal ($[0.1, 31.6]$) and $+16.6$ on the old ($[6.2, 26.9]$).

Stage 3: retuning in proved units beats PPO (registered NSGA-II, 120 trials on both GPUs; one test). Stage 3 added sleep replay of stored old-goal episodes (interleaved replay [16]) and searched the value rate in the units of the Lean trace bound (Sec. 19.1, item x), $\rho = \eta_v/(1 - \gamma\lambda)$, with K and c fixed. Old-goal replay did not help on dev (best dev sum 34.3 without, 18.4–26.6 with) and both winners use none; the gated winner is the stage-2 rule and reproduces its test exactly. The ungated winner (f=2.2%, λ=.94, ρ=1.45, E=4, T=16, adaptive dopamine, metaplasticity) learns the new goal in 73% of test runs: $+12.4$ pp over PPO ($[3.8, 21.1]$, $p = .006$) and $+13.1$ over stage 2 ($[4.5, 21.6]$), while the old goal stays equivalent to PPO within ± 10 pp ($+3.7$, $[-2.2, 9.7]$, TOST $p = .019$); 0 of 90 runs diverged. In the unseen room it still trails PPO on the new goal (-7.4 pp, $[-13.4, -1.5]$) and equals stage 2 there ($+0.5$, TOST $p < .001$). Human-choice priors learn the new goal faster than scratch ($+16.2$ pp, $[2.1, 30.3]$) but not than legal labels ($+7.4$, $[-6.9, 21.8]$). The gain is selection within a registered search, tested once; the stage-3 mechanism itself (old replay) was rejected.

Stage 4: a dense lateral-horn pathway is rejected (registered NSGA-II, 120 trials on one GPU; one test). Stage 4 targeted the unseen-room deficit. It added a dense, unit-normalised copy of the cortical input (gain w) to the sparse code on the same output synapses, as the insect lateral horn runs parallel to the mushroom body [14], and added the unseen-room new goal as a third dev objective. At $w = 0$ the code reproduces stage 3 exactly. Both dev winners use $w = 0$, so the pathway was rejected. The gated winner is the stage-3 rule and reproduces its test exactly. The ungated winner (f=2.2%, λ=.83, ρ=1.99, E=4, T=8, adaptive dopamine) learns the new goal in 75% of test runs ($+14.6$ pp over PPO, $[5.9, 23.4]$, $p = .001$). It keeps the old goal equivalent to PPO (-1.4, $[-7.6, 4.7]$, TOST $p = .004$), and in the unseen room it no longer trails PPO significantly on the new goal (-5.0, $[-10.9, 0.9]$, TOST $p = .047$). It does trail on the familiar goal (-7.2, $[-11.5, -2.9]$). Against stage 3 the stage-4 winner is equivalent on both new-goal probes (TOST $p \leq .016$) and lower on the familiar goal in the unseen room (-4.9, $[-8.7, -1.1]$). It is a fourth tested selection, so the main text keeps stage 3.

Stage 5: a proved transfer identity motivates a place drive, which is rejected (registered NSGA-II, 120 trials on one GPU; one test). For the three-factor update $\Delta W = \eta\, \delta\, g\, z_A^\top$ we prove in Lean 4 (Mathlib; `proofs_ml/ProofsML/Transfer.lean`, standard axioms only) that the readout at any other state B moves by exactly $\eta\, \delta\, g\, \langle z_A, z_B \rangle$. Transfer to an unseen room is therefore proportional to code overlap. The same view in the trained and unseen rooms shares cosine .71 of its Kenyon-cell code, versus .95 for PPO's learned hidden layer. The filter's place belief is room-invariant (cosine 1.00 along matched paths). We also prove that a common drive βc added to both pre-activations leaves their difference unchanged and raises their inner product by $\beta(\langle a, c\rangle + \langle c, b\rangle) + \beta^2 \|c\|^2$. Stage 5 therefore fed the 100-cell place belief to every Kenyon cell through c_p random synapses (gain $\beta \in \{0, .5, 1, 2, 4\}$, $c_p \in \{3, 7, 15\}$), with the stage-4 objectives. One deviation is disclosed: a probe-shape bug crashed every $\beta > 0$ trial at the first launch, and it was fixed before any $\beta > 0$ outcome existed (ADDENDUM1). The ungated dev winner uses $\beta = 0$, so the drive is rejected there. Its test is a new stage-3 configuration that learns the new goal in 69% of runs ($+8.1$ pp over PPO, $[-0.6, 16.7]$). In the unseen room it reaches 23% on the new goal (-4.7 vs PPO, $[-10.8, 1.4]$, TOST $p = .044$; $+2.7$ vs stage 3, $[-2.0, 7.5]$). The gated winner ($\beta = 1$) keeps the old goal better than PPO ($+12.3$, $[6.1, 18.4]$) but falls to 11% on the new goal in the unseen room (-16.7, $[-22.3, -11.2]$). Higher overlap did not translate into transfer, so the result is a registered null; the main text keeps stage 3.

Stage 6: a context-gated goal-vector pathway removes most forgetting but not the unseen-room deficit (registered NSGA-II, 120 trials on one GPU; one test). Following central-complex models of vector memory, the readout also sees the place belief directly, $[z;\, g\, b]$ with $g \in \{0, .1, .25, .5, 1, 2\}$; with the inferred gate each context writes its own copy of b. We prove in Lean 4 that the joined code's overlap is $\langle z_A, z_B \rangle + g^2 \langle b_A, b_B \rangle$ and that copies for different contexts are orthogonal, so learning in one context cannot move the other context's place weights. Both dev winners use the pathway ($g = 1$ ungated, $g = 2$ gated). On the test the gated circuit learns the new goal in 84% of runs and still reaches the old goal in 58%: $+22.9$ ($[15.0, 30.8]$) and $+33.6$ ($[26.1, 41.0]$) over PPO, and $+30.3$ and $+20.3$ over gated stage 3. In the unseen room it reaches the new goal in only 7.5% (-20.3 vs PPO, $[-25.7, -14.9]$; -5.1 vs stage 3). The ungated circuit learns 81% ($+20.1$ vs PPO) but forgets (old goal 18%) and reaches 13% in the unseen room (-15.2, $[-20.5, -9.8]$). The place pathway thus buys continual learning in the trained room and costs transfer: a place-to-action map learned in one layout steers into walls in another. No configuration matches PPO in the unseen room.

Stage 7: a hippocampal goal map transfers to never-seen rooms (registered NSGA-II, 80 trials on one GPU; one test). Every agent's own place belief peaks on the true cell at every step in all 16 fresh rooms, so the deficit is not perception: stages 1–6 store the goal in view→action associations, which are layout-specific. Mammals store goals on the hippocampal place map [18, 31], where place fields accumulate at rewarded places [5, 10], and read routes out of it by recurrent propagation and replay [20, 21]. Stage 7 adds this to the stage-6 circuit: a one-shot dopamine-gated Hebbian write of the rewarded place (fixed place-field shape, as in behavioural-timescale plasticity [3]), a recurrent wavefront value over the place-cell lattice [21], short-term depression of a link after a bump [32], and inhibition of a remembered goal that gives no reward (a dopamine dip at an omitted reward [9], acting as inhibition of return on places [22]); both reset every episode, and no synapse or goal memory changes in the probes. Its drive, in steps to the goal, is added to the circuit's logits with gain κ. We prove in Lean 4 (`Wavefront.lean`) that, in any layout, the wavefront has no local maximum away from a goal and that climbing it reaches a remembered goal within $|S|$ steps. Two scaling choices were fixed on one dev smoke run before registration (disclosed); one search worker was restarted after a transient checkpoint read (ADDENDUM1). On the test, the ungated winner ($\kappa = 50$) learns the new goal in 92% of runs, keeps the old goal in 100%, and reaches the new goal in the never-seen room in 83% ($+55.2$ pp over PPO, $[47.4, 63.0]$; $+70.4$ over stage 6) and the old goal there in 73% ($+51.9$). The registered ablation without the two within-episode mechanisms falls to 8% in the never-seen room (-19.4 vs PPO): transfer

needs both the room-invariant goal memory and online repair of the map, a within-episode memory the feed-forward PPO baseline does not have. Scope (descriptive, after the test): what transfers is a goal place in the arena frame. In the fresh pairs the familiar goal is the same cell in both rooms and the moved goal is the same cell (2 pairs) or one cell away (6 pairs). The goal map reaches it in 73% and 86% of these never-seen-room trials respectively (PPO 32%, 27%; stage 3 23%, 20%), so it is not replaying one coordinate, but a goal far from any remembered place is outside this benchmark and would require search. Leakage control (same 15 agents, browser port): with the goal moved $\geq$4 cells from every remembered place the goal map succeeds in 3% (PPO 4%), and 99.6% when its memory is re-centred there, so nothing in the input reveals the goal; the belief's input (distal cue rows) is identical across layouts. The old goal is kept because the map holds both goal places and inhibition of return tries the other after an empty visit.

Stage 8: a dopamine dip at every visited place removes the remaining loops (registered, no search; one test). *Diagnosis* (descriptive; the project page's step-exact port of the tested agents, seeds 1000–1004 $\times$ 3 priors, the 30-trial probe in each seed's trained and never-seen fresh room, both goals). The memoryless agents (frozen priors, PPO, the stage-3 circuit) fail by pushing into a wall: at trapped steps the place belief is correct (100%) while the habit's preferred move is optimal in 2–25% of steps with $p = 0.74$–0.95, and 8–14 of the last 16 moves are bumps; no within-episode state can change this (`trapped_forever`). The stage-7 goal map still failed with the familiar goal in never-seen rooms (62% in these 15 agents; 90% of its failures were loops), and there the *drive itself* asked for the bump: the chosen link was already depressed (99% of trapped steps), yet it was the drive's best move ($D_a = 0$, $p_{\mathrm{drive}} = 0.78$–$1.00$). A depressed link is valued as staying, and the blurred goal field makes the agent's own cell a local maximum of v next to a wall ($v_c = G_{e,c} \geq \gamma_h\, v$ of every open neighbour), so staying, i.e. bumping, is optimal and short-term depression, which only closes links, cannot help. Stage 7 inhibited a place only when G_e exceeded 70% of its maximum (a searched threshold), never on the blur around a goal; a rarer second case was a field peak written at a mis-estimated, unreachable cell. Tested at probe time with the stage-7 weights, inhibition at every visited place in proportion to its expectation ($\theta = 0$) raised the never-seen familiar goal from 61.8% to 100%, left the other three probes unchanged (81.8$\rightarrow$84.4, 93.3, 100) and removed every loop (trapped failures 0%; bumps per episode 14.7$\rightarrow$2.5). Alternatives tried there were worse or redundant: valuing a known collision at zero (91.1%), removing the field behind a bump (harmful, 29.6% on the moved goal), and an oracle that pre-closes the three visible links (69.6%): the loop is not a perception failure. *Brain basis.* A dopamine pause at an omitted reward scales with the expectation that was violated [9, 27]; the stage-7 rule already computes this dip ($G_e \leftarrow G_e(1 - K_\sigma(c))$, with $K_\sigma(c)_c = 1$ so a visit removes the expectation at that cell exactly) and acts as inhibition of return on places [22]; the 70% threshold had no biological reading and is dropped. Lean 4 corollary (`Visited.lean`, standard axioms): after the dip the visited cell is not a source, so by `wave_ascent` some open neighbour has strictly higher value: the drive can never prefer to stay at a visited cell. *Test* (registered with the diagnosis and predictions before any run; the whole learner re-run with $\theta = 0$ in both stage-7 winners, nothing else changed; with $\theta = 0.7$ the script reproduces the stage-7 record exactly; 30 seeds $\times$ 3 priors, paired with stage 7). Ungated: new goal 96.7%, old goal 100%, never-seen room new goal 88.8% ($+5.7$ pp, $[0.4, 11.1]$; PPO 27.8%), never-seen room old goal **100%** ($+27.3$, $[21.4, 33.3]$; excluding the five diagnosis seeds $+25.7$, $[19.3, 32.2]$). Predictions: P1 ($\geq +20$ on the never-seen old goal) and P3 (trained-room probes within ± 5: $+4.4$, 0.0) met; P2 (never-seen new goal within ± 5) exceeded in the favourable direction ($+5.7$). The gated winner does not share the gain (never-seen old goal $+6.5$, $[3.1, 10.0]$; never-seen new goal -6.6, $[-12.7, -0.4]$; its predictions not met), so the ungated circuit remains the one we report. Disclosed: the rule was chosen after probe-time outcomes on five seeds, two of them test seeds (hence the 25-seed contrast); a dry run of the registered analysis on 40 partial records per arm was seen before completion (ADDENDUM2); the Lean file was added after registration (ADDENDUM1). The page's loop diagnostic (`site/test/loops.mjs`) and the probe-time scripts are in the study folder. *What "never seen" means here, and what 100% does not mean* (descriptive, after the test; `site/test/leakage.mjs`, `efficiency.mjs`). The goal is not new: the familiar goal is cell (3,3) in every room, and the moved goal of the never-seen room lies 0–1 cells from the one learnt in the trained room (the registered mirror rule). What is new is the layout: each never-seen room differs from its trained partner in 30–32 of 100 cells (disjoint wall sets), from every development, prior-training and Tartarus layout in $\geq$15 cells, and no two of the 16 rooms coincide. Learning always happens in the trained room (`room_of`), probes run with frozen weights and never write the goal memory, and the belief filter starts uniform and reads only the distal-cue rows, which are identical across rooms (maximum difference 0); the floor rows differ (the adjacent walls are visible, as they should be). Controls with the same 15 agents: a goal $\geq$4 cells from every remembered place is reached in 5.3% of trials (stage 3: 3.8%, PPO: 4.2%), 100% when the memory is re-centred on it, 8% with no memory; so the 100% is the remembered place reached through unknown walls, not a goal read from the input. Nor is it the shortest route: in never-seen rooms the old goal is reached in $1.67\times$ the shortest path on average (median 1.42; exactly shortest in 17% of trials; 3 bumps per episode), the moved goal in $4.1\times$ (search around the shifted place), against

$1.14\times$ in the trained room; the longest shortest path is 14 moves, and the budget is 45.


The same networks in the animals' own mazes (registered, descriptive; the paper's claims are unchanged). *Shared Tartarus layouts.* Configurations 6–25 were walked by both species and seen by no network (imitation used choices from 1–5). With each layout's own ten starts and no retraining, recorded humans reach the familiar goal within 45 moves in 97% of trials and rats in 85%. Frozen networks trained on human or rat actions reach it in 57% and 55%. After learning the moved goal, PPO keeps 10% (new goal 21%), stage 3 16% (17%) and stage 7 66% (70%). Successful human-trained paths are $1.32\times$ the shortest (humans 1.26, rats 1.67); visited-cell distributions overlap the humans' with a Bhattacharyya coefficient of 0.73 (human versus rat 0.94). One analysis fix (rat tracking cells on removed modules, starts off the native set) was registered as an addendum before any agent metric. *Brain geometry on the same states.* We rebuilt two recorded mazes in our arena with the same renderer and moves: the rat W-track (DANDI 000978; 8 rats, dorsal CA1 and prefrontal units) and the human virtual towns (Zenodo 8058006; 11 patients, hippocampal iEEG; streets rasterized at $\sim$14 units per cell, overlap 0.66/0.55). Each recorded trial was replayed through every network, so model and brain are compared at identical positions and headings. RSA between condition RDMs (rats: cell $\times$ heading, 32–36 conditions; humans: cell, 19–36) is above permutation for all networks, but much of it is space: a track-distance RDM alone gives ρ=0.29 (rats) and 0.28 (humans), against split-half ceilings of 0.90 and 0.55. After partialling out space, heading and raw pixels, rat RSA is $\leq$0.07 for every network (best CA1: trained on rat actions, 0.071 ± 0.048), and human RSA is largest for the network trained on human actions (0.117 ± 0.052; stage 3 0.107, stage 7 0.105, rat-trained 0.034). Post hoc, the human-trained minus rat-trained difference is $+0.084 \pm 0.048$ in human hippocampus (9 of 11 patients) and points the other way in rat CA1 and PFC (-0.015 to -0.027, intervals include 0). The data come from different tasks and recording methods, so this is a descriptive species-matched trend, not a test. *Open arenas (second registered study).* The same replay in two open arenas: humans navigating to remembered object locations (OpenNeuro ds005522; 40 patients with medial-temporal or hippocampal contacts, bipolar iEEG) and rats foraging in an open field (DANDI 000405; 5 rats, 115 sessions of entorhinal, pre- and parasubiculum units). Here neural geometry is mostly space: the track-distance RDM gives ρ=0.26 (rats) and 0.22 (humans); the human split-half ceiling is only 0.04. Beyond space, heading and pixels, every network adds little (partial ρ 0.00–0.05). In rats, the imitation networks and both brain circuits sit slightly above PPO (0.048–0.054 versus 0.018; n=5); in humans no family differs (0.02–0.04). One analysis fix (rat sessions with a single active unit give an undefined RDM) was added after the first output and is disclosed. *Rosetta modalities against the brain.* On these replayed states the Rosetta modalities (image: DINOv2 view; text: MPNet caption; each network's action probabilities and hidden layer) enter the same condition-RDM comparison as the recordings (Spearman ρ, seeds then subjects averaged; space and heading partialled out; registered before this output, though brain–image/text and brain–network values above had been seen). Too few conditions (13–36) remain for the unpaired solver, so this is geometry only. Beyond space, every network's hidden layer is closer to human hippocampal geometry in the towns (0.04–0.12; human-trained 0.121) than the view (0.011) or caption (-0.001). In rat CA1 the view is as close (0.079) as most hidden layers (0.055–0.115), in rat PFC the caption (0.095) is exceeded only by PPO after learning (0.148), and in both open arenas view and caption (0.03–0.09) are as close as any network (0.02–0.05). Action probabilities are never closer than the hidden layer by more than 0.03 (-0.04 to 0.07). Caption and view share geometry (0.33–0.59); each hidden layer shares more with its actions than with the view, except the goal-map circuit, whose actions are driven by the place map. The interactive matrices for every setting and network are on the project page.

Spiking cost of the learned networks. The learned networks were converted to signed integrate-and-fire networks exactly as the priors were (10 seeds $\times$ 3 priors, learned task, trained room). Conversion preserves success at every T (PPO 63–64% versus 63% dense; search 2 99.3–99.9% versus 99.4–99.9%). The expansion costs operations: search-2 networks need 0.8–3.5M synaptic operations per decision at T=8–32, versus 24–100k for PPO and TD-readout. Their dense equivalent is 153k multiply-accumulates, versus 21k. The brain-constrained circuit has 29k synapses; 141 of its 4,096 granule cells (3.4%) are active per decision, so its output stage needs about 0.7k operations.

24. Rosetta geometry across brains, priors and learners


The Rosetta geometry scores [26] (upstream code, unmodified) were computed between the hidden layer of every network and each modality of the matched-content moments. The modalities are the image, the text, the predicted mouse cortex (144 PCs and all 9,941 units) and the action. Networks were also compared with each other, all on the same 1,000 held-out moments per job. There are 3 policy seeds $\times$ 3 Rosetta seeds, and shuffled controls are $\leq$0.01 everywhere (Fig. 22). These analyses are descriptive. *Schedule deviation:* the geometry scores were computed first in one pass, with code identical to

the registered jobs; the 882 WassersteinProcrustes retrieval jobs finished afterwards (FOSCTTM on held-out moments; 0.5 is chance, lower is better). **Retrieval.** Without pairs, modality-to-modality retrieval is at chance for image, text, cortex and action (0.43–0.67), so the shared geometry does not identify individual moments; 16 pairs bring every pair to 0.12–0.47 (hidden→action 0.12–0.28, cortex→hidden 0.19–0.28, image→action 0.42–0.47). The three-way bridge (image or cortex → text → action, unpaired) is no better than the direct map (0.46–0.53 versus 0.48–0.63). Between networks, however, unpaired alignment works when the training choices are shared, as in brain-to-brain alignment: human-choice networks of different seeds 0.06; human choices versus legal labels 0.31; versus rat choices 0.59 and scratch 0.50 (chance). Learning keeps a network alignable with its prior (PPO 0.20, local rule 0.32; with 16 pairs 0.11 and 0.06). The choices, not the views, set the network geometry ("same views, different choices" in the main text). **PCA.** CKA between the 144-PC and the full cortex code is 1.00, and every comparison gives the same CKA with either code. Only local neighbourhoods differ (mutual kNN between the codes is 0.36), so the reduction keeps the geometry the main text uses. **Brains.** Text describing the view shares more geometry with the predicted cortex than pixels do (0.51 versus 0.19). Hidden layers trained on human choices are closer to the cortex (0.49) than those trained on rat choices or legal labels (0.40) or from scratch (0.44). **Networks.** Human-choice networks from different seeds share most of their geometry (0.82–0.88). A human-choice network shares less with a rat network (0.58–0.71), with a legal-label network (0.50–0.70) or with a scratch network (0.47–0.57). Learning a new goal keeps most of it, with PPO (0.65–0.80) and with local rules (0.77–0.88). TD-readout leaves the hidden layer unchanged, a built-in check. With the expansion, the action is read from new cells, and hidden–action CKA falls from 0.58 to 0.23–0.31.




*generated plan text: constructed descriptions, a control. †after a backprop + Adam warm start, a matched 65,536 extra source frames of backprop or local rate updates. ‡MICrONS foundation-model predictions of recorded mouse visual-cortex neurons, not recordings. Random-core responses retain the trained readout, perspective and modulation. Policy models use one training seed (60); five alignment seeds measure optimizer variation, not biological or training replication. Ranges are not confidence intervals.

Figure 17. **Complete offline action/text readouts.** All primary families, both recorded-species subsets, zero-pair means and ranges only when all five algorithm seeds complete, fixed-first-seed 16 anchors and paired-only references. Incomplete groups have no mean. Generated plan text is a constructed reference; cortical features are predictions. Five alignment seeds are optimizer variation, not biological or policy-training replication.



*generated plan text: constructed descriptions, a control. †after a backprop + Adam warm start, a matched 65,536 extra source frames of backprop or local rate updates. ‡MICrONS foundation-model predictions of recorded mouse visual-cortex neurons, not recordings. Random-core responses retain the trained readout, perspective and modulation. Policy models use one training seed (60); five alignment seeds measure optimizer variation, not biological or training replication. Ranges are not confidence intervals. Rooms are the same 16 exposed E2 benchmark rooms, unseen by these source checkpoints; not an independent fresh test.

Figure 18. **Complete unpaired acting readouts.** Action and generated-text targets in the same 16 exposed rooms; one policy/evaluation seed. Own sampled and greedy heads are separate controls; fixed rotations are paired with their own unrotated first-seed maps. The uniform line is 4/30 successes (13.3%); the offline persistence reference is a different metric. Sensory-only maps lack input-matched heads.



One policy-training seed (60); alignment seeds measure optimizer variation, not training/biological replication. No confidence intervals.
The same 16 exposed rooms; 30 episodes/room. Native head is a comparator, not an upper bound. Sensory-only maps lack matched heads.
*Both continuations start from backprop-trained policies, then receive the same extra source frames; local updates are rate based.
Text is a fixed generated command catalog. Rat/human labels identify supervision sources, not online animal or neural inputs.

Figure 19. **Every calibrated control comparison.** Top: map minus its own greedy head. Bottom: trained-map minus matched untrained-map, with the same target, alignment method, anchor count and algorithm seed. All 16-anchor and paired-only comparisons are shown. Some calibrated maps improve over untrained maps; all evaluated trained-policy maps remain below their own heads. Means and ranges are descriptive, not confidence intervals.




Figure 20. Keep versus learn for every learning run (dots) and learner means (markers): PPO, local rules of the main text, search 2, consolidation with old replay, context gating (red) and the joint-training reference (diamonds).




Figure 21. Old goal in the unseen room after learning, per learner and prior (learners of the main-text four-claims figure).




Figure 22. Rosetta CKA. **a** Hidden layer versus image, text, predicted cortex (PCA and all units) and action; rows are priors and learners started from human choices. **b** Hidden layer versus the human-choice network (dots: jobs).