

Har kaam ki *poori tafseel*

20-din ke plan ka har missing aur adhoora feature — kaun si file, kya code, kis tarteeb se, aur kaise check karna hai ke ho gaya.

DIN 1 SE PEHLE

Ek faisla jo abhi karna hai

Project Expo SDK 54 par hai, magar `AGENTS.md` SDK 57 ke docs ki taraf ishara karta hai. SDK 57 React Native 0.86 aur React 19.2.3 ke saath aata hai; aapka project abhi RN 0.81.5 aur React 19.1.0 par hai — yani do version peeche.

Mera mashwara: abhi upgrade na karein. Do SDK versions ka jump beech sprint mein reanimated, gesture-handler aur camera ki breaking changes le kar aata hai — aasani se 3–4 din kha jaayega, aur wo din aapke paas hain nahi. V1 launch ke baad, alag branch par upgrade karein.

Agar client ki sharat SDK 57 hai, to ye kaam 20-din ke plan se *bahar* rakhein aur uske liye alag se waqt maangein.

Din 1–5: Woh kaam jinke baghair baqi sab nakli hai

DIN 1

Photos ka asli upload

Abhi `mediaUpload.ts` ki har function local URI hi wapas kar deti hai, aur wohi `file:// ...` Firestore mein save hota hai. Natija: har user doosron ki profile blank dekhta hai. Ye poora din sirf ek file par kharch hoga.

KAUN SI FILES

```
src/services/mediaUpload.ts
```

```
storage.rules – pehle se likhi hui
```

STEPS

1 Blaze plan on karo. Firebase Console → Settings → Usage and billing → Modify plan → Blaze. Foran budget alert lagao (\$5 kaafi hai). Blaze ka apna free quota hai (5 GB storage, 1 GB/din download) — test phase mein bill practically zero rahega.

2 Storage enable karo. Console → Build → Storage → Get started → Start in production mode. Bucket ka naam `.env` ke `EXP0_PUBLIC_FIREBASE_STORAGE_BUCKET` se match hona chahiye.

3 Rules deploy karo. `storage.rules` pehle se poori likhi hui hai — kuch badalna nahi, sirf bhejna hai:

```
npx firebase deploy --only storage
```

4 Ab asli upload likho. `mediaUpload.ts` ki chhe placeholder functions replace karo. React Native mein local file ko blob banane ka tareeqa `fetch(uri).blob()` hai:

```
// src/services/mediaUpload.ts
import { ref, uploadBytes, getDownloadURL, deleteObject } from
'firebase/storage';
import { storage } from './firebase';

// RN mein File/Blob polyfill nahi hai — fetch se blob banate hain.
async function toBlob(localUri: string): Promise<Blob> {
  const res = await fetch(localUri);
  return await res.blob();
}

async function upload(path: string, localUri: string): Promise<string> {
  const blob = await toBlob(localUri);
  const fileRef = ref(storage, path);
  await uploadBytes(fileRef, blob);
  // @ts-ignore — RN ka blob close() rakhta hai, memory free karne ke liye
  if (typeof (blob as any).close === 'function') (blob as any).close();
  return await getDownloadURL(fileRef);
}

async function uploadPhoto(userId: string, localUri: string) {
  return upload(`public/${userId}/photos/${Date.now()}.jpg`, localUri);
}
```

Baqi functions isi tarah — sirf path badalta hai.

- 5 **Paths storage.rules se match karao.** Rules do hi jagahein allow karti hain, is liye path bilkul yehi rakhna hai:

FUNCTION	PATH
uploadPhoto	public/{uid}/photos/{time}.jpg
uploadVoiceIntro	public/{uid}/voice/intro.m4a
uploadVideoIntro	public/{uid}/video/intro.mp4
uploadChatImage	public/{uid}/chat/{matchId}/{time}.jpg
uploadChatAudio	public/{uid}/chat/{matchId}/{time}.m4a
uploadCnicPhoto	verification/{uid}/cnic.jpg
uploadSelfiePhoto	verification/{uid}/selfie.jpg

- 6 **removeFiles aur verificationUrl bhi asli karo.** `removeFiles` mein `deleteObject(ref(storage, url))`, aur har delete ko `try/catch` mein rakho — pehle se ghayab file par error nahi aana chahiye.

- 7 **Purana ganda data saaf karo.** Console → Firestore → `profiles`. Jis bhi doc ke `photos` array mein `file://` ya `content://` ho, wo entry hata do — warna wo hamesha ke liye toota hua image rahega.

DHYAN RAKHEIN

`isLocalUri()` ko haath na lagayein — `authService.ts` uspar bharosa karta hai ke pehle se upload ho chuki photo dobara upload na ho (`authService.ts:404`).

Purane users ke photos khud se theek nahi honge. Test accounts hain to unhein delete kar dena sab se saaf raasta hai.

KAISE CHECK KAREIN

Phone A se signup kar ke photo lagao. Firebase Console → Storage mein file nazar aani chahiye, aur Firestore mein `photos[0]` ab `https://firebasestorage.googleapis.com/...` hona chahiye, `file://` nahi. Phir phone B se login kar ke A ki profile dekho — photo dikhni chahiye.

DIN 2

Naya database schema aur rules

Ye poore plan ka sab se ahem din hai. Abhi har cheez `users/{uid}/` ke neeche owner-only hai — isi wajah se chat, match aur Move to Rishta teenon nakli hain. Aaj naye *shared* collections banenge jinhein dono users parh aur likh sakein.

KAUN SI FILES`firestore.rules``src/services/firestorePaths.ts``src/services/ids.ts – naya`**STEPS**

- 1 **Naya layout samajh lein.** Chaar naye top-level collections aayenge. Purani `profiles` aur `users/{uid}/private` jaisi hain waisi hi rahengi:

```
likes/{fromUid}_{toUid}
  { fromUid, toUid, mode, createdAt }

matches/{uidA}_{uidB}          // uids hamesha sorted
  { members: [uidA, uidB], mode, createdAt,
    lastMessage, lastMessageAt,
    unreadBy: [uid],           // jisne abhi nahi parha
    movedToRishta: false,
    rishtaRequestBy: null,     // kis ne request bheji
    blockedBy: [] }

matches/{matchId}/messages/{autoId}
  { senderId, kind, text, audioUrl, imageUrl,
    durationSec, sentAt, reactions: {} }

reports/{autoId}
  { reporterId, targetId, reason, context, createdAt }
```

- 2 **Match ID hamesha ek jaisi banao.** Dono taraf se wohi ID nikalni chahiye, warna do alag match doc ban jaayenge. Naya chhota file banao:

```
// src/services/ids.ts
// Firebase uid mein underscore nahi hota, is liye '_' se
// jorna aur split karna dono mehfooz hain.
export function matchIdFor(a: string, b: string): string {
  return [a, b].sort().join('_');
}

export function likeIdFor(from: string, to: string): string {
  return `${from}_${to}`; // tarteeb ahem hai – sort mat karo
}
```

- 3 **Rules likho.** Yehi aapka backend logic hai. Poora block `firestore.rules` mein `profiles` wale block ke baad daalein:

```

// Kisi ko like karna - doc id se hi pata chalta hai kaun kis ko.
match /likes/{likeId} {
  allow create: if isSignedIn()
    && likeId = request.auth.uid + '_' + request.resource.data.toUid
    && request.resource.data.fromUid = request.auth.uid;

  // Aap apne bheje hue like dekh sakte ho, aur wo bhi jo aapko mile.
  allow get, list: if isSignedIn()
    && (request.auth.uid = resource.data.fromUid
      || request.auth.uid = resource.data.toUid);

  allow delete: if isSignedIn() && resource.data.fromUid = request.auth.uid;
  allow update: if false;
}

match /matches/{matchId} {
  function members() { return matchId.split('_'); }
  function isMember() { return isSignedIn() && request.auth.uid in members(); }
  function other() {
    return members()[0] = request.auth.uid ? members()[1] : members()[0];
  }

  allow read: if isMember();

  // Match sirf tab banta hai jab DONO ne ek doosre ko like kiya ho.
  // Ye nakli "It's a match" ko namumkin bana deta hai.
  allow create: if isMember()
    && exists(/databases/${database}/documents/likes/${request.auth.uid + '_' +
other()})
    && exists(/databases/${database}/documents/likes/${other() + '_' +
request.auth.uid});

  allow update: if isMember();
  allow delete: if false; // unmatch soft hoga, field se

  match /messages/{messageId} {
    function inMatch() {
      return isSignedIn() && request.auth.uid in matchId.split('_');
    }
    allow read: if inMatch();
    allow create: if inMatch()
      && request.resource.data.senderId = request.auth.uid;
    allow update: if inMatch(); // reactions ke liye
    allow delete: if false;
  }
}

// Report likh sakte ho, parh koi nahi sakta. Aap Console se dekhein ge.
match /reports/{reportId} {
  allow create: if isSignedIn()
    && request.resource.data.reporterId = request.auth.uid;
  allow read, update, delete: if false;
}

```

4 **Rules Playground mein test karo** — deploy se pehle. Console → Firestore → Rules → Playground. Yeh chaar cases zaroor check karein:

- User A, `likes/A_B` create → **allow**
- User A, `likes/B_C` create → **deny** (dusre ki taraf se like)
- User C, `matches/A_B` read → **deny** (member nahi)
- User A, `matches/A_B` create jab sirf A ne like kiya ho → **deny**

5 **Deploy karo:** `npx firebase deploy --only firestore:rules`

6 **firestorePaths.ts mein naye helpers add karo** — `likeDoc()`, `likesCollection()`, `matchDoc()`, `matchesCollection()`, `messagesCollection(matchId)`, `reportsCollection()`. Purane `users/{uid}/matches` aur `/messages` wale helpers filhaal rehne dein — kal hatayenge.

7 **Purana dev data wipe karo.** Console se har user ke `matches` aur `messages` subcollections delete kar dein. Ye test data hai, iska koi nuqsan nahi.

YAHAN GALTİ AASAN HAI

`likeIdFor` mein tarteeb *kabhi sort na karein* — `A_B` ka matlab "A ne B ko like kiya" hai, jo `B_A` se bilkul alag baat hai. Lekin `matchIdFor` mein sort *lazmi* hai.

Rules ke andar `exists()` aur `get()` ki hadd ek request mein 10 hai. Upar wale rules do use karte hain — gunjaish kaafi hai, magar aur add karte waqt yaad rakhein.

KAISE CHECK KAREIN

Rules Playground ke chaaron case theek jawab dein. Phir `USER_SUBCOLLECTIONS` mein se `matches` aur `messages` hata kar dekhein ke `deleteAccount` abhi bhi compile hota hai.

Chat ka service layer

Kal ka schema ab code mein lagana hai. Sab se bara concept badal raha hai:

`fromMe` ab database mein save nahi hoga — kyunki ek hi message doc ko dono log parhenge, aur dono ke liye jawab alag hai.

KAUN SI FILES

`src/services/matchesService.ts``src/store/MatchesContext.tsx``src/types/content.ts``src/components/matches/MessageBubble.tsx`

STEPS

- 1 **Types badlo.** `ChatMessage` mein `fromMe: boolean` ki jagah `senderId: string` aayega. `Match` mein `members: string[]` aur `unreadBy: string[]`.

```
// src/types/content.ts
export interface ChatMessage {
  id: string;
  senderId: string;          // fromMe ki jagah
  text: string;
  sentAt: string;
  kind?: ChatMessageKind;
  audioUri?: string;
  durationSec?: number;
  imageUri?: string;
  reactions?: Record<string, string>; // uid → emoji, Din 10
}
```

`matchId` ab message ke andar nahi chahiye — wo path mein hai.

- 2 **UI mein `fromMe` ab hisaab se nikalo.** Jahan bhi `message.fromMe` tha, wahan ab `message.senderId === user.id`. Ye `MessageBubble` aur `ChatScreen` dono jagah hai. TypeScript aapko har jagah khud le jaayega — `npx tsc --noEmit` chala kar list nikal lein.
- 3 **`matchesService.ts` dobara likho.** Har function ka pehla parameter ab `profileId` nahi, `matchId` hoga (ya dono, jahan zaroorat ho):

```

async function fetchMatches(userId: string): Promise<Match[]> {
  const snap = await getDocs(query(
    collection(db, 'matches'),
    where('members', 'array-contains', userId),
    orderBy('lastMessageAt', 'desc')
  ));
  return snap.docs.map(mapMatchSnapshot);
}

async function sendText(matchId: string, senderId: string, text: string) {
  const data = { senderId, kind: 'text', text, sentAt: new Date().toISOString() };
  await addDoc(collection(db, 'matches', matchId, 'messages'), data);

  // Match doc bhi update — list screen isi se chalti hai.
  const other = matchId.split('_').find((id) => id !== senderId!);
  await updateDoc(doc(db, 'matches', matchId), {
    lastMessage: text,
    lastMessageAt: data.sentAt,
    unreadBy: arrayUnion(other),
  });
}

```

- 4 **Unread ko array bana do.** Purana `unread: boolean` ab kaam nahi karega, kyunki ek doc do logon ka hai. `arrayUnion(other)` se mark karo, aur chat kholte hi `arrayRemove(myId)` .
- 5 **MatchesContext.tsx update karo** — naye service signatures ke mutabiq. `getOrCreateMatchForProfile` filhaal chhor dein; kal (Din 5) wo likes se chalega.
- 6 **Voice aur image messages bhi shift karo** — `insertVoiceMessage` aur `insertImageMessage` ab `matchId` lenge. Din 1 ka asli upload inhein khud-ba-khud theek kar dega.
- 7 **`npx tsc --noEmit` chalao** jab tak sab errors khatam na ho jaayein. Aaj UI shayad theek se na chale — koi baat nahi, kal chalegi.

KAISE CHECK KAREIN

Console se manually ek `matches/` doc banao jis ke `members` mein aapke do test uids hon. App khol kar dekho — Matches list mein wo match nazar aana chahiye. Message bhejo, aur Console mein `matches/{id}/messages` ke andar naya doc banna chahiye.

Abhi `getDocs` use hota hai — yani data sirf ek dafa aata hai. Aaj usay `onSnapshot` se badalna hai, taake naya message screen par khud aa jaaye, refresh ke baghair.

KAUN SI FILES

`src/store/MatchesContext.tsx``src/screens/matches/ChatScreen.tsx``src/services/cache.ts`

STEPS

- 1 **Matches list ka listener.** `MatchesContext` ke `useEffect` mein:

```
useEffect(() => {
  if (!user) return;
  const q = query(
    collection(db, 'matches'),
    where('members', 'array-contains', user.id),
    orderBy('lastMessageAt', 'desc')
  );
  const stop = onSnapshot(q, (snap) => {
    setMatches(snap.docs.map(mapMatchSnapshot));
  });
  return stop; // screen band hote hi listener band — LAZMI
}, [user?.id]);
```

- 2 **Messages ka listener sirf khuli hui chat par lagao** — poori history par nahi. `ChatScreen` ke andar, us `matchId` ke liye. Har chat ka listener hamesha chalte rehna reads ka kharcha bekaar barha dega.
- 3 **Har listener ka cleanup wapas karo.** `useEffect` se `stop` function return karna bhoolna sab se aam galti hai — is se memory leak hoti hai aur bill barhta hai.
- 4 **Chat khulte hi read mark karo:** `updateDoc(matchDoc, { unreadBy: arrayRemove(user.id) })`.
- 5 **`cache.ts` theek karo.** Us mein comment likha hai ke messages jaan bujh kar cache nahi hote — wo ab bhi durust hai, `onSnapshot` ke saath aur bhi zyada. Sirf matches list ka cache shape naye `Match` type se match karayein.
- 6 **Do device se test karo.** Phone A se message bhejo — phone B ki khuli hui chat par bina kuch kiye aana chahiye.

KHARCHA KA DHYAN

Har `onSnapshot` update ek read count karta hai. Sirf wahi listener chalayein jo us waqt screen par chahiye. Din 18 par Console mein reads ka number zaroor dekhein.

KAISE CHECK KAREIN

Do phone saath rakh kar chat karein — message ek second ke andar doosri taraf aa jaana chahiye. Phir chat se bahar aa kar Matches list dekhein: unread badge apne aap update hona chahiye.

DIN 5

Asli likes, asli match, asli Move to Rishta

Aaj app se saara jhoot nikal jaayega: `HomeScreen` ka nakli celebration, aur `MatchesContext.tsx:201` ka `setTimeout` jo khud hi "accepted" likh deta hai.

KAUN SI FILES

`src/services/likesService.ts` — naya

`src/screens/home/HomeScreen.tsx`
`src/store/MatchesContext.tsx`
`src/screens/matches/ChatScreen.tsx`

STEPS

1 **Naya** `likesService.ts` **banao** teen kaam ke saath:

```
export async function sendLike(fromUid, toUid, mode) {
  await setDoc(doc(db, 'likes', likeIdFor(fromUid, toUid)), {
    fromUid, toUid, mode, createdAt: new Date().toISOString(),
  });
}

// "Kya unhon ne pehle mujhe like kiya tha?"
export async function theyLikedMe(myUid, theirUid): Promise<boolean> {
  const snap = await getDoc(doc(db, 'likes', likeIdFor(theirUid, myUid)));
  return snap.exists();
}

export async function whoLikedMe(myUid) {
  const snap = await getDocs(query(
    collection(db, 'likes'), where('toUid', '=', myUid)
  ));
  return snap.docs.map((d) => d.data());
}
```

2 `HomeScreen.tsx` ka `onLike` **badlo** (line 161 se shuru). Nayi tarteeb:

- Daily like limit check karo — ye purana code theek hai, rehne dein
- `sendLike()` chalao
- `theyLikedMe()` se poochho
- Agar **haan** → `matches/` mein doc banao aur celebration dikhao
- Agar **nahi** → sirf "interest sent" ka toast — koi celebration nahi

3 **Nakli celebration hatao.** Abhi `HomeScreen.tsx:185` par har dating like ke baad seedha `setCelebration()` chalta hai. Usay upar wale mutual check ke andar le jaayein.

4 **Move to Rishta ka** `setTimeout` **hatao.** `MatchesContext.tsx:201` par. Uski jagah:

- Request bhejne wala: `updateDoc(matchDoc, { rishtaRequestBy: user.id })`
- Doosra user apni chat mein "Accept / Decline" ke buttons dekhta hai
- Accept par: `{ movedToRishta: true, rishtaRequestBy: null }`

- Decline par: `{ rishtaRequestBy: null }`

5 `ChatScreen.tsx` mein **accept/decline ka UI banao**. Shart: `match.rishtaRequestBy` maujood ho aur wo `user.id` ke barabar *na* ho. Jo bhej chuka hai usay "pending" hi dikhta rahega — ye state pehle se maujood hai.

6 **Favorites ko likes se alag rakhein**. Abhi `onLike` mein `toggleFavorite` bhi chalta hai. Favorites aapki apni niji list hai; `likes/` woh cheez hai jo doosre ko nazar aati hai. Dono chalne dein, magar mila na dein.

KAISE CHECK KAREIN

Phone A se B ko like karo — sirf toast aana chahiye, celebration

NAHI

. Phir phone B se A ko like karo — ab

DONO

phones par match banna chahiye. Chat khol kar Move to Rishta bhejo — doosre phone par accept/decline ke buttons aane chahiyein, aur accept karne par dono taraf badge lag jaana chahiye.

Din 6–10: Safety, filters, paywall ka asli maal

DIN 6

Report ko asli karo + password reset

Do chhote magar launch-blocking kaam. Report abhi reason discard kar ke sirf toast dikhata hai. Aur password bhoolne wala user hamesha ke liye locked out hai — koi reset flow hai hi nahi.

KAUN SI FILES

src/services/reportService.ts — naya

src/screens/home/HomeScreen.tsx

src/screens/matches/ChatScreen.tsx

src/services/authService.ts

src/screens/auth/LoginScreen.tsx

STEPS

- 1 **reportService.ts** **banao** — ek hi function kaafi hai:

```
export async function submitReport(input: {
  reporterId: string; targetId: string;
  reason: string; context: 'profile' | 'chat';
}) {
  await addDoc(collection(db, 'reports'), {
    ...input, createdAt: new Date().toISOString(), status: 'open',
  });
}
```

- 2 **Dono handlers wire karo.** HomeScreen.tsx:225 aur ChatScreen.tsx:124 par `_reason` ko `reason` banao aur `submitReport()` chhalao. Toast tab hi dikhayein jab write kaamyab ho.

- 3 **Report ke saath block ka option do.** Confirm dialog mein poochein "Isay block bhi kar dein?" — zyada tar log yehi chahte hain, aur ye safety bar mazboot karta hai.

- 4 **Password reset add karo.** authService.ts mein:

```
import { sendPasswordResetEmail } from 'firebase/auth';

export async function requestPasswordReset(email: string) {
  await sendPasswordResetEmail(auth, email.trim().toLowerCase());
}
```

- 5 **Login screen par "Password bhool gaye?" link lagao.** Email poochein, function chalayein, aur hamesha ek hi paighaam dikhayein — "agar ye email registered hai to link bhej diya gaya hai". Ye batana ke email maujood hai ya nahi, privacy ka masla ban jaata hai.

- 6 **Reset email ka template dekh lein.** Firebase Console → Authentication → Templates. App ka naam theek karein, warna email mein project ID nazar aayega.

7

Reports parhne ka tareeqa likh kar rakhein — Console → Firestore → `reports`, `status = 'open'` par filter. Ye V1 ke liye kaafi hai, admin panel ki zaroorat nahi.

KAISE CHECK KAREIN

Ek profile report karein — Console ke `reports` mein reason ke saath doc aana chahiye. Phir dobara koi doosra user us collection ko app se parhne ki koshish kare — `permission denied` aana chahiye. Aur ek asli email par reset link mangwa kar password badal kar dekh lein.

Filters — dono modes, aur indexes

Roadmap ki do features ek hi kaam hain. Achhi khabar: `FilterSheet.tsx` poora bana hua hai, magar poore project mein kahin import nahi hota. Aaj usay zinda karna hai.

KAUN SI FILES

`src/components/common/FilterSheet.tsx`

`src/store/DiscoveryContext.tsx`

`src/services/discoveryService.ts`

`src/screens/home/HomeScreen.tsx`

`firebase.indexes.json`

STEPS — DIN 7 (DATING)

1 Filter ki shakal tay karo:

```
export interface DiscoveryFilters {
  minAge: number; maxAge: number; // default 18-60
  city: string | null;
  intent: Intent | null; // dating
  sect: string | null; // rishta
  readiness: RishtaReadiness | null; // rishta
}
```

2 Age ka filter `dob` par lagao. Firestore mein umar store nahi hai, magar `dob` ek `'YYYY-MM-DD'` string hai — aur strings par range query chalti hai. Umar ko dob ki hadd mein badlein:

```
// 25 saal ka banda = aaj se 25 saal pehle paida hua
const maxDob = isoDateYearsAgo(minAge); // kam umar = naya dob
const minDob = isoDateYearsAgo(maxAge + 1);

query(profilesCollection(),
  where('gender', '=', target),
  where('city', '=', filters.city),
  where('dob', '≥', minDob),
  where('dob', '≤', maxDob),
  orderBy('dob', 'desc'));
```

3 Filter state `DiscoveryContext` mein rakho aur AsyncStorage mein save karo, taake app dobara kholne par yaad rahe. `storage.ts` pehle se maujood hai.

4 `FilterSheet` ko `HomeScreen` mein lagao. Header mein filter icon, aur jab koi filter laga ho to us par ek chhota dot dikhao.

5 Khali natije ka empty state banao — "Is filter par koi nahi mila" plus "Filters reset karein" ka button. Filters ke saath ye halat aam hogi.

STEPS — DIN 8 (RISHTA + INDEXES)

1 **Rishta ke filters wahi tareeqa** — sect aur readiness par equality, city aur age wahi jaise dating mein.

2 **Indexes likho.** `firestore.indexes.json` abhi bilkul khali hai. Har filter combination ke liye ek index chahiye:

```
{
  "indexes": [
    {
      "collectionGroup": "profiles",
      "queryScope": "COLLECTION",
      "fields": [
        { "fieldPath": "gender",      "order": "ASCENDING" },
        { "fieldPath": "city",        "order": "ASCENDING" },
        { "fieldPath": "dob",         "order": "DESCENDING" }
      ]
    },
    {
      "collectionGroup": "likes",
      "queryScope": "COLLECTION",
      "fields": [
        { "fieldPath": "toUid",      "order": "ASCENDING" },
        { "fieldPath": "createdAt", "order": "DESCENDING" }
      ]
    }
  ],
  "fieldOverrides": []
}
```

Range wala field (dob) hamesha aakhir mein aata hai.

3 **Deploy:** `npx firebase deploy --only firestore:indexes`. Index banne mein kuch minute lagte hain — Console mein status "Building" se "Enabled" hone ka intezaar karein.

4 **Har combination test karo.** Jab koi index kam hoga, Firestore console mein error dega jis mein *index banane ka seedha link* hota hai — wo link kholein, index banayein, aur phir usay `firestore.indexes.json` mein bhi likh dein taake wo repo ka hissa rahe.

FIRESTORE KI EK HADD

Ek query mein *sirf ek* field par range ($\geq$ / $\leq$) chal sakta hai. Age ne wo jagah le li hai, is liye height ya kisi aur cheez par range filter server par nahi lag sakta — wo natije aane ke baad client par filter karna parega. V1 ke liye ye theek hai.

KAISE CHECK KAREIN

Filter mein age 25–30 aur ek city choose karein — deck mein sirf wahi profiles aani chahiyein. App band kar ke dobara kholein, filter yaad rehna chahiye. Console log mein koi "requires an index" error nahi hona chahiye.

“Who liked you” asli karo

Abhi `ExplorePlusScreen.tsx:54` deck se 4 random profiles utha kar "aapko kis ne like kiya" ke naam se dikha deta hai. Din 5 ki `likes/` collection ne asli data ka intezaam kar diya hai — ab usay lagana hai.

KAUN SI FILES

`src/screens/monetization/ExplorePlusScreen.tsx``src/services/likesService.ts``src/store/LikeLimitContext.tsx`

STEPS

- 1 Random admirers hatao.** `ExplorePlusScreen.tsx:54` ka poora `useMemo` nikal dein aur `whoLikedMe(user.id)` se replace karein.
- 2 Profiles la kar jorein.** `likes` se sirf uids milte hain; har uid ka card `profiles/{uid}` se lena hoga. Ek saath 10 se zyada na laayein — paging kar dein.
- 3 Block ka filter lagana na bhoolein** — jo log block kiye hue hain wo yahan nahi aane chahiyein. Purani code mein ye check maujood tha, usay barqarar rakhein.
- 4 Free banam paid ka farq banao:**
 - **Free** — sirf ginti dikhao ("3 logon ne aapko like kiya"), photos blur ke peeche
 - **Paid** — poori list, aur seedha profile kholne ka raastaBlur ke liye `expo-blur` pehle se project mein hai aur `ProfileDetailScreen` mein use bhi ho raha hai.
- 5 Unlimited likes ka gating check karo.** `LikeLimitContext.tsx:36` par `isUnlimited` theek se `isExplorePlus` parh raha hai — ye hissa pehle se durust hai, bas confirm kar lein.
- 6 Poore app mein `isExplorePlus` ke istemal ki list banao** — kal (Din 12) ye value `RevenueCat` se aayegi, is liye pata hona chahiye ke kahan kahan asar parega.

KAISE CHECK KAREIN

Phone B se A ko like karein, magar A se B ko nahi. Phone A par Explore+ kholein — free account mein "1 like" ki ginti blur ke saath, aur `isExplorePlus` manually true kar ke dekhein to B ki asli profile.

Emoji reactions + saara mock data hatao

Roadmap V1 mein "text chat with basic emoji reactions" likha hai — reactions abhi bilkul nahi hain. Aur app mein jo bacha hua nakli data hai, aaj wo bhi saaf hoga.

KAUN SI FILES

src/components/matches/MessageBubble.tsx

src/services/matchesService.ts

src/store/DiscoveryContext.tsx

src/screens/explore/ExploreScreen.tsx

STEPS

1 Reactions ka shape: `reactions: { [uid]: emoji }` — har banda ek reaction laga sakta hai, dobara lagane par purani badal jaati hai.

2 Message par long-press se chhoti si emoji bar kholo — paanch kaafi hain (❤️😂😮😬👍).

3 Save karo:

```
await updateDoc(doc(db, 'matches', matchId, 'messages', messageId), {
  [`reactions.${user.id}`]: emoji,
});
```

Din 2 ki rules messages par update allow karti hain — isi liye.

4 Bubble par dikhao — neechे kone mein chhota sa emoji. Din 4 ka `onSnapshot` doosre user ko khud dikha dega.

5 Demo deck ka fallback hatao. `DiscoveryContext.tsx:73` par collection khali ho to mock profiles dikhte hain. Ab jab asli users honge, ye asli khali halat ko chhupa dega. Uski jagah proper empty state: "Aap ke ilaqe mein abhi koi nahi — thori der baad dekhein".

6 Explore tab ka faisla karo. Wo poora `mockEvents` par chal raha hai aur roadmap ki V1 list mein hai hi nahi. Do raaste: (a) tab ko V1 se hata dein, ya (b) ek chhota `events/` collection banayein jise aap Console se bharein. **Mera mashwara: hata dein** — nakli events ke saath launch karna app ki sakhti ko nuqsan pohanchata hai. Tab ke bagair navigation teen tabs par aa jaayegi.

7 Poore project mein `mockDiscover`, `mockRishta`, `mockEvents` **ke imports dhoondein** aur ek bhi baaqi na chhorein.

KAISE CHECK KAREIN

Message par long-press kar ke emoji lagayein — doosre phone par turant dikhna chahiye. Phir naya account banayein jis ki koi match na ho: har khali screen par asli empty state aana chahiye, koi demo profile nahi.

Din 11–15: Payment, verification, launch ki tayyari

DIN 11-12

Explore+ ki asli payment

Abhi `ExplorePlusScreen.tsx:71` par Upgrade dabate hi `isExplorePlus: true` set ho jaata hai — har koi muft mein pro. Roadmap ka poora maqsad hi ye jaanna tha ke "log paisay dete bhi hain ya nahi", jo is haalat mein maloom nahi ho sakta.

KAUN SI FILES

`src/screens/monetization/ExplorePlusScreen.tsx`

`src/services/purchases.ts` — **naya**

`src/store/AuthContext.tsx`

`app.json`

Pehle ye samajh lein. Google Play aur Apple digital saman ke liye apna in-app purchase lazmi karte hain — JazzCash ya Easypaisa app ke andar lagayenge to app reject ho jaayegi. Aur IAP ki receipt verify karna server ka kaam hai, warna banda jhooti receipt bana kar muft pro ban sakta hai. RevenueCat yehi apne server par karta hai. Expo SDK mein IAP ka apna koi package nahi hai, is liye `react-native-purchases` hi maamool ka raasta hai.

STEPS — DIN 11 (SETUP)

- 1 Play Console par products banao.** Monetize → Subscriptions. Roadmap ke mutabiq Explore+ PKR 999/mah. Product ID note kar lein.
- 2 App Store Connect par bhi wahi karo.** Auto-renewable subscription, ek subscription group mein.
- 3 RevenueCat account banao,** project banayein, aur dono stores ki keys jorein (Play ke liye service account JSON, Apple ke liye shared secret).
- 4 Ek entitlement banao** — naam `explore_plus` — aur dono products usay assign karein. App sirf isi entitlement ka naam janegi.
- 5 Library install karo.** `react-native-purchases` plus uska Expo config plugin. **Install se pehle apne SDK 54 ke liye current docs zaroor dekh lein** — is library ke setup steps versions ke saath badalte rehte hain.
- 6 Development build banao:** `eas build --profile development --platform android`. **IAP Expo Go mein bilkul nahi chalti** — native code chahiye. Aapka `eas.json` pehle se tayyar hai.

STEPS — DIN 12 (PAYWALL)

- 1 `purchases.ts` banao** teen functions ke saath: `init(userId)`, `buy(planId)`, `restore()`, aur `isPro()`.

- 2 **Login ke waqt init karo** — RevenueCat ko Firebase ka `uid` hi apna user id dein, taake dono taraf ek hi banda pehchana jaaye.
- 3 **Muft toggle hatao.** `ExplorePlusScreen.tsx:71` ka `updateUser({ isExplorePlus: true })` nikal dein. Ab `isExplorePlus` RevenueCat ke entitlement se aayega, aap ki marzi se nahi.
- 4 **Firestore mein bhi likhein, magar sirf aaine ke taur par.** Asli sach hamesha RevenueCat ka jawab hai; Firestore wali value sirf isliye hai ke app khulte hi kuch dikha sake.
- 5 **"Restore Purchases" ka button lagao** — Apple ke bagair iske app reject kar deta hai.
- 6 **Sandbox se poora flow test karo** — kharidna, cancel karna, phir restore. Play ke liye license testers, Apple ke liye sandbox account.

WAQT KA MASLA

Store par products approve hone mein kuch din lag sakte hain.

DIN 11 KA KAAM AGAR MUMKIN HO TO DIN 1 HI KO SHURU KAR DEIN

— ye plan ka woh hissa hai jo aapke haath mein nahi.

KAISE CHECK KAREIN

Sandbox account se Explore+ kharidein — unlimited likes aur poori "who liked you" list khul jaani chahiye. App band kar ke dobara kholein: pro status barqarar rahe. Phir naye device par usi account se login kar ke Restore dabayein — wapas mil jaana chahiye.

Verification पूरी करो

CNIC ka kaam pehle se mazboot hai — format check, aakhri digit se gender ka milaan, aur photo ka on-device analysis. Magar `selfieVerified` sirf `Boolean(selfieUri)` hai (`SelfieVerificationScreen.tsx:95`), yani photo li = verified. Aaj is badge ko asli banana hai.

KAUN SI FILES

`src/screens/auth/SelfieVerificationScreen.tsx`

`src/screens/profile/CnicVerificationScreen.tsx`

`src/services/authService.ts`

`firestore.rules`

STEPS

- 1 **Ab photos waqai jaati hain.** Din 1 ke baad selfie aur CNIC `verification/{uid}/` par upload ho rahe hain — aur wo path owner-only hai, is liye koi doosra user unhein dekh nahi sakta. Confirm kar lein ke aisa hi ho raha hai.

- 2 **`selfieVerified: boolean` ki jagah teen halat rakho:**

```
verificationStatus: 'pending' | 'approved' | 'rejected'
```

- 3 **Rules mein isay locked karo** — user apna status khud nahi badal sakta, warna badge bekaar hai:

```
match /profiles/{uid} {
  allow update: if isOwner(uid)
    && request.resource.data.verificationStatus
      = resource.data.verificationStatus;
}
```

Aap Console se badenge — Console rules ke bahar chalta hai.

- 4 **Badge sirf `approved` par dikhao** — deck cards, profile detail, chat header, har jagah.
- 5 **Pending ka pata chalta rahe.** Apni profile par ek chhoti si line: "Verification zer-e-ghhaur — 24 ghante mein" — taake user ko lagta rahe ke kuch ho raha hai.
- 6 **Apna review ka tareeqa likh kar rakhein:** Console → Firestore → `profiles`, `verificationStatus = 'pending'` par filter. Storage se selfie aur CNIC dekhein, phir field haath se badal dein. V1 par ye din mein paanch minute ka kaam hoga.

EK PRIVACY KI BAAT

CNIC ka number aur photo Pakistan mein hassas data hai. Wo `users/{uid}/private/verification` aur `verification/{uid}/` mein hi rahe — `profiles/` mein kabhi na aaye, kyunki wo har logged-in user parh sakta hai. Din 14 ki privacy policy mein saaf likhein ke ye kyun jama kiya jaata hai aur kab tak rakha jaata hai.

KAISE CHECK KAREIN

Naya account banayein — badge nahi hona chahiye. App se `verificationStatus` badalne ki koshish karein — `permission denied` aana chahiye. Console se `approved` karein — badge doosre phone par nazar aana chahiye.

Legal, store listing, aur edge cases

Coding ka kaam khatam. Ab wo cheezein jinke baghair store app qubool nahi karta, aur wo halat jo asli users par zaroor aayengi.

DIN 14 — LEGAL AUR STORE

- 1 **Privacy Policy aur Terms likhein aur kisi public URL par host karein.** Bina iske dono stores dating app reject kar dete hain. Us mein ye batana lazmi hai: kaun sa data jama hota hai (photos, CNIC, location, chat), kyun, kitne arse tak, aur user usay kaise delete kara sakta hai. Aap ka `deleteAccount` pehle se maujood hai — is ka zikr karein, ye aap ke haq mein jaata hai.
- 2 **Legal screen mein asli matn dalein** — ya kam az kam hosted URL par le jaane wala link.
- 3 **Play Store ka Data Safety form bharein.** App ke andar se jo bhi jama hota hai, sab batana hai. Ghalat bharna baad mein app suspend kara sakta hai.
- 4 **Content rating ka questionnaire** — dating apps ke liye alag qawaid hain, sach sach bharein.
- 5 **Listing tayyar karein** — description (Urdu wala pehlu zaroor batayein, wahi aapki asli pehchan hai), screenshots, feature graphic.

DIN 15 — EDGE CASES

- 1 **Har khali halat check karein** — koi match nahi, koi message nahi, deck khatam, filter par kuch nahi mila, koi notification nahi.
- 2 **Internet band kar ke har screen kholein** — app ko crash nahi karna chahiye. `cache.ts` ko apna kaam dikhana chahiye.
- 3 **Firestore ki `permission-denied` error user ko theek se dikhayein** — kachi error string nahi.
- 4 **`deleteAccount` dobara test karein** — ab naye shared collections bhi hain. Faisla karein ke unmatched hone par doosre banday ki chat ka kya hoga (mera mashwara: match par `deletedBy` field, taake doosre ki history na toote).
- 5 **Block ka poora asar check karein** — block kiya hua banda deck, likes, who-liked-you aur matches, har jagah se ghayab hona chahiye.
- 6 **Ek chhote phone par layout dekhein** — 5-inch device par, aur Urdu RTL ke saath.

KAISE CHECK KAREIN

Privacy policy ka URL browser mein khulta ho. Aeroplane mode on kar ke poora app ghoomein — kahin crash nahi. Ek account delete kar ke dekhein ke doosre user ki chat list mein wo match theek se ghayab ya "deleted user" ban jaata hai.

Din 16–20: Test aur launch

Ye din code likhne ke nahi, code todne ke hain. Tafseel se zyada tarteeb ahem hai — poora plan pehli report mein maujood hai. Yahan sirf wo cheezein hain jo aksar bhool jaati hain.

DIN	KAAM	JO AKSAR BHOOL JAATA HAI
16	Do device se poora end-to-end test	Teenon zabanein, khaas kar Urdu ka RTL layout. Aur light + dark dono themes mein har screen
17	Bugs fix — pehla round	Chhote phone (5-inch) par layout — aksar sab kuch bare phone par hi test hota hai
18	Preview APK 8–10 doston ko	Firebase Console mein reads/writes ka number dekhna — agar zyada ho to Din 4 ke listeners par shak karein
19	Feedback fixes + production build	Rules dobara parhna — koi test wala loophole na reh jaaye. Aur version numbers
20	Store par submit	Analytics lagana. Bina iske aapko pata hi nahi chalega ke V1 ne apna sawal ka jawab diya ya nahi

Din 20 par ye chaar numbers naapne ka intezaam zaroor kar lein — poori V1 inhi ke liye banayi ja rahi hai: kitne logon ne signup poora kiya, kitne match bane, kitni dafa ‘Move to Rishta’ dabaya gaya, aur kitne logon ne paisay diye. Firebase Analytics mein chaar custom events kaafi hain.

Play Console ka 12-testers wala qanoon dobara yaad dila doon. Naye personal accounts ke liye Google 12 testers ke saath 14 din closed testing maangta hai. Ye clock Din 20 se nahi, jis din aap testers add karte hain us din se chalta hai — is liye **Din 1 hi ko Play Console account aur testers ki list tayyar kar lein.**

Manual `dev-faizan` branch ke code par likha gaya, 26 August 2026. Har file aur line number khud parh kar verify kiya gaya hai. Code ke tukre asal shakal dikhane ke liye hain — likhte waqt apne SDK version ke docs saath rakhein. Rang app ki apni `src/theme/palettes.ts` se liye gaye hain.