




ASSEMBLY CHECK SHEET OIL COOLER KOMATSU ENGINE 12V140-1	WO NUMBER		DOCUMENT NO	RC/QR04/EG/06/01
	ENGINE MODEL	SAA12V140E-1	PUBLICATION DATE	27/07/2010
	ENGINE S/N		REVISION NO	00
	MACHINE MODEL		PAGE	1 of 1

PROCESS	START DATE / TIME		ASSEMBLY BY	
	FINISH DATE / TIME			

NO	PARTS	CHECK POINT	CONDITION TO BE CHECKED	SPEC.	SIGN			REMARKS (SKETCH, PHOTOS, COMMENTS)
					MEC	QA	SPV	
1	Oil Cooler Element	Leakage	- Inspect for cracks and leakage by oil cooler flusher. Test and check leakage on core element. No Leakage	√ = CHECK No Leakage				  
		Mounting surface	- Inspect for corrosion, scratches and wear Depth of corrosion, scratch and wear No corrosion No scratch No wear	√ = CHECK Depth ≤ 0.2mm				
		Bolt Hole	- Inspect tread portion appear corrosion, scratch and wear Depth of corrosion, scratch and wear No corrosion No scratch No wear	√ = CHECK Depth ≤ 0.4mm				
2	Oil Cooler Housing	Mounting surface	- Inspect for corrosion, scratches and wear Depth of corrosion, scratch and wear No corrosion No scratch No wear	√ = CHECK Depth ≤ 0.2mm				 
		Bolt Hole	- Inspect tread portion appear corrosion, scratch and wear Depth of corrosion, scratch and wear No corrosion No scratch No wear	√ = CHECK Depth ≤ 0.4mm				
3	Assembly element Oil Cooler		- Fit O ring or gasket on housing - Install washer and nut then tighten. - Tighten Torque : Actual : Kgm	Apply LG-6 M10 = 2.8~ 3.8 Kgm M12 = 5.6~ 6.6 Kgm (Komatsu assembly manual)				

COMMENT :

ASSEMBLY BY	INSPECTION & APPROVED BY
MECHANIC (MECH)	QUALITY ASSURANCE (QA)
	GL/SPV PRODUCTION

