


WATER LEAK TEST CHECK SHEET OIL COOLER ASSY KOMATSU ENGINE 6D140 SERIES	WO NUMBER		DOCUMENT NO	
	ENGINE MODEL	6D140 SERIES	PUBLISHED DATE	
	ENGINE S/N		REVISION NO	01
	MACHINE MODEL		PAGE	

PROCESS	START		TEST BY	
	FINISH			

NO	PARTS	CHECK POINT	CONDITION TO BE CHECKED	SPEC.	SIGN			REMARKS (SKETCH, PHOTOS, COMMENTS)
					MEC	QA	SPV	
1	Core Element		- Check Element normal condition. (broken from bend,rust etc) - Install hook/hanger (a).	Visual check				
2	Plug,adapter and Air inlet connector		- Install plug on housing (1). - Install adapter and use O ring (2) - Install inlet air connector and use sealant or rubber for this connector (3)					  
3	Water leak tester and indicator		- Prepare water leak tester tool (b) - Setting water temperature at standar range '(c). Actual : °C - Setting air pressure on Regulator valve (d) Actual : Kg/cm	Water leak tester tool STD range tmpratur 75° ~ 90°C (Shop manual) 3 ~ 4 kg/cm (Reman manual)				  
4	Water leak test oil cooler		Install coupler and test oil cooler assy Time for test Actual : Minutes	5 Minutes (Reman manual)				

Comment :

ASSEMBLY BY	INSPECTION & APPROVED BY
MECHANIC (MEC)	QUALITY ASSURANCE (QA)
	GL/SPV PRODUCTION