



PT SAPTAINDRA SEJATI

**FINAL DRIVE
RECEIVING INSPECTION
CHECKSHEET**

MACHINE MODEL

PC1250SP-8

RO NO :

POWERTRAIN SECTION

RECEIVING INSPECTION SHEET FINAL DRIVE	MACHINE MODEL	PC1250-8	REPORT NO.		DOCUMENT NO.	QR01-PT- 030
	COMP. MODEL		COMP. S/N		PUBL. DATE	14/05/2008
	RECEIVING DATE		FINAL INSPECT		REVISION NO.	00
	DELIVERY DATE		WO NO.		PAGE	1 of 1

BELOW ARE THE ITEMS RELATED TO DELIVERY INSPECTION AND WHILE YOU DOING THIS INSPECTION JOB, PLEASE REFERRING TO THE REMANUFACTURED COMPONENTS - STANDARD CONFIGURATION.

✓ : GOOD CONDITION X : BAD CONDITION ⊗ : NONE

[illegible]

Jakarta,

2014

Inspected by,

Approved by,

QA Inspector

SPV / Sect.Head



PT SAPTAINDRA SEJATI

FINAL DRIVE DISASSEMBLY & MEASUREMENT

CHECKSHEET

MACHINE MODEL

PC1250SP-8

RO NO :

POWERTRAIN SECTION

DISASSEMBLY CHECK SHEET FINAL DRIVE EXCAVATOR PC1250-8	COMP.MODEL		W/O NO.		NUMBER.DOC	QR02 - PT - 072
	COMP. S/N		PART.NO		PUB.DATE	26/05/2003
	UNIT MODEL		START.DATE		REV.NO	00
	UNIT S/N		FINISH. DATE		PAGE	1 of 2

PROCESS	START		DISASSEMBLY BY	
	FINISH			

No	PARTS NAME	METHODE	CHECK POINT	EVALUATION		U/A/U/FR/N	FIGURE OF PARTS TO BE CHECKED																		
				ACTUAL																					
1	HUB ASSY	VISUAL CHECK	Damage especially at bolt hole (worn. Crack, check used crack detector) wear at surface.	<table><tr><td>CONTENTS CHECK</td><td>% Targe</td></tr><tr><td>Crack</td><td></td></tr><tr><td>Damage</td><td></td></tr><tr><td>Wear</td><td></td></tr></table>	CONTENTS CHECK	% Targe	Crack		Damage		Wear		<table><tr><td></td><td></td><td></td></tr></table>												
CONTENTS CHECK	% Targe																								
Crack																									
Damage																									
Wear																									
2	CASE COVER	VISUAL CHECK	- Crack/abnormal wear at bearing seat - Check used crack detector - Check thread for damage	<table><tr><td>CONTENTS CHECK</td><td>% Targe</td></tr><tr><td>Crack</td><td></td></tr><tr><td>Damage</td><td></td></tr><tr><td>Wear</td><td></td></tr></table>	CONTENTS CHECK	% Targe	Crack		Damage		Wear		<table><tr><td></td><td></td><td></td></tr></table>												
CONTENTS CHECK	% Targe																								
Crack																									
Damage																									
Wear																									
3	SHAFT	VISUAL CHECK	- Pitting/crack & abnormal wear wear (used crack detector) - Wear of spline area Max. wear less than 0.35 mm - Wear at bearing seat	<table><tr><td>CONTENTS CHECK</td><td>% Targe</td></tr><tr><td>Pitting</td><td></td></tr><tr><td>Crack</td><td></td></tr><tr><td>Scoring</td><td></td></tr></table>	CONTENTS CHECK	% Targe	Pitting		Crack		Scoring		<table><tr><td></td><td></td><td></td></tr></table>												
CONTENTS CHECK	% Targe																								
Pitting																									
Crack																									
Scoring																									
4	CARRIER 1st	VISUAL CHECK	Pitting/crack on teeth wear of spline	<table><tr><td>CONTENTS CHECK</td><td>% Targe</td></tr><tr><td>Pitting</td><td></td></tr><tr><td>Crack</td><td></td></tr><tr><td>Scoring</td><td></td></tr></table>	CONTENTS CHECK	% Targe	Pitting		Crack		Scoring		<table><tr><td></td><td></td><td></td></tr></table>												
CONTENTS CHECK	% Targe																								
Pitting																									
Crack																									
Scoring																									
5	CARRIER 2nd	VISUAL CHECK	- Crack/abnormal wear at spline - Abnormal wear at hole shaft (inspection used crack detector)	<table><tr><td>CONTENTS CHECK</td><td>% Targe</td></tr><tr><td>Worn</td><td></td></tr><tr><td>Crack</td><td></td></tr></table>	CONTENTS CHECK	% Targe	Worn		Crack		<table><tr><td></td><td></td><td></td></tr></table>														
CONTENTS CHECK	% Targe																								
Worn																									
Crack																									
6	CARRIER 3rd	VISUAL CHECK	Pitting crack, scoring, abnormal weat	<table><tr><td>CONTENTS CHECK</td><td>1</td><td>2</td><td>3</td></tr><tr><td>Pitting</td><td></td><td></td><td></td></tr><tr><td>Crack</td><td></td><td></td><td></td></tr><tr><td>Scoring</td><td></td><td></td><td></td></tr></table>	CONTENTS CHECK	1	2	3	Pitting				Crack				Scoring				<table><tr><td></td><td></td><td></td></tr></table>				
CONTENTS CHECK	1	2	3																						
Pitting																									
Crack																									
Scoring																									
7	GEAR SHAFT CARRIER (SMALL)	VISUAL CHECK	Crack/abnormal wear	<table><tr><td>CONTENTS CHECK</td><td>1</td><td>2</td><td>3</td></tr><tr><td>Wear</td><td></td><td></td><td></td></tr><tr><td>Crack</td><td></td><td></td><td></td></tr></table>	CONTENTS CHECK	1	2	3	Wear				Crack				<table><tr><td></td><td></td><td></td></tr></table>								
CONTENTS CHECK	1	2	3																						
Wear																									
Crack																									
8	CARRIER LARGE	VISUAL CHECK	Check crack/abnormal wear on thrust washer contact (Inspection used crack detector)	<table><tr><td>CONTENTS CHECK</td><td>% targe</td></tr><tr><td>Crack</td><td></td></tr><tr><td>Wear</td><td></td></tr></table>	CONTENTS CHECK	% targe	Crack		Wear		<table><tr><td></td><td></td><td></td></tr></table>														
CONTENTS CHECK	% targe																								
Crack																									
Wear																									
9	PIN CARRIER	VISUAL CHECK	Pitting,crack,scooring & abnormal wear on teeth	<table><tr><td>CONTENTS CHECK</td><td>1</td><td>2</td><td>3</td></tr><tr><td>Pitting</td><td></td><td></td><td></td></tr><tr><td>Crack</td><td></td><td></td><td></td></tr><tr><td>Scoring</td><td></td><td></td><td></td></tr></table>	CONTENTS CHECK	1	2	3	Pitting				Crack				Scoring				<table><tr><td></td><td></td><td></td></tr></table>				
CONTENTS CHECK	1	2	3																						
Pitting																									
Crack																									
Scoring																									
10	SPROCKET	VISUAL CHECK	Check abnormal wear	<table><tr><td>CONTENTS CHECK</td><td>1</td><td>2</td><td>3</td></tr><tr><td>Wear</td><td></td><td></td><td></td></tr><tr><td>Crack</td><td></td><td></td><td></td></tr></table>	CONTENTS CHECK	1	2	3	Wear				Crack				<table><tr><td></td><td></td><td></td></tr></table>								
CONTENTS CHECK	1	2	3																						
Wear																									
Crack																									



PT SAPTAINDRA SEJATI

FINAL DRIVE

RECEIVING INSPECTION

CHECKSHEET

MACHINE MODEL

PC1250SP-8

RO NO :

POWERTRAIN SECTION

RECEIVING INSPECTION SHEET FINAL DRIVE	MACHINE MODEL	PC1250-8	REPORT NO.		DOCUMENT NO.	QR01-PT- 030
	COMP. MODEL		COMP. S/N		PUBL. DATE	14/05/2008
	RECEIVING DATE		FINAL INSPECT		REVISION NO.	00
	DELIVERY DATE		WO NO.		PAGE	1 of 1

BELOW ARE THE ITEMS RELATED TO DELIVERY INSPECTION AND WHILE YOU DOING THIS INSPECTION JOB, PLEASE REFERRING TO THE REMANUFACTURED COMPONENTS - STANDARD CONFIGURATION.

✓ : GOOD CONDITION X : BAD CONDITION ⊗ : NONE

[illegible]

Jakarta,

2014

Inspected by,

Approved by,

QA Inspector

SPV / Sect.Head



PT SAPTAINDRA SEJATI

**FINAL DRIVE
DISASSEMBLY &
MEASUREMENT CHECKSHEET
MACHINE MODEL**

PC1250SP-8

RO NO :

POWERTRAIN SECTION

DISASSEMBLY CHECK SHEET	COMP.MODEL		WQ NO.		NUMBER.DOC	QR02 - PT - 072
FINAL DRIVE EXCAVATOR PC1250-8	COMP. S/N		PART.NO		PUB. DATE	26/05/2003
	UNIT MODEL		START. DATE		REV. NO	00
	UNIT S/N		FINISH. DATE		PAGE	1 of 2

PROCESS	START	FINISH	DISASSEMBLY BY
---------	-------	--------	----------------

No	PARTS NAME	METHODE	CHECK POINT	EVALUATION		U/I/J/R/N	FIGURE OF PARTS TO BE CHECKED																																		
				ACTUAL																																					
1	HUB ASSY	VISUAL CHECK	Damage especially at bolt hole (worn. Crack, check used crack detector) wear at surface.	<table><tr><td>CONTENTS CHECK</td><td>% Targe</td></tr><tr><td>Crack</td><td></td></tr><tr><td>Damage</td><td></td></tr><tr><td>Wear</td><td></td></tr></table>	CONTENTS CHECK	% Targe	Crack		Damage		Wear			<table><tr><td></td><td></td><td></td></tr></table>																											
CONTENTS CHECK	% Targe																																								
Crack																																									
Damage																																									
Wear																																									
2	CASE COVER	VISUAL CHECK	- Crack/abnormal wear at bearing seat - Check used crack detector - Check thread for damage	<table><tr><td>CONTENTS CHECK</td><td>% Targe</td></tr><tr><td>Crack</td><td></td></tr><tr><td>Damage</td><td></td></tr><tr><td>Wear</td><td></td></tr></table>	CONTENTS CHECK	% Targe	Crack		Damage		Wear			<table><tr><td></td><td></td><td></td></tr></table>																											
CONTENTS CHECK	% Targe																																								
Crack																																									
Damage																																									
Wear																																									
3	SHAFT	VISUAL CHECK	- Pitting/crack & abnormal wear wear (used crack detector) - Wear of spline area Max. wear less than 0.35 mm - Wear at bearing seat	<table><tr><td>CONTENTS CHECK</td><td>% Targe</td></tr><tr><td>Pitting</td><td></td></tr><tr><td>Crack</td><td></td></tr><tr><td>Scoring</td><td></td></tr></table>	CONTENTS CHECK	% Targe	Pitting		Crack		Scoring			<table><tr><td></td><td></td><td></td></tr></table>																											
CONTENTS CHECK	% Targe																																								
Pitting																																									
Crack																																									
Scoring																																									
4	CARRIER 1st	VISUAL CHECK	Pitting/crack on teeth wear of spline	<table><tr><td>CONTENTS CHECK</td><td>% Targe</td></tr><tr><td>Pitting</td><td></td></tr><tr><td>Crack</td><td></td></tr><tr><td>Scoring</td><td></td></tr></table>	CONTENTS CHECK	% Targe	Pitting		Crack		Scoring			<table><tr><td></td><td></td><td></td></tr></table>																											
CONTENTS CHECK	% Targe																																								
Pitting																																									
Crack																																									
Scoring																																									
5	CARRIER 2nd	VISUAL CHECK	- Crack/abnormal wear at spline - Abnormal wear at hole shaft (inspection used crack detector)	<table><tr><td>CONTENTS CHECK</td><td>% Targe</td></tr><tr><td>Worn</td><td></td></tr><tr><td>Crack</td><td></td></tr></table>	CONTENTS CHECK	% Targe	Worn		Crack			<table><tr><td></td><td></td><td></td></tr></table>																													
CONTENTS CHECK	% Targe																																								
Worn																																									
Crack																																									
6	CARRIER 3rd	VISUAL CHECK	Pitting crack, scoring, abnormal weat	<table><tr><td>CONTENTS CHECK</td><td>1</td><td>2</td><td>3</td></tr><tr><td>Pitting</td><td></td><td></td><td></td></tr><tr><td>Crack</td><td></td><td></td><td></td></tr><tr><td>Scoring</td><td></td><td></td><td></td></tr></table>	CONTENTS CHECK	1	2	3	Pitting				Crack				Scoring					<table><tr><td></td><td></td><td></td></tr></table>																			
CONTENTS CHECK	1	2	3																																						
Pitting																																									
Crack																																									
Scoring																																									
7	GEAR SHAFT CARRIER (SMALL)	VISUAL CHECK	Crack/abnormal wear	<table><tr><td>CONTENTS CHECK</td><td>1</td><td>2</td><td>3</td></tr><tr><td>Wear</td><td></td><td></td><td></td></tr><tr><td>Crack</td><td></td><td></td><td></td></tr></table>	CONTENTS CHECK	1	2	3	Wear				Crack					<table><tr><td></td><td></td><td></td></tr></table>																							
CONTENTS CHECK	1	2	3																																						
Wear																																									
Crack																																									
8	CARRIER LARGE	VISUAL CHECK	Check crack/abnormal wear on thrust washer contact. (Inspection used crack detector)	<table><tr><td>CONTENTS CHECK</td><td>% tage</td></tr><tr><td>Crack</td><td></td></tr><tr><td>Wear</td><td></td></tr></table>	CONTENTS CHECK	% tage	Crack		Wear			<table><tr><td></td><td></td><td></td></tr></table>																													
CONTENTS CHECK	% tage																																								
Crack																																									
Wear																																									
9	PIN CARRIER	VISUAL CHECK	Pitting, crack, scooring & abnormal wear on teeth	<table><tr><td>CONTENTS CHECK</td><td>1</td><td>2</td><td>3</td><td></td><td></td><td></td></tr><tr><td>Pitting</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>Crack</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>Scoring</td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	CONTENTS CHECK	1	2	3				Pitting							Crack							Scoring								<table><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>							
CONTENTS CHECK	1	2	3																																						
Pitting																																									
Crack																																									
Scoring																																									
10	SPROCKET	VISUAL CHECK	Check abnormal wear	<table><tr><td>CONTENTS CHECK</td><td>1</td><td>2</td><td>3</td><td></td><td></td><td></td></tr><tr><td>Wear</td><td></td><td></td><td></td><td></td><td></td><td></td></tr><tr><td>Crack</td><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>	CONTENTS CHECK	1	2	3				Wear							Crack								<table><tr><td></td><td></td><td></td><td></td><td></td><td></td></tr></table>														
CONTENTS CHECK	1	2	3																																						
Wear																																									
Crack																																									



PT SAPTAINDRA SEJATI

**FINAL DRIVE
ASSEMBLY
CHECKSHEET
MACHINE MODEL**

PC1250SP-8

RO NO :

POWERTRAIN SECTION



PT SAPTAINDRA SEJATI
NAROGONG REBUILD CENTER







ASSEMBLY CHECK SHEET FINAL DRIVE PC1250-8	UNIT MODEL	PC1250-8	DOCUMENT NO.	
	COMP. MODEL	FINAL DRIVE RH	PUBLIC. DATE	15/10/2010
	COMP. S/N		REVISION NO.	00
	WO.NO		PAGE	1 of 4

PROCESS	START		ASSEMBLY BY	
	FINISH			

NO.	PARTS	CHECK POINT	SPECIFICATION	SIGN			REMARKS (SKETCH, PHOTOS, COMMENTS)	
				MEC	SPV	QA		
1	ASSEMBLY CARRIER 1st and SUN GEAR ASSY	- Clean all part,check for dirt or damage - Install bearing to gear - install Thrust washer then set to carrier Align position of pin holes of carrier and shaft rotate the planetary gear and make sure thrust washer no damage	Then tap with a plastic hammer to install shaft					
		- Install Pin to carrier Make sure no damage fix outer gear and cage with floating seal after assembly carrier,check that gear rotates smoothly	after install pin marked by arrows of the carrier					
		- Install carrier 1st to shaft		using eye bolt				











ASSEMBLY CHECK SHEET FINAL DRIVE PC1250-8	UNIT MODEL	PC1250-8	DOCUMENT NO.	
	COMP. MODEL	FINAL DRIVE RH	PUBLIC. DATE	15/10/2010
	COMP. S/N		REVISION NO.	00
	WO.NO		PAGE	2 of 4

NO.	PARTS	CHECK POINT	SPECIFICATION	SIGN			REMARKS (SKETCH, PHOTOS, COMMENTS)
				MEC	SPV	QA	
3	ASSEMBLY FLOATING SEAL and HUB ASSY	make sure floating seal no damage - after install measure dimension a between the inner gear and floating seal set at 4 places that measurement Act. : mm	using tool J8 - std max 1mm After install floating seal coat the sliding surface with engine oil				
		make sure surface area contact seal no damage - Install Floating seal to shaft					
		- Install bearing to shaft shrinking fit Act. : deg c	- shrinking fit warm up to 100 C using tool J7				
		- Install outer race bearing to hub	using tool J8				
		make sure floating seal no damage - Install Floating seal to Hub - Install Hub assy to shaft					
		- install bearing to shaft - Install Nut push bearing inner race portion with specified force rotate hub assy 3 turn Act. : ton	using tool J7 pushing force 3.5 - 3.9 Ton				
		- Measure dimension a - Measure thickness b of Nut Calculate a - b = c using tool J1 ,tighten Nut where dimension c = 0.15 -0.05 mm Act. : mm - Install Lock plate Act. : kgm	std c = 0.15 - 0.05 mm - LT2 - std torque 6 - 7.5 kgm				



ASSEMBLY CHECK SHEET FINAL DRIVE PC1250-8	UNIT MODEL	PC1250-8	DOCUMENT NO.	
	COMP. MODEL	FINAL DRIVE RH	PUBLIC DATE	15/10/2010
	COMP. S/N		REVISION NO.	00
	WO.NO		PAGE	3 of 4

NO.	PARTS	CHECK POINT	SPECIFICATION	SIGN			REMARKS (SKETCH, PHOTOS, COMMENTS)
				MEC	SPV	QA	
4	ASSEMBLY RING GEAR ASSY	- Install oring to shaft end - Install Ring gear					
5	ASSEMBLY CARRIER 3rd and SUN GEAR	- Install outer race to gear	- press fit using tool J4				
		- Install bearing and spacer to gear align the carrier, bearing and spacer holes accurately	- std torque 50 - 62 kgm				
		- Install pin to carrier press fit make sure no clearance between the pin and end face (m) of the bearing - after install pin, check that the gear rotates smoothly - Install holder to shaft - monting bolt Act : kgm	- shrinking fit warm up to 100 C - std torque 90 - 105 kgm				 
		- Install carrier 3rd assy to Hub align the lower portion 4 places of spacer and shaft when the install - measure distance i from the top of planetary gear to that of ring gear 3rd if the (i) less than 3.8 mm check assembly gear again	- std (i) max 3.8 mm				 
		- Install thrust washer to carrier - Install sun gear to carrier 3rd - Install spacer to sun gear	thrust washer p/n 209-27-71360 spacer P/N 207-27-52270				
		- Install cover to hub assy monting surface coat gasket sealant LG 6 torque monting bolt Act : kgm	- std torque 90 - 105 kgm LT2				

RANDOM ITEM CHECK

Name :

Name :


QA INSPECTOR

PROD. SUPERVISOR



PT SAPTAINDRA SEJATI
NAROGONG REBUILD CENTER

ASSEMBLY CHECK SHEET FINAL DRIVE PC1250-8	UNIT MODEL	PC1250-8	DOCUMENT NO.	
	COMP. MODEL	FINAL DRIVE RH	PUBLIC DATE	15/10/2010
	COMP. S/N		REVISION NO.	00
	WO.NO		PAGE	4 of 4

6	Inner part for delivery	- Prepare part for delivery F/D RH,LH after assembly F/D assy,prepared for part bellow : 1.spacer p/n 209-27-71521 1pc 2.oring p/n 209-27-71370 1pc 3.button p/n 208-27-61350 1pc	packing part for delivery					
---	-------------------------	---	---------------------------	--	--	--	--	---

NOTE :

ASSEMBLY BY

(MECHANIC)

INSPECTED BY

(QA)

APPROVED BY

(GL / SPV)