

DOCUMENT NO.	RC/QR05/EG/02/01
PUBLICATION DATE	18/08/2009
REVISION NO.	01
PAGE	

RUNNING TEST				
No	STANDARD (MANUAL)		ACTUAL TESTED	
	RPM	HP	RPM	HP
1	650	0		
2	1000	79		
3	1250	197		
4	1550	489		
5	1800	852		
6	1900	1200		

MEASUREMENT BLOWBY PRESSURE AT RATED SPEED (WITH MANUAL TEST)					
	STANDARD PRESSURE		ACTUAL		REMARK
	MAXIMUM PRESSURE	300 mmH2O(2.94 Kpa)	1st		
	SERVICE LIMIT VALUE	600 mmH2O(5.88 Kpa)	2nd		
	ALTERNATOR OUTPUT VOLTAGE	STANDARD	ACTUAL		REMARK
		27.5 ~ 29.5			

SPEED (Rpm)		OIL		WATER		BOOST PRESS (mmHg)	BLOW BY (mmH2O)	EXH TEMP (°C)
		Press. (Kg/cm ²)	Temp (°C)	Press. (Kg/cm ²)	Temp (°C)			
Low idle	650 ± 20	Min. 0.8	90 ~ 110	-	70~90	Min. 1250 at rated HP	Max 300 permissible 600	Max 650 at rated HP and Max. 700 at Max.torque
High idle	2250 ± 25	3.0 ~ 4.5						
POWER (HP) / RPM		1160 ~ 1240 / 1900 ± 50						
TORQUE (Kgm) / RPM		502~ 534 / 1350 ± 50						
EXHAUST TEMP DIFF		Maximum 10°C RH and LH Bank						

ENGINE PERFORMANCE TEST REPORT	DOCUMENT NO.	RC/QR05/EG/02/01
	PUBLICATION DATE	18/08/2009
	REVISION NO.	01
	PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA12V140E-3	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	HD 785-7	TEST BY	

RECHECK VALVE CLEARANCE AFTER LOAD				
Adjustment valve clearance	* Penentuan posisi top cylinder engine harus dicek dan disetujui oleh QA.			
	Step and method adjustment of value clearance following to the shop manual attached.			
	Firing Order: R1-L1-R5-L5-R3-L3-R6-L6-R2-L2-R4-L4.			
	Valve clearance:			
	Intake valve : 0.35 ± 0.02	Act :	mm	
Rocker Arm cover	Exhaust valve : 0.57 ± 0.02	Act :	mm	
	Tighten locknut to secure adjustment screw.			
	Locknut: 5.4 ~ 6.6 kgm	Act :	kgm	
	Fit O ring and install rocker arm cover.			
	Since the bolt at the front on the air intake manifold side is also used to secure the wiring harness clamp,tighten it temporary.			
Rocker Arm cover	Mounting bolt : 3.0 ~ 3.5 kgm.	Act :	kgm	

ENGINE PERFORMANCE TEST REPORT	DOCUMENT NO.	RC/QR05/EG/02/01
	PUBLICATION DATE	18/08/2009
	REVISION NO.	01
	PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA12V140E-3	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	HD 785-7	TEST BY	

TOP 1 RH						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX		X		X		X
IN			X		X	X

TOP 1 LH						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX		X		X		X
IN			X		X	X

TOP 6 RH						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX	X		X		X	
IN	X	X		X		

TOP 6 LH						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX	X		X		X	
IN	X	X		X		

INSPECTION BY

INSPECTION & APPROVAL BY

MECHANIC

QUALITY ASSURANCE (QA)

GL/SPV PRODUCTION