



ENGINE PERFORMANCE TEST REPORT	DOCUMENT NO.	RC/QR05/EG/02/02
	PUBLICATION DATE	18/08/2009
	REVISION NO.	01
	PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA12V140E-3	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	PC 2000-8	TEST BY	

ENGINE PERFORMANCE TEST REPORT	DOCUMENT NO.	RC/QR05/EG/02/02
	PUBLICATION DATE	18/08/2009
	REVISION NO.	01
	PAGE	

3 of 6

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA12V140E-3	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	PC 2000-8	TEST BY	

[illegible]



ENGINE PERFORMANCE TEST REPORT	DOCUMENT NO.	RC/QR05/EG/02/02
	PUBLICATION DATE	18/08/2009
	REVISION NO.	01
	PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA12V140E-3	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	PC 2000-8	TEST BY	

--

ENGINE PERFORMANCE TEST REPORT	DOCUMENT NO.	RC/QR05/EG/02/02
	PUBLICATION DATE	18/08/2009
	REVISION NO.	01
	PAGE	

5 of 6

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA12V140E-3	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	PC 2000-8	TEST BY	

RECHECK VALVE CLEARANCE AFTER LOAD

Adjustment valve clearance	* Penentuan posisi top cylinder engine harus dicek dan disetujui oleh QA. Step and method adjustment of value clearance following to the shop manual attached. Firing Order: R1-L1-R5-L5-R3-L3-R6-L6-R2-L2-R4-L4. Valve clearance:		
	Intake valve : 0.35 ± 0.02	Act : mm	
	Exhaust valve : 0.57 ± 0.02	Act : mm	
	Tighten locknut to secure adjustment screw. Locknut: 5.4 ~ 6.6 kgm	Act : kgm	
Rocker Arm cover	Fit O ring and install rocker arm cover. Since the bolt at the front on the air intake manifold side is also used to secure the wiring harness clamp,tighten it temporary.		
	Mounting bolt : 3.0 ~ 3.5 kgm.	Act : kgm	

ENGINE PERFORMANCE TEST REPORT

DOCUMENT NO.	RC/QR05/EG/02/02
PUBLICATION DATE	18/08/2009
REVISION NO.	01
PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA12V140E-3	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	PC 2000-8	TEST BY	

TOP 1 RH						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX		X		X		X
IN			X		X	X

TOP 1 LH						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX		X		X		X
IN			X		X	X

TOP 6 RH						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX	X		X		X	
IN	X	X		X		

TOP 6 LH						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX	X		X		X	
IN	X	X		X		

INSPECTION BY

INSPECTION & APPROVAL BY

MECHANIC

QUALITY ASSURANCE (QA)

GL/SPV PRODUCTION