



ENGINE PERFORMANCE TEST REPORT	DOCUMENT NO.	RC/QR05/EG/02/07
	PUBLICATION DATE	18/08/2009
	REVISION NO.	01
	PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA6D170-5	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	D 375-6R	TEST BY	

QUALITY PROBLEM	
DESCRIPTION	REMARKS
WHAT (PROBLEM NAME)	
WHERE (PROBLEM LOCATION)	
WHEN (PROBLEM DATE)	
WHO (INSPECTED BY)	
HOW (PROBLEM EXPLAIN)	
CORRECTIVE ACTION:	
PREVENTIVE ACTION:	
REMARKS :	

ENGINE PERFORMANCE TEST REPORT

DOCUMENT NO.	RC/QR05/EG/02/07
PUBLICATION DATE	18/08/2009
REVISION NO.	01
PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA6D170-5	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	D 375-6R	TEST BY	

RECHECK VALVE CLEARANCE AFTER LOAD

Adjustment valve clearance	* Penentuan posisi top cylinder engine harus dicek dan disetujui oleh QA.		
	Step and method adjustment of value clearance following to the shop manual attached.		
	Firing Order: 1-5-3-6-2-4		
	Valve clearance:		
	Intake valve : 0.32 ± 0.02	Act :	mm
Rocker Arm cover	Exhaust valve : 0.62 ± 0.02	Act :	mm
	Tighten locknut to secure adjustment screw.		
	Locknut: 5,9 ~ 7,9 kgm	Act :	kgm
	Fit O ring and install rocker arm cover.		
	Mounting bolt cover 1,3,4,5&6 =1 ± 0,1 Kg		
		Act :	kgm
	Mounting bolt cover 2 =6 ~ 7,5 Kg		
		Act :	kgm

TOP 1						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX		X		X		X
IN			X		X	X

INSPECTION BY

TOP 6						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX	X		X		X	
IN	X	X		X		

INSPECTION & APPROVAL BY

MECHANIC

QUALITY ASSURANCE (QA)

GL/SPV PRODUCTION