

DOCUMENT NO.	RC/QR05/EG/02/06
PUBLICATION DATE	18/08/2009
REVISION NO.	01
PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA6D170-5	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	PC1250-8	TEST BY	

RUNNING TEST				
No	STANDARD (MANUAL)		ACTUAL TESTED	
	RPM	HP	RPM	HP
1	900	0		
2	1000	68		
3	1200	211		
4	1500	424		
5	1800	690		
6				

MEASUREMENT BLOWBY PRESSURE AT RATED SPEED (WITH MANUAL TEST)					
	STANDARD PRESSURE		ACTUAL		REMARK
	350 MMH2O(3,43 Kpa)		1st		
			2nd		
	ALTERNATOR OUTPUT VOLTAGE	STANDARD	ACTUAL		REMARK
		27.5 ~ 29.5			

MAINTENANCE STANDARD								
SPEED (Rpm)		OIL		WATER		BOOST PRESS (mmHg)	BLOW BY (mmH2O)	EXH TEMP (°C)
		Press. (Kg/cm ²)	Temp (°C)	Press. (Kg/cm ²)	Temp (°C)			
Low idle	650 ± 20	Min. 1,2	80 ~ 110	-	70~90	Min. 950 at rated HP	Max 300 permissible 960	Max 700 at rated HP and torque
High idle	2250 ± 25	3.0 ~ 5.5						
POWER (HP) / RPM		690/1800±50						
TORQUE (Kgm) / RPM		308/1300±50						



ENGINE PERFORMANCE TEST REPORT	DOCUMENT NO.	RC/QR05/EG/02/06
	PUBLICATION DATE	18/08/2009
	REVISION NO.	01
	PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA6D170-5	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	PC1250-8	TEST BY	

QUALITY PROBLEM	
DESCRIPTION	REMARKS
WHAT (PROBLEM NAME)	
WHERE (PROBLEM LOCATION)	
WHEN (PROBLEM DATE)	
WHO (INSPECTED BY)	
HOW (PROBLEM EXPLAIN)	
CORRECTIVE ACTION :	
PREVENTIVE ACTION :	
REMARKS :	

ENGINE PERFORMANCE TEST REPORT	DOCUMENT NO.	RC/QR05/EG/02/06
	PUBLICATION DATE	18/08/2009
	REVISION NO.	01
	PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA6D170-5	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	PC1250-8	TEST BY	

RECHECK VALVE CLEARANCE AFTER LOAD			
Adjustment valve clearance	* Penentuan posisi top cylinder engine harus dicek dan disetujui oleh QA.		
	Step and method adjustment of value clearance following to the shop manual attached.		
	Firing Order: 1-5-3-6-2-4		
	Valve clearance:		
	Intake valve : 0.32 ± 0.02	Act : mm	
	Exhaust valve : 0.62 ± 0.02	Act : mm	
	Tighten locknut to secure adjustment screw.		
	Locknut: 5,9 ~ 7,9 kgm	Act : kgm	
Rocker Arm cover	Fit O ring and install rocker arm cover.		
	Mounting bolt cover 1,3,4,5&6 =1 ± 0,1 Kgm		
		Act : kgm	
	Mounting bolt cover 2 =6 ~ 7,5 Kgm		
		Act : kgm	

TOP 1						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX		X		X		X
IN			X		X	X

TOP 6						
	CYL 1	CYL 2	CYL 3	CYL 4	CYL 5	CYL 6
EX	X		X		X	
IN	X	X		X		

INSPECTION BY

INSPECTION & APPROVAL BY

MECHANIC

QUALITY ASSURANCE (QA)

GL/SPV PRODUCTION