

ENGINE PERFORMANCE TEST REPORT

DOCUMENT NO.	QR05-ENG-070
PUBLICATION DATE	11/06/2009
REVISION NO.	01
PAGE	

~~1 of 4~~

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA6D140E-5	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	D155-6	TEST BY	

RUNNING TEST

No	STANDARD (MANUAL)		ACTUAL TESTED	
	RPM	HP	RPM	HP
1	740	0		
2	1197	90		
3	1501	181		
4	1729	270		
5	1900	360		

MEASUREMENT BLOWBY PRESSURE AT RATED SPEED (WITH MANUAL TEST)

STANDARD MAXIMUM			ACTUAL		REMARK
TANDARD MAXIMU	300 mmH2O (2.94 Kpa)		1st		
ERVICE LIMIT VALU	400 mmH2O (3.92 Kpa)		2nd		
ALTERNATOR TEST :					
STANDARD MAXIMUM			ACTUAL LOW IDLE		ACTUAL HIGH IDLE
LOW IDLE:	HIGH IDLE:				

MAINTENANCE STANDARD

SPEED (Rpm)		OIL		WATER		BOOST PRESS (mmHg)	BLOW BY (mmH2O)	EXH TEMP (°C)
		Press. (Kg/cm ²)	Temp (°C)	Press. (Kg/cm ²)	Temp (°C)			
Low idle	740 (+ 25/0)	Min. 1.2	80 ~ 110	-	70 ~ 90	Min.880 at rated HP Permissible value 750	Max 300 permissible 400	Max 650 permissible 680
High idle	2100 (0/-50)	3.5 ~ 5.0						
POWER (HP) / RPM		349 ~ 371 / 1900						
TORQUE (Kgm) / RPM		179.4 ~ 190.6 / 1250						

DOCUMENT NO.	QR05-ENG-070
PUBLICATION DATE	11/06/2009
REVISION NO.	01
PAGE	2 of 4

~~2 of 4~~

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA6D140E-5	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	D155-6	TEST BY	

[illegible]

ENGINE PERFORMANCE TEST REPORT	DOCUMENT NO.	QR05-ENG-070
	PUBLICATION DATE	11/06/2009
	REVISION NO.	01
	PAGE	3 of 4

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA6D140E-5	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	D155-6	TEST BY	

RECHECK VALVE CLEARANCE AFTER LOAD			
Adjustment valve clearance	Step and method adjustment of value clearance following to the shop manual attached.		
	Firing Order: 1 - 5 - 3 - 6 - 2 - 4		
	Valve clearance:		
	Intake valve : 0.35 ± 0.02	Act :	mm
	Exhaust valve : 0.57 ± 0.02	Act :	mm
Rocker Arm cover	Tighten locknut to secure adjustment screw.		
	Locknut: 5.4 ~ 6.6 kgm	Act :	kgm
	Fit O ring and install rocker arm cover.		
Rocker Arm cover	Since the bolt at the front on the air intake manifold side is also used to secure the wiring harness clamp,then tighten temporarily.		
	Mounting bolt : 3.0 ~ 3.5 kgm	Act :	kgm

ENGINE PERFORMANCE TEST REPORT

DOCUMENT NO.	QR05-ENG-070
PUBLICATION DATE	11/06/2009
REVISION NO.	01
PAGE	

WO NUMBER		START DATE / TIME	
ENGINE MODEL	SAA6D140E-5	FINISH DATE / TIME	
ENGINE SER.NO.		DYNO.ARM LENGTH	716 mm
MACHINE MODEL	D155-6	TEST BY	

TOP 1						
	CYL 1	CYL 2	CYL	CYL 4	CYL 5	CYL 6
EX		X		X		X
IN			X		X	X

TOP 6						
	CYL 1	CYL 2	CYL	CYL 4	CYL 5	CYL 6
EX	X		X		X	
IN	X	X		X		

INSPECTION BY

INSPECTION & APPROVAL BY

MECHANIC

QUALITY ASSURANCE (QA)

PROD. SUPERVISOR (SPV)