Surface Mount

Power Splitter/Combiner

BP2U1+

2 Way-0° 50Ω 1750 to 3000 MHz

CASE STYLE: XX211

Maximum Ratings

Operating Temperature	-40°C to 85°C
Storage Temperature	-65°C to 150°C
Power Input (as a splitter)	1.5W max.
Internal Dissipation	0.75W max.

Permanent damage may occur if any of these limits are exceeded.

Pin Connections

SUM PORT	2
PORT 1	8
PORT 2	5
GROUND	1,3,4,6,7

Features

- wide bandwidth 1750-3000 MHz
- good isolation, 20 dB typ.
- good output VSWR, 1.40:1 typ.
- excellent power handling, 1.5W
- low profile
- aqueous washable

Applications

- blue tooth
- IEEE 802.11b, g

+RoHS Compliant

The +Suffix identifies RoHS Compliance. See our web site for RoHS Compliance methodologies and qualifications

Available Tape and Reel at no extra cost

Reel Size	Devices/Reel
7"	20, 50, 100, 200, 500, 1000
13"	2000

Outline Drawing



Outline Dimensions (inch / mm)

A	B	C	D	E	F	G
.163	.210	.077	.250	.220	.050	.017
4.14	5.33	1.96	6.35	5.59	1.27	0.43

H	J	K	M	N	P	wt
.009	.025	.030	.050	.030	.270	grams
0.23	0.64	0.76	1.27	0.76	6.86	0.10

Electrical Specifications

FREQ. RANGE (MHz)	ISOLATION (dB)		INSERTION LOSS (dB) ABOVE 3.0 dB		PHASE UNBALANCE (Degrees)	AMPLITUDE UNBALANCE (dB)	VSWR (:1)	
							S-Port	Output-Ports
f_L-f_U	Typ.	Min.	Typ.	Max.	Max.	Max.	Typ.	Typ.
1750-3000	20	10	0.5	1.6	4.0	0.4	1.60	1.40

Typical Performance Data at 25°C

Frequency (MHz)	Total Loss[1] (dB)		Amplitude Unbalance (dB)	Isolation (dB)	Phase Unbalance (deg.)	VSWR S	VSWR 1	VSWR 2
	S-1	S-2						
1750.00	3.42	3.39	0.04	12.10	0.48	1.27	1.50	1.52
1800.00	3.42	3.38	0.05	12.89	0.49	1.24	1.46	1.48
1900.00	3.43	3.37	0.06	14.80	0.43	1.18	1.37	1.39
2000.00	3.43	3.36	0.07	17.29	0.45	1.12	1.28	1.30
2100.00	3.43	3.35	0.08	20.75	0.41	1.06	1.19	1.22
2200.00	3.45	3.36	0.09	26.34	0.40	1.02	1.11	1.13
2300.00	3.48	3.37	0.10	40.24	0.32	1.08	1.05	1.07
2400.00	3.52	3.40	0.12	28.92	0.32	1.15	1.10	1.09
2500.00	3.56	3.43	0.13	22.75	0.23	1.23	1.19	1.17
2550.00	3.59	3.46	0.13	20.76	0.14	1.27	1.24	1.22
2600.00	3.63	3.48	0.14	19.38	0.16	1.33	1.30	1.28
2700.00	3.71	3.55	0.16	17.10	0.01	1.43	1.41	1.39
2800.00	3.82	3.65	0.18	15.46	0.01	1.56	1.55	1.52
2900.00	3.96	3.78	0.18	14.21	0.27	1.72	1.71	1.67
3000.00	4.14	3.93	0.21	13.20	0.39	1.91	1.88	1.83

1. Total Loss = Insertion Loss + 3dB splitter loss.







electrical schematic



Demo Board MCL P/N: TB-37
Suggested PCB Layout (PL-053)



NOTES: 1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.020" ± 0.0015". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)
DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

ESD Rating
Human Body Model (HBM): Class 1A (250 v to <500 v) in accordance with ANSI/ESD STM 5.1 - 2001
Machine Model (MM): Class M1 (< 100 v) in accordance with ANSI/ESD STM 5.2 - 1999 (pass 50V)

Notes

A. Performance and quality attributes and conditions not expressly stated in this specification document are intended to be excluded and do not form a part of this specification document.
B. Electrical specifications and performance data contained in this specification document are based on Mini-Circuit's applicable established test performance criteria and measurement instructions.
C. The parts covered by this specification document are subject to Mini-Circuits standard limited warranty and terms and conditions (collectively, "Standard Terms"); Purchasers of this part are entitled to the rights and benefits contained therein. For a full statement of the Standard Terms and the exclusive rights and remedies thereunder, please visit Mini-Circuits' website at www.minicircuits.com/MCLStore/terms.jsp

REV. B
M151107
ED-12348C/6+
BP2U1+
RS/LC/CP/AM
150618

2 Way-0° Power Splitter/Combiner BP2U1+

Typical Performance Data

TEST CONDITIONS: INPUT POWER = 0dBm @Temperature = +25°C

FREQ. (MHz)	TOTAL LOSS[1] (dB)		AMP. UNBAL. (dB)	PHASE UNBAL. (deg.)	ISOLATION (dB)	VSWR (:1)		
	S-1	S-2			1-2	S	1	2
1500	3.50	3.53	0.03	0.41	8.74	1.53	1.65	1.68
1550	3.49	3.51	0.02	0.42	9.22	1.50	1.62	1.65
1600	3.48	3.49	0.01	0.43	9.75	1.47	1.59	1.62
1650	3.47	3.48	0.01	0.44	10.32	1.44	1.56	1.59
1700	3.47	3.46	0.01	0.42	10.95	1.40	1.53	1.55
1750	3.46	3.45	0.01	0.45	11.63	1.37	1.50	1.51
1800	3.45	3.44	0.01	0.49	12.39	1.34	1.46	1.47
1850	3.45	3.42	0.03	0.48	13.24	1.30	1.43	1.44
1900	3.44	3.41	0.03	0.49	14.16	1.27	1.39	1.39
1950	3.44	3.40	0.04	0.50	15.24	1.23	1.36	1.35
2000	3.43	3.39	0.04	0.50	16.45	1.20	1.32	1.31
2050	3.44	3.39	0.05	0.47	17.84	1.16	1.28	1.27
2100	3.44	3.38	0.06	0.51	19.53	1.12	1.24	1.23
2150	3.44	3.38	0.06	0.49	21.58	1.08	1.20	1.18
2200	3.44	3.38	0.06	0.48	24.23	1.05	1.16	1.14
2250	3.46	3.39	0.07	0.45	28.07	1.03	1.11	1.10
2300	3.46	3.40	0.06	0.50	34.34	1.05	1.08	1.07
2350	3.48	3.41	0.07	0.53	41.39	1.09	1.04	1.05
2400	3.50	3.43	0.07	0.55	31.77	1.14	1.04	1.06
2450	3.53	3.46	0.07	0.60	26.92	1.19	1.07	1.09
2500	3.56	3.49	0.07	0.63	23.80	1.24	1.12	1.14
2505	3.56	3.49	0.07	0.62	23.55	1.25	1.13	1.14
2510	3.57	3.49	0.08	0.63	23.32	1.26	1.13	1.15
2520	3.57	3.50	0.07	0.64	22.83	1.27	1.14	1.16
2530	3.58	3.51	0.07	0.67	22.37	1.28	1.15	1.17
2540	3.59	3.51	0.08	0.66	21.95	1.29	1.16	1.18
2550	3.59	3.52	0.07	0.68	21.55	1.31	1.17	1.19
2560	3.60	3.53	0.07	0.72	21.17	1.32	1.18	1.20
2570	3.61	3.54	0.07	0.71	20.82	1.33	1.20	1.21
2580	3.62	3.55	0.07	0.72	20.50	1.35	1.21	1.22
2590	3.63	3.56	0.07	0.75	20.18	1.36	1.22	1.23
2600	3.64	3.57	0.07	0.73	19.85	1.37	1.23	1.24
2650	3.69	3.61	0.08	0.88	18.43	1.45	1.29	1.30
2700	3.75	3.67	0.08	0.93	17.27	1.53	1.36	1.37
2750	3.82	3.74	0.08	1.04	16.28	1.62	1.43	1.44
2800	3.90	3.82	0.08	1.15	15.42	1.71	1.51	1.51
2850	3.99	3.90	0.09	1.19	14.67	1.82	1.59	1.59
2900	4.09	4.00	0.09	1.29	14.01	1.93	1.68	1.68
2950	4.21	4.11	0.10	1.41	13.42	2.05	1.78	1.77
3000	4.34	4.22	0.12	1.55	12.89	2.19	1.88	1.87
3050	4.48	4.35	0.13	1.64	12.40	2.34	2.00	1.97
3100	4.63	4.49	0.14	1.76	11.97	2.50	2.12	2.08
3150	4.79	4.64	0.15	1.91	11.58	2.67	2.25	2.20
3200	4.97	4.81	0.16	2.04	11.23	2.86	2.38	2.33
3250	5.16	4.99	0.17	2.20	10.91	3.07	2.52	2.46
3300	5.36	5.17	0.19	2.35	10.61	3.30	2.68	2.60
3350	5.58	5.37	0.21	2.45	10.34	3.54	2.84	2.75
3400	5.80	5.58	0.22	2.62	10.10	3.80	3.00	2.90
3450	6.05	5.80	0.25	2.73	9.87	4.08	3.18	3.07
3500	6.30	6.03	0.27	2.84	9.67	4.38	3.35	3.24

[1]Total Loss = Insertion Loss + 3dB Splitter Loss

2 Way-0° Power Splitter/Combiner BP2U1+

Typical Performance Data

TEST CONDITIONS: INPUT POWER = 0dBm @Temperature = -40°C

FREQ. (MHz)	TOTAL LOSS[1] (dB)		AMP. UNBAL. (dB)	PHASE UNBAL. (deg.)	ISOLATION (dB)	VSWR (:1)		
	S-1	S-2			1-2	S	1	2
1500	3.35	3.38	0.03	0.94	8.42	1.54	1.65	1.69
1550	3.35	3.36	0.01	1.00	8.87	1.52	1.62	1.65
1600	3.33	3.34	0.01	1.01	9.38	1.49	1.60	1.62
1650	3.33	3.32	0.01	1.04	9.94	1.45	1.57	1.58
1700	3.33	3.29	0.04	0.86	10.55	1.42	1.53	1.53
1750	3.30	3.28	0.02	0.90	11.22	1.39	1.49	1.50
1800	3.29	3.27	0.02	0.98	11.95	1.36	1.46	1.46
1850	3.29	3.25	0.04	1.01	12.77	1.33	1.43	1.42
1900	3.28	3.23	0.05	1.01	13.67	1.30	1.39	1.38
1950	3.28	3.22	0.06	1.05	14.70	1.26	1.36	1.33
2000	3.28	3.20	0.08	1.00	15.88	1.22	1.32	1.29
2050	3.27	3.19	0.08	0.94	17.20	1.19	1.28	1.25
2100	3.27	3.19	0.08	1.00	18.85	1.15	1.24	1.20
2150	3.27	3.18	0.09	0.92	20.83	1.11	1.20	1.16
2200	3.26	3.18	0.08	0.88	23.21	1.08	1.16	1.13
2250	3.27	3.18	0.09	0.90	26.45	1.06	1.12	1.09
2300	3.27	3.18	0.09	0.95	31.31	1.05	1.08	1.05
2350	3.28	3.20	0.08	1.03	36.75	1.08	1.04	1.02
2400	3.29	3.22	0.07	1.07	31.56	1.12	1.03	1.03
2450	3.31	3.23	0.08	1.16	26.85	1.17	1.06	1.06
2500	3.34	3.26	0.08	1.27	23.76	1.22	1.11	1.11
2505	3.34	3.26	0.08	1.25	23.47	1.23	1.11	1.11
2510	3.35	3.26	0.09	1.24	23.19	1.23	1.12	1.12
2520	3.35	3.27	0.08	1.27	22.69	1.25	1.13	1.13
2530	3.36	3.28	0.08	1.34	22.24	1.26	1.14	1.14
2540	3.37	3.28	0.09	1.33	21.80	1.27	1.15	1.15
2550	3.37	3.29	0.08	1.33	21.39	1.28	1.16	1.16
2560	3.37	3.29	0.08	1.40	21.00	1.30	1.17	1.16
2570	3.39	3.30	0.09	1.42	20.65	1.31	1.18	1.17
2580	3.41	3.30	0.11	1.43	20.33	1.32	1.19	1.18
2590	3.41	3.31	0.10	1.39	19.97	1.33	1.20	1.19
2600	3.42	3.32	0.10	1.36	19.65	1.35	1.21	1.20
2650	3.46	3.35	0.11	1.54	18.25	1.42	1.27	1.25
2700	3.52	3.41	0.11	1.58	17.02	1.51	1.33	1.31
2750	3.58	3.47	0.11	1.71	16.00	1.59	1.40	1.38
2800	3.66	3.54	0.12	1.80	15.09	1.69	1.47	1.44
2850	3.75	3.61	0.14	1.91	14.29	1.80	1.55	1.51
2900	3.85	3.70	0.15	1.98	13.62	1.92	1.65	1.60
2950	3.95	3.80	0.15	2.14	13.05	2.05	1.75	1.69
3000	4.08	3.91	0.17	2.32	12.56	2.19	1.87	1.79
3050	4.23	4.02	0.21	2.33	12.10	2.35	1.99	1.90
3100	4.38	4.16	0.22	2.41	11.71	2.53	2.12	2.03
3150	4.54	4.29	0.25	2.60	11.37	2.71	2.27	2.16
3200	4.72	4.44	0.28	2.54	11.11	2.92	2.44	2.31
3250	4.92	4.63	0.29	2.49	10.80	3.17	2.59	2.47
3300	5.13	4.83	0.30	2.50	10.55	3.45	2.77	2.67
3350	5.35	5.04	0.31	2.55	10.35	3.73	2.97	2.86
3400	5.58	5.25	0.33	2.55	10.16	4.04	3.17	3.07
3450	5.82	5.48	0.34	2.46	9.97	4.39	3.37	3.29
3500	6.07	5.72	0.35	2.37	9.79	4.78	3.58	3.52

[1]Total Loss = Insertion Loss + 3dB Splitter Loss

2 Way-0° Power Splitter/Combiner BP2U1+

Typical Performance Data

TEST CONDITIONS: INPUT POWER = 0dBm @Temperature = +85°C

FREQ. (MHz)	TOTAL LOSS[1] (dB)		AMP. UNBAL. (dB)	PHASE UNBAL. (deg.)	ISOLATION (dB)	VSWR (:1)		
	S-1	S-2			1-2	S	1	2
1500	3.59	3.58	0.01	0.19	8.99	1.52	1.66	1.69
1550	3.59	3.57	0.02	0.18	9.49	1.49	1.64	1.67
1600	3.58	3.55	0.03	0.16	10.02	1.46	1.61	1.64
1650	3.57	3.55	0.02	0.13	10.61	1.43	1.58	1.61
1700	3.56	3.53	0.03	0.06	11.26	1.40	1.55	1.58
1750	3.55	3.52	0.03	0.13	11.96	1.37	1.52	1.54
1800	3.54	3.51	0.03	0.13	12.75	1.33	1.48	1.51
1850	3.53	3.49	0.04	0.16	13.63	1.29	1.45	1.47
1900	3.53	3.49	0.04	0.15	14.59	1.26	1.41	1.43
1950	3.53	3.48	0.05	0.16	15.70	1.22	1.37	1.39
2000	3.52	3.47	0.05	0.20	16.96	1.18	1.33	1.35
2050	3.52	3.47	0.05	0.20	18.41	1.14	1.29	1.31
2100	3.53	3.47	0.06	0.27	20.19	1.10	1.25	1.27
2150	3.53	3.47	0.06	0.29	22.37	1.06	1.20	1.22
2200	3.54	3.47	0.07	0.31	25.22	1.02	1.16	1.18
2250	3.56	3.48	0.08	0.29	29.59	1.01	1.12	1.14
2300	3.57	3.49	0.08	0.34	38.19	1.05	1.08	1.10
2350	3.60	3.51	0.09	0.39	42.04	1.10	1.05	1.08
2400	3.62	3.53	0.09	0.40	31.26	1.15	1.05	1.09
2450	3.65	3.55	0.10	0.43	26.61	1.20	1.09	1.12
2500	3.69	3.58	0.11	0.42	23.74	1.26	1.14	1.17
2505	3.70	3.59	0.11	0.40	23.46	1.27	1.14	1.17
2510	3.70	3.59	0.11	0.39	23.22	1.28	1.15	1.18
2520	3.71	3.60	0.11	0.40	22.77	1.29	1.16	1.19
2530	3.71	3.61	0.10	0.45	22.35	1.30	1.17	1.20
2540	3.73	3.62	0.11	0.43	21.92	1.32	1.18	1.21
2550	3.74	3.63	0.11	0.43	21.56	1.33	1.19	1.22
2560	3.74	3.63	0.11	0.49	21.20	1.34	1.20	1.24
2570	3.75	3.64	0.11	0.47	20.89	1.36	1.22	1.25
2580	3.77	3.65	0.12	0.43	20.57	1.37	1.23	1.26
2590	3.78	3.66	0.12	0.41	20.24	1.39	1.24	1.27
2600	3.79	3.67	0.12	0.37	19.94	1.40	1.25	1.29
2650	3.84	3.73	0.11	0.52	18.62	1.48	1.32	1.36
2700	3.90	3.80	0.10	0.53	17.48	1.56	1.39	1.43
2750	3.98	3.88	0.10	0.61	16.54	1.65	1.46	1.51
2800	4.06	3.96	0.10	0.67	15.69	1.75	1.55	1.60
2850	4.15	4.05	0.10	0.72	14.97	1.86	1.64	1.69
2900	4.25	4.16	0.09	0.77	14.31	1.97	1.73	1.78
2950	4.36	4.28	0.08	0.90	13.72	2.10	1.82	1.89
3000	4.49	4.41	0.08	1.07	13.19	2.23	1.92	1.99
3050	4.62	4.54	0.08	1.15	12.70	2.38	2.03	2.10
3100	4.77	4.70	0.07	1.34	12.27	2.54	2.15	2.22
3150	4.93	4.86	0.07	1.56	11.84	2.71	2.26	2.34
3200	5.10	5.03	0.07	1.79	11.44	2.89	2.39	2.46
3250	5.29	5.21	0.08	2.10	11.08	3.09	2.52	2.57
3300	5.49	5.40	0.09	2.34	10.75	3.30	2.66	2.70
3350	5.70	5.60	0.10	2.60	10.42	3.52	2.79	2.82
3400	5.92	5.80	0.12	2.86	10.13	3.76	2.94	2.93
3450	6.15	6.01	0.14	3.19	9.86	4.00	3.09	3.05
3500	6.40	6.22	0.18	3.43	9.61	4.27	3.24	3.18

[1]Total Loss = Insertion Loss + 3dB Splitter Loss

2 Way-0° Power Splitter/Combiner BP2U1+

Typical Performance Curves

Total Loss



Total Loss S-1 vs. TEMPERATURE



Amplitude Unbalance vs. TEMPERATURE



Phase Unbalance vs. TEMPERATURE



Isolation 1-2 vs. TEMPERATURE



2 Way-0° Power Splitter/Combiner BP2U1+

Typical Performance Curves

VSWR



VSWR SUM vs. TEMPERATURE



VSWR OUT1 vs. TEMPERATURE



Case Style XX

XX211

Outline Dimensions



PCB Land Pattern



Suggested Layout,
Tolerance to be within ±.002

CASE #	A	B	C	D	E	F	G	H	J	K	L	M	N	P
XX211	.163 (4.14)	.210 (5.33)	.077 (1.96)	.250 (6.35)	.220 (5.59)	.050 (1.27)	.017 (0.43)	.009 (0.23)	.025 (0.64)	.030 (0.76)	-- --	.050 (1.27)	.030 (0.76)	.270 (6.86)

CASE #	Q	R	S	WT. GRAM
XX211	-- --	-- --	-- --	.10

Dimensions are in inches (mm). Tolerances: 2 Pl. ± .03; 3 Pl. ± .015

Notes:

1. Case material: Plastic.
2. Termination finish:
   For RoHS Case Styles: Tin-Silver alloy plate over Nickel barrier. All models, (+) suffix. ⊗
   For RoHS-5 Case Styles: Tin-Lead plate. All models, No (+) suffix.
3. Special Tolerances: Termination width ± .005 inch, termination thickness ± .003 inch.

⊗ Model BP4C+ will be supplied with either Tin finish or Tin-Silver-Nickel finish until Tin finish inventory is depleted.

Mini-Circuits®
INTERNET http://www.minicircuits.com
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661
Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010
Mini-Circuits ISO 9001 & ISO 14001 Certified

Tape & Reel Packaging TR-F16



Tape Width, mm	Device Cavity Pitch, mm	Reel Size, inches	Devices per Reel	
12	8	7	Small quantity standards (see note)	20
				50
				100
				200
				500
			Standard	1000*
		13	Standard	2000**

Note : Please Consult individual model data sheet to determine device per reel availability
* BP models only
** MSW and MSWA models

Mini-Circuits carrier tape materials provide protection from ESD (Electro-Static Discharge) during handling and transportation. Tapes are static dissipative and comply with industry standards EIA-481/EIA-541.

Go to: www.minicircuits.com/pages/pdfs/tape.pdf

Mini-Circuits®
INTERNET http://www.minicircuits.com
P.O. Box 350166, Brooklyn, New York 11235-0003 (718) 934-4500 Fax (718) 332-4661
Distribution Centers NORTH AMERICA 800-654-7949 • 417-335-5935 • Fax 417-335-5945 • EUROPE 44-1252-832600 • Fax 44-1252-837010
Mini-Circuits ISO 9001 & ISO 14001 Certified

THIRD ANGLE PROJECTION

REVISIONS					
REV	ECN No.	DESCRIPTION	DATE	DR	AUTH
OR	M82272	NEW RELEASE	08/06/02	GF	DJ
A	M102713	UPDATED NOTES, ADDED "...WITH SMOBC"	01/16/06	GT	IL

SUGGESTED MOUNTING CONFIGURATION FOR XX211 CASE STYLE, "jm" PIN CONNECTION



NOTES:
1. TRACE WIDTH IS SHOWN FOR ROGERS RO4350B WITH DIELECTRIC THICKNESS 0.020" ± 0.0015". COPPER: 1/2 OZ. EACH SIDE. FOR OTHER MATERIALS TRACE WIDTH MAY NEED TO BE MODIFIED.
2. BOTTOM SIDE OF THE PCB IS CONTINUOUS GROUND PLANE.

DENOTES PCB COPPER LAYOUT WITH SMOBC (SOLDER MASK OVER BARE COPPER)

DENOTES COPPER LAND PATTERN FREE OF SOLDER MASK

UNLESS OTHERWISE SPECIFIED		INITIALS	DATE
DIMENSIONS ARE IN INCHES	DRAWN	GF	07/17/02
TOLERANCES ON:	CHECKED	HY	08/06/02
2 PL DECIMALS ±	APPROVED	DJ	08/06/02
3 PL DECIMALS ± .005			
ANGLES ±			
FRACTIONS ±			

Mini-Circuits®

ASHEETA1.DWG REV:A DATE:01/12/95

Mini-Circuits® 13 Neptune Avenue Brooklyn NY 11235

PL, jm, XX211, BP2, TB-37

SIZE	CODE IDENT	DRAWING NO:	REV:
A	15542	98-PL-053	A

FILE:	SCALE:	SHEET:
98PL053	8:1	1 OF 1

Evaluation Board and Circuit



TB-37



Schematic Diagram

Notes:

1. SMA Female connectors.
2. PCB Material: Rogers RO4350 or equivalent, Dielectric Constant=3.5, Thickness=.020 inch.

Mini-Circuits®

Mini-Circuits

Environmental Specifications ENV12

All Mini-Circuits products are manufactured under exacting quality assurance and control standards, and are capable of meeting published specifications after being subjected to any or all of the following physical and environmental test.

Specification	Test/Inspection Condition	Reference/Spec
Operating Temperature	-40° to 85° C Ambient Environment	Individual Model Data Sheet
Storage Temperature	-65° to 150° C Ambient Environment	Individual Model Data Sheet
Autoclave	15 psig, 100% RH, 121°C, 96 hours	JESD22-A102-C, Condition C
Temperature Cycling	-65° to 150°C, 100 cycles	JESD22-A104
Temperature Humidity	85°C/ 85% RH, 168 hours	JESD22-113
Solder Reflow Heat	Sn-Pb Eutetic Process: 240°C peak Pb-Free Process: 260°C peak	J-STD-020, Table 4-1, 4-2 and 5-2; Figure 5-1
Moisture Sensitivity: Level 1	Bake at 125°C for 24 hours Soak at 85°C/85% RH for 168 hours, Reflow 3 cycles at 240°C peak (Non-RoHS) or 260°C (RoHS)	J-STD-020
Solderability	10X magnification, 95% coverage	JESD22-B102, Method 1: Dip and Look Test
Mechanical Shock	50g, 11 ms, 1/2-sine, 18 shocks: 3 each direction, each of 3 axes	MIL-STD-202, Method 213, Condition A
Vibration (High Frequency)	20g peak, 10-2000 Hz, 12 times in each of three perpendicular directions (total 36)	MIL-STD-202, Method 204, Condition D