

INTERNATIONAL STANDARD

IEC
60099-4

Edition 2.1
2006-07

Edition 2:2004 consolidated with amendment 1:2006

Surge arresters –

Part 4: Metal-oxide surge arresters without gaps for a.c. systems

© IEC 2006 Copyright - all rights reserved

No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the publisher.

International Electrotechnical Commission, 3, rue de Varembe, PO Box 131, CH-1211 Geneva 20, Switzerland
Telephone: +41 22 919 02 11 Telefax: +41 22 919 03 00 E-mail: inmail@iec.ch Web: www.iec.ch



Commission Electrotechnique Internationale
International Electrotechnical Commission
Международная Электротехническая Комиссия

CONTENTS

FOREWORD.....	13
INTRODUCTION.....	17
1 Scope.....	19
2 Normative references	19
3 Terms and definitions	21
4 Identification and classification	37
4.1 Arrester identification	37
4.2 Arrester classification	39
5 Standard ratings and service conditions	39
5.1 Standard rated voltages	39
5.2 Standard rated frequencies	39
5.3 Standard nominal discharge currents	39
5.4 Service conditions	41
6 Requirements	41
6.1 Insulation withstand of the arrester housing.....	41
6.2 Reference voltage	43
6.3 Residual voltages.....	43
6.4 Internal partial discharges	43
6.5 Seal leak rate	43
6.6 Current distribution in a multi-column arrester.....	43
6.7 Thermal stability.....	43
6.8 Long-duration current impulse withstand	43
6.9 Operating duty.....	45
6.10 Power-frequency voltage versus time characteristics of an arrester	51
6.11 Short-circuit.....	51
6.12 Disconnecter	51
6.13 Requirements for auxiliary equipment such as grading components	51
6.14 Mechanical loads.....	51
6.15 Electromagnetic compatibility	53
6.16 End of life.....	53
6.17 Lightning impulse discharge capability	53
7 General testing procedure	53
7.1 Measuring equipment and accuracy	53
7.2 Reference voltage measurements	55
7.3 Test samples	55
8 Type tests (design tests)	55
8.1 General	55
8.2 Insulation withstand tests on the arrester housing	59
8.3 Residual voltage tests	61
8.4 Long-duration current impulse withstand test.....	67
8.5 Operating duty tests	71
8.6 Tests of arrester disconnectors/fault indicators.....	93
8.7 Short-circuit tests	97
8.8 Internal partial discharge tests	117

8.9	Test of the bending moment	117
8.10	Environmental tests	119
8.11	Seal leak rate test	121
8.12	Radio interference voltage (RIV) test	123
9	Routine tests and acceptance tests	125
9.1	Routine tests	125
9.2	Acceptance tests	127
10	Test requirements on polymer-housed surge arresters	131
10.1	Scope	131
10.2	Normative references	131
10.3	Terms and definitions	131
10.4	Identification and classification	131
10.5	Standard ratings and service conditions	131
10.6	Requirements	131
10.7	General testing procedure	133
10.8	Type tests (design tests)	133
11	Test requirements on gas-insulated metal enclosed arresters (GIS-arresters)	165
11.1	Scope	165
11.2	Normative references	165
11.3	Terms and definitions	165
11.4	Identification and classification	165
11.5	Standard ratings and service conditions	165
11.6	Requirements	167
11.7	General testing procedures	169
11.8	Type tests (design tests)	169
11.9	Routine tests	179
11.10	Test after erection on site	179
12	Separable and dead-front arresters	185
12.1	Scope	185
12.2	Normative references	185
12.3	Terms and definitions	185
12.4	Identification and classification	185
12.5	Standard ratings and service conditions	185
12.6	Requirements	185
12.7	General testing procedure	187
12.8	Type tests (design tests)	187
12.9	Routine tests and acceptance tests	199
13	Liquid-immersed arresters	199
13.1	Scope	199
13.2	Normative references	199
13.3	Terms and definitions	199
13.4	Identification and classification	199
13.5	Standard ratings and service conditions	201
13.6	Requirements	201
13.7	General testing procedure	201
13.8	Type tests (design tests)	201
13.9	Routine tests and acceptance tests	217

Annex A (normative) Abnormal service conditions	219
Annex B (normative) Test to verify thermal equivalency between complete arrester and arrester section	221
Annex C (normative) Requirements for high lightning duty arresters for voltage range 1 kV to 52 kV	223
Annex D (normative) Procedure to verify the power-frequency voltage-versus-time characteristics of an arrester	229
Annex E (informative) Guide to selection of line discharge class	233
Annex F (normative) Artificial pollution test with respect to the thermal stress on porcelain-housed multi-unit metal-oxide surge arresters	237
Annex G (informative) Typical information given with enquiries and tenders	267
Annex H (informative) Typical circuit for high current impulse operating duty test (see 8.5.4)	273
Annex I (informative) Typical circuit for a distributed constant impulse generator for the long duration current impulse withstand test (see 8.4)	277
Annex J (informative) Typical maximum residual voltages	279
Annex K (informative) Ageing test procedure – Arrhenius law – Problems with higher temperatures	281
Annex L (informative) Guide for the determination of the voltage distribution along metal-oxide surge arresters	285
Annex M (normative) Mechanical considerations	301
Annex N (normative) Test procedure to determine the lightning impulse discharge capability	309
Bibliography	315
Figure 1 – Operating duty test on 10 000 A line discharge Class 1, 5 000 A, 2 500 A and 1 500 A arresters (see 8.5.4)	47
Figure 2 – Operating duty test on 10 000 A arresters line discharge Classes 2 and 3 and 20 000 A arresters line discharge Classes 4 and 5 (see 8.5.5)	49
Figure 3 – Power losses of the arrester at elevated temperatures versus time	75
Figure 4 – Thermal stability test on 10 000 A line discharge Class 1, 5 000 A, 2 500 A and 1 500 A arresters	129
Figure 5 – Thermal stability test on 10 000 A arresters line discharge Classes 2 and 3 and 20 000 A arresters line discharge Classes 4 and 5	131
Figure 6 – Thermomechanical test	153
Figure 7 – Example of the test arrangement for the thermomechanical test and direction of the cantilever load	155
Figure 8 – Water immersion	157
Figure 9 – Example of an accelerated weather ageing cycle under operating voltage (according to IEC 61109)	163
Figure 10 – Another example of an accelerated weather ageing cycle	165
Figure 11 – Test set-up for insulation withstand test of separable arresters in insulating housings	189

Figure 12 – Power losses of arrester at elevated temperatures versus time	207
Figure 13 – Examples of arrester units	113
Figure 14 – Short-circuit test setup	115
Figure 15 – Example of a test circuit for re-applying pre-failing circuit immediately before applying the short-circuit test current	117
Figure C.1 – Operating duty test on 20 000 A high lightning duty arresters	227
Figure C.2 – Thermal stability test on 20 000 A high lightning duty arresters (see 9.2.2)	227
Figure D.1 – Test on 10 000 A line discharge class 1, 5 000 A, 2 500 A and 1 500 A arresters	229
Figure D.2 – Test on 20 000 A high lightning duty arresters	231
Figure D.3 – Test on 10 000 A arresters, line discharge Classes 2 and 3 and 20 000 A arresters, line discharge Classes 4 and 5	231
Figure E.1 – Specific energy in kJ per kV rating dependant on the ratio of switching impulse residual voltage (U_a) to the r.m.s. value of the rated voltage U_r of the arrester	235
Figure F.1 – Flow-chart showing the procedure for determining the preheating of a test sample	243
Figure H.1 – Typical test circuit diagram for high current impulse operating duty test	273
Figure I.1 – Typical distributed constant impulse generator for the long-duration impulse test	277
Figure L.1 – Typical three-phase arrester installation	295
Figure L.2 – Simplified multi-stage equivalent circuit of an arrester	295
Figure L.3 – Geometry of arrester model	297
Figure L.4 – Example of voltage-current characteristic of metal-oxide resistors at +20 °C in the leakage current region	299
Figure L.5 – Calculated voltage stress along the resistor column in case B	299
Figure M.1 – Bending moment – multi-unit surge arrester	301
Figure M.2 – Surge arrester unit	305
Figure M.3 – Surge arrester dimensions	307
Table 1 – Arrester classification	39
Table 2 – Steps of rated voltages	39
Table 3 – Arrester type tests ^a	57
Table 4 – Peak currents for switching impulse residual voltage test	67
Table 5 – Parameters for the line discharge test on 20 000 A and 10 000 A arresters	69
Table 6 – Requirements for the long-duration current impulse test on 5 000 A and 2 500 A arresters	71
Table 7 – Determination of elevated rated and continuous operating voltages	77
Table 8 – Requirements for high current impulses	87
Table 14 – Test requirements	109
Table 15 – Required currents for short-circuit tests	111

Table 8 – Requirements for high current impulses	139
Table 9 – 10 000 A and 20 000 A three-phase GIS-arresters – Required withstand voltages	181
Table 10 – 1 500 A, 2 500 A and 5 000 A three – phase – GIS arresters – Required withstand voltages	183
Table 11 – Insulation withstand test voltages for unscreened separable arresters.....	189
Table 12 – Insulation withstand test voltages for dead-front arresters or separable arresters in a screened housing.....	189
Table 8 – Requirements for high current impulses	193
Table 13 – Partial discharge test values for separable and dead-front arresters.....	199
Table 7 – Determination of elevated rated and continuous operating voltages	207
Table 8 – Requirements for high current impulses	209
Table C.1 – Test requirements on 20 000 A high lightning duty arresters ^a	225
Table F.1 – Mean external charge for different pollution severities.....	245
Table F.2 – Characteristic of the sample used for the pollution test.....	247
Table F.3 – Requirements for the device used for the measurement of the charge.....	249
Table F.4 – Requirements for the device used for the measurement of the temperature.....	251
Table F.5 – Calculated values of $\Delta T_{z \max}$ for the selected example.....	263
Table F.6 – Results of the salt fog test for the selected example.....	263
Table F.7 – Calculated values of ΔT_z and of T_{OD} after 5 cycles for the selected example.....	265
Table F.8 – Calculated values of ΔT_z and of T_{OD} after 10 cycles for the selected example.....	265
Table J.1 – Residual voltages for 20 000 A and 10 000 A arresters in per unit of rated voltage.....	279
Table J.2 – Residual voltages for 5 000 A, 2 500 A and 1 500 A arresters in per unit of rated voltage.....	279
Table K.1 – Minimum demonstrated lifetime prediction	281
Table K.2 – Relationship between test durations at 115 °C and equivalent time at upper limit of ambient temperature.....	283
Table L.1 – Results from example calculations	293

INTERNATIONAL ELECTROTECHNICAL COMMISSION

SURGE ARRESTERS –

Part 4: Metal-oxide surge arresters without gaps for a.c. systems

FOREWORD

- 1) The International Electrotechnical Commission (IEC) is a worldwide organization for standardization comprising all national electrotechnical committees (IEC National Committees). The object of IEC is to promote international co-operation on all questions concerning standardization in the electrical and electronic fields. To this end and in addition to other activities, IEC publishes International Standards, Technical Specifications, Technical Reports, Publicly Available Specifications (PAS) and Guides (hereafter referred to as “IEC Publication(s)”). Their preparation is entrusted to technical committees; any IEC National Committee interested in the subject dealt with may participate in this preparatory work. International, governmental and non-governmental organizations liaising with the IEC also participate in this preparation. IEC collaborates closely with the International Organization for Standardization (ISO) in accordance with conditions determined by agreement between the two organizations.
- 2) The formal decisions or agreements of IEC on technical matters express, as nearly as possible, an international consensus of opinion on the relevant subjects since each technical committee has representation from all interested IEC National Committees.
- 3) IEC Publications have the form of recommendations for international use and are accepted by IEC National Committees in that sense. While all reasonable efforts are made to ensure that the technical content of IEC Publications is accurate, IEC cannot be held responsible for the way in which they are used or for any misinterpretation by any end user.
- 4) In order to promote international uniformity, IEC National Committees undertake to apply IEC Publications transparently to the maximum extent possible in their national and regional publications. Any divergence between any IEC Publication and the corresponding national or regional publication shall be clearly indicated in the latter.
- 5) IEC provides no marking procedure to indicate its approval and cannot be rendered responsible for any equipment declared to be in conformity with an IEC Publication.
- 6) All users should ensure that they have the latest edition of this publication.
- 7) No liability shall attach to IEC or its directors, employees, servants or agents including individual experts and members of its technical committees and IEC National Committees for any personal injury, property damage or other damage of any nature whatsoever, whether direct or indirect, or for costs (including legal fees) and expenses arising out of the publication, use of, or reliance upon, this IEC Publication or any other IEC Publications.
- 8) Attention is drawn to the Normative references cited in this publication. Use of the referenced publications is indispensable for the correct application of this publication.
- 9) Attention is drawn to the possibility that some of the elements of this IEC Publication may be the subject of patent rights. IEC shall not be held responsible for identifying any or all such patent rights.

International Standard 60099-4 has been prepared by IEC technical committee 37: Surge arresters.

This edition includes the following significant technical changes with respect to the previous edition.

- Clauses 1, 2 and 3 contain common subclauses that cover all arrester types. Clauses 4 to 9 contain subclauses that apply to porcelain-housed arresters. To a great extent, the content of Clauses 4 to 9 also applies to arrester types other than porcelain-housed. Any exceptions that apply to polymer-housed, GIS, separable and dead-front, and liquid-immersed arresters are included in Clauses 10 to 13 as entire subclauses, not as parts of subclauses. That is, if any subclause of Clauses 4 to 9 does not apply in its entirety to a particular type of arrester, then a replacement subclause is given in its entirety in the appropriate Clauses 10, 11, 12, or 13. This avoids the necessity for the user of the document to judgewhich part of a clause has been amended.

- Table 1 has been modified. The previous Table 1 included references to subclauses for type testing. Such references are really not appropriate in Clause 4 and have been transferred to a new table in Clause 8.
- Clauses 6, 8, 11, 12 and 13: modifications have been made to short-circuit requirements.
- Requirements of Clause 13 (mechanical considerations) have been incorporated into Clauses 5, 6, 8, 10, 11, 12 and 13, and Annex A of this new edition.

This consolidated version of IEC 60099-4 consists of the second edition (2004) [documents 37/298/FDIS and 37/300/RVD] and its amendment 1 (2006) [documents 37/324/FDIS and 37/325/RVD].

The technical content is therefore identical to the base edition and its amendment and has been prepared for user convenience.

It bears the edition number 2.1.

A vertical line in the margin shows where the base publication has been modified by amendment 1.

This publication has been drafted in accordance with the ISO/IEC Directives, Part 2.

The committee has decided that the contents of the base publication and its amendments will remain unchanged until the maintenance result date indicated on the IEC web site under "<http://webstore.iec.ch>" in the data related to the specific publication. At this date, the publication will be

- reconfirmed,
- withdrawn,
- replaced by a revised edition, or
- amended.

INTRODUCTION

This part of IEC 60099 presents the minimum criteria for the requirements and testing of gapless metal-oxide surge arresters that are applied to a.c. power systems.

Arresters covered by this standard are commonly applied to live/front overhead installations in place of the non-linear resistor-type gapped arresters covered in IEC 60099-1.

Withdrawn

SURGE ARRESTERS –

Part 4: Metal-oxide surge arresters without gaps for a.c. systems

1 Scope

This part of IEC 60099 applies to non-linear metal-oxide resistor type surge arresters without spark gaps designed to limit voltage surges on a.c. power circuits.

2 Normative references

The following referenced documents are indispensable for the application of this document. For dated references, only the edition cited applies. For undated references, the latest edition of the referenced document (including any amendments) applies.

IEC 60060-1:1989, *High-voltage test techniques – Part 1: General definitions and test requirements*

IEC 60060-2:1994, *High-voltage test techniques – Part 2: Measuring systems*

IEC 60068-2-11:1981, *Environmental testing – Part 2: Tests – Test Ka: Salt mist*

IEC 60068-2-14:1984, *Environmental testing – Part 2: Tests – Test N: Change of temperature*

IEC 60068-2-42:2003, *Environmental testing – Part 2-42: Tests – Test Kc: Sulphur dioxide test for contacts and connections*

IEC 60071-1:1993, *Insulation co-ordination – Part 1: Definitions, principles and rules*

IEC 60071-2:1996, *Insulation co-ordination – Part 2: Application guide*

IEC 60270:2000, *High-voltage test techniques – Partial discharge measurements*

IEC 60507:1991, *Artificial pollution tests on high-voltage insulators to be used on a.c. systems*

IEC 60815:1986, *Guide for the selection of insulators in respect of polluted conditions*

IEC 61109:1992, *Composite insulators for a.c. overhead lines with a nominal voltage greater than 1 000 V – Definitions, test methods and acceptance criteria*

IEC 61166:1993, *High-voltage alternating current circuit-breakers – Guide for seismic qualification of high-voltage alternating current circuit-breakers*

IEC 61330:1995, *High-voltage/low-voltage prefabricated substations*

IEC 62271-200:2003, *High-voltage switchgear and controlgear – Part 200: A.C. metal-enclosed switchgear and controlgear for rated voltages above 1 kV and up to and including 52 kV*

IEC 62271-203:2003, *High-voltage switchgear and controlgear – Part 203: Gas-insulated metal-enclosed switchgear for rated voltages above 52 kV*

CISPR 16-1:1999, *Specification for radio disturbance and immunity measuring apparatus and methods – Part 1: Radio disturbance and immunity measuring apparatus*

CISPR 18-2:1986, *Radio interference characteristics of overhead power lines and high-voltage equipment – Part 2: Methods of measurement and procedure for determining limits*

Withdrawn