MLHVDC-LCS-ECI-DD-HA-0102-001A

30-B003701S-N0102-001

巴基斯坦默蒂亚里—拉合尔±660kV 直流输电工程
拉合尔±660kV 换流站工程

±660kV HVDC Project from Matiari to Lahore in Pakistan

±660kV Lahore Converter Station

施工图设计
Detail Design

暖 通 部 分

HVAC Part

暖通设备及材料清册

List of HVAC Equipment and Major Materials

a) 中国电力技术装备有限公司
China Electric Power Equipment and Technology Co., Ltd.
b) 中国电力工程顾问集团华东电力设计院有限公司
East China Electric Power Design Institute of China Power Engineering Consulting Group
April, 2019

拉合尔±660kV 换流站 工程

施工图 阶段

中国电力工程顾问集团华东电力设计院有限公司

工程设计综合资质甲级 A131000025 工程勘察综合类甲级 B131000025

卷册检索号	30	B003701S	N0102
文本编号	B003701S	N0102	001

版号	日期	状态	修改内容摘要	设计	校核	审核	批准
0	201904	CFC	新制				

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任。

批准	2019.04	暖通设备及材料清册 List of HVAC Equipment and Major Materials		
审核	2019.04			
校核	2019.04			
设计	2019.04			
日期 2019.04	状态 CFC	版号	A	

序号	名称	规格及技术参数	单位	数量	备注
一	极1阀厅通风及空调 30-B003701S-N0203				
1	风冷热泵机组	LSRF500A，制冷设计工况：室外空气干球温度为tw=48℃,冷冻水供回水温度为7/12℃；制热设计工况：室外空气干球温度为tw=3.9℃，热水供回水温度为45/40℃。 制冷量：500kW，制热量：520kW，制冷剂：R134a 总功率：243kW/380V,制冷性能系数≥2.70, 外形尺寸：4800x2100x2547(H)mm，重量：6040kg	台	2	极1阀厅室外
2	离心水泵	GLC100-160，流量：94m³/h，扬程：352kPa 转速：2900r/min，功率：15kW，电源：380V/50Hz 设计压力:1.0MPa。配减震台座。	台	2	极1阀厅室外
3	定压补水机组	SXBY-600，膨胀罐DN600，全容积：0.35m³，补水箱有效容积：1.25m³,补水泵2台，流量：2.5m³/h，扬程：200kPa 带水位仪，泄水电磁阀，补水电磁阀，配套电控柜 底座尺寸：2800x1100mm，高度：1900mm，重量：1900kg	台	1	极1阀厅室外
4	全自动清洗水过滤器	设计流量：94m³/h，阻力：0.01MPa 连接方式：法兰连接,连接管径：DN150 耐压：1.6MPa	台	1	极1阀厅室外
5	水处理器	激光负离子智能型水处理器 设计流量：94m³/h，阻力：0.01MPa 连接方式：法兰连接,连接管径：DN150 耐压：1.6MPa	台	1	极1阀厅室外
6	组合式 空气处理机组	ZK50型，风量：50000m³/h,制冷量:500kW,电加热：150kW，加湿量：150kg/h,蒸发冷却加湿量:500kg/h。 包括回风机段、排风新风调节段、初效过滤段、中效过滤器、冷却加热盘管段、蒸发冷却段、喷雾加湿段、辅助电加热段、送风机段、亚高效过滤段、消声段、电动风阀及必要的检修段 送/回风机机外余压:350/250Pa。 输入功率：56.5kW,380V/50Hz。 尺寸：14300(L)x2400(W)x2535(H)mm	台	2	极1阀厅室外
7	排烟风机	型号:HTF-D.No6.5,转速：960r/min， 风量：14580m³/h，风压190Pa，电源380V50Hz,功率2.2kW	台	2	
8	全自动防火阀	常态开启，输入DC24V信号或70℃熔断关闭，输出联动及反馈信号，电动复位			
		尺寸：1800x1250mm	只	1	
		尺寸：1500x1000mm	只	1	
		尺寸：1250x800mm	只	1	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
9	全自动排烟防火阀	常态开启，输入DC24V信号或280℃熔断关闭，输出联动及反馈信号，电动复位, 尺寸：Ø700 mm	只	2	
10	电动风阀	尺寸：Ø700 mm, 220V50Hz	只	2	
11	对开式多叶调节阀	尺寸：1500x1000mm	只	1	
		尺寸：1250x800mm	只	1	
12	单层防雨防沙百叶	铝合金制作,2200x800(H),内侧带不锈钢丝网	只	2	组合机组排风口
		铝合金制作,2200x1300(H),内侧带不锈钢丝网	只	2	组合机组新风口
13	单层防雨百叶	铝合金制作,1000x700(H),内侧带不锈钢丝网	只	2	排烟风机出口
14	固定叶片回风口	FC-XB型，铝合金制作,1800x1250mm	只	1	
15	双层百叶送风口	FC-SB型，不锈钢制作,900x600mm，带FK-11风量调节阀	只	6	
16	球形送风口	不锈钢制作,Ø400mm，带电动风量调节阀	只	6	
17	风管	镀锌钢板，厚度：0.75~1.2mm	m^2	560	
		镀锌钢板，厚度：2.0mm	m^2	10	
18	防火软接	A级不燃,硅橡胶布	m^2	5	
19	风管保温材料	离心玻璃棉，厚50mm，密度64kg/m³，外敷牛皮纸铝箔，导热系数0.032W/m.K	m^2	560	
20	电动切换蝶阀	DN150，工作压力：1.6MPa，开关型，电源：AC220V/50Hz	只	4	
21	电动三通调节阀	DN125，工作压力：1.6MPa，调节型，电源：AC220V/50Hz	只	2	
22	蝶阀	D41X-16型，DN150，法兰连接	只	13	
23	截止阀	J41H-16型，DN150，法兰连接	只	2	
		J41H-16型，DN125，法兰连接	只	2	
		J11H-16型，DN25，螺纹连接	只	4	
24	球阀	Q41F-16型，DN50，法兰连接	只	3	
		Q11F-16型，DN40，螺纹连接	只	1	
		Q11F-16型，DN20，螺纹连接	只	8	
25	止回阀	H41X-16型，DN150，法兰连接	只	2	
26	自动放气阀	DN20, PN=1.6MPa, 耐温>120℃,带DN20球阀	只	7	
27	压力表	Y-100T型,压力范围：0～1.6MPa,配仪表阀和弹簧管	只	17	
28	温度计	WNY-12型,PN=1.6MPa,适用温度0～100℃	只	8	
29	橡胶软接管	DN150，工作压力：1.6MPa，法兰连接	只	8	
		DN65，工作压力：1.6MPa，法兰连接	只	8	
30	不锈钢无缝钢管	D159x4.5	m	80	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
		D133x4	m	10	
		D76x3	m	20	
31	不锈钢焊接钢管	DN50	m	20	
		DN40	m	30	
		DN25	m	10	
32	水管保温材料	闭孔橡塑海棉（难燃B1级)，K=0.032W/m.K,厚40mm			
		DN150	m	80	
		DN125	m	10	
		DN65	m	20	
		DN50	m	20	
		DN40	m	30	
		DN25	m	10	
		保温板材	m^2	20	用于过滤器，阀门和水泵等
33	铝皮	1.00mm厚	m^2	700	
34	橡胶减震垫	120x120x21mm，每块2层，上下设5mm厚钢板	只	16	
35	安装材料	包括管道支吊架、抗震支吊架、垫圈、螺栓等	套	1	
36	配电及监控系统	包括配电柜、控制柜、传感器、控制和动力电缆等	套	1	
二	**极2阀厅通风及空调** 30-B003701S-N0204				
1	风冷热泵机组	LSRF500A，制冷设计工况：室外空气干球温度为tw=48℃,冷冻水供回水温度为7/12℃；制热设计工况：室外空气干球温度为tw=3.9℃，热水供回水温度为45/40℃。 制冷量：500kW，制热量：520kW，制冷剂：R134a 总功率：243kW/380V,制冷性能系数≥2.70, 外形尺寸：4800x2100x2547(H)mm，重量：6040kg	台	2	极2阀厅室外
2	离心水泵	GLC100-160，流量：94m³/h，扬程：352kPa 转速：2900r/min，功率：15kW，电源：380V/50Hz 设计压力:1.0MPa。配减震台座。	台	2	极2阀厅室外
3	定压补水机组	SXBY-600，膨胀罐DN600，全容积：0.35m³，补水箱有效容积：1.25m³,补水泵2台，流量：2.5m³/h，扬程：200kPa 带水位仪，泄水电磁阀，补水电磁阀，配套电控柜 底座尺寸：2800x1100mm，高度：1900mm，重量：1900kg	台	1	极2阀厅室外
4	全自动清洗水过滤器	设计流量：94m³/h，阻力：0.01MPa 连接方式：法兰连接,连接管径：DN150 耐压：1.6MPa	台	1	极2阀厅室外
5	水处理器	激光负离子智能型水处理器 设计流量：94m³/h，阻力：0.01MPa 连接方式：法兰连接,连接管径：DN150 耐压：1.6MPa	台	1	极2阀厅室外

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
6	组合式 空气处理机组	ZK50型，风量：50000m³/h,制冷量:500kW,电加热：150kW， 加湿量：150kg/h,蒸发冷却加湿量:500kg/h。 包括回风机段、排风新风调节段、初效过滤段、中效过滤器、 冷却加热盘管段、蒸发冷却段、喷雾加湿段、辅助电加热段、 送风机段、亚高效过滤段、消声段、电动风阀及必要的检修段 送/回风机机外余压:350/250Pa。 输入功率：56.5kW,380V/50Hz。 尺寸：14300(L)x2400(W)x2535(H)mm	台	2	极2阀厅室外
7	排烟风机	型号:HTF-D.No6.5,转速：960r/min， 风量：14580m³/h，风压190Pa，电源380V50Hz,功率2.2kW	台	2	
8	全自动防火阀	常态开启，输入DC24V信号或70℃熔断关闭，输出联动及 反馈信号，电动复位			
		尺寸：1800x1250mm	只	1	
		尺寸：1500x1000mm	只	1	
		尺寸：1250x800mm	只	1	
9	全自动排烟防火阀	常态开启，输入DC24V信号或280℃熔断关闭，输出联动及 反馈信号，电动复位, 尺寸：Ø700 mm	只	2	
10	电动风阀	尺寸：Ø700 mm, 220V50Hz	只	2	
11	对开式多叶调节阀	尺寸：1500x1000mm	只	1	
		尺寸：1250x800mm	只	1	
12	单层防雨防沙百叶	铝合金制作,2200x800(H),内侧带不锈钢丝网	只	2	组合机组排风口
		铝合金制作,2200x1300(H),内侧带不锈钢丝网	只	2	组合机组新风口
13	单层防雨百叶	铝合金制作,1000x700(H),内侧带不锈钢丝网	只	2	排烟风机出口
14	固定叶片回风口	FC-XB型，铝合金制作,1800x1250mm	只	1	
15	双层百叶送风口	FC-SB型，不锈钢制作,900x600mm，带FK-11风量调节阀	只	6	
16	球形送风口	不锈钢制作,Ø400mm，带电动风量调节阀	只	6	
17	风管	镀锌钢板，厚度：0.75~1.2mm	m^2	560	
		镀锌钢板，厚度：2.0mm	m^2	10	
18	防火软接	A级不燃,硅橡胶布	m^2	5	
19	风管保温材料	离心玻璃棉，厚50mm，密度64kg/m³，外敷牛皮纸铝箔， 导热系数0.032W/m.K	m^2	560	
20	电动切换蝶阀	DN150，工作压力：1.6MPa，开关型，电源：AC220V/50Hz	只	4	
21	电动三通调节阀	DN125，工作压力：1.6MPa，调节型，电源：AC220V/50Hz	只	2	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
22	蝶阀	D41X-16型，DN150，法兰连接	只	13	
23	截止阀	J41H-16型，DN150，法兰连接	只	2	
		J41H-16型，DN125，法兰连接	只	2	
		J11H-16型，DN25，螺纹连接	只	4	
24	球阀	Q41F-16型，DN50，法兰连接	只	3	
		Q11F-16型，DN40，螺纹连接	只	1	
		Q11F-16型，DN20，螺纹连接	只	8	
25	止回阀	H41X-16型，DN150，法兰连接	只	2	
26	自动放气阀	DN20, PN=1.6MPa, 耐温>120℃,带DN20球阀	只	7	
27	压力表	Y-100T型,压力范围：0～1.6MPa,配仪表阀和弹簧管	只	17	
28	温度计	WNY-12型,PN=1.6MPa,适用温度0～100℃	只	8	
29	橡胶软接管	DN150，工作压力：1.6MPa，法兰连接	只	8	
		DN65，工作压力：1.6MPa，法兰连接	只	8	
30	不锈钢无缝钢管	D159x4.5	m	80	
		D133x4	m	10	
		D76x3	m	20	
31	不锈钢焊接钢管	DN50	m	20	
		DN40	m	30	
		DN25	m	10	
32	水管保温材料	闭孔橡塑海棉（难燃B1级)，K=0.032W/m.K,厚40mm			
		DN150	m	80	
		DN125	m	10	
		DN65	m	20	
		DN50	m	20	
		DN40	m	30	
		DN25	m	10	
		保温板材	m^2	20	用于过滤器，阀门和水泵等
33	铝皮	1.00mm厚	m^2	700	
34	橡胶减震垫	120x120x21mm，每块2层，上下设5mm厚钢板	只	16	
35	安装材料	包括管道支吊架、抗震支吊架、垫圈、螺栓等	套	1	
36	配电及监控系统	包括配电柜、控制柜、传感器、控制和动力电缆等	套	1	
三	**主控楼通风及空调** 30-B003701S-N0201				

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
1	风冷热泵机组	LSRF440A，制冷设计工况：室外空气干球温度为tw=43℃,冷冻水供回水温度为7/12℃；制热设计工况：室外空气干球温度为tw=3.9℃，热水供回水温度为45/40℃。 制冷量：442kW，制热量：491kW，制冷剂：R134a 总功率：225kW/380V,制冷性能系数≥1.96, 外形尺寸：4800x2100x2547(H)mm，重量：5240kg	台	2	主控楼屋面
2	离心水泵	GLC80-200，流量：83m³/h，扬程：300kPa 转速：2900r/min，功率：11kW，电源：380V/50Hz 设计压力:1.0MPa。配减震台座。	台	2	主控楼屋面
3	定压补水机组	SXBY-600，膨胀罐DN600，全容积：0.35m³，补水箱有效容积：1.25m³,补水泵2台，流量：2.5m³/h，扬程：200kPa 带水位仪，泄水电磁阀，补水电磁阀，配套电控柜 底座尺寸：2800x1100mm，高度：1900mm，重量：1900kg	台	1	主控楼屋面
4	全自动清洗水过滤器	设计流量：83m³/h，阻力：0.01MPa 连接方式：法兰连接,连接管径：DN125 耐压：1.6MPa	台	1	主控楼屋面
5	水处理器	激光负离子智能型水处理器 设计流量：83m³/h，阻力：0.01MPa 连接方式：法兰连接,连接管径：DN125 耐压：1.6MPa	台	1	主控楼屋面
6	组合式 空气处理机组	ZK10型，风量：10000m³/h,制冷量：45kW,制热量：10kW，电加热：10kW，加湿量：35kg/h。机外余压:250Pa。 包括新回风混合段、初中效过滤段、加热表冷段、加湿挡水段、电加热段、送风机段。输入功率：18kW,380V/50Hz。 尺寸：4000(L)x1200(W)x1305(H)mm	台	2	±0.00m空调设备间
7	组合式 空气处理机组	ZK18型，风量：17000m³/h,制冷量：70kW,制热量：25kW，电加热：25kW，加湿量：55kg/h。机外余压:250Pa。 包括新回风混合段、初中效过滤段、加热表冷段、加湿挡水段、电加热段、送风机段、消声段。输入功率：38.5kW,380V/50Hz。 尺寸：5900(L)x1500(W)x1605(H)mm	台	2	极1阀厅室外
8	组合式 空气处理机组	ZK55型，风量：54000m³/h,制冷量：225kW,制热量：60kW，电加热：60kW，加湿量：180kg/h。机外余压:送风机 350Pa，回风机 250Pa。包括回风机段、排风段、新回风混合段、初中效过滤段、加热表冷段、加湿挡水段、电加热段、送风机段。 输入功率：111kW，380V/50Hz。 尺寸：9000(L)x3300(W)x2135(H)mm	台	2	6.00m空调设备间

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
9	组合式 空气处理机组	ZK18型，风量：18000m³/h,制冷量：85kW,制热量：25kW， 电加热：25kW，加湿量：65kg/h。机外余压:送风机 200Pa， 回风机 100Pa。包括回风机段、排风段、新回风混合段、初中 效过滤段、加热表冷段、加湿挡水段、电加热段、送风机段、 消声段。 输入功率：49kW，380V/50Hz。 尺寸：9400(L)x1500(W)x1605(H)mm	台	2	主控楼屋面
10	蒸发冷却 空气处理机组	ZKX18型，湿膜加湿，风量：18000m³/h,加湿量：180kg/h。 机外余压:250Pa。包括新风段、初中效过滤段、加湿挡水段、 送风机段。输入功率：13.4kW,380V/50Hz。 尺寸：2700(L)x1500(W)x2810(H)mm	台	2	±0.00m空调设备间
11	蒸发冷却 空气处理机组	ZKX08型，湿膜加湿，风量：8000m³/h,加湿量：75kg/h。 机外余压:250Pa。包括新风段、初中效过滤段、加湿挡水段、 送风机段、消声段。输入功率：8kW,380V/50Hz。 尺寸：4800(L)x1200(W)x1105(H)mm	台	4	极1阀厅室外 极2阀厅室外
12	新风 空气处理机组	GXDB2.0型，风量：2000m³/h,制冷量：29kW,制热量：22kW， 机外余压:250Pa。输入功率：3.5kW,380V/50Hz。 尺寸：900(L)x1300(W)x510(H)mm，配电动风阀	台	1	12.00m走道
13	风机盘管	型号:FP-136WA,形式：卧式暗装高静压型，带回风箱（后回风） 标准工况下：风量1360m³/h，出口静压30Pa，制冷量7.92kW 制热量13.59kW， 电源220V50Hz,功率150W,水阻40kPa 噪声47dB(A),配:恒温器、三速开关、三通电动阀	台	13	6.00m检修备品库 12.00m层会议室、资料室、 休息室、办公室、礼拜室
14	防爆型 分体壁挂式空调	KT3F-35GW/T13型，T3工况，制冷量：3.5kW,制冷功率：1.2kW， 制热量：3.9kW，制热功率：1.2kW，电源220V/50Hz EER=2.92，配冷媒管和电缆，长度为：20m。 防爆等级为ExdIICT1	台	8	各蓄电池室
15	方形轴流风机	型号:T35-11-5.6,转速：1450r/min， 风量：7724m³/h，风压83Pa，电源380V50Hz,功率0.37kW 出口带出风防雨百叶 (风机留孔尺寸：800x800mm)	台	10	站公用控制保护设备室 通信机房 交流阀组配电间 阀冷却设备间
16	方形轴流风机	型号:T35-11-4,转速：1450r/min， 风量：4263m³/h，风压97Pa，电源380V50Hz,功率0.18kW 出口带出风防雨百叶 (风机留孔尺寸：600x600mm)	台	6	换流变直流场接口设备室 阀冷控制保护设备室 控制保护设备室
18	方形轴流风机	型号:T35-11-3.55,转速：1450r/min， 风量：2737m³/h，风压71Pa，电源380V50Hz,功率0.12kW 出口带出风防雨百叶 (风机留孔尺寸：600x600mm)	台	3	各直流屏室
19	方形轴流风机	型号:T35-11-2.8,转速：1450r/min， 风量：1086m³/h，风压45Pa，电源380V50Hz,功率0.12kW 出口带出风防雨百叶(风机留孔尺寸：500x500mm)	台	2	培训室 暖通屏柜间

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
20	防腐防爆 方形轴流风机	型号:BFT35-11-2.8,转速：1450r/min， 风量：1086m³/h，风压45Pa，电源380V50Hz,功率0.12kW 出口带出风防雨百叶。防爆等级为ExdIICT1 (风机留孔尺寸：	台	8	各蓄电池室
21	换气扇	吊顶式，风量：400m³/h，电源：220V50Hz，功率：0.045kW 出风口带止回阀、金属软管2m及不锈钢出风口	台	4	卫生间
22	全自动防火阀	常态开启，输入DC24V信号或70℃熔断关闭，输出联动及 反馈信号，电动复位			
		尺寸：2000x1000mm	只	1	
		尺寸：2000x630mm	只	1	
		尺寸：1600x800mm	只	3	
		尺寸：1600x500mm	只	1	
		尺寸：1250x800mm	只	1	
		尺寸：1250x630mm	只	1	
		尺寸：1250x500mm	只	5	
		尺寸：1000x800mm	只	1	
		尺寸：1000x500mm	只	11	
		尺寸：800x500mm	只	2	
		尺寸：800x320mm	只	2	
		尺寸：800x250mm	只	3	
		尺寸：630x500mm	只	2	
		尺寸：630x400mm	只	2	
		尺寸：630x320mm	只	6	
		尺寸：630x250mm	只	1	
		尺寸：500x500mm	只	8	
		尺寸：500x320mm	只	2	
		尺寸：500x250mm	只	2	
		尺寸：400x320mm	只	1	
		尺寸：400x200mm	只	1	
23	防爆型防火阀	常态开启，输入DC24V信号或70℃熔断关闭，输出联动及 反馈信号，手动复位，防爆等级为ExdIICT1			
		尺寸：400x320mm	只	9	各蓄电池室
24	水平式止回阀	尺寸：640x640mm	只	8	
25	对开式多叶调节阀	尺寸：1250x500mm	只	1	
		尺寸：1000x500mm	只	1	
		尺寸：800x400mm	只	10	
		尺寸：800x250mm	只	2	
		尺寸：630x320mm	只	1	
		尺寸：630x250mm	只	1	
		尺寸：630x200mm	只	1	
		尺寸：500x400mm	只	2	
		尺寸：400x160mm	只	1	
		尺寸：320x120mm	只	1	
		尺寸：200x120mm	只	4	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
26	方形散流器	FC-FS型，铝合金，尺寸：360x360mm	只	22	
		FC-FS型，铝合金，尺寸：300x300mm	只	46	
		FC-FS型，铝合金，尺寸：240x240mm	只	26	
27	双层百叶送风口	FC-SB型，铝合金制作,600x400，带FK-11风量调节阀	只	4	
		FC-SB型，铝合金制作,500x300，带FK-11风量调节阀	只	4	
		FC-SB型，铝合金制作,500x200，带FK-11风量调节阀	只	28	
		FC-SB型，铝合金制作,300x300，带FK-11风量调节阀	只	1	
		FC-SB型，铝合金制作,200x200，带FK-11风量调节阀	只	1	
		FC-SB型，铝合金制作,200x100，带FK-11风量调节阀	只	4	
28	固定叶片回风口	FC-XB型，铝合金制作,1000x500	只	26	
		FC-XB型，铝合金制作,800x500	只	8	
		FC-XB型，铝合金制作,800x400	只	3	
		FC-XB型，铝合金制作,800x250	只	1	
		FC-XB型，铝合金制作,600x400	只	1	
		FC-XB型，铝合金制作,500x400	只	13	
		FC-XB型，铝合金制作,500x250	只	12	
29	双层防雨防沙百叶	铝合金制作,留孔尺寸：3200x2200(H),内侧带不锈钢丝网	只	1	
		铝合金制作,留孔尺寸：1500x1500(H),内侧带不锈钢丝网	只	2	
30	单层防雨防沙百叶	铝合金制作,留孔尺寸：3200x1100(H),内侧带不锈钢丝网	只	1	
		铝合金制作,留孔尺寸：1500x500(H),内侧带不锈钢丝网	只	1	
31	风管	镀锌钢板，厚度：0.75~1.2mm	m^2	3800	
		有机玻璃钢材料，厚度：3.2mm	m^2	300	蓄电池室排风管
32	静压联箱	镀锌钢板，厚度：1.2mm			
		11300(L)x2500(W)x1800(H) mm	只	1	
		11100(L)x2500(W)x800(H) mm	只	1	
		9600(L)x2500(W)x1600(H) mm	只	1	
		3300(L)x2000(W)x1000(H) mm	只	1	
		3300(L)x1500(W)x1000(H) mm	只	1	
		4500(L)x1250(W)x1000(H) mm	只	1	
		4500(L)x1000(W)x1000(H) mm	只	2	
		2400(L)x1500(W)x800(H) mm	只	2	
		2500(L)x1800(W)x800(H) mm	只	1	
33	防火软接	A级不燃,硅橡胶布	m^2	30	
34	风管保温材料	离心玻璃棉，厚50mm，密度64kg/m³，外敷牛皮纸铝箔，导热系数0.032W/m.K	m^2	3500	
35	不锈钢丝网	D1.6，10x10	m^2	50	
36	电动切换蝶阀	DN125，工作压力：1.6MPa，开关型，电源：AC220V/50Hz	只	2	
		DN100，工作压力：1.6MPa，开关型，电源：AC220V/50Hz	只	2	
		DN65，工作压力：1.6MPa，开关型，电源：AC220V/50Hz	只	4	
		DN50，工作压力：1.6MPa，开关型，电源：AC220V/50Hz	只	2	
37	电动三通调节阀	DN80，工作压力：1.6MPa，调节型，电源：AC220V/50Hz	只	2	
		DN50，工作压力：1.6MPa，调节型，电源：AC220V/50Hz	只	4	
		DN40，工作压力：1.6MPa，调节型，电源：AC220V/50Hz	只	2	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
		DN25，工作压力：1.6MPa，调节型，电源：AC220V/50Hz	只	1	
		DN20，工作压力：1.6MPa，调节型，电源：AC220V/50Hz	只	13	
38	蝶阀	D41X-16型，DN125，法兰连接	只	9	
		D41X-16型，DN100，法兰连接	只	4	
		D41X-16型，DN65，法兰连接	只	8	
		D41X-16型，DN50，法兰连接	只	4	
39	截止阀	J41H-16型，DN125，法兰连接	只	2	
		J41H-16型，DN80，法兰连接	只	2	
		J41H-16型，DN65，法兰连接	只	2	
		J41H-16型，DN50，法兰连接	只	7	
		J41H-16型，DN40，法兰连接	只	3	
		J11H-16型，DN25，螺纹连接	只	1	
		J11H-16型，DN20，螺纹连接	只	27	
40	球阀	Q41F-16型，DN50，法兰连接	只	4	
		Q11F-16型，DN32，螺纹连接	只	8	
		Q11F-16型，DN20，螺纹连接	只	43	
41	止回阀	H41X-16型，DN125，法兰连接	只	2	
42	自动放气阀	DN20, PN=1.6MPa, 耐温>120℃,带DN20球阀	只	25	
43	Y型水过滤器	不锈钢制，DN65，PN=1.6MPa，法兰连接，不锈钢网	只	1	
		不锈钢制，DN20，PN=1.6MPa，法兰连接，不锈钢网	只	13	
44	压力表		只	40	
45	温度计		只	25	
46	橡胶软接管	DN125，工作压力：1.6MPa，法兰连接	只	8	
		DN65，工作压力：1.6MPa，法兰连接	只	8	
		DN50，工作压力：1.6MPa，法兰连接	只	4	
		DN32，工作压力：1.6MPa，法兰连接	只	18	
47	不锈钢软管	DN20，PN=1.6MPa，L=200mm，内丝接口	只	26	
48	不锈钢无缝钢管	D133x4	m	100	
		D108x4	m	200	
		D89x4	m	100	
		D76x3	m	200	
49	不锈钢焊接钢管	DN50	m	200	
		DN40	m	10	
		DN32	m	60	
		DN25	m	100	
		DN20	m	200	
50	PVC排水管	DN40	m	50	
		DN32	m	50	
		DN20	m	50	
51	水管保温材料	闭孔橡塑海棉（难燃B1级)，K=0.032W/m.K,厚40mm			
		DN125	m	100	
		DN100	m	200	
		DN65	m	200	
		DN50	m	200	
		DN40	m	10	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
		DN32	m	60	
		DN25	m	100	
		DN20	m	200	
		保温板材	m^2	50	
		闭孔橡塑海棉（难燃B1级)，K=0.032W/m.K,厚25mm			
		DN40	m	50	
		DN32	m	50	
		DN20	m	50	
52	铝皮	1.00mm厚	m^2	3000	
53	防火短管	钢板，2.00mm厚，表面涂防锈漆2度，防火漆2度	m^2	100	
54	橡胶减震垫	120x120x21mm，每块2层，上下设5mm厚钢板	只	16	
55	地漏	De50，带水封，(给水排水标准图集04S301页30)	只	1	
56	安装材料	包括管道支吊架、抗震支吊架、垫圈、螺栓等	套	1	
57	配电及监控系统	包括配电柜、控制柜、传感器、控制和动力电缆等	套	1	
四	**#1继电器室及11kV站用电室通风及空调 30-B003701S-N0205**				
1	热泵型分体柜机	制冷量：7.5kW，制热量：8.3kW，功率：2.95kW，电源：380V50Hz，	台	6	
2	热泵型防爆分体柜机	制冷量：7.5kW，制热量：8.3kW，功率：2.95kW，电源：380V50Hz，T3工况，防爆等级：ExdIICT1	台	2	
3	单冷型分体柜机	制冷量：7.5kW，功率：2.95kW，电源：380V50Hz，T3工况	台	4	
4	防爆轴流风机	型号:BFT35-11-2.8,转速：1450r/min， 风量：1086m³/h，风压45Pa，电源380V50Hz,功率0.12kW 防爆等级为ExdIICT1	台	2	
5	轴流风机	型号:T35-11-3.15,转速：1450r/min， 风量：1905m³/h，风压56Pa，电源380V50Hz,功率0.04kW	台	6	
6	不锈钢防雨罩	D290mm	个	8	
7	镀锌钢板	0.6mm厚度	m^2	20	
8	不锈钢丝网	D1，10x10	m^2	1	
9	冷凝水管	De25	m	10	
10	橡塑保温管壳	15mm厚度	m^3	0.02	
五	**#2继电器室及计量小室通风及空调 30-B003701S-N0206**				
1	热泵型分体柜机	制冷量：7.5kW，制热量：8.3kW，功率：2.95kW，电源：380V50Hz，	台	7	
2	热泵型防爆分体柜机	制冷量：7.5kW，制热量：8.3kW，功率：2.95kW，电源：380V50Hz，T3工况，防爆等级：ExdIICT1	台	2	
3	防爆轴流风机	型号:BFT35-11-2.8,转速：1450r/min， 风量：1086m³/h，风压45Pa，电源380V50Hz,功率0.12kW 防爆等级为ExdIICT1	台	2	
4	轴流风机	型号:T35-11-2.8,转速：1450r/min， 风量：1346m³/h，风压45Pa，电源380V50Hz,功率0.025kW	台	1	
5	轴流风机	型号:T35-11-3.15,转速：1450r/min， 风量：1905m³/h，风压56Pa，电源380V50Hz,功率0.04kW	台	4	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
6	不锈钢防雨罩	D290mm	个	7	
7	镀锌钢板	0.6mm厚度	m^2	18	
8	不锈钢丝网	D1，10x10	m^2	1	
9	冷凝水管	De25	m	8	
10	橡塑保温管壳	15mm厚度	m^3	0.02	
六	**#3继电器室通风及空调 30-B003701S-N0207**				
1	热泵型分体柜机	制冷量：7.5kW，制热量：8.3kW，功率：2.95kW，电源：380V50Hz，	台	6	
2	热泵型防爆分体柜机	制冷量：7.5kW，制热量：8.3kW，功率：2.95kW，电源：380V50Hz， T3工况，防爆等级：ExdIICT1	台	2	
3	防爆轴流风机	型号:BFT35-11-2.8,转速：1450r/min， 风量：1086m³/h，风压45Pa，电源380V50Hz,功率0.12kW 防爆等级为ExdIICT1	台	2	
4	轴流风机	型号:T35-11-3.15,转速：1450r/min， 风量：1905m³/h，风压56Pa，电源380V50Hz,功率0.04kW	台	4	
5	不锈钢防雨罩	D290mm	个	6	
6	镀锌钢板	0.6mm厚度	m^2	16	
7	不锈钢丝网	D1，10x10	m^2	1	
8	冷凝水管	De25	m	7	
9	橡塑保温管壳	15mm厚度	m^3	0.02	
七	**132kV继电器室通风及空调 30-B003701S-N0208**				
1	热泵型分体柜机	制冷量：7.5kW，制热量：8.3kW，功率：2.95kW，电源：380V50Hz，	台	3	
2	轴流风机	型号:T35-11-2.8,转速：1450r/min， 风量：1364m³/h，风压45Pa，电源380V50Hz,功率0.0025kW	台	1	
3	轴流风机	型号:T35-11-3.15,转速：1450r/min， 风量：1905m³/h，风压56Pa，电源380V50Hz,功率0.04kW	台	1	
4	不锈钢防雨罩	D290mm	个	1	
5	不锈钢防雨罩	D320mm	个	1	
6	镀锌钢板	0.6mm厚度	m^2	3	
7	不锈钢丝网	D1，10x10	m^2	0.2	
8	冷凝水管	De25	m	2	
9	橡塑保温管壳	15mm厚度	m^3	0.01	
八	**400V站用电室通风及空调 30-B003701S-N0209**				
1	单冷型分体柜机	制冷量：12kW，功率：4.13kW，电源：380V50Hz，T3工况	台	4	
2	轴流风机	型号:T35-11-3.15,转速：1450r/min， 风量：1905m³/h，风压56Pa，电源380V50Hz,功率0.04kW	台	2	
3	不锈钢防雨罩	D290mm	个	2	
4	镀锌钢板	0.6mm厚度	m^2	3	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
5	不锈钢丝网	D1，10x10	m^2	0.2	
6	冷凝水管	De25	m	4	
7	橡塑保温管壳	15mm厚度	m^3	0.02	
九	**综合泵房及消防泵房通风及空调** 30-B003701S-N0210				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	2	
2	轴流风机	型号:T35-11-2.8,转速：1450r/min， 风量：1346m³/h，风压45Pa，电源380V50Hz,功率0.025kW	台	2	
3	防爆轴流风机	型号:BFT35-11-2.8,转速：1450r/min， 风量：1086m³/h，风压45Pa，电源380V50Hz,功率0.12kW 防爆等级为ExdIICT1	台	1	
4	轴流风机	型号:T35-11-4.5,转速：1450r/min， 风量：5581m³/h，风压115Pa，电源380V50Hz,功率0.25kW	台	2	
5	防爆轴流风机	型号:BFT35-11-5.6,转速：1450r/min， 风量：7724m³/h，风压83Pa，电源380V50Hz,功率0.37kW 防爆等级为ExdIICT1	台	2	
6	防烟防火阀（70℃）	400x400	个	1	
7	防烟防火阀（70℃）	500x500	个	1	
8	不锈钢防雨罩	D290mm	个	2	
9	不锈钢防雨罩	D365mm	个	2	
10	不锈钢防雨罩	D410mm	个	2	
11	镀锌钢板	0.6mm厚度	m^2	15	
12	不锈钢丝网	D1，10x10	m^2	1	
13	冷凝水管	De25	m	2	
14	橡塑保温管壳	15mm厚度	m^3	0.01	
15	金属软管	D290mm	m	0.1	
16	单层百叶	400x400	个	1	
17	防雨百叶	500x500	个	1	
18	防雨百叶	1200x3300	个	2	
十	**专用品库通风及空调** 30-B003701S-N0211				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	1	
2	橡塑保温管壳	15mm厚度	m^3	0.002	
十一	**深井泵房通风** 30-B003701S-N0212				
1	轴流风机	型号:T35-11-2.8,转速：1450r/min， 风量：1346m³/h，风压45Pa，电源380V50Hz,功率0.025kW	台	1	
2	不锈钢防雨罩	D290mm	个	1	
3	镀锌钢板	0.6mm厚度	m^2	2	
4	不锈钢丝网	D1，10x10	m^2	0.2	
5	防雨百叶	400x400	个	1	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
十二	**站前区办公楼通风及空调** **30-B003701S-N0213**				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	39	
2	热泵型分体柜机	制冷量：7.5kW，制热量：8.3kW，功率：2.95kW，电源：380V50Hz，	台	2	
3	热泵型分体柜机	制冷量：12kW，制热量：13kW，功率：4.13kW，电源：380V50Hz，T3	台	6	
4	轴流风机	型号:T35-11-2.8,转速：1450r/min， 风量：1346m³/h，风压45Pa，电源380V50Hz,功率0.025kW	台	1	
5	轴流风机	型号:T35-11-3.55,转速：1450r/min， 风量：2737m³/h，风压71Pa，电源380V50Hz,功率0.09kW	台	1	
6	排气扇	风量：300m³/h，电源220V50Hz,功率0.06kW，自带止回阀	台	6	
7	排气扇	风量：800m³/h，电源220V50Hz,功率0.15kW，自带止回阀	台	3	
8	防烟防火阀（70℃）	250x250	个	3	
9	防烟防火阀（70℃）	200x160	个	3	
10	铝合金单层百叶风口	300x200	个	2	
11	铝合金单层百叶风口	600x300	个	2	
12	镀锌钢板	0.75mm厚度	m^2	3	
13	镀锌钢板	0.5mm厚度	m^2	50	
14	不锈钢丝网	D1，10x10	m^2	1	
15	冷凝水管	De25	m	45	
16	橡塑保温管壳	15mm厚度	m^3	0.06	
17	金属软管	D280mm	m	0.2	
18	金属软管	D355mm	m	0.2	
十三	**站前区中方宿舍通风及空调** 30-B003701S-N0214				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	48	
2	排气扇	风量：150m³/h，电源220V50Hz,功率0.03kW，自带止回阀	台	46	
3	防烟防火阀（70℃）	160x160	个	3	
4	防烟防火阀（70℃）	160x100	个	40	
5	镀锌钢板	0.5mm厚度	m^2	50	
6	不锈钢丝网	D1，10x10	m^2	2	
7	冷凝水管	De25	m	70	
8	橡塑保温管壳	15mm厚度	m^3	0.08	
十四	**中方食堂通风及空调** 30-B003701S-N0215				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	3	
2	热泵型分体柜机	制冷量：12kW，制热量：13kW，功率：4.13kW，电源：380V50Hz，T3	台	4	
3	排气扇	风量：150m³/h，电源220V50Hz,功率0.03kW，自带止回阀	台	1	
4	排气扇	风量：300m³/h，电源220V50Hz,功率0.06kW，自带止回阀	台	2	
5	排气扇	风量：800m³/h，电源220V50Hz,功率0.15kW，自带止回阀	台	3	
6	不锈钢防雨罩	D250mm	个	3	
7	不锈钢防雨罩	D150mm	个	2	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
8	镀锌钢板	0.6mm厚度	m^2	9	
9	镀锌钢板	0.5mm厚度	m^2	6	
10	不锈钢丝网	D1，10x10	m^2	0.02	
11	冷凝水管	De25	m	7	
12	橡塑保温管壳	15mm厚度	m^3	0.01	
十五	**活动室通风及空调** 30-B003701S-N0216				
1	热泵型分体柜机	制冷量：12kW，制热量：13kW，功率：4.13kW，电源：380V50Hz，T3	台	4	
2	排气扇	风量：800m³/h，电源220V50Hz,功率0.15kW，自带止回阀	台	1	
3	镀锌钢板	0.5mm厚度	m^2	2	
4	不锈钢丝网	D1，10x10	m^2	0.08	
5	冷凝水管	De25	m	4	
6	橡塑保温管壳	15mm厚度	m^3	0.01	
十六	**站前区巴方宿舍通风及空调** 30-B003701S-N0217				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	32	
2	排气扇	风量：800m³/h，电源220V50Hz,功率0.15kW，自带止回阀	台	8	
3	防烟防火阀（70℃）	250x250	个	8	
4	镀锌钢板	0.5mm厚度	m^2	30	
5	不锈钢丝网	D1，10x10	m^2	1	
6	冷凝水管	De25	m	50	
7	橡塑保温管壳	15mm厚度	m^3	0.05	
十七	**巴方食堂通风及空调** 30-B003701S-N0218				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	1	
2	热泵型分体柜机	制冷量：12kW，制热量：13kW，功率：4.13kW，电源：380V50Hz，T3	台	4	
3	排气扇	风量：150m³/h，电源220V50Hz,功率0.03kW，自带止回阀	台	1	
4	排气扇	风量：800m³/h，电源220V50Hz,功率0.15kW，自带止回阀	台	3	
5	不锈钢防雨罩	D250mm	个	3	
6	镀锌钢板	0.6mm厚度	m^2	1	
7	镀锌钢板	0.5mm厚度	m^2	9	
8	不锈钢丝网	D1，10x10	m^2	0.02	
9	冷凝水管	De25	m	5	
10	橡塑保温管壳	15mm厚度	m^3	0.01	
十八	**门卫室通风及空调** 30-B003701S-N0219				
1	热泵型分体壁挂机	制冷量：3.5kW，制热量：3.9kW，功率：1.2kW，电源：220V50Hz，T3	台	1	
2	排气扇	风量：150m³/h，电源220V50Hz,功率0.03kW，自带止回阀	台	1	
3	不锈钢防雨罩	D100mm	个	1	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
4	镀锌钢板	0.5mm厚度	m^2	0.8	
5	不锈钢丝网	D1，10x10	m^2	0.01	
6	冷凝水管	De25	m	1	
7	橡塑保温管壳	15mm厚度	m^3	0.002	
十九	**建维区办公楼通风及空调** 30-B003701S-N0220				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	29	
2	热泵型分体柜机	制冷量：7.5kW，制热量：8.3kW，功率：2.95kW，电源：380V50Hz，	台	4	
3	热泵型分体柜机	制冷量：12kW，制热量：13kW，功率：4.13kW，电源：380V50Hz，T3	台	2	
4	轴流风机	型号:T35-11-2.8,转速：1450r/min， 风量：800m³/h，风压38Pa，电源380V50Hz,功率0.025kW	台	1	
5	排气扇	风量：300m³/h，电源220V50Hz,功率0.06kW，自带止回阀	台	2	
6	排气扇	风量：800m³/h，电源220V50Hz,功率0.15kW，自带止回阀	台	3	
7	防烟防火阀（70℃）	250x250	个	2	
8	防烟防火阀（70℃）	200x160	个	2	
9	铝合金单层百叶风口	300x200	个	2	
10	镀锌钢板	0.5mm厚度	m^2	50	
11	不锈钢丝网	D1，10x10	m^2	1	
12	冷凝水管	De25	m	40	
13	橡塑保温管壳	15mm厚度	m^3	0.05	
14	金属软管	D280mm	m	0.2	
二十	**管理人员宿舍楼通风及空调** 30-B003701S-N0221				
	(东楼)				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	24	
2	排气扇	风量：150m³/h，电源220V50Hz,功率0.03kW，自带止回阀	台	22	
3	防烟防火阀（70℃）	160x160	个	2	
4	防烟防火阀（70℃）	160x100	个	18	
5	镀锌钢板	0.5mm厚度	m^2	100	
6	不锈钢丝网	D1，10x10	m^2	3	
7	冷凝水管	De25	m	35	
8	橡塑保温管壳	15mm厚度	m^3	0.04	
	(西楼)				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	26	
2	热泵型分体柜机	制冷量：7.5kW，制热量：8.3kW，功率：2.95kW，电源：380V50Hz，	台	3	
3	热泵型分体柜机	制冷量：12kW，制热量：13kW，功率：4.13kW，电源：380V50Hz，T3	台	7	
4	排气扇	风量：150m³/h，电源220V50Hz,功率0.03kW，自带止回阀	台	20	
5	排气扇	风量：300m³/h，电源220V50Hz,功率0.06kW，自带止回阀	台	2	
6	排气扇	风量：800m³/h，电源220V50Hz,功率0.15kW，自带止回阀	台	3	
7	防烟防火阀（70℃）	250x250	个	2	
8	防烟防火阀（70℃）	200x160	个	2	
9	防烟防火阀（70℃）	160x160	个	4	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
10	防烟防火阀（70℃）	160x100	个	12	
11	镀锌钢板	0.5mm厚度	m^2	100	
12	不锈钢丝网	D1，10x10	m^2	4	
13	冷凝水管	De25	m	50	
14	橡塑保温管壳	15mm厚度	m^3	0.06	
二十一	**员工宿舍楼通风及空调** 30-B003701S-N0222				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	72	
2	热泵型分体柜机	制冷量：12kW，制热量：13kW，功率：4.13kW，电源：380V50Hz，T3	台	5	
3	排气扇	风量：150m³/h，电源220V50Hz,功率0.03kW，自带止回阀	台	140	
4	排气扇	风量：300m³/h，电源220V50Hz,功率0.06kW，自带止回阀	台	3	
5	排气扇	风量：800m³/h，电源220V50Hz,功率0.15kW，自带止回阀	台	3	
6	防烟防火阀（70℃）	250x250	个	4	
7	防烟防火阀（70℃）	200x160	个	5	
8	防烟防火阀（70℃）	160x160	个	70	
9	镀锌钢板	0.5mm厚度	m^2	250	
10	不锈钢丝网	D1，10x10	m^2	7	
11	冷凝水管	De25	m	110	
12	橡塑保温管壳	15mm厚度	m^3	0.13	
二十二	**巴方安保宿舍楼通风及空调** 30-B003701S-N0223				
1	热泵型分体壁挂机	制冷量：5kW，制热量：5.6kW，功率：1.82kW，电源：220V50Hz，T3	台	16	
2	热泵型分体柜机	制冷量：12kW，制热量：13kW，功率：4.13kW，电源：380V50Hz，T3	台	1	
3	排气扇	风量：150m³/h，电源220V50Hz,功率0.03kW，自带止回阀	台	1	
4	排气扇	风量：800m³/h，电源220V50Hz,功率0.15kW，自带止回阀	台	3	
5	不锈钢防雨罩	D250mm	个	1	
6	防烟防火阀（70℃）	250x250	个	2	
7	镀锌钢板	0.6mm厚度	m^2	5	
8	镀锌钢板	0.5mm厚度	m^2	20	
9	不锈钢丝网	D1，10x10	m^2	0.3	
10	冷凝水管	De25	m	15	
11	橡塑保温管壳	15mm厚度	m^3	0.02	
					Remark
No	Name	Type and Specification	Unit	Quantity	
1	**Ventilation and Air Conditioning of Pole 1 Valve Hall** **30-B003701S-N0203**				Outside the valve hall

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
1	Air cooled heat pump unit	LSRF500A,The temperature of supply/return chilled water is 7/12℃；The temperature of supply/return hot water is 45/40℃. Cooling capacity:550kW，Heating capacity: 520kW，refrigerant:R134a Power:243kW/380V,COP≥2.70, Size:4800x2100x2547(H)mm，Weight:6040kg	Set	2	Outside the valve hall
2	Centrifugal pump	GLC100-160，Flow rate：94m³/h，Head：352kPa Speed：2900r/min，Power：15kW，380V/50Hz Design pressure:1.0MPa. With shock absorbing.	Set	2	Outside the valve hall
3	Constant pressure water supply device	SXBY-600，DN600，total volume:0.35m³，Effective volume:1.25m³,pump 2 Set，flow rate:2.5m³/h，head: 200kPa,Size:2800x1100mm，height:1900mm，Weight:1900kg	Set	1	Outside the valve hall
4	Automatic strainer	Flow rate:94m³/h，Resistance:0.01MPa flange connection, connecting pipe diameter:DN150 Pressure:1.6MPa	Set	1	Outside the valve hall
5	Water treatment device	Laser negative ion intelligent water treatment Flow rate:94m³/h，Resistance:0.01MPa flange connection, connecting pipe diameter:DN150 Pressure:1.6MPa	Set	1	Outside the valve hall
6	Air handling unit	ZK50，Air volume：50000m³/h,Cooling capacity:500kW,Electric heating：150kW， Humidifying capacity：150kg/h,EvaporatingHumidifying capacity:500kg/h。 Power：56.5kW,380V/50Hz。 Size：14300(L)x2400(W)x2535(H)mm,	Set	2	
7	Fan	Model:HTF-D.No6.3,Speed: 960r/mm, Air volume：14580m³/h，Pressure190Pa，Power380V50Hz,Power consumption2.2kW	Set	2	
8	Automatic fire damper	Normal open, input DC24V signal or 70 centigrade fuse and turn off, output linkage and feedback signal, electric reset			
		Size：1800x1250mm	Piece	1	
		Size：1500x1000mm	Piece	1	
		Size：1250x800mm	Piece	1	
9	Automatic smoke damper	Normal open, input DC24V signal or 280 centigrade fuse and turn off, output linkage and feedback signal, electric reset Size：Ø700 mm	Piece	2	
10	Electric damper	Size：Ø700 mm, 220V50Hz	Piece	2	
11	Multileaf regulating valve	Size：1500x1000mm	Piece	1	
		Size：1250x800mm	Piece	1	
12	Single-layer rain and sand prevention Shutter	Aluminium alloy,2200x800(H),with Stainless wire mesh	Piece	2	
		Aluminium alloy,2200x1300(H),with Stainless wire mesh	Piece	2	
13	Single-layer rain prevention Shutter	Aluminium alloy,1000x700(H),with Stainless wire mesh	Piece	2	
14	Fixed blade air inlet	FC-XB，Aluminium alloy,1800x1250mm	Piece	1	
15	Double Shutter outlet	FC-SB，Stainless,900x600mm，With FK-11Air volumedamper	Piece	6	
16	Ball air outlet	Stainless,Ø400mm，With electric Air volumedamper	Piece	6	
17	Duct	Galvanized steel sheet，thickness：0.75~1.2mm	m^2	560	
		Galvanized steel sheet，thickness：2.0mm	m^2	10	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
18	Soft joint	Class A nonflammable, silicone rubber cloth	m^2	5	
19	Duct insulation material	Centrifugal glass wool，thickness50mm，density64kg/m³，with kraft paper aluminum foil，thermal conductivity 0.032W/m.K	m^2	560	
20	Electric butterfly valve	DN150，Pressure：1.6MPa，Switch type，Power：AC220V/50Hz	Piece	4	
21	Electric three way regulating valve	DN125，Pressure：1.6MPa，Modulating type，Power：AC220V/50Hz	Piece	2	
22	Butterfly valve	D41X-16，DN150，Flange connection	Piece	13	
23	Globe valve	J41H-16，DN150，Flange connection	Piece	2	
		J41H-16，DN125，Flange connection	Piece	2	
		J11H-16，DN25，Threaded connection	Piece	4	
24	Ball valve	Q41F-16，DN50，Flange connection	Piece	3	
		Q11F-16，DN40，Threaded connection	Piece	1	
		Q11F-16，DN20，Threaded connection	Piece	8	
25	Check valve	H41X-16，DN150，Flange connection	Piece	2	
26	Automatic exhaust valve	DN20, PN=1.6MPa, Temperature>120℃,with DN20 ball valve	Piece	7	
27	Pressure gauge	Y-100T,range：0～1.6MPa,with instrument valve and spring tube	Piece	17	
28	Thermometer	WNY-12,PN=1.6MPa,range:0～100℃	Piece	8	
29	Rubber soft nozzle	DN150，Pressure：1.6MPa，Flange connection	Piece	8	
		DN65，Pressure：1.6MPa，Flange connection	Piece	8	
30	Stainless steel seamless steel pipe	D159x4.5	m	80	
		D133x4	m	10	
		D76x3	m	20	
31	Stainless steel welded steel pipe	DN50	m	20	
		DN40	m	30	
		DN25	m	10	
32	Water pipeinsulation material	Closed hole rubber plastic sea cotton (refractory B1 grade)，K=0.032W/m.K,thickness40mm			
		DN150	m	80	
		DN125	m	10	
		DN65	m	20	
		DN50	m	20	
		DN40	m	30	
		DN25	m	10	For strainer, valve and pump
		Insulation board	m^2	20	
33	Aluminum skin	1.00mm thickness	m^2	700	
34	Rubber cushions	120x120x21mm, 2 layers per block, 5mm thick steel plate	Piece	16	
35	Auxiliary materials for installation	Including hangers & supports of air ducts and water pipes, gaskets, nuts, bolts, cable trays etc.	Set	1	
36	Power and control for HVAC system	Including control panel with PLC, software, transducer and sensor, I/O module, control cables .etc.	Set	1	
2	**Ventilation and Air Conditioning of Pole 2 Valve Hall 30-B003701S-N0204**				Outside the valve hall

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
1	Air cooled heat pump unit	LSRF500A,The temperature of supply/return chilled water is 7/12℃；The temperature of supply/return hot water is 45/40℃. Cooling capacity:550kW，Heating capacity: 520kW，refrigerant:R134a Power:243kW/380V,COP≥2.70, Size:4800x2100x2547(H)mm，Weight:6040kg	Set	2	Outside the valve hall
2	Centrifugal pump	GLC100-160，Flow rate：94m³/h，Head：352kPa Speed：2900r/min，Power：15kW，380V/50Hz Design pressure:1.0MPa. With shock absorbing.	Set	2	Outside the valve hall
3	Constant pressure water supply device	SXBY-600，DN600，total volume:0.35m³，Effective volume:1.25m³,pump 2 Set，flow rate:2.5m³/h，head: 200kPa,Size:2800x1100mm，height:1900mm，Weight:1900kg	Set	1	Outside the valve hall
4	Automatic strainer	Flow rate:94m³/h，Resistance:0.01MPa flange connection, connecting pipe diameter:DN150 Pressure:1.6MPa	Set	1	Outside the valve hall
5	Water treatment device	Laser negative ion intelligent water treatment Flow rate:94m³/h，Resistance:0.01MPa flange connection, connecting pipe diameter:DN150 Pressure:1.6MPa	Set	1	Outside the valve hall
6	Air handling unit	ZK50，Air volume：50000m³/h,Cooling capacity:500kW,Electric heating：150kW， Humidifying capacity：150kg/h,EvaporatingHumidifying capacity:500kg/h。 Power：56.5kW,380V/50Hz。 Size：14300(L)x2400(W)x2535(H)mm,	Set	2	
7	Fan	Model:HTF-D.No6.5,Speed: 960r/mm, Air volume：14580m³/h，Pressure190Pa，Power380V50Hz,Power consumption2.2kW	Set	2	
8	Automatic fire damper	Normal open, input DC24V signal or 70 centigrade fuse and turn off, output linkage and feedback signal, electric reset			
		Size：1800x1250mm	Piece	1	
		Size：1500x1000mm	Piece	1	
		Size：1250x800mm	Piece	1	
9	Automatic smoke damper	Normal open, input DC24V signal or 280 centigrade fuse and turn off, output linkage and feedback signal, electric reset Size：Ø700 mm	Piece	2	
10	Electric damper	Size：Ø700 mm, 220V50Hz	Piece	2	
11	Multileaf regulating valve	Size：1500x1000mm	Piece	1	
		Size：1250x800mm	Piece	1	
12	Single-layer rain and sand prevention Shutter	Aluminium alloy,2200x800(H),with Stainless wire mesh	Piece	2	
		Aluminium alloy,2200x1300(H),with Stainless wire mesh	Piece	2	
13	Single-layer rain prevention Shutter	Aluminium alloy,1000x700(H),with Stainless wire mesh	Piece	2	
14	Fixed blade air inlet	FC-XB，Aluminium alloy,1800x1250mm	Piece	1	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
15	Double Shutter outlet	FC-SB，Stainless,900x600mm，With FK-11Air volumedamper	Piece	6	
16	Ball air outlet	Stainless,Ø400mm，With electric Air volumedamper	Piece	6	
17	Duct	Galvanized steel sheet，thickness：0.75~1.2mm	m^2	560	
		Galvanized steel sheet，thickness：2.0mm	m^2	10	
18	Soft joint	Class A nonflammable, silicone rubber cloth	m^2	5	
19	Ductinsulation material	Centrifugal glass wool，thickness50mm，density64kg/m³，with kraft paper aluminum foil， thermal conductivity 0.032W/m.K	m^2	560	
20	Electric butterfly valve	DN150，Pressure：1.6MPa，Switch type，Power：AC220V/50Hz	Piece	4	
21	Electric three way regulating valve	DN125，Pressure：1.6MPa，Modulating type，Power：AC220V/50Hz	Piece	2	
22	Butterfly valve	D41X-16，DN150，Flange connection	Piece	13	
23	Globe valve	J41H-16，DN150，Flange connection	Piece	2	
		J41H-16，DN125，Flange connection	Piece	2	
		J11H-16，DN25，Threaded connection	Piece	4	
24	Ball valve	Q41F-16，DN50，Flange connection	Piece	3	
		Q11F-16，DN40，Threaded connection	Piece	1	
		Q11F-16，DN20，Threaded connection	Piece	8	
25	Check valve	H41X-16，DN150，Flange connection	Piece	2	
26	Automatic exhaust valve	DN20, PN=1.6MPa, Temperature>120℃,with DN20 ball valve	Piece	7	
27	Pressure gauge	Y-100T,range：0～1.6MPa,with instrument valve and spring tube	Piece	17	
28	Thermometer	WNY-12,PN=1.6MPa,range:0～100℃	Piece	8	
29	Rubber soft nozzle	DN150，Pressure：1.6MPa，Flange connection	Piece	8	
		DN65，Pressure：1.6MPa，Flange connection	Piece	8	
30	Stainless steel seamless steel pipe	D159x4.5	m	80	
		D133x4	m	10	
		D76x3	m	20	
31	Stainless steel welded steel pipe	DN50	m	20	
		DN40	m	30	
		DN25	m	10	
32	Water pipeinsulation material	Closed hole rubber plastic sea cotton (refractory B1 grade)， K=0.032W/m.K,thickness40mm			
		DN150	m	80	
		DN125	m	10	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
		DN65	m	20	
		DN50	m	20	
		DN40	m	30	
		DN25	m	10	For strainer, valve and pump
		Insulation board	m^2	20	
33	Aluminum skin	1.00mm thickness	m^2	700	
34	Rubber cushions	120x120x21mm, 2 layers per block, 5mm thick steel plate	Piece	16	
35	Auxiliary materials for installation	Including hangers & supports of air ducts and water pipes, gaskets, nuts, bolts, cable trays etc.	Set	1	
36	Power and control for HVAC system	Including control panel with PLC, software, transducer and sensor, I/O,module, control cables .etc.	Set	1	
3	**Ventilation and Air Conditioning of Main Control Building 30-B003701S-N0201**				Roof of control building
1	Air cooled heat pump unit	LSRF440A,The temperature of supply/return chilled water is 7/12℃；The temperature of supply/return hot water is 45/40℃. Cooling capacity:442kW，Heating capacity: 491kW，refrigerant:R134a Power:225kW/380V,COP≥1.96, Size:4800x2100x2547(H)mm，Weight:5240kg	Set	2	Roof of control building
2	Centrifugal pump	GLC80-200，Flow rate:83m³/h，Head:300kPa Speed:2900r/min，Power:11kW,380V/50Hz Design pressure:1.0MPa. With shock absorbing.	Set	2	Roof of control building
3	Constant pressure water supply device	SXBY-600，DN600，total volume:0.35m³，Effective volume:1.25m³,pump 2 Set，flow rate:2.5m³/h，head: 200kPa,Size:2800x1100mm，height:1900mm，Weight:1900kg	Set	1	Roof of control building
4	Automatic strainer	Flow rate:83m³/h，Resistance:0.01MPa flange connection, connecting pipe diameter:DN125 Pressure:1.6MPa	Set	1	Roof of control building
5	Water treatment device	Laser negative ion intelligent water treatment Flow rate:83m³/h，Resistance:0.01MPa flange connection, connecting pipe diameter:DN125 Pressure:1.6MPa	Set	1	±0.00m Air Conditioner Equipment Room
6	Air handling unit	ZK10，Air volume：10000m³/h,Cooling capacity：45kW,Heating capacity：10kW， Electric heating：10kW，Humidifying capacity：35kg/h。Power：18kW,380V/50Hz	Set	2	Outside Valve Hall Pole 1
7	Air handling unit	ZK18，Air volume：17000m³/h,Cooling capacity：70kW,Heating capacity：25kW， Electric heating：25kW，Humidifying capacity：55kg/h。Power：28.5kW,380V/50Hz，Size：5900(L)x1500(W)x1605(H)mm	Set	2	6.00m Air Conditioner Equipment Room
8	Air handling unit	ZK35，Air volume：34000m³/h,Cooling capacity：225kW,Heating capacity：60kW， Electric heating：60kW，Humidifying capacity：180kg/h。 Power：111kW，380V/50Hz。 Size：9000(L)x3300(W)x2135(H)mm	Set	2	Roof of control building

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
9	Air handling unit	ZK18，Air volume：18000m³/h,Cooling capacity：85kW,Heating capacity：25kW， Electric heating：25kW，Humidifying capacity：65kg/h。 Power：49kW，380V/50Hz。 Size：9400(L)x1500(W)x1605(H)mm	Set	2	±0.00m Air Conditioner Equipment Room
10	Evaporative cooling air handling unit	ZKX18，Air volume：18000m³/h,Humidifying capacity：180kg/h。 机外余压:250Pa。Power：13.4kW,380V/50Hz。 Size： 2700(L)x1500(W)x2810(H)mm	Set	2	Outside Valve Hall Pole 1 and 2
11	Evaporative cooling air handling unit	ZKX08，Air volume：8000m³/h,Humidifying capacity：75kg/h。 Power：8kW,380V/50Hz。 Size：4800(L)x1200(W)x1105(H)mm	Set	4	12.00m Cooridor
12	Fresh air handling unit	GXDB2.0，Air volume：2000m³/h,Cooling capacity：29kW,Heating capacity：22kW， Residual pressure:250Pa。Power：3.5kW,380V/50Hz。 Size：900(L)x1300(W)x510(H)mm，Electric damper	Set	1	
13	Fan coil unit	FP-136WA,Air flow rate1360m³/h，Exit static pressure 30Pa，Cooling capacity 7.92kW Heating capacity 13.59kW Power150W,220V50Hz, Water resistance 40kPa,noise 47dB (A)	Set	13	
14	Explosion-proof type Split air conditioner	KT3F-35GW/T13，T3，Cooling capacity:3.5kW, Heating capacity:3.9kW，Power:1.2kW，220V/50Hz EER=2.92，Cold medium tube and cable, length: 20m. Explosion-proof grade	Set	8	
15	Square axial fan	Model:T35-11-5.6,Speed：1450r/min， Air volume：7724m³/h，Pressure83Pa，Power380V50Hz,Power consumption0.37kW With Rainproof shutter	Set	10	
16	Square axial fan	Model:T35-11-4,Speed：1450r/min， Air volume：4263m³/h，Pressure97Pa，Power380V50Hz,Power consumption0.18kW With Rainproof shutter	Set	6	
18	Square axial fan	Model:T35-11-3.55,Speed：1450r/min， Air volume：2737m³/h，Pressure71Pa，Power380V50Hz,Power consumption0.12kW With Rainproof shutter	Set	3	
19	Square axial fan	Model:T35-11-2.8,Speed：1450r/min， Air volume：1086m³/h，Pressure45Pa，Power380V50Hz,Power consumption0.12kW With Rainproof shutter	Set	2	
20	Anticorrosion and explosion-proof Square axial fan	BFT35-11-2.8,speed:1450r/min，Air flow rate: 1086m³/h，Pressure:45Pa,Power:0.12kW，380V50Hz，With Rainproof shutter.Explosion-proof grade ExdIICT1	Set	8	
21	Ventilator	Ceiling type，Air flow rate:400m³/h， Power:0.045kW,220V50Hz,With Outlet valve, metal hose 2m and stainless steel outlet	Set	4	
22	Automatic fire damper	Normal open, input DC24V signal or 70 centigrade fuse and turn off, output linkage and feedback signal, electric reset			
		Size：2000x1000mm	Piece	1	
		Size：2000x630mm	Piece	1	
		Size：1600x800mm	Piece	3	
		Size：1600x500mm	Piece	1	
		Size：1250x800mm	Piece	1	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
		Size：1250x630mm	Piece	1	
		Size：1250x500mm	Piece	5	
		Size：1000x800mm	Piece	1	
		Size：1000x500mm	Piece	11	
		Size：800x500mm	Piece	2	
		Size：800x320mm	Piece	2	
		Size：800x250mm	Piece	3	
		Size：630x500mm	Piece	2	
		Size：630x400mm	Piece	2	
		Size：630x320mm	Piece	6	
		Size：630x250mm	Piece	1	
		Size：500x500mm	Piece	8	
		Size：500x320mm	Piece	2	
		Size：500x250mm	Piece	2	
		Size：400x320mm	Piece	1	
		Size：400x200mm	Piece	1	
23	Explosion-proof damper	Normal open, input DC24V signal or 70 centigrade fuse and turn off, output linkage and feedback signal, Explosion-proof grade ExdIICT1			
		Size：400x320mm	Piece	9	
24	Check valve	Size：640x640mm	Piece	8	
25	Multileaf regulating valve	Size：1250x500mm	Piece	1	
		Size：1000x500mm	Piece	1	
		Size：800x400mm	Piece	10	
		Size：800x250mm	Piece	2	
		Size：630x320mm	Piece	1	
		Size：630x250mm	Piece	1	
		Size：630x200mm	Piece	1	
		Size：500x400mm	Piece	2	
		Size：400x160mm	Piece	1	
		Size：320x120mm	Piece	1	
		Size：200x120mm	Piece	4	
26	Square diffuser	FC-FS，Aluminium alloy，Size：360x360mm	Piece	22	
		FC-FS，Aluminium alloy，Size：300x300mm	Piece	46	
		FC-FS，Aluminium alloy，Size：240x240mm	Piece	26	
27	Double Shutter outlet	FC-SB，Aluminium alloy,600x400，with FK-11 damper	Piece	4	
		FC-SB，Aluminium alloy,500x300，with FK-11 damper	Piece	4	
		FC-SB，Aluminium alloy,500x200，with FK-11 damper	Piece	28	
		FC-SB，Aluminium alloy,300x300，with FK-11 damper	Piece	1	
		FC-SB，Aluminium alloy,200x200，with FK-11 damper	Piece	1	
		FC-SB，Aluminium alloy,200x100，with FK-11 damper	Piece	4	
28	Fixed blade air inlet	FC-XB，Aluminium alloy,1000x500	Piece	26	
		FC-XB，Aluminium alloy,800x500	Piece	8	
		FC-XB，Aluminium alloy,800x400	Piece	3	
		FC-XB，Aluminium alloy,800x250	Piece	1	
		FC-XB，Aluminium alloy,600x400	Piece	1	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
		FC-XB，Aluminium alloy,500x400	Piece	13	
		FC-XB，Aluminium alloy,500x250	Piece	12	
29	Double-layer rain and sand prevention Shutter	Aluminium alloy,3000x2000(H),with Stainless wire mesh	Piece	1	
		Aluminium alloy,1300x1300(H),with Stainless wire mesh	Piece	2	
30	Single-layer rain and sand prevention Shutter	Aluminium alloy,3000x900(H),with Stainless wire mesh	Piece	1	
		Aluminium alloy,1300x300(H),with Stainless wire mesh	Piece	1	
31	Duct	Galvanized steel sheet，thickness：0.75~1.2mm	m^2	3800	
		Organic glass steel material，thickness：3.2mm	m^2	300	
32	Attenuator box	Galvanized steel sheet，thickness：1.2mm			
		11300(L)x2500(W)x1800(H) mm	Piece	1	
		11100(L)x2500(W)x800(H) mm	Piece	1	
		9600(L)x2500(W)x1600(H) mm	Piece	1	
		3300(L)x2000(W)x1000(H) mm	Piece	1	
		3300(L)x1500(W)x1000(H) mm	Piece	1	
		4500(L)x1250(W)x1000(H) mm	Piece	1	
		4500(L)x1000(W)x1000(H) mm	Piece	2	
		2400(L)x1500(W)x800(H) mm	Piece	2	
		2500(L)x1800(W)x800(H) mm	Piece	1	
33	Soft joint	Class A nonflammable, silicone rubber cloth	m^2	30	
34	Duct insulation material	Centrifugal glass wool，thickness50mm，density64kg/m³，with kraft paper aluminum foil，thermal conductivity 0.032W/m.K	m^2	3500	
35	Stainless steel wire mesh	D1.6，10x10	m^2	50	
36	Electric butterfly valve	DN125，Pressure：1.6MPa，Switch type，Power：AC220V/50Hz	Piece	2	
		DN100，Pressure：1.6MPa，Switch type，Power：AC220V/50Hz	Piece	2	
		DN65，Pressure：1.6MPa，Switch type，Power：AC220V/50Hz	Piece	4	
		DN50，Pressure：1.6MPa，Switch type，Power：AC220V/50Hz	Piece	2	
37	Electric three way regulating valve	DN80，Pressure：1.6MPa，Modulating type，Power：AC220V/50Hz	Piece	2	
		DN50，Pressure：1.6MPa，Modulating type，Power：AC220V/50Hz	Piece	4	
		DN40，Pressure：1.6MPa，Modulating type，Power：AC220V/50Hz	Piece	2	
		DN25，Pressure：1.6MPa，Modulating type，Power：AC220V/50Hz	Piece	1	
		DN20，Pressure：1.6MPa，Modulating type，Power：AC220V/50Hz	Piece	13	
38	Butterfly valve	D41X-16 ，DN125，Flange connection	Piece	9	
		D41X-16 ，DN100，Flange connection	Piece	4	
		D41X-16 ，DN65，Flange connection	Piece	8	
		D41X-16 ，DN50，Flange connection	Piece	4	
39	Globe valve	J41H-16 ，DN125，Flange connection	Piece	2	
		J41H-16 ，DN80，Flange connection	Piece	2	
		J41H-16 ，DN65，Flange connection	Piece	2	
		J41H-16 ，DN50，Flange connection	Piece	7	
		J41H-16 ，DN40，Flange connection	Piece	3	
		J11H-16 ，DN25，Threaded connection	Piece	1	
		J11H-16 ，DN20，Threaded connection	Piece	27	
40	Ball valve	Q41F-16 ，DN50，Flange connection	Piece	4	
		Q11F-16 ，DN32，Threaded connection	Piece	8	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
		Q11F-16 ，DN20，Threaded connection	Piece	43	
41	Check valve	H41X-16 ，DN125，Flange connection	Piece	2	
42	Automatic exhaust valve	DN20, PN=1.6MPa, Temperature>120℃,with DN20 ball valve	Piece	25	
43	Y shaped filter	Stainless steel，DN65，PN=1.6MPa，Flange connection	Piece	1	
		Stainless steel，DN20，PN=1.6MPa，Flange connection	Piece	13	
44	Pressure gauge	Y-100T,range：0～1.6MPa,with instrument valve and spring tube	Piece	40	
45	Thermometer	WNY-12,PN=1.6MPa,range:0～100℃	Piece	25	
46	Rubber soft nozzle	DN125，Pressure：1.6MPa，Flange connection	Piece	8	
		DN65，Pressure：1.6MPa，Flange connection	Piece	8	
		DN50，Pressure：1.6MPa，Flange connection	Piece	4	
		DN32，Pressure：1.6MPa，Flange connection	Piece	18	
47	Metal hose	DN20，PN=1.6MPa，L=200mm，Internal filament interface	Piece	26	
48	Stainless steel seamless steel pipe	D133x4	m	100	
		D108x4	m	200	
		D89x4	m	100	
		D76x3	m	200	
49	Stainless steel welded steel pipe	DN50	m	200	
		DN40	m	10	
		DN32	m	60	
		DN25	m	100	
		DN20	m	200	
50	PVC Pipe	DN40	m	50	
		DN32	m	50	
		DN20	m	50	
51	Water pipeinsulation material	Closed hole rubber plastic sea cotton (refractory B1 grade)，K=0.032W/m.K,thickness40mm			
		DN125	m	100	
		DN100	m	200	
		DN65	m	200	
		DN50	m	200	
		DN40	m	10	
		DN32	m	60	
		DN25	m	100	
		DN20	m	200	
		Insulation board	m^2	50	
		1.00mm thickness			
		DN40	m	50	
		DN32	m	50	
		DN20	m	50	
52	Aluminum skin	1.00mm	m^2	3000	
53	Fireproof short duct	Steel plate, 2.00mm thick, surface coated Antirust Paint 2 degrees, fireproof lacquer Paint 2 degrees	m^2	100	
54	Rubber cushions	120x120x21mm, 2 layers per block, 5mm thick steel plate	Piece	16	
55	Floor drain	De50, with water seal	Piece	1	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
56	Auxiliary materials for installation	Including hangers & supports of air ducts and water pipes, gaskets, nuts, bolts, cable trays etc.	Set	1	
57	Power and control for HVAC system	Including control panel with PLC, software, transducer and sensor, I/O module, control cables .etc.	Set	1	
4	**Ventilation and Air Conditioning of #1 Relay and 11kV Station Service House 30-B003701S-N0205**				
1	Heat pump type split cabinet unit	Cooling capacity：7.5kW，Heating capacity：8.3kW，Power consumption：2.95kW，Power：380V50Hz，T3condition	Set	6	
2	Heat pump Explosion-proof type split cabinet unit	Cooling capacity：7.5kW，Heating capacity：8.3kW，Power consumption：2.95kW，Power：380V50Hz，T3condition，Explosion-proof grade：Ex dIICT1	Set	2	
3	Single cooling type split cabinet unit	Cooling capacity：7.5kW，Power consumption：2.95kW，Power：380V50Hz，T3condition	Set	4	
4	Explosion-proof fan	Model:BFT35-11-2.8,Speed：1450r/min，Air volume：1086m³/h，Pressure45Pa，Power380V50Hz,Power consumption0.12kW Explosion-proof grade:Ex dIICT1	Set	2	
5	Axial Fan	Model:T35-11-3.15,Speed：1450r/min，Air volume：1905m³/h，Pressure56Pa，Power380V50Hz,Power consumption0.04kW	Set	6	
6	Stainless rainproof cover	D290mm	piece	8	
7	Galvanized steel sheet	0.6mm thickness	m^2	20	
8	Stainless steel mesh	D1，10x10	m^2	1	
9	PVC pipe	De25	m	10	
10	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.02	
5	**Ventilation and Air Conditioning of #2 Relay and Metering House 30-B003701S-N0206**				
1	Heat pump type split cabinet unit	Cooling capacity：7.5kW，Heating capacity：8.3kW，Power consumption：2.95kW，Power：380V50Hz，T3condition	Set	7	
2	Heat pump Explosion-proof type split cabinet unit	Cooling capacity：7.5kW，Heating capacity：8.3kW，Power consumption：2.95kW，Power：380V50Hz，T3condition，Explosion-proof grade：Ex dIICT1	Set	2	
3	Explosion-proof fan	Model:BFT35-11-2.8,Speed：1450r/min，Air volume：1086m³/h，Pressure45Pa，Power380V50Hz,Power consumption0.12kW Explosion-proof grade:Ex dIICT1	Set	2	
4	Axial Fan	Model:T35-11-2.8,Speed：1450r/min，Air volume：1346m³/h，Pressure45Pa，Power380V50Hz,Power consumption0.035kW	Set	1	
5	Axial Fan	Model:T35-11-3.15,Speed：1450r/min，Air volume：1905m³/h，Pressure56Pa，Power380V50Hz,Power consumption0.04kW	Set	4	
6	Stainless rainproof cover	D290mm	piece	7	
7	Galvanized steel sheet	0.6mm thickness	m^2	18	
8	Stainless steel mesh	D1，10x10	m^2	1	
9	PVC pipe	De25	m	8	
10	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.02	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
6	**Ventilation and air conditioning of #3 Relay House 30-B003701S-N0207**				
1	Heat pump type split cabinet unit	Cooling capacity：7.5kW，Heating capacity：8.3kW，Power consumption：2.95kW，Power：380V50Hz，T3condition	Set	6	
2	Heat pump Explosion-proof type split cabinet unit	Cooling capacity：7.5kW，Heating capacity：8.3kW，Power consumption：2.95kW，Power：380V50Hz，T3condition，Explosion-proof grade：ExdIICT1	Set	2	
3	Explosion-proof fan	Model:Br T35-11-2.8,Speed：1450r/min，Air volume：1086m³/h，Pressure45Pa，Power380V50Hz,Power consumption0.12kW Explosion-proof grade:ExdIICT1	Set	2	
4	Axial Fan	Model:T35-11-3.15,Speed：1450r/min，Air volume：1905m³/h，Pressure56Pa，Power380V50Hz,Power consumption0.04kW	Set	4	
5	Stainless rainproof cover	D290mm	piece	6	
6	Galvanized steel sheet	0.6mm thickness	m^2	16	
7	Stainless steel mesh	D1，10x10	m^2	1	
8	PVC pipe	De25	m	7	
9	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.02	
7	**Ventilation and air conditioning of 400V Station Service House 30-B003701S-N0208**				
1	Heat pump type split cabinet unit	Cooling capacity：7.5kW，Heating capacity：8.3kW，Power consumption：2.95kW，Power：380V50Hz，T3condition	Set	3	
2	Axial Fan	Model:T35-11-2.8,Speed：1450r/min，Air volume：1364m³/h，Pressure45Pa，Power380V50Hz,Power	Set	1	
3	Axial Fan	Model:T35-11-3.15,Speed：1450r/min，Air volume：1905m³/h，Pressure56Pa，Power380V50Hz,Power consumption0.04kW	Set	1	
4	Stainless rainproof cover	D290mm	piece	1	
5	Stainless rainproof cover	D320mm	piece	1	
6	Galvanized steel sheet	0.6mm thickness	m^2	3	
7	Stainless steel mesh	D1，10x10	m^2	0.2	
8	PVC pipe	De25	m	2	
9	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.01	
8	**Ventilation and air conditioning of 400V Station Service House 30-B003701S-N0209**				
1	Single cooling type split cabinet unit	Cooling capacity：12kW，Power consumption：4.13kW，Power：380V50Hz，T3condition	Set	4	
2	Axial Fan	Model:T35-11-3.15,Speed：1450r/min，Air volume：1905m³/h，Pressure56Pa，Power380V50Hz,Power consumption0.04kW	Set	2	
3	Stainless rainproof cover	D290mm	piece	2	
4	Galvanized steel sheet	0.6mm thickness	m^2	3	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
5	Stainless steel mesh	D1，10x10	m^2	0.2	
6	PVC pipe	De25	m	4	
7	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.02	
9	**Ventilation and air conditioning of Pump House and Fire Pump House 30-B003701S-N0210**				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	2	
2	Axial Fan	Model:T35-11-2.8,Speed：1450r/min，Air volume：1346m³/h，Pressure45Pa，Power380V50Hz,Power consumption0.025kW	Set	2	
3	Explosion-proof fan	Model:BFT35-11-2.8,Speed：1450r/min，Air volume：1086m³/h，Pressure45Pa，Power380V50Hz,Power consumption0.12kW Explosion-proof grade ExdIICT1	Set	1	
4	Axial Fan	Model:T35-11-4.5,Speed：1450r/min，Air volume：5581m³/h，Pressure115Pa，Power380V50Hz,Power consumption0.25kW	Set	2	
5	Explosion-proof fan	Model:BFT35-11-5.6,Speed：1450r/min，Air volume：7724m³/h，Pressure83Pa，Power380V50Hz,Power consumption0.37kW Explosion-proof grade ExdIICT1	Set	2	
6	Fire damper（70℃）	400x400	piece	1	
7	Fire damper（70℃）	500x500	piece	1	
8	Stainless rainproof cover	D290mm	piece	2	
9	Stainless rainproof cover	D365mm	piece	2	
10	Stainless rainproof cover	D410mm	piece	2	
11	Galvanized steel sheet	0.6mm thickness	m^2	15	
12	Stainless steel mesh	D1，10x10	m^2	1	
13	PVC pipe	De25	m	2	
14	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.01	
15	Metal hose	D290mm	m	0.1	
16	Single layer louver	400x400	piece	1	
17	Rain proof louver	500x500	piece	1	
18	Rain proof louver	1200x3300	piece	2	
10	**Air conditioning of Special materials storage 30-B003701S-N0211**				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	1	
2	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.002	
11	**Ventilation of Deep well 30-B003701S-N0212**				
1	Axial Fan	Model:T35-11-2.8,Speed：1450r/min，Air volume：1346m³/h，Pressure45Pa，Power380V50Hz,Power consumption0.025kW	Set	1	
2	Stainless rainproof cover	D290mm	piece	1	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
3	Galvanized steel sheet	0.6mm thickness	m^2	2	
4	Stainless steel mesh	D1，10x10	m^2	0.2	
5	Rain proof louver	400x400	piece	1	
12	**Ventilation and air conditioning of Office building in the first building area 30-B003701S-N0213**				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	39	
2	Heat pump type split cabinet unit	Cooling capacity：7.5kW，Heating capacity：8.3kW，Power consumption：2.95kW，Power：380V50Hz，T3condition	Set	2	
3	Heat pump type split cabinet unit	Cooling capacity：12kW，Heating capacity：13kW，Power consumption：4.13kW，Power：380V50Hz，T3condition	Set	6	
4	Axial Fan	Model:T35-11-2.8,Speed：1450r/min，Air volume：1346m³/h，Pressure45Pa，Power380V50Hz,Power consumption0.035kW	Set	1	
5	Axial Fan	Model:T35-11-3.55,Speed：1450r/min，Air volume：2737m³/h，Pressure71Pa，Power380V50Hz,Power consumption0.09kW	Set	1	
6	Ventilator	Air volume：300m³/h，Power220V50Hz,Power consumption0.06kW，With check damper	Set	6	
7	Ventilator	Air volume：800m³/h，Power220V50Hz,Power consumption0.15kW，With check damper	Set	3	
8	Fire damper（70℃）	250x250	piece	3	
9	Fire damper（70℃）	200x160	piece	3	
10	Aluminium alloySingle layer louver	300x200	piece	2	
11	Aluminium alloySingle layer louver	600x300	piece	2	
12	Galvanized steel sheet	0.75mm thickness	m^2	3	
13	Galvanized steel sheet	0.5mm thickness	m^2	50	
14	Stainless steel mesh	D1，10x10	m^2	1	
15	PVC pipe	De25	m	45	
16	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.06	
17	Metal hose	D280mm	m	0.2	
18	Metal hose	D355mm	m	0.2	
13	**Ventilation and air conditioning of Domitory building for chinese in the first building area 30-B003701S-N0214**				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	48	
2	Ventilator	Air volume：150m³/h，Power220V50Hz,Power consumption0.03kW，With check damper	Set	46	
3	Fire damper（70℃）	160x160	piece	3	
4	Fire damper（70℃）	160x100	piece	40	
5	Galvanized steel sheet	0.5mm thickness	m^2	50	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
6	Stainless steel mesh	D1，10x10	m^2	2	
7	PVC pipe	De25	m	70	
8	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.08	
14	**Ventilation and air conditioning of Refectory for chinese 30-B003701S-N0215**				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	3	
2	Heat pump type split cabinet unit	Cooling capacity：12kW，Heating capacity：13kW，Power consumption：4.13kW，Power：380V50Hz，T3condition	Set	4	
3	Ventilator	Air volume：150m³/h，Power220V50Hz,Power consumption0.03kW，With check damper	Set	1	
4	Ventilator	Air volume：300m³/h，Power220V50Hz,Power consumption0.06kW，With check damper	Set	2	
5	Ventilator	Air volume：800m³/h，Power220V50Hz,Power consumption0.15kW，With check damper	Set	3	
6	Stainless rainproof cover	D250mm	piece	3	
7	Stainless rainproof cover	D150mm	piece	2	
8	Galvanized steel sheet	0.6mm thickness	m^2	9	
9	Galvanized steel sheet	0.5mm thickness	m^2	6	
10	Stainless steel mesh	D1，10x10	m^2	0.02	
11	PVC pipe	De25	m	7	
12	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.01	
15	**Ventilation and air conditioning of Activity house 30-B003701S-N0216**				
1	Heat pump type split cabinet unit	Cooling capacity：12kW，Heating capacity：13kW，Power consumption：4.13kW，Power：380V50Hz，T3condition	Set	4	
2	Ventilator	Air volume：800m³/h，Power220V50Hz,Power consumption0.15kW，With check damper	Set	1	
3	Galvanized steel sheet	0.5mm thickness	m^2	2	
4	Stainless steel mesh	D1，10x10	m^2	0.08	
5	PVC pipe	De25	m	4	
6	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.01	
16	**Ventilation and air conditioning of Dormitory building for pakistani in the first building area 30-B003701S-N0217**				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	32	
2	Ventilator	Air volume：800m³/h，Power220V50Hz,Power consumption0.15kW，With check damper	Set	8	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
3	Fire damper（70℃）	250x250	piece	8	
4	Galvanized steel sheet	0.5mm thickness	m^2	30	
5	Stainless steel mesh	D1，10x10	m^2	1	
6	PVC pipe	De25	m	50	
7	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.05	
17	**Ventilation and air conditioning of Refectory for pakistani 30-B003701S-N0218**				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	1	
2	Heat pump type split cabinet unit	Cooling capacity：12kW，Heating capacity：13kW，Power consumption：4.13kW，Power：380V50Hz，T3condition	Set	4	
3	Ventilator	Air volume：150m³/h，Power220V50Hz,Power consumption0.03kW，With check damper	Set	1	
4	Ventilator	Air volume：800m³/h，Power220V50Hz,Power consumption0.15kW，With check damper	Set	3	
5	Stainless rainproof cover	D250mm	piece	3	
6	Galvanized steel sheet	0.6mm thickness	m^2	1	
7	Galvanized steel sheet	0.5mm thickness	m^2	9	
8	Stainless steel mesh	D1，10x10	m^2	0.02	
9	PVC pipe	De25	m	5	
10	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.01	
18	**Ventilation and air conditioning of Guard room 30-B003701S-N0219**				
1	Heat pump type split wall hanging unit	Cooling capacity：3.5kW，Heating capacity：3.9kW，Power consumption：1.2kW，Power：220V50Hz，T3condition	Set	1	
2	Ventilator	Air volume：150m³/h，Power220V50Hz,Power consumption0.03kW，With check damper	Set	1	
3	Stainless rainproof cover	D100mm	piece	1	
4	Galvanized steel sheet	0.5mm thickness	m^2	0.8	
5	Stainless steel mesh	D1，10x10	m^2	0.01	
6	PVC pipe	De25	m	1	
7	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.002	
19	**Ventilation and air conditioning of Office building in the temporary building area 30-B003701S-N0220**				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	29	
2	Heat pump type split cabinet unit	Cooling capacity：7.5kW，Heating capacity：8.3kW，Power consumption：2.95kW，Power：380V50Hz，T3condition	Set	4	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
3	Heat pump type split cabinet unit	Cooling capacity：12kW，Heating capacity：13kW，Power consumption：4.13kW，Power：380V50Hz，T3condition	Set	2	
4	Axial Fan	Model:T35-11-2.8,Speed：1450r/min，Air volume：800m³/h，Pressure38Pa，Power380V50Hz,Power consumption0.025kW	Set	1	
5	Ventilator	Air volume：300m³/h，Power220V50Hz,Power consumption0.06kW，With check damper	Set	2	
6	Ventilator	Air volume：800m³/h，Power220V50Hz,Power consumption0.15kW，With check damper	Set	3	
7	Fire damper（70℃）	250x250	piece	2	
8	Fire damper（70℃）	200x160	piece	2	
9	Aluminium alloySingle layer louver	300x200	piece	2	
10	Galvanized steel sheet	0.5mm thickness	m^2	50	
11	Stainless steel mesh	D1，10x10	m^2	1	
12	PVC pipe	De25	m	40	
13	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.05	
14	Metal hose	D280mm	m	0.2	
20	**Ventilation and air conditioning of Domitory building for managers 30-B003701S-N0221**				
	(East building)				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	24	
2	Ventilator	Air volume：150m³/h，Power220V50Hz,Power consumption0.03kW，With check damper	Set	22	
3	Fire damper（70℃）	160x160	piece	2	
4	Fire damper（70℃）	160x100	piece	18	
5	Galvanized steel sheet	0.5mm thickness	m^2	100	
6	Stainless steel mesh	D1，10x10	m^2	3	
7	PVC pipe	De25	m	35	
8	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.04	
	(West building)				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	26	
2	Heat pump type split cabinet unit	Cooling capacity：7.5kW，Heating capacity：8.3kW，Power consumption：2.95kW，Power：380V50Hz，T3condition	Set	3	
3	Heat pump type split cabinet unit	Cooling capacity：12kW，Heating capacity：13kW，Power consumption：4.13kW，Power：380V50Hz，T3condition	Set	7	
4	Ventilator	Air volume：150m³/h，Power220V50Hz,Power consumption0.03kW，With check damper	Set	20	
5	Ventilator	Air volume：300m³/h，Power220V50Hz,Power consumption0.06kW，With check damper	Set	2	
6	Ventilator	Air volume：800m³/h，Power220V50Hz,Power consumption0.15kW，With check damper	Set	3	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
7	Fire damper（70℃）	250x250	piece	2	
8	Fire damper（70℃）	200x160	piece	2	
9	Fire damper（70℃）	160x160	piece	4	
10	Fire damper（70℃）	160x100	piece	12	
11	Galvanized steel sheet	0.5mm thickness	m^2	100	
12	Stainless steel mesh	D1，10x10	m^2	4	
13	PVC pipe	De25	m	50	
14	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.06	
21	**Ventilation and air conditioning of Domitory building for staff 30-B003701S-N0222**				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	72	
2	Heat pump type split cabinet unit	Cooling capacity：12kW，Heating capacity：13kW，Power consumption：4.13kW，Power：380V50Hz，T3condition	Set	5	
3	Ventilator	Air volume：150m³/h，Power220V50Hz,Power consumption0.03kW，With check damper	Set	140	
4	Ventilator	Air volume：300m³/h，Power220V50Hz,Power consumption0.06kW，With check damper	Set	3	
5	Ventilator	Air volume：800m³/h，Power220V50Hz,Power consumption0.15kW，With check damper	Set	3	
6	Fire damper（70℃）	250x250	piece	4	
7	Fire damper（70℃）	200x160	piece	5	
8	Fire damper（70℃）	160x160	piece	70	
9	Galvanized steel sheet	0.5mm thickness	m^2	250	
10	Stainless steel mesh	D1，10x10	m^2	7	
11	PVC pipe	De25	m	110	
12	Rubber-Plastic Insulation Tube Shell	15mm thickness	m^3	0.13	
22	**Ventilation and air conditioning of Domitory building for security 30-B003701S-N0223**				
1	Heat pump type split wall hanging unit	Cooling capacity：5kW，Heating capacity：5.6kW，Power consumption：1.82kW，Power：220V50Hz，T3condition	Set	16	
2	Heat pump type split cabinet unit	Cooling capacity：12kW，Heating capacity：13kW，Power consumption：4.13kW，Power：380V50Hz，T3condition	Set	1	
3	Ventilator	Air volume：150m³/h，Power220V50Hz,Power consumption0.03kW，With check damper	Set	1	
4	Ventilator	Air volume：800m³/h，Power220V50Hz,Power consumption0.15kW，With check damper	Set	3	
5	Stainless rainproof cover	D250mm	piece	1	
6	Fire damper（70℃）	250x250	piece	2	
7	Galvanized steel sheet	0.6mm thickness	m^2	5	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任

序号	名称	规格及技术参数	单位	数量	备注
8	Galvanized steel sheet	0.5mm thickness	m^2	20	
9	Stainless steel mesh	D1，10x10	m^2	0.3	
10	PVC pipe	De25	m	15	

本文件的知识产权为华东电力设计院有限公司所有，任何单位或个人未经许可不得复制和使用，违者将被追究法律责任