

The <div> tag is utilized to group elements together, primarily for styling and layout purposes.

The <h1> heading is the largest and most important heading, typically used for crucial content.

The <h2> heading is smaller in size and less important than the `<h1>` heading.

The <h3> heading is smaller in size and lower in importance compared to the `<h2>` heading.

List tags in HTML are used to organize and structure content into a list format, making the information easier to read and understand. There are three main types of list tags:

Ordered List : Used for lists where the order or sequence is important, such as steps, rankings, or instructions.

Example:

I used the DIV tage

The <div> tag is used to group elements together for styling and layout purposes.

The <h1> heading is the largest and most important heading, used for crucial content.

The <h2> heading is smaller in size and lower in importance compared to <h1>.

The <h3> heading is smaller in size and lower in importance compared to. <h2>.

The list tag in HTML is used to organize and structure content into a list format, making it easier to read and understand. There are three main types of list tags:

1. **Ordered List (OL):**
Used for lists with a specific order or sequence, such as steps, rankings, or instructions.
2. **Unordered List (UL):**
Used for lists without a specific order or sequence, such as items, features, or options.
3. **Definition List (DL):**
Used for lists with terms and definitions, such as glossaries or dictionaries.

1. **Ordered List with **
Used for lists with a specific order or sequence.

1. First item
2. Second item
3. Third item

Unordered List : Used for lists where the order is not important, such as a list of items, features, or options.

Definition List <dl>: Used for lists that include terms and their definitions, such as glossaries or dictionaries.

2. Unordered List with

Used for lists without a specific order or sequence.

- Item 1
- Item 2
- Item 3

3. Definition List <dl> with dt <

Used for lists with terms and definitions.

Term 1

There we write description of 1

Term 2

There we write description of 2

The tag, combined with the `` tag, is used for creating lists with a specific order or sequence.

The tag, combined with the `` tag, is used for creating lists without a specific order or sequence.

The <dl> tag, along with the `<dt>` (definition term) and `<dd>` (definition description) tags, is used for creating lists with terms and their corresponding descriptions.

Tables in HTML are used to display data in a structured format, typically with rows and columns

Table containing Name, Age and City coloum

Name	Age	City
John	25	New York
Jane	30	Los Angeles
Total: 2 people		

The `` tag is used to display images on a webpage. It requires the image's path and complete filename to function.

The `` tag get image path with complete name and show it in to Webpage.



The `<a>` (anchor) tag is used to create hyperlinks that open another HTML page or destination. It requires the full path or URL to the destination.

The `
` tag is used to insert a line break, moving the content to the next line.

The `<caption>` tag is used to add a title or caption to a table. This is an optional tag that provides a brief description of the table's content.

The `<a>` Anchor tag use for open another page html it takes link or destination complete path.
[google](#)

The `
` tag use for brack the line in new line.
i used the `
` the containd go to next line.

The Caption Tag `<caption>` is used to add a caption or title to a table. It is an optional tag that provides a brief description of the table's content.

Student Information

Name	Age
John	25

The `<input>` tag is used to create input fields for various types of user input.

Text Input: `<input>` with the ``type="text"``` attribute is used for entering text, such as a username or email.

Password Input: `<input>` with the ``type="password"``` attribute is used for entering a password.

Checkbox Input: `<input>` with the ``type="checkbox"``` attribute is used for selections.

Radio Input: `<input>` with the ``type="radio"``` attribute is used for multiple selections within a group.

This text provides clear explanations of the HTML elements and their uses in a simple and formal manner.

The `<input>` tag are uses input values defent types.

The `<input>` with argument `<text>` tag for it take user name or email as input.

The `<input>` with argument `<password>` tag for it take user password as input.

The `<input>` with argument `<Checkbox>` tag use for selection.

☐ I agree to the terms

The `<input>` with argument `<radio>` tag use for multi-selection .

☐ Male
☐ Female